```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <limits.h>
#include <time.h>
typedef struct information
   char user[50];
   char process;
   int arrival;
   int duration;
   int deadLine;
   int total;
   int lengthOnCPu;
   int inUse;
} information;
information *init(char * userInput, char processInput, int arrivalInput, int
durationInput, int deadLine);
void motherboard(information *list, int ep, int cpuNum);
information * edf(information *list, int time);
int freeList(information * list);
void printOutput(information * list);
int changeLoc = -1;
int main(){
    char *trashCollector = NULL;
    // this a pointer to the headers which would be taking into account but not used.
   information *processList;
    int cpuNum = 0;
    if((processList = malloc(4*sizeof(information)))==NULL){
        return 1;
    printf("Please specify num of CPU:");
    scanf("%d", &cpuNum);
    printf("\n");
    int d;
    for(d=0; d<5; d++){
        scanf("%s\t", trashCollector);
    int ep = 0;
    int i;
    for (i = 0; i < 4; i++){}
       char expectedName[50] = "/0";
       char expectedProcess = 'a':
```

```
int expectedArrival = 0;
        int expectedDuration = 0;
        int expectedDeadline;
        if(scanf("%s\t%c\t%d\t%d\t%d",expectedName, &expectedProcess,
&expectedArrival, &expectedDuration, &expectedDeadline)<5 && ep<0){
            printf("Error in scanning the data");
            return 1;
    information *newStorage;
    newStorage = init(expectedName, expectedProcess, expectedArrival,
expectedDuration, expectedDeadline);
    processList[i] = *newStorage;
    ep++;
   motherboard(processList, ep, cpuNum);;
    freeList(processList);
    return 0;
information *init(char * userInput, char processInput, int arrivalInput, int
durationInput, int deadLineInput){
    information * current;
    if((current = malloc(sizeof(information))) == NULL)
        return NULL;
    strcpy(current->user, userInput);
    current->process = processInput;
    current->arrival = arrivalInput;
    current->duration = durationInput;
    current->deadLine = deadLineInput;
    return current;
void motherboard(information *list, int ep, int cpuNum){
    int lightsOff[ep];
    int checklist[ep];
   int changed[ep];
    int trialTime = 0;
    int count = 0;
    int safteycount = 0;
    int f;
    int cpuCheck = 0;
    int conAge = 3 * cpuNum;
```

```
for(f=0; f<ep; f++){
    checklist[f] = 1;
    lightsOff[f] = 0;
printf("This Would Result in:\nTime");
for(y=0;y<cpuNum;y++){</pre>
    printf("\tCPU%d",y+1);
printf("\n");
while(count !=ep && safteycount != 100){
    count = 0;
    cpuCheck = 0;
    printf("%d\t",trialTime);
    int mn;
    for(mn = 0; mn<ep; mn++){</pre>
        changed [mn] = 0;
        if(list[mn].arrival == trialTime){
            list[mn].lengthOnCPu = 1;
        }if(list[mn].lengthOnCPu == conAge){
            list[mn].lengthOnCPu = 1;
    while(cpuCheck != cpuNum){
        changeLoc = -1;
        information * temp;
        temp = edf(list, trialTime);
        if(changeLoc > -1){
            lightsOff[changeLoc] = 1;
        int q;
        for(q=0;q<ep;q++){</pre>
            if(changeLoc > -1 \&\& changeLoc == q){
                changed[q] = 1;
        list = temp;
        cpuCheck++;
    int d;
    for(d = 0; d < ep; d++){
        if(changed[d] != 1){
            list[d].lengthOnCPu = list[d].lengthOnCPu +1;
        }else{
            list[d].lengthOnCPu = 0;
```

```
printf("\n");
    int e;
    for(e=0; e<ep; e++){
        if(list[e].duration == 0 && checklist[e]!=0){
            checklist[e] = 0;
        if(checklist[e] == 0){
            count++;
        if(lightsOff[e] > 0 || list[e].inUse > 0){
            list[e].inUse = 0;
            lightsOff[e] = 0;
            if(e == 0){
    trialTime++;
    safteycount++;
printf("%d", trialTime);
int rr;
for(rr=0;rr<cpuNum;rr++){</pre>
    printf("\tIDLE");
printf("\n");
printf("\n\tSummary\n");
int spot[ep];
int sumCount=0;
int u;
for(u=0; u<ep; u++){
   spot[u]=0;
int l;
for(h=0; h<ep; h++){
    for(l=0;l<ep;l++){
        if(spot[h] < 1 && spot[l] < 1){
            if(h != l && strcmp(list[h].user, list[l].user)==0){
            spot[l] = 1;
            spot[h] = 2;
            sumCount++;
                if(list[l].total > list[h].total){
                    list[h].total = list[l].total;
```

```
int value = ep-sumCount;
    information * sumList;
    if((sumList = malloc(value * sizeof(information))) ==NULL){
        return;
    int increment = 0;
    int o;
    for(o=0; o<ep; o++){
        if(spot[o]!=1){
            sumList[increment] = list[o];
            increment++;
    int p;
    for(p=0;p<value;p++){</pre>
        printf("\t%s\t%d\n", sumList[p].user, sumList[p].total+1);
information * edf(information *list, int time){
    int minDuration = 999;
    int processLoc;
    int minDeadLine;
    int check = 0;
    int j;
    for(j=0;j<4;j++){
        minDeadLine = list[j].deadLine;
        if(list[j].arrival <= time && list[j].deadLine < minDeadLine){</pre>
            if(list[j].duration < minDuration && list[j].duration != 0){</pre>
                minDuration = list[j].duration;
                processLoc = j;
                check++;
    if(check != 0){
        list[processLoc].duration = list[processLoc].duration - 1;
        list[processLoc].total = time;
        printf("\t%c\t%c\n", list[processLoc].process, list[processLoc + 1].process);
    return list;
```

```
int freeList(information *list){
    free(list);
    return 1;
}

void printOutput(information * in){
    int j;
    for(j=0;j<4;j++){
        printf("%s\t%c\t%d\t%dn", in[j].user, in[j].process, in[j].arrival,
in[j].duration, in[j].deadLine);
    }
}</pre>
```