

# HTML kbd tag

---

 [w3schools.com/tags/tag\\_kbd.asp](https://www.w3schools.com/tags/tag_kbd.asp)

## Example

---

Define some text as keyboard input in a document:

`<p>Press <kbd>Ctrl</kbd> + <kbd>C</kbd> to copy text (Windows).</p>`

`<p>Press <kbd>Cmd</kbd> + <kbd>C</kbd> to copy text (Mac OS).</p>`

## Definition and Usage

---

The `<kbd>` tag is used to define keyboard input. The content inside is displayed in the browser's default monospace font.

**Tip:** This tag is not deprecated. However, it is possible to achieve richer effect by using CSS (see example below).

Also look at:

Tag	Description
<code>&lt;code&gt;</code>	Defines a piece of computer code
<code>&lt;samp&gt;</code>	Defines sample output from a computer program
<code>&lt;var&gt;</code>	Defines a variable
<code>&lt;pre&gt;</code>	Defines preformatted text

## Browser Support

---

Element
<code>&lt;kbd&gt;</code> Yes    Yes    Yes    Yes    Yes

## Global Attributes

---

The `<kbd>` tag also supports the [Global Attributes in HTML](#).

## Event Attributes

---

The `<kbd>` tag also supports the [Event Attributes in HTML](#).

## More Examples

---

## Example

---

Use CSS to style the `<kbd>` element:

```
<html>
<head>
<style>
kbd {
  border-radius: 2px;
  padding: 2px;
  border: 1px solid black;
}
</style>
</head>
<body>

<p>Press <kbd>Ctrl</kbd> + <kbd>C</kbd> to copy text (Windows).</p>
<p>Press <kbd>Cmd</kbd> + <kbd>C</kbd> to copy text (Mac OS).</p>

</body>
</html>
```

[Try it Yourself »](#)

## Related Pages

---

HTML tutorial: [HTML Text Formatting](#)

HTML DOM reference: [Kbd Object](#)

## Default CSS Settings

---

Most browsers will display the `<kbd>` element with the following default values:

## Example

---

```
kbd {
  font-family: monospace;
}
```