HTML input tag

```
w³ w3schools.com/tags/tag_input.asp
```

Example

An HTML form with three input fields; two text fields and one submit button:

```
<form action="/action_page.php">
<label for="fname">First name:</label>
<input type="text" id="fname" name="fname"><br><br><label for="lname">Last name:</label>
<input type="text" id="lname" name="lname"><br><br><input type="text" id="lname" name="lname"><br><input type="submit" value="Submit">
</form>
```

Definition and Usage

The <input> tag specifies an input field where the user can enter data.

The <input> element is the most important form element.

The <input> element can be displayed in several ways, depending on the type attribute.

The different input types are as follows:

```
• <input type="button">
• <input type="checkbox">
• <input type="color">
• <input type="date">
• <input type="datetime-local">
• <input type="email">
• <input type="file">
• <input type="hidden">
• <input type="image">
• <input type="month">
• <input type="number">
• <input type="password">
• <input type="radio">
• <input type="range">
• <input type="reset">
• <input type="search">
• <input type="submit">
• <input type="tel">
```

- <input type="text"> (default value)
- <input type="time">
- <input type="url">
- <input type="week">

Look at the type attribute to see examples for each input type!

Tips and Notes

Tip: Always use the <a href=

Browser Support

Element

<input> Yes Yes Yes Yes Yes

Attributes

Attribute	Value	Description
<u>accept</u>	file_extension audio/* video/* image/* media_type	Specifies a filter for what file types the user can pick from the file input dialog box (only for type="file")
<u>alt</u>	text	Specifies an alternate text for images (only for type="image")
<u>autocomplete</u>	on off	Specifies whether an <input/> element should have autocomplete enabled
<u>autofocus</u>	autofocus	Specifies that an <input/> element should automatically get focus when the page loads
checked	checked	Specifies that an <input/> element should be pre-selected when the page loads (for type="checkbox" or type="radio")
<u>dirname</u>	<i>inputname</i> .dir	Specifies that the text direction will be submitted
disabled	disabled	Specifies that an <input/> element should be disabled
<u>form</u>	form_id	Specifies the form the <input/> element belongs to

formaction	URL	Specifies the URL of the file that will process the input control when the form is submitted (for type="submit" and type="image")
<u>formenctype</u>	application/x- www-form- urlencoded multipart/form- data text/plain	Specifies how the form-data should be encoded when submitting it to the server (for type="submit" and type="image")
formmethod	get post	Defines the HTTP method for sending data to the action URL (for type="submit" and type="image")
<u>formnovalidate</u>	formnovalidate	Defines that form elements should not be validated when submitted
<u>formtarget</u>	_blank _self _parent _top <i>framename</i>	Specifies where to display the response that is received after submitting the form (for type="submit" and type="image")
<u>height</u>	pixels	Specifies the height of an <input/> element (only for type="image")
list	datalist_id	Refers to a <datalist> element that contains pre-defined options for an <input/> element</datalist>
<u>max</u>	number date	Specifies the maximum value for an <input/> element
<u>maxlength</u>	number	Specifies the maximum number of characters allowed in an <input/> element
min	number date	Specifies a minimum value for an <input/> element
<u>minlength</u>	number	Specifies the minimum number of characters required in an <input/> element
multiple	multiple	Specifies that a user can enter more than one value in an <input/> element
name	text	Specifies the name of an <input/> element
<u>pattern</u>	regexp	Specifies a regular expression that an <input/> element's value is checked against
placeholder	text	Specifies a short hint that describes the expected value of an <input/> element
<u>popovertarget</u>	element_id	Specifies which popover element to invoke (only for type="button")

popovertargetaction	hide show toggle	Specifies what happens to the popover element when you click the button (only for type="button")
<u>readonly</u>	readonly	Specifies that an input field is read-only
required	required	Specifies that an input field must be filled out before submitting the form
<u>size</u>	number	Specifies the width, in characters, of an <input/> element
src	URL	Specifies the URL of the image to use as a submit button (only for type="image")
<u>step</u>	<i>number</i> any	Specifies the interval between legal numbers in an input field
type	button checkbox color date datetime-local email file hidden image month number password radio range reset search submit tel text time url week	Specifies the type <input/> element to display
<u>value</u>	text	Specifies the value of an <input/> element
width	pixels	Specifies the width of an <input/> element (only for type="image")

Global Attributes

The <input> tag also supports the Global Attributes in HTML.

Event Attributes

The <input> tag also supports the Event Attributes in HTML.

Related Pages

HTML tutorial:

- HTML Forms
- HTML Form Elements
- HTML Input Types
- HTML Input Attributes
- HTML Input form* Attributes

HTML DOM reference:

- Input Button Object
- Input Checkbox Object
- Input Color Object
- Input Date Object
- Input Datetime Object
- Input DatetimeLocal Object
- Input Email Object
- Input FileUpload Object
- Input Hidden Object
- Input Image Object
- Input Month Object
- Input Number Object
- Input Password Object
- Input Range Object
- Input Radio Object
- Input Reset Object
- Input Search Object
- Input Submit Object
- Input Text Object
- Input Time Object
- Input URL Object
- Input Week Object

Default CSS Settings

None.