

# HTML tfoot tag

---

 [w3schools.com/tags/tag\\_tfoot.asp](https://www.w3schools.com/tags/tag_tfoot.asp)

## Example

---

An HTML table with a <thead>, <tbody>, and a <tfoot> element:

```
<table>
  <thead>
    <tr>
      <th>Month</th>
      <th>Savings</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td>January</td>
      <td>$100</td>
    </tr>
    <tr>
      <td>February</td>
      <td>$80</td>
    </tr>
  </tbody>
  <tfoot>
    <tr>
      <td>Sum</td>
      <td>$180</td>
    </tr>
  </tfoot>
</table>
```

## Definition and Usage

---

The **<tfoot>** tag is used to group footer content in an HTML table.

The **<tfoot>** element is used in conjunction with the <thead> and <tbody> elements to specify each part of a table (footer, header, body).

Browsers can use these elements to enable scrolling of the table body independently of the header and footer. Also, when printing a large table that spans multiple pages, these elements can enable the table header and footer to be printed at the top and bottom of each page.

**Note:** The **<tfoot>** element must have one or more <tr> tags inside.

The `<tfoot>` tag must be used in the following context: As a child of a `<table>` element, after any `<caption>`, `<colgroup>`, `<thead>`, and `<tbody>` elements.

**Tip:** The `<thead>`, `<tbody>`, and `<tfoot>` elements will not affect the layout of the table by default. However, you can use CSS to style these elements (see example below)!

## Browser Support

---

### Element

---

<code>&lt;tfoot&gt;</code>	Yes	Yes	Yes	Yes	Yes
----------------------------	-----	-----	-----	-----	-----

## Global Attributes

---

The `<tfoot>` tag also supports the [Global Attributes in HTML](#).

## Event Attributes

---

The `<tfoot>` tag also supports the [Event Attributes in HTML](#).

## More Examples

---

### Example

---

Style `<thead>`, `<tbody>`, and `<tfoot>` with CSS:

```
<html>
<head>
<style>
thead {color: green;}
tbody {color: blue;}
tfoot {color: red;}

table, th, td {
  border: 1px solid black;
}
</style>
</head>
<body>

<table>
  <thead>
    <tr>
      <th>Month</th>
      <th>Savings</th>
    </tr>
```

```

</thead>
<tbody>
  <tr>
    <td>January</td>
    <td>$100</td>
  </tr>
  <tr>
    <td>February</td>
    <td>$80</td>
  </tr>
</tbody>
<tfoot>
  <tr>
    <td>Sum</td>
    <td>$180</td>
  </tr>
</tfoot>
</table>

```

## Example

---

How to align content inside <tfoot> (with CSS):

```

<table style="width:100%">
  <tr>
    <th>Month</th>
    <th>Savings</th>
  </tr>
  <tr>
    <td>January</td>
    <td>$100</td>
  </tr>
  <tr>
    <td>February</td>
    <td>$80</td>
  </tr>
  <tfoot style="text-align:center">
    <tr>
      <td>Sum</td>
      <td>$180</td>
    </tr>
  </tfoot>
</table>

```

## Example

---

How to vertical align content inside `<tfoot>` (with CSS):

```
<table style="width:100%">
  <tr>
    <th>Month</th>
    <th>Savings</th>
  </tr>
  <tr>
    <td>January</td>
    <td>$100</td>
  </tr>
  <tr>
    <td>February</td>
    <td>$80</td>
  </tr>
  <tfoot style="vertical-align:bottom">
    <tr style="height:100px">
      <td>Sum</td>
      <td>$180</td>
    </tr>
  </tfoot>
</table>
```

## Default CSS Settings

---

Most browsers will display the `<tfoot>` element with the following default values:

```
tfoot {
  display: table-footer-group;
  vertical-align: middle;
  border-color: inherit;
}
```