

HTML tbody tag

 [w3schools.com/tags/tag_tbody.asp](https://www.w3schools.com/tags/tag_tbody.asp)

Example

An HTML table with a <thead>, <tbody>, and a <tfoot> element:

```
<table>
  <thead>
    <tr>
      <th>Month</th>
      <th>Savings</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td>January</td>
      <td>$100</td>
    </tr>
    <tr>
      <td>February</td>
      <td>$80</td>
    </tr>
  </tbody>
  <tfoot>
    <tr>
      <td>Sum</td>
      <td>$180</td>
    </tr>
  </tfoot>
</table>
```

Definition and Usage

The **<tbody>** tag is used to group the body content in an HTML table.

The **<tbody>** element is used in conjunction with the <thead> and <tfoot> elements to specify each part of a table (body, header, footer).

Browsers can use these elements to enable scrolling of the table body independently of the header and footer. Also, when printing a large table that spans multiple pages, these elements can enable the table header and footer to be printed at the top and bottom of each page.

Note: The **<tbody>** element must have one or more <tr> tags inside.

The `<tbody>` tag must be used in the following context: As a child of a `<table>` element, after any `<caption>`, `<colgroup>`, and `<thead>` elements.

Tip: The `<thead>`, `<tbody>`, and `<tfoot>` elements will not affect the layout of the table by default. However, you can use CSS to style these elements (see example below)!

Browser Support

Element

<code><tbody></code>	Yes	Yes	Yes	Yes	Yes
----------------------------	-----	-----	-----	-----	-----

Global Attributes

The `<tbody>` tag also supports the [Global Attributes in HTML](#).

Event Attributes

The `<tbody>` tag also supports the [Event Attributes in HTML](#).

More Examples

Example

Style `<thead>`, `<tbody>`, and `<tfoot>` with CSS:

```
<html>
<head>
<style>
thead {color: green;}
tbody {color: blue;}
tfoot {color: red;}

table, th, td {
  border: 1px solid black;
}
</style>
</head>
<body>

<table>
  <thead>
    <tr>
      <th>Month</th>
      <th>Savings</th>
    </tr>
```

```

</thead>
<tbody>
  <tr>
    <td>January</td>
    <td>$100</td>
  </tr>
  <tr>
    <td>February</td>
    <td>$80</td>
  </tr>
</tbody>
<tfoot>
  <tr>
    <td>Sum</td>
    <td>$180</td>
  </tr>
</tfoot>
</table>

```

Example

How to align content inside <tbody> (with CSS):

```

<table style="width:100%">
  <thead>
    <tr>
      <th>Month</th>
      <th>Savings</th>
    </tr>
  </thead>
  <tbody style="text-align:right">
    <tr>
      <td>January</td>
      <td>$100</td>
    </tr>
    <tr>
      <td>February</td>
      <td>$80</td>
    </tr>
  </tbody>
</table>

```

Example

How to vertical align content inside <tbody> (with CSS):

```
<table style="width:50%;">
  <tr>
    <th>Month</th>
    <th>Savings</th>
  </tr>
  <tbody style="vertical-align:bottom">
    <tr style="height:100px">
      <td>January</td>
      <td>$100</td>
    </tr>
    <tr style="height:100px">
      <td>February</td>
      <td>$80</td>
    </tr>
  </tbody>
</table>
```

Default CSS Settings

Most browsers will display the `<tbody>` element with the following default values:

```
tbody {
  display: table-row-group;
  vertical-align: middle;
  border-color: inherit;
}
```