

# HTML textarea tag

---

 [w3schools.com/tags/tag\\_textarea.asp](https://www.w3schools.com/tags/tag_textarea.asp)

## Example

---

A multi-line text input control (text area):

```
<label for="w3review">Review of W3Schools:</label>
```

```
<textarea id="w3review" name="w3review" rows="4" cols="50">
```

At w3schools.com you will learn how to make a website. They offer free tutorials in all web development technologies.

```
</textarea>
```

## Definition and Usage

---

The `<textarea>` tag defines a multi-line text input control.

The `<textarea>` element is often used in a form, to collect user inputs like comments or reviews.

A text area can hold an unlimited number of characters, and the text renders in a fixed-width font (usually Courier).

The size of a text area is specified by the `cols` and `rows` attributes (or with CSS).

The `name` attribute is needed to reference the form data after the form is submitted (if you omit the `name` attribute, no data from the text area will be submitted).

The `id` attribute is needed to associate the text area with a label.

**Tip:** Always add the `<label>` tag for best accessibility practices!

## Browser Support

---

### Element

---

<code>&lt;textarea&gt;</code>	Yes	Yes	Yes	Yes	Yes
-------------------------------	-----	-----	-----	-----	-----

## Attributes

---

Attribute	Value	Description
-----------	-------	-------------

---

<u>autofocus</u>	autofocus	Specifies that a text area should automatically get focus when the page loads
<u>cols</u>	<i>number</i>	Specifies the visible width of a text area
<u>dirname</u>	<i>textareaname.dir</i>	Specifies that the text direction of the textarea will be submitted
<u>disabled</u>	disabled	Specifies that a text area should be disabled
<u>form</u>	<i>form_id</i>	Specifies which form the text area belongs to
<u>maxlength</u>	<i>number</i>	Specifies the maximum number of characters allowed in the text area
<u>name</u>	<i>text</i>	Specifies a name for a text area
<u>placeholder</u>	<i>text</i>	Specifies a short hint that describes the expected value of a text area
<u>readonly</u>	readonly	Specifies that a text area should be read-only
<u>required</u>	required	Specifies that a text area is required/must be filled out
<u>rows</u>	<i>number</i>	Specifies the visible number of lines in a text area
<u>wrap</u>	hard soft	Specifies how the text in a text area is to be wrapped when submitted in a form

## Global Attributes

The `<textarea>` tag also supports the [Global Attributes in HTML](#).

## Event Attributes

The `<textarea>` tag also supports the [Event Attributes in HTML](#).

## More Examples

### Example

Disable default resize option:

```
<html>
<head>
<style>
textarea {
  resize: none;
}
</style>
</head>
```

```
<body>
```

```
<label for="w3review">Review of W3Schools:</label>
```

```
<textarea id="w3review" name="w3review" rows="4" cols="50">
```

At w3schools.com you will learn how to make a website. They offer free tutorials in all web development technologies.

```
</textarea>
```

```
</body>
```

```
</html>
```

## Related Pages

---

HTML DOM reference: [Textarea Object](#)

CSS Tutorial: [Styling Forms](#)

## Default CSS Settings

---

None.