

# HTML output Tag

---

 [w3schools.com/tags/tag\\_output.asp](https://www.w3schools.com/tags/tag_output.asp)

## Example

---

Perform a calculation and show the result in an <output> element:

```
<form oninput="x.value=parseInt(a.value)+parseInt(b.value)">
  <input type="range" id="a" value="50">
  +<input type="number" id="b" value="25">
  =<output name="x" for="a b"></output>
</form>
```

## Definition and Usage

---

The **<output>** tag is used to represent the result of a calculation (like one performed by a script).

## Browser Support

---

The numbers in the table specify the first browser version that fully supports the element.

### Element

---

<output>	10.0	13.0	4.0	5.1	11.0
----------	------	------	-----	-----	------

## Attributes

---

Attribute	Value	Description
<u>for</u>	<i>element_id</i>	Specifies the relationship between the result of the calculation, and the elements used in the calculation
<u>form</u>	<i>form_id</i>	Specifies which form the output element belongs to
<u>name</u>	<i>name</i>	Specifies a name for the output element

## Global Attributes

---

The **<output>** tag also supports the [Global Attributes in HTML](#).

## Event Attributes

---

The **<output>** tag also supports the [Event Attributes in HTML](#).

## Related Pages

---

HTML DOM reference: [Output Object](#)

## Default CSS Settings

---

Most browsers will display the `<output>` element with the following default values:

```
output {  
  display: inline;  
}
```