

# Copyright Notice

These slides are distributed under the Creative Commons License.

[DeepLearning.AI](#) makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite [DeepLearning.AI](#) as the source of the slides.

For the rest of the details of the license, see <https://creativecommons.org/licenses/by-sa/2.0/legalcode>




deeplearning.ai


# Neural Networks for Sentiment Analysis

# Outline


- Neural networks and forward propagation
- Structure for sentiment analysis



# Neural Networks



# Forward propagation




$a^{[i]}$  Activations ith layer

$$a^{[0]} = X$$


$$z^{[i]} = W^{[i]} a^{[i-1]}$$

$$a^{[i]} = g^{[i]}(z^{[i]})$$

# Neural Networks for sentiment analysis



# Neural Networks for sentiment analysis



# Initial Representation

Word	Number
a	1
able	2
about	3
...	...
hand	615
...	...
happy	621
...	...
zebra	1000

Tweet: This movie was  
almost good

[700 680 720 20 55]

Padding

[700 680 720 20 55 0 0 0 0 0 0]

To match size of longest tweet



# Summary

- Structure for sentiment analysis
- Classify complex tweets
- Initial representation




deeplearning.ai

# Trax: Neural Networks


---

# Outline


- Define a basic neural network using Trax
- Benefits of Trax




# Neural Networks in Trax



## Neural networks in Trax



# Neural Networks in Trax



```
from trax import layers as tl
Model = tl.Serial(
    tl.Dense(4),
    tl.Sigmoid(),
    tl.Dense(4),
    tl.Sigmoid(),
    tl.Dense(3),
    tl.Softmax())
```

# Advantages of using frameworks

- Run fast on CPUs, GPUs and TPUs
- Parallel computing
- Record algebraic computations for gradient evaluation

Tensorflow

Pytorch

JAX

# Summary

- Order of computation  $\longrightarrow$  Model in Trax
- Benefits from using frameworks






deeplearning.ai

# Classes, Subclasses and Inheritance


---

# Outline

- How classes work and their implementation
- Subclasses and inheritance



# Classes



# Classes in Python

```
class MyClass:
```

```
    def __init__(self, y):  
        self.y = y
```

```
    def my_method(self, x):  
        return x + self.y
```

```
    def __call__(self, x):  
        return
```


```
self.my_method(x)
```

```
f = MyClass(7)
```

```
print(f(3))
```

```
10
```

# Subclasses and Inheritance



Convenient when classes share common **parameters** and **methods**.

# Subclasses

```
class MyClass:
```

```
    def __init__(self,y):  
        self.y = y
```

```
    def my_method(self,x):  
        return x +
```

```
    def __call__(self,x):  
        return
```

```
self.my_method(x)
```

```
class SubClass(MyClass):
```

```
    def my_method(self,x):  
        return x +
```

```
self.y**2
```

```
f = SubClass(7)
```

```
print(f(3))
```

```
52
```

# Summary

- Classes, subclasses, instances and inheritance.



deeplearning.ai


# Dense and ReLU Layers

---




# Outline


- Dense layer in detail
- ReLU function



## Neural networks in Trax



## Dense Layer




$$z_j^{[i]} = w_j^{[i]T} a^{[i-1]}$$

Dense layer

$$z^{[i]} = \boxed{W^{[i]}} a^{[i-1]}$$

Trainable parameters


# ReLU Layer



$$a_j^{[i]} = g^{[i]}(z_j^{[i]})$$

ReLU = Rectified linear  
unit

$$g(z^{[i]}) = \max(\underline{0}, \underline{z^{[i]}})$$



# Summary

- Dense Layer  $\longrightarrow z^{[i]} = W^{[i]} a^{[i-1]}$
- ReLU Layer  $\longrightarrow g(z^{[i]}) = \max(0, z^{[i]})$




deeplearning.ai

# Serial Layer

---

# Serial Layer



Composition of layers  
in *serial* arrangement

- Dense Layers
- Activation Layers

Compute forward propagation of  
the entire model

# Summary

- Serial layer is a composition of sublayers
- Forward propagation by calling the method from the serial layer






deeplearning.ai

# Other Layers

---

# Outline

- Embedding layer
- Mean layer



# Embedding Layer

Vocabulary	Index		
I	1	0.020	0.006
am	2	-0.003	0.010
happy	3	0.009	0.010
because	4	-0.011	-0.018
learning	5	-0.040	-0.047
NLP	6	0.009	0.050
sad	7	-0.044	0.001
not	8	0.011	-0.022

Trainable  
weights

Vocabulary  
x  
Embedding

# Mean Layer

Tweet: I am happy

Vocabulary	Index		
I	1	0.020	0.006
am	2	-0.003	0.010
happy	3	0.009	0.010

0.020	0.006
-0.003	0.010
0.009	0.010

Mean of the  
word  
embeddings

0.009
0.009

No trainable  
parameters

# Summary

- Embedding is trainable using an embedding layer
- Mean layer gives a vector representation




deeplearning.ai

# Training

---

# Outline

- Computing gradients
- Training



# Computing gradients in Trax

$$f(x) = 3x^2 + x$$

$$\frac{\delta f(x)}{\delta x} = 6x + 1$$


Gradient

```
def f(x):  
    return 3*x**2 + x  
grad_f = trax.math.grad(f)
```

Returns a  
function



# Training with grad()



# Summary

- `grad()` allows much easier training
- Forward and backpropagation in one line!