# Applied Cryptography Week 5: Hash Functions and Keyed Hashing

Bernardo Portela

M:ERSI, M:SI, M:CC - 25

### What is a Hash Function?

#### Hash functions are everywhere

Key derivation

Hash Functions

- Digest for authentication
- Randomness extraction
- Password protection
- Proofs of work

### What is a Hash Function?

#### Hash functions are everywhere


Key derivation

Hash Functions •00000000

- Digest for authentication
- Randomness extraction
- Password protection
- Proofs of work

#### Not only in crypto:

- Indexing in version management
- Deduplication in cloud storage systems
- File integrity in intrusion detection



The hash output is short, aka hash, fingerprint or digest

Cryptographic hash functions give strong security guarantees

#### Use hash as an identifier

Hash Functions

0.0000000

Cryptographic hash functions cannot be injective

The hash output is short, aka hash, fingerprint or digest

Cryptographic hash functions give strong security guarantees

#### Use hash as an identifier

- Cryptographic hash functions cannot be injective
  - Why?

Hash Functions

0.0000000

The hash output is short, aka hash, fingerprint or digest

Cryptographic hash functions give strong security guarantees

#### Use hash as an identifier

- Cryptographic hash functions cannot be injective
  - Why?

Hash Functions

- Yet they should be well distributed and unpredictable
- Hash values can identify arbitrarily large inputs

The hash output is short, aka hash, fingerprint or digest

Cryptographic hash functions give strong security guarantees

#### Use hash as an identifier

- Cryptographic hash functions cannot be injective
  - Why?

Hash Functions

- Yet they should be well distributed and unpredictable
- Hash values can identify arbitrarily large inputs

Signing H(m) is as secure as signing m

Hash functions need to be deterministic and public

- Everyone should be able to recompute hash/identifier
- ... So what do we mean by security here?

00000000

# Secure Cryptographic Hash Functions

## Efficient algorithms with nice properties

- Unpredictable outputs
- Hard to find pre-images
- Hard to find collisions

## Secure Cryptographic Hash Functions

## Efficient algorithms with nice properties

- Unpredictable outputs
- Hard to find pre-images
- Hard to find collisions

## Hash functions are validated heuristically

- Similar to process for AES
- International competition for select designs
- Competitors are scrutinized wrt security and performance
- Several rounds, so more eyes on small number of proposals
- Most recent one: SHA-3

## #1: Pre-image resistance

It is *hard* to find the input that produced a given hash value How can we establish this in concrete terms?

It is hard to find the input that produced a given hash value

How can we establish this in concrete terms?

#### Pre-image experiment

Hash Functions

- Let S be the set of pre-images (domain)
- Let  $\mathcal{R}$  be the set of images (range)
- Attacker is given a value  $y \in \mathcal{R}$
- Attacker guesses  $x \in S$  and wins if h(x) = y

# #2: Collision Resistance (CR)

- By definition, collisions must exist.
  - Recall that  $|\mathcal{S}| >> |\mathcal{R}|$
- This can be argued from the pidgeonhole principle
  - If you have m holes and n pidgeons to put in these holes, if n > m, at least one hole will have more than one pidgeon!
- But can we find  $m_0$  and  $m_1$  s.t.  $h(m_0) = h(m_1)$ ?

# #2: Collision Resistance (CR)

- By definition, collisions must exist.
  - Recall that  $|\mathcal{S}| >> |\mathcal{R}|$
- This can be argued from the pidgeonhole principle
  - If you have m holes and n pidgeons to put in these holes, if n > m, at least one hole will have more than one pidgeon!
- But can we find  $m_0$  and  $m_1$  s.t.  $h(m_0) = h(m_1)$ ?

Suppose we have the best possible hash function?

# #2: Collision Resistance (CR)

- By definition, collisions must exist.
  - Recall that  $|\mathcal{S}| >> |\mathcal{R}|$
- This can be argued from the pidgeonhole principle
  - If you have m holes and n pidgeons to put in these holes, if n > m, at least one hole will have more than one pidgeon!
- But can we find  $m_0$  and  $m_1$  s.t.  $h(m_0) = h(m_1)$ ?

Suppose we have the best possible hash function?

Q1: What could that be?

# #2: Collision Resistance (CR)

- By definition, collisions must exist.
  - Recall that  $|\mathcal{S}| >> |\mathcal{R}|$
- This can be argued from the pidgeonhole principle
  - If you have m holes and n pidgeons to put in these holes, if n > m, at least one hole will have more than one pidgeon!
- But can we find  $m_0$  and  $m_1$  s.t.  $h(m_0) = h(m_1)$ ?

Suppose we have the best possible hash function?

#### Q1: What could that be?

- Lets think of the probability of collision
- Outputs are random, so  $1/2^n$  where n is the output length
- Collision will be found if we check roughly 2<sup>n</sup> pairs

#### Q2: Is CR harder or easier then pre-image resistance?

## Attack that finds a pre-image

- Search through all possible pre-images (brute-force)
- Consider a perfect hash function with output of *n* bits
- Cost: potentially more than 2<sup>n</sup> operations!
- Absolutely unfeasible for modern hash functions
  - n = 256 for SHA-256 and BLAKE

## Attack that finds a pre-image

- Search through all possible pre-images (brute-force)
- Consider a perfect hash function with output of *n* bits
- Cost: potentially more than 2<sup>n</sup> operations!
- Absolutely unfeasible for modern hash functions
  - n = 256 for SHA-256 and BLAKE

#### And if we want to find another pre-image?

- Nothing better than before
- Keep trying different values until you guess correctly

## **Breaking Hash Functions**

## Attack that finds a pre-image

- Search through all possible pre-images (brute-force)
- Consider a perfect hash function with output of *n* bits
- Cost: potentially more than 2<sup>n</sup> operations!
- Absolutely unfeasible for modern hash functions
  - n = 256 for SHA-256 and BLAKE

#### And if we want to find another pre-image?

- Nothing better than before
- Keep trying different values until you guess correctly

But what if we only want to find a collision?

## Finding Collisions

Collisions can be found with work  $\sqrt{2^n}$ , much better than  $2^n$ !

## Methodology

Hash Functions

- Compute values like the brute-force attack
- Store them in a data structure indexed by image value
- Each new image value is searched in data structure
- Repeat until a collision is found

## Finding Collisions

Collisions can be found with work  $\sqrt{2^n}$ , much better than  $2^n$ !

## Methodology

Hash Functions

- Compute values like the brute-force attack
- Store them in a data structure indexed by image value
- Each new image value is searched in data structure
- Repeat until a collision is found

#### How many operations?

• After *n* values, we checked n\*(n-1)/2 pairs **Q: why?** 

## Finding Collisions

Collisions can be found with work  $\sqrt{2^n}$ , much better than  $2^n$ !

### Methodology

- Compute values like the brute-force attack
- Store them in a data structure indexed by image value
- Each new image value is searched in data structure
- Repeat until a collision is found

#### How many operations?

- After *n* values, we checked n\*(n-1)/2 pairs **Q: why?**
- Checking  $2^n$  pairs takes roughly  $\sqrt{2^n}$  values
- Overall complexity is that of finding the pre-image of a hash with n/2 bits of output (only half of the range)

The birthday paradox (not very paradoxical, just counterintuitive)

000000000

#### For CR, hash outputs must be 2x security parameter

- 128-bit security  $\rightarrow$  256-bit hashes
- 256-bit security  $\rightarrow$  512-bit hashes

#### For CR, hash outputs must be 2x security parameter

- 128-bit security → 256-bit hashes
- 256-bit security  $\rightarrow$  512-bit hashes

We can use security-parameter-sized hash outputs when:

- Security against arbitrary collisions is not required
- E.g. we might only need pre-image resistance
- Deriving a key from a secret input



- Hash functions are one-way functions
  - From any sized inputs to fixed-size output
  - Never injective



- Hash functions are one-way functions
  - From any sized inputs to fixed-size output
  - Never injective
- Easy to go from x to f(x)
- Hard to go from f(x) to x



- · Hash functions are one-way functions
  - From any sized inputs to fixed-size output
  - Never injective
- Easy to go from x to f(x)
- Hard to go from f(x) to x
- Pre-image resistance
  - Give me some x for which f(x)
- Collision resistance
  - Give me any  $x_1, x_2$  for which  $f(x_1) = f(x_2)$
  - Much easier!!



- Hash functions are one-way functions
  - From any sized inputs to fixed-size output
  - Never injective
- Easy to go from x to f(x)
- Hard to go from f(x) to x
- Pre-image resistance
  - Give me some x for which f(x)
- Collision resistance
  - Give me any  $x_1, x_2$  for which  $f(x_1) = f(x_2)$
  - Much easier!!
- For output of  $2^n$ , collision can be found in  $\approx 2^{\sqrt{n}}$
- So for 2<sup>128</sup> resistance, output must be at least 2<sup>256</sup>
- Birthday attack

# **Building Hash Functions**

#### Two main approaches that use iterative processes

 Merkle-Damgård construction: Used for MD4, MD5, SHA-1, SHA-256, SHA-512. Relies on a m + n-to-n bits compression function to construct a hash function of output length n for arbitrary input lengths

## **Building Hash Functions**


#### Two main approaches that use iterative processes

- Merkle-Damgård construction: Used for MD4, MD5, SHA-1, SHA-256, SHA-512. Relies on a m + n-to-n bits compression function to construct a hash function of output length n for arbitrary input lengths
- Sponge construction: Used for SHA-3, uses a *I*-bit permutation to construct a hash function for arbitrary input and output lengths

## Merkle-Damgård Construction

All prominent hash functions from 80s-2000s.


- $H_0$  is the initial value: constant and **public**
- M is broken into blocks of size  $m, M_1, M_2, \dots$



## Merkle-Damgård Construction

All prominent hash functions from 80s-2000s.

- H<sub>0</sub> is the initial value: constant and **public**
- M is broken into blocks of size m,  $M_1, M_2, \ldots$



- SHA-256: block size 512, output size 256 bits
- SHA-512: block size 1024, output size 512 bits
- What if messages are not of the same size as the block?

# Merkle-Damgård Construction – Padding

#### Padding is always added to the message

- Append the message with a 1 bit
- Fill with zeros up to 64/128 bits away from the block end
- Last 64/128 bits encode the message length in bits

## Merkle-Damgård Construction – Padding

#### Padding is always added to the message

- Append the message with a 1 bit
- Fill with zeros up to 64/128 bits away from the block end
- Last 64/128 bits encode the message length in bits

E.g. we want to hash the 8-bit string 10101010 using SHA-256

Message is: 101010101010000(...)000001000

# Merkle-Damgård Construction – Padding

#### Padding is always added to the message

- Append the message with a 1 bit
- Fill with zeros up to 64/128 bits away from the block end
- Last 64/128 bits encode the message length in bits

E.g. we want to hash the 8-bit string 10101010 using SHA-256

Message is: 101010101010000(...)000001000

Q: Can't we just pad by adding 0s?

#### Useful result


- Compression result is CR (for small inputs)
- Then the whole construction is CR (for arbitrary inputs)

To break the hash function you must break the compression function

So, does having a 2n-to-n CR compression function solve all our problems?

## Compression Functions: Davis-Meyer


All popular MD constructions use the Davis-Meyer construction:



Block ciphers used as compression functions!

- Message is the encryption key!
- Construction creates a fixed point when  $H_{i-1} = D(M_i, 0)$

#### All popular MD constructions use the Davis-Meyer construction:



Block ciphers used as compression functions!

- Message is the encryption key!
- Construction creates a fixed point when  $H_{i-1} = D(M_i, 0)$


$$H_i = E(M_i, H_{i-1}) \oplus H_{i-1}$$
  
 $H_i = E(M_i, D(M_i, 0)) \oplus D(M_i, 0)$   
 $H_i = H_{i-1}$ 

# A more recent alternative to the MD is the spong

A more recent alternative to the MD is the sponge construction It relies on a fixed (non-keyed) permutation

### Very Versatile

- Varying input/output lengths
- PRGs and stream ciphers
- PRFs and keyed hashes



## Sponge Construction – Description

Sponge operates in two phases: absorb and squeeze. The state is the same size w as the permutation input

## Sponge Construction – Description

Sponge operates in two phases: absorb and squeeze. The state is the same size w as the permutation input

#### **Absorb**

- Fixed initial value  $h_0$ , gradually accumulate message into state
- Message broken in blocks of size r (rate)
- Block is smaller than state size
- Block XOR'ed into state
- Permutation recomputed

### Sponge Construction – Description

Sponge operates in two phases: absorb and squeeze. The state is the same size w as the permutation input

#### Absorb

- Fixed initial value  $h_0$ , gradually accumulate message into state
- Message broken in blocks of size r (rate)
- Block is smaller than state size
- Block XOR'ed into state
- Permutation recomputed

### Squeeze

- Dual process iteratively constructs output
- Output constructed block by block
- Permutation computed over the entire state
- Block-sized part of the state is accumulated in the output

### MD5

- Broken! 128-bit output
- Most popular hash function until broken in 2005
- These days, it takes seconds to find collisions
- The SHA function family (next) uses a similar design

## Secure Hash Function (SHA)

Standardized by NIST in the US. International de facto standard SHA-0 published in 93', replaced with SHA-1 in 95'

- Both with 160-bit outputs
- Vulnerability not public at the time
- Later discovered collision attack in  $2^{60} << 2^{80}$  operations
- More recent attacks reduced it to 2<sup>33</sup>

### Secure Hash Function (SHA)

Standardized by NIST in the US. International *de facto* standard SHA-0 published in 93', replaced with SHA-1 in 95'

- Both with 160-bit outputs
- Vulnerability not public at the time
- Later discovered collision attack in  $2^{60} << 2^{80}$  operations
- More recent attacks reduced it to 2<sup>33</sup>

SHA-1 remained unbroken until quite recently -(2017)

Most applications currently use SHA-2 (256 or 512 bits)

• Same design principles; larger parameters

Future applications adopting SHA-3 evolve to the Sponge

• Flexible output size is very useful!

### SHA-1 Internals

- Merkle-Damgård, with Davis-Meyer compression function
- Block cipher used in compression function called SHACAL
  - Block cipher with 160-bit block sizes!

- Merkle-Damgård, with Davis-Meyer compression function
- Block cipher used in compression function called SHACAL
  - Block cipher with 160-bit block sizes!
- Message blocks are 512-bits, hashes are 160-bits long
- Davis-Meyer addition (not XOR): five 32-bit additions
- Insecure! Expected collisions in 2<sup>63</sup> ops in 2015, found in 2017

#### SHA-1 Internals

- Merkle-Damgård, with Davis-Meyer compression function
- Block cipher used in compression function called SHACAL
  - Block cipher with 160-bit block sizes!
- Message blocks are 512-bits, hashes are 160-bits long.
- Davis-Meyer addition (not XOR): five 32-bit additions
- Insecure! Expected collisions in 2<sup>63</sup> ops in 2015, found in 2017

```
SHA1-blockcipher(a, b, c, d, e, M) {
  W = expand(M);
  for i = 0 to 79 { // K are constants
    new = (a <<< 5) + f(i, b, c, d) + e + K[i] + W[i]
    (a, b, c, d, e) = (new, a, b >>> 2, c, d)
 return (a, b, c, d, e)
```

## SHA-2 Family

- Family of 4 hash functions
  - SHA-224;256;384;512

## SHA-2 Family

- Family of 4 hash functions
  - SHA-224;256;384;512
- Three digit identifier defines the output length
- Increased parameters and improved internal block ciphers
- SHA-224 and 256 still use 512 bit blocks (64 rounds)
  - SHA-224 is exactly the same as SHA-256, but has different IV and truncated output
  - SHA-384 and SHA-512 are similarly related
- SHA-512 compression function very similar, but has 80 rounds

## SHA-2 Family

- Family of 4 hash functions
  - SHA-224;256;384;512
- Three digit identifier defines the output length
- Increased parameters and improved internal block ciphers
- SHA-224 and 256 still use 512 bit blocks (64 rounds)
  - SHA-224 is exactly the same as SHA-256, but has different IV and truncated output
  - SHA-384 and SHA-512 are similarly related
- SHA-512 compression function very similar, but has 80 rounds

#### No non-generic attacks exist on these hash functions

- Still SHA-3 was (prudently) developed with different design
- Also has the benefit of varying sized outputs
- Good to generate keys!

SHA-3

- Keccack selected in 2009
- 3-year NIST SHA-3 competition
- Competition called for new design, if SHA-2 gets attacked

### SHA-3

- Keccack selected in 2009
- 3-year NIST SHA-3 competition
- Competition called for new design, if SHA-2 gets attacked

#### Keccack is very different and very flexible

- Sponge based with 1600-bits permutation (in SHA-3)
- Blocks can be 1152, 1088, 832 or 576 bits
- Corresponding to 224, 256, 384 or 512 bit outputs
- As a bonus we get the SHAKE functions
  - SHAKE128 and SHAKE256
  - eXtendable Output Functions (XOFs)
  - You can specify output length



• Two main constructions: MD and Sponge



- Two main constructions: MD and Sponge
- Merkle-Damgård
  - Used in MD5; SHA1; SHA2
  - Sequential compression of message DM
  - Davis-Meyer compresses using a block cipher



- Two main constructions: MD and Sponge
- Merkle-Damgård
  - Used in MD5; SHA1; SHA2
  - Sequential compression of message DM
  - Davis-Meyer compresses using a block cipher
- Sponge
  - Used in SHA3 and SHAKE
  - Absorb phase permutes message
  - Squeeze phase retrieves the output



- Two main constructions: MD and Sponge
- Merkle-Damgård
  - Used in MD5; SHA1: SHA2
  - Sequential compression of message DM
  - Davis-Meyer compresses using a block cipher
- Sponge
  - Used in SHA3 and SHAKE
  - Absorb phase permutes message
  - Squeeze phase retrieves the output
- SHA-2 and SHA-3 currently the de facto standards

## MACs as Keyed Hashes

### Short Summaries of Potentially Large Messages

- Called a hash if everything is public
- Keyed hashes allows for conditional hash computation

## MACs as Keyed Hashes

### Short Summaries of Potentially Large Messages

- Called a hash if everything is public
- Keyed hashes allows for conditional hash computation

#### Message Authentication Codes - MACs

- Symmetric Authentication  $t \leftarrow MAC(k, m)$
- t guarantees that m was produced by someone that knows k
- Implies message *m* was not changed since its creation
- Digital signatures in the symmetric paradigm!

## Message Authentication Codes

#### Typical use of MACs – SSH, IPSec, TLS

- Two parties was message authentication and integrity
- Some form of set-up/agreement to establish common key k
- Sender computes  $t \leftarrow \mathsf{MAC}(k, m)$  and sends (m, t)
- Receiver gets (m, t), recomputes  $t' \leftarrow MAC(k, m)$
- If  $t \neq t'$ , message is rejected!

## Message Authentication Codes

#### Typical use of MACs – SSH, IPSec, TLS


- Two parties was message authentication and integrity
- Some form of set-up/agreement to establish common key k
- Sender computes  $t \leftarrow \mathsf{MAC}(k, m)$  and sends (m, t)
- Receiver gets (m, t), recomputes  $t' \leftarrow MAC(k, m)$
- If  $t \neq t'$ , message is rejected!

Acceptance means m was produced while knowing k

In this process, message is public!

MACs do not give confidentiality. They provide integrity

Its orthogonal to encryption. In real-world applications, we will need to combine these



- No possibility of computing t without k implies
- Adversary cannot change the message
- Adversary cannot conjure new messages

## MAC Security

#### Standard notion is UF-CMA

- Goal: Unforgeability
- Adversary power: Chosen Message Attacks

## MAC Security

#### Standard notion is UF-CMA

- Goal: Unforgeability
- Adversary power: Chosen Message Attacks

#### Security Experiment

- Experiment generates a key k
- Adversary (adaptively) sends m to get  $t \leftarrow MAC(k, m)$
- Eventually, attacker outputs  $(m^*, t^*)$

Attacker wins if  $t^* = MAC(k, m^*)$ , and if  $t^*$  was not produced by the experiment. Contrary to IND-CPA, a victory here implies a broken MAC scheme.

### **MAC Security Nuances**

- MAC on its own does not protect against replay attacks
- Suppose a network scenario
  - Attacker sees authenticated message (m, t)
  - Delivers (m, t) multiple times
  - MAC will verify every time!

- MAC on its own does not protect against replay attacks
- Suppose a network scenario
  - Attacker sees authenticated message (m, t)
  - Delivers (m, t) multiple times
  - MAC will verify every time!
- Simple technique: impose message never repeats in network
- Sequence numbers
  - Prepend counter and keep counter as state in both sides
  - Prepend timestamp (local clock reading)
  - How should the receiver operate in both cases?

### Some Context

MACs constructed from hash functions and block ciphers

Simplest construction: prefix key

$$MAC(k, m) = H(K||M)$$
 or  $PRF(k, m) = H(K||M)$ 

### Some Context

MACs constructed from hash functions and block ciphers

Simplest construction: prefix key

$$MAC(k, m) = H(K||M)$$
 or  $PRF(k, m) = H(K||M)$ 

#### MD yields insecure MAC and PRF!

- Given (m, t), attacker outputs H(K||M||pad||M')
- This can be computed just from t' and m'
- Length extension attack

### Some Context

MACs constructed from hash functions and block ciphers

Simplest construction: prefix key

$$MAC(k, m) = H(K||M)$$
 or  $PRF(k, m) = H(K||M)$ 

#### MD yields insecure MAC and PRF!

- Given (m, t), attacker outputs H(K||M||pad||M')
- This can be computed just from t' and m'
- Length extension attack


#### A consideration in SHA-3 construction

- Abandon MD construction
- Include explicit keyed hash

#### **HMAC Construction**

#### When instantiated with MD construction

- Compression function is PRF → Secure MAC
- HMAC is simply  $H((K \oplus opad)||H((k \oplus ipad)||m))$
- ipad and opad are constraints: align to block size



### On Collision-based Forgeries

Hash function collisions  $\rightarrow$  hash-based MAC forgeries However, attacker cannot easily search for them w/o key

### On Collision-based Forgeries

Hash function collisions  $\rightarrow$  hash-based MAC forgeries However, attacker cannot easily search for them w/o key

#### Collisions in MAC also yield forgeries

- True for any MAC
- Collision occur when  $\sqrt{2^n}$  MACs are issued

### Building MACs from Block Ciphers

We have seen block ciphers  $\rightarrow$  hash functions  $\rightarrow$  MACs


But there are also direct constructions: block ciphers  $\rightarrow$  MACs

#### **CMAC**

- Used in IPSec
- CMAC improves on CBC-MAC (which was broken!)
- Use CBC mode of operation
- Fix IV to all zero blocks
- Take the last ciphertext block as a tag

## CMAC fixes CBC-MAC by processing last block differently

- All blocks except last are processed like CBC-MAC
- Keys  $k_1$  and  $k_2$  derived from k
  - $I \leftarrow E(k,0)$
  - $k_1 = (I << 1) \oplus (0 \times 00..0087 * LSB(I)))$
  - $k_2 = (k_1 << 1) \oplus (0 \times 00..0087 * LSB(k_1)))$



## Custom MAC Constructions

More efficient MAC constructions are designed from scratch

Poly1305 is one such construction by D. J. Bernstein

#### Based on

- Universal Hash Functions
- Wegman-Carter construction

### Universal Hash Functions

## UHF are a Weak form of Hashing

- Don't need to be collision resistant
- Parametrised by a key UH(k, m)
- Guarantee that, for two fixed messages  $m_0 \neq m_1$ :

$$\Pr[\mathsf{UH}(k,m_0)=\mathsf{UH}(k,m_1)]\leq \epsilon$$

ullet Considering random k and very small  $\epsilon$ 

## Universal Hash Functions

## UHF are a Weak form of Hashing

- Don't need to be collision resistant
- Parametrised by a key UH(k, m)
- Guarantee that, for two fixed messages  $m_0 \neq m_1$ :

$$\Pr[\mathsf{UH}(k,m_0) = \mathsf{UH}(k,m_1)] \le \epsilon$$

ullet Considering random k and very small  $\epsilon$ 

No other security requirements  $\rightarrow$  easy to construct

We can use a universal hash function as a MAC

Provided that we only authenticate one message!

# Wegman-Carter Construction

#### How to circumvent this limitation?

- Use a PRF to strengthen the UH
- Converts a UH into a fully secure MAC
- AES can fill the PRF role!

# Wegman-Carter Construction

#### How to circumvent this limitation?

- Use a PRF to strengthen the UH
- Converts a UH into a fully secure MAC
- AES can fill the PRF role!

## Intuition: Encrypt Universal Hash Value

$$\mathsf{UH}(k_1,m) \oplus \mathsf{PRF}(k_2,n)$$

- The full MAC key is  $(k_1, k_2)$
- n is a public value that must never repeat
  - A.k.a. a nonce
- This can be kept as a counter, or generated at random

# Poly1305-AES: Wegman-Carter in Practice

- Initial proposal used AES as the Wegman-Carter PRF
- The universal hash function uses prime  $p^{130} 5$

Poly1305
$$((k_1, k_2), m) = (m_1 k + \ldots + m_n k^n \pmod{p}) + AES(k_2, n)$$

- Blocks are 128 bits and last block is padded with 100
- All blocks set bit 129, so MSB is 1
- The final addition is performed modulo  $2^{128}$
- TLS recommends Poly1305 with ChaCha20, rather than AES



- Keyed hashing allows for message authentication
- For hash function h, one cannot produce h(k, x) w/o k
- Provides integrity; ciphers give confidentiality



- Keyed hashing allows for message authentication
- For hash function h, one cannot produce h(k,x) w/o k
- Provides <u>integrity</u>; ciphers give <u>confidentiality</u>
- Just add a key as prefix!
  - Problem! Length extension attacks



- Keyed hashing allows for message authentication
- For hash function h, one cannot produce h(k,x) w/o k
- Provides <u>integrity</u>; ciphers give <u>confidentiality</u>
- Just add a key as prefix!
  - Problem! Length extension attacks
- HMAC
  - Input padding and output padding, both using the key



- Keyed hashing allows for message authentication
- For hash function h, one cannot produce h(k,x) w/o k
- Provides integrity; ciphers give confidentiality
- Just add a key as prefix!
  - Problem! Length extension attacks
- HMAC
  - Input padding and output padding, both using the key
- CMAC
  - Do AES-CBC without IV; return the last block
  - With a twist to prevent prefix extension



- Keyed hashing allows for message authentication
- For hash function h, one cannot produce h(k,x) w/o k
- Provides <u>integrity</u>; ciphers give <u>confidentiality</u>
- Just add a key as prefix!
  - Problem! Length extension attacks
- HMAC
  - Input padding and output padding, both using the key
- CMAC
  - Do AES-CBC without IV; return the last block
  - With a twist to prevent prefix extension
- Wegman-Carter
  - Use a UHF for a unique message
  - XOR it with an encryption of a nonce
  - Used in AES-GCM (next class)

# Applied Cryptography Week 5: Hash Functions and Keyed Hashing

Bernardo Portela

M:ERSI, M:SI, M:CC - 25