

# Mathematics for Computer Science - notes

Angjoo Kanazawa

July 20, 2011

## 8 Chapter 8 Communication Networks

### 8.1 Complete Binary Tree

Definitions/formulas:

- **Switches** direct packets through the network (circle nodes)
- **Latency** is the time required for a packet to travel from an input to an output.
- The **diameter** of a network is the number of switches on the shortest path between the input and output that are farthest apart. Approximates the worst-case latency.
- The diameter of a complete binary tree with  $N$  in/outputs is  $2\log N + 1$ . Not bad, even with  $2^{10}$  terminals, latency is  $2\log(2^{10}) + 1 = 21$
- Total number of switches in a complete binary tree is  $2N - 1$ .
- A **permutation** is a bijective function  $\pi : 0, 1, \dots, N - 1 \rightarrow 0, 1, \dots, N - 1$
- $\forall \pi \exists$  **permutation routing problem**, where the challenge is to direct a packet starting at input  $i$  to output  $\pi(i)$ 
  - Solution: specification for the path taken for all  $N$  packets. Where the path of packet  $i$  to output  $\pi(i)$  is denoted  $P_{i,\pi(i)}$ .
  - The **congestion** of a set of paths  $P_{0,\pi(0)}, \dots, P_{N-1,\pi(N-1)}$ , is the largest number of paths that pass through a single switch. i.e for  $\pi(i) = i$ , the congestion is 1, for  $\pi(i) = (N - 1) - i$ , the congestion is 4. Lower the congestion, the better the set of paths.
  - The **Max congestion** of a network is “maximum over all permutations  $\pi$  of the minimum over all paths’ congestion...  $\arg \max_{\pi} \arg \min_{\text{all possible paths}} Cong(P_{i,\pi(i)})$  where  $Cong$  is the congestion of a given path?
  - The max congestion of a complete binary tree is  $N$  with  $\pi(i) = (N - 1) - i$ , because with that  $\pi$ , every packet needs to go through the root. You can’t do better and its horrible.
  - over all permutation.. =  $N!$  permutations for  $N$  in/out networks. For each of those permutations, there are paths that takes  $i$  to  $\pi(i)$  = a lot of paths, but chose the BEST congestion. And the max of those out of  $N!$  perm is the max congestion..

Goals:

- larger the switches  $\rightarrow$  smaller diameter. Most nodes in a binary tree takes 3 in/out edges = 3x3 switches
- Want: how to get  $N \times N$  monster switch using 3x3 simple switches

## 8.2 2-D Array/Grid/Crossbar

- Diameter of an array with  $N$  in/outputs is  $2N - 1$ .
- Each switch takes two in/out edges, so switch size is  $2 \times 2$ .
- # of switches is the number of elem in  $N \times N$  array  $= N^2$

**Theorem 8.2.1.** *The (max) congestion of an  $N$ -input array is 2*

*Proof.* It's at most 2: Let  $\pi$  be any permutation. Let  $P_{i,\pi(i)}$  to be the path from input  $i$  rightward to col  $j$ , downward to output  $\pi(i)$  (can go other ways but this is the best path), so the  $(i, j)$ th switch transmits at most 2 packets. The one coming from left and the one coming from the top..?

It's at least 2: With  $\pi(0) = 0$  and  $\pi(N - 1) = N - 1$ , the packet in the lower left corner must pass two packets. (It's at least so just show it exists).  $\square$

## 8.3 Butterfly

- All terminals and switches are in  $N$  rows, where inputs, ordered, are the first col, output, ordered, are the last col. Now label the rows in binary, so row  $i$  has binary number  $b_1 b_2 \dots b_{\log N}$  that represents  $i$ .
- $\exists \log(N) + 1$  levels of switches (nodes), numbered from 0 to  $\log N$ . Each level is a column of  $N$  switches. So every switch has a unique sequence  $(b_1, b_2, \dots, b_{\log N}, l)$ , where  $b_1 b_2 \dots b_{\log N}$  is the switch's row label and  $l$  is the level of the switch ( $0 \rightarrow \log N$ ).
- So...  $N \text{ by } 1 \rightarrow N \text{ by } \log(N) + 1 \rightarrow N \text{ by } 1$
- Connection: there are directed edges from  $(b_1, b_2, \dots, b_{\log N}, l)$  to two switches in the next level, one in the same row, one in the row with label  $l + 1$  (inverting bit  $l + 1$ ).
- Recursive structure. A butterfly of size  $2N$  is made up of two  $N$  butterflies plus one more level of switches.

There is only one path from an input to an output, where the path is by correcting each successive bit with the bit of the output.

**Corollary 8.3.1.** *The congestion of the butterfly network is exactly  $\sqrt{N}$  when  $N$  is an even power of 2:*

*Proof.* Let  $B_n$  denote the butterfly network with  $N = 2^n$  inputs and  $N$  outputs.

For  $B_n$ , there is a unique path from each input to each output, so congestion is the max number of transmission for a vertex. (The number of total vertices is  $N(\log(N) + 1)$ , or  $2^n(n + 1)$ ... useless)

For every vertex  $v$  at level  $i$ , there's a path from exactly  $2^i$  input vertices to  $v$  and exactly  $2^{n-i}$  output vertices (where  $n$  is the power of 2).

Since there is a unique path from each input to output, the number of messages that passes through a vertex is at most the minimum of number of input or output vertices it has a path from/to.

So congestion must be worst at the center level of the network. i.e for  $n = 3$ , level 0 vertices have a path from 1 input vertex and have a path to 8 output vertices, level 1 has 2-from and 4-to, level 2 has 4-from and 2-to, and the last level has 8-from and 1-to. Now there are  $n + 1$  levels (or  $\log(N) + 1$ ). So with even  $n$ , there exists a center level with vertices that have a path from exactly  $2^{(n/2)}$  input vertices, and a path to exactly  $2^{n/2}$  output vertices.

Which means that congestion of vertices at the middle level is at most  $\sqrt{N} = 2^{n/2}$ .

... not clear which one is at least and at most.. It's like.. at most and at least because in the middle its  $\sqrt{N}$  from and  $\sqrt{N}$ ..  $\square$

## 8.4 Benes Network

A back to back butterfly.

- Diameter:  $2\log N$ , switch size 2 by 2, # of switches  $2N\log N$ , congestion 1!!

**Theorem 8.4.1.** *The congestion of the  $N$ -input Benes network is 1, where  $N = 2^a$  for some  $a \leq 1$ .*

*Proof.* Inductive: Let  $P(a)$  be the proposition that congestion of the size  $2^a$  Benes network is 1.

Base case: WTS: congestion of  $N = 2^1 = 2$  Benes network is 1. For 2 input network, there are  $2! = 2$  permutations, for identity, we can just take the straight path, for the other one, they'll just take the diagonal. So congestion is 1.

Inductive arg: WTS:  $P(a) \rightarrow P(a+1)$  where  $a \leq 1$ . Key insight: a 2-coloring of the constraints graph corresponds to a solution to the routing problem. If we show that the graph is 2-colorable, that means we can solve the routing problem with such constraints.

Here's a theorem:

**Theorem 8.4.2.** *If the graphs  $G_1(V, E_1)$  and  $G_2 = (V, E_2)$  both have max degree 1, then the egraph  $G = (V, E_1 \cup E_2)$  is 2-colorable.*

Using that idea, let  $\pi$  be any permutation of  $0, 1, \dots, 2N-1$ . Define two graphs with those vertices, but one where with edge  $u-v$  with  $|u-v| = N$ , and one with edge  $u-v$  with  $|\pi(u) - \pi(v)| = N$ . By the above theorem, the graph  $G = (V, E_1 \cup E_2)$  is 2-colorable. Route one color with the upper subnetwork and one color with lower subnetwork. By induction hypothesis  $P(a)$ , the subnetworks can each route any permutation with congestion 1, and so we're done. (We only needed to show that the first and the last levels have congestion 1)  $\square$

## 9 Relations

A *relation* from a set  $A$  to set  $B$  is a subset  $R \subseteq A \times B$ . Where  $R := \{(a, b) | a \in A, b \in B\}$ .  $(a, b) \in R$  also written as  $aRb$ ,  $a \sim_R b$ .

- Relations on one set: Focus on relations on a single set, i.e.  $R \subseteq A \times A$ .
- Relations and Directed Graphs: A relation on a single set  $A$  is the same as a directed graph  $G = (V, E)$  where  $V = A$ , and  $E = R$ .

### 9.1 Properties

A relation  $R$  on a set  $A$  is:

- reflexive:  $\forall x \in A, xRx$
- symmetric/commutative:  $\forall x, y \in A, xRy \Rightarrow yRx$
- antisymmetric:  $\forall x, y \in A, xRy \wedge yRx \Rightarrow x = y$
- transitive:  $\forall x, y, z \in A, xRy \wedge yRz \Rightarrow xRz$

## 9.2 Equivalence Relations

### Definitions:

- A relation is an *equivalence relation* if its reflexive, symmetric, and transitive. i.e.  $Z_n$
- If  $R$  is an equivalence relation on a set  $A$ , *Equivalence class* of an element  $x$ , is  $[x] = \{y | xRy\}$
- A *partition/coset* of a set  $A$  is disjoint, nonempty subsets  $A_1, A_2, \dots, A_n$  s.t.  $A = \bigcup A_i$ .

**Theorem 9.2.1.** *The equivalence classes of an equivalence relation on a set  $A$  form a partition of  $A$ .*

## 9.3 Partial Orders

- A relation is a *partial order* if its reflexive, *antisymmetric*, and transitive. i.e. rings under division,  $\leq$  relation on  $Z$
- Denoted:  $\preceq$ , if  $\preceq$  is a partial order on the set  $A$ ,  $(A, \preceq)$  is called a *poset*.
- From theorem 9.3.1, without self-loops, posets are *DAGs*, directed acyclic graphs.
- $\exists a, b \in (A, \preceq)$  s.t.  $\nexists$  relation.
- such  $a, b$  are *incomparable*. i.e. neither  $a \preceq b$  nor  $b \preceq a$ . Otherwise they are *comparable*.
- A *total order* is a poset where all pairs are comparable.
- A total order is called a *topological sort*. A topological sort of a poset  $(A, \preceq)$  is a total order  $(A, \preceq_T)$  s.t.  $x \preceq y \Rightarrow x \preceq_T y$ .

**Theorem 9.3.1.** *A poset has no directed cycles other than self-loops.*

**Theorem 9.3.2.** *Every finite poset has a topological sort*

**Theorem 9.3.3.** *Every finite poset has a minimal element*