

Online learning using limited feedback

Yoav Freund

February 21, 2006

Outline

The multiple-arm bandits problem

Outline

The multiple-arm bandits problem

The classical analysis - Gittins Index

Outline

The multiple-arm bandits problem

The classical analysis - Gittins Index

The adversarial setup

Outline

The multiple-arm bandits problem

The classical analysis - Gittins Index

The adversarial setup

The basic algorithm

Outline

- The multiple-arm bandits problem
- The classical analysis - Gittins Index
- The adversarial setup
- The basic algorithm
- Lower bound

Outline

- The multiple-arm bandits problem
- The classical analysis - Gittins Index
- The adversarial setup
- The basic algorithm
- Lower bound
- Tuning γ online

Outline

- The multiple-arm bandits problem
- The classical analysis - Gittins Index
- The adversarial setup
- The basic algorithm
- Lower bound
- Tuning γ online
- the non stationary scenario

Outline

- The multiple-arm bandits problem
- The classical analysis - Gittins Index
- The adversarial setup
- The basic algorithm
- Lower bound
- Tuning γ online
- the non stationary scenario
- Combining strategies

Outline

- The multiple-arm bandits problem
- The classical analysis - Gittins Index
- The adversarial setup
- The basic algorithm
- Lower bound
- Tuning γ online
- the non stationary scenario
- Combining strategies
- Summary

The one armed bandit



The multiple arm bandit problem

Given



Play
these
machines



The multiple arm bandit problem

Given



Play
these
machines



Goal: Maximize expected wealth.

The multiple arm bandit problem

Given



Play
these
machines



Goal: Maximize expected wealth.
Mathematical formulation for common
Exploration vs. Exploitation dilemma.

The multiple arm bandit problem

Given



Play
these
machines



Goal: Maximize expected wealth.

Mathematical formulation for common

Exploration vs. Exploitation dilemma.

single-iteration reward is in the range $[0, 1]$

Classical analysis

- Rewards generated **independently at random**

Classical analysis

- ▶ Rewards generated **independently at random**
- ▶ Each machine has a different distribution of rewards.

Classical analysis

- ▶ Rewards generated **independently at random**
- ▶ Each machine has a different distribution of rewards.
- ▶ **Basic idea:** sample so as to minimize uncertainty in identity of best arm.

Playing in a Rigged casino

- ▶ The casino operator watches you and changes rewards of the machines to **confuse** you!

Playing in a Rigged casino

- ▶ The casino operator watches you and changes rewards of the machines to **confuse** you!
- ▶ Can you still find the best machine?

Playing in a Rigged casino

- ▶ The casino operator watches you and changes rewards of the machines to **confuse** you!
- ▶ Can you still find the best machine?
- ▶ What does “**best machine**” mean?

Example adversarial MAB game

Example adversarial MAB game

action1
action2
action3
action4
action5
action6
action7
action8

Example adversarial MAB game

	P_1
action1	1/8
action2	1/8
action3	1/8
action4	1/8
action5	1/8
action6	1/8
action7	1/8
action8	1/8

Example adversarial MAB game

	P_1	i_1
action1	1/8	
action2	1/8	
action3	1/8	
action4	1/8	\Rightarrow
action5	1/8	
action6	1/8	
action7	1/8	
action8	1/8	

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$
action1	1/8		.1
action2	1/8		.8
action3	1/8		.3
action4	1/8	\Rightarrow	.5
action5	1/8		.9
action6	1/8		0
action7	1/8		1
action8	1/8		.8

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$	p_2
action1	1/8		.1	.12
action2	1/8		.8	.12
action3	1/8		.3	.12
action4	1/8	\Rightarrow	.5	.16
action5	1/8		.9	.12
action6	1/8		0	.12
action7	1/8		1	.12
action8	1/8		.8	.12

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$	p_2	i_2
action1	1/8		.1	.12	
action2	1/8		.8	.12	
action3	1/8		.3	.12	
action4	1/8	\Rightarrow	.5	.16	
action5	1/8		.9	.12	
action6	1/8		0	.12	
action7	1/8		1	.12	\Rightarrow
action8	1/8		.8	.12	

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$	p_2	i_2	$\mathbf{x}(2)$
action1	1/8		.1	.12		.1
action2	1/8		.8	.12		.5
action3	1/8		.3	.12		.2
action4	1/8	\Rightarrow	.5	.16		.7
action5	1/8		.9	.12		1
action6	1/8		0	.12		.1
action7	1/8		1	.12	\Rightarrow	.7
action8	1/8		.8	.12		.2

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$	p_2	i_2	$\mathbf{x}(2)$	p^3
action1	1/8		.1	.12		.1	0.11
action2	1/8		.8	.12		.5	0.11
action3	1/8		.3	.12		.2	0.11
action4	1/8	\Rightarrow	.5	.16		.7	0.15
action5	1/8		.9	.12		1	0.11
action6	1/8		0	.12		.1	0.11
action7	1/8		1	.12	\Rightarrow	.7	0.19
action8	1/8		.8	.12		.2	0.11

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$	p_2	i_2	$\mathbf{x}(2)$	p^3	i_3
action1	1/8		.1	.12		.1	0.11	
action2	1/8		.8	.12		.5	0.11	\Rightarrow
action3	1/8		.3	.12		.2	0.11	
action4	1/8	\Rightarrow	.5	.16		.7	0.15	
action5	1/8		.9	.12		1	0.11	
action6	1/8		0	.12		.1	0.11	
action7	1/8		1	.12	\Rightarrow	.7	0.19	
action8	1/8		.8	.12		.2	0.11	

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$	p_2	i_2	$\mathbf{x}(2)$	p^3	i_3	$\mathbf{x}(3)$
action1	1/8		.1	.12		.1	0.11		0
action2	1/8		.8	.12		.5	0.11	\Rightarrow	.2
action3	1/8		.3	.12		.2	0.11		.2
action4	1/8	\Rightarrow	.5	.16		.7	0.15		.8
action5	1/8		.9	.12		1	0.11		.8
action6	1/8		0	.12		.1	0.11		.2
action7	1/8		1	.12	\Rightarrow	.7	0.19		.4
action8	1/8		.8	.12		.2	0.11		.6

Example adversarial MAB game

	P_1	i_1	$\mathbf{x}(1)$	p_2	i_2	$\mathbf{x}(2)$	p^3	i_3	$\mathbf{x}(3)$	total
action1	1/8		.1	.12		.1	0.11		0	.2
action2	1/8		.8	.12		.5	0.11	\Rightarrow	.2	1.5
action3	1/8		.3	.12		.2	0.11		.2	.7
action4	1/8	\Rightarrow	.5	.16		.7	0.15		.8	2.0
action5	1/8		.9	.12		1	0.11		.8	2.7
action6	1/8		0	.12		.1	0.11		.2	.3
action7	1/8		1	.12	\Rightarrow	.7	0.19		.4	2.1
action8	1/8		.8	.12		.2	0.11		.6	1.6

The goal

- ▶ Total reward be close to total reward of best action.

The goal

- ▶ Total reward be close to total reward of best action.
- ▶ **Weak:** in expectation, **Strong:** With high probability.

The goal

- ▶ Total reward be close to total reward of best action.
- ▶ **Weak:** in expectation, **Strong:** With high probability.
- ▶ Why reward instead of loss?

The goal

- ▶ Total reward be close to total reward of best action.
- ▶ **Weak:** in expectation, **Strong:** With high probability.
- ▶ Why reward instead of loss?
- ▶ Because regret bounds that depend on the **loss** of the best action (rather than **T**) are impossible.

The basic algorithm (EXP3)

For each $t = 1, 2, \dots$

1. Set

$$p_i(t) = (1 - \gamma) \frac{w_i^t}{\sum_{j=1}^K w_j^t} + \frac{\gamma}{K} \quad i = 1, \dots, K.$$

The basic algorithm (EXP3)

For each $t = 1, 2, \dots$

1. Set

$$p_i(t) = (1 - \gamma) \frac{w_i^t}{\sum_{j=1}^K w_j^t} + \frac{\gamma}{K} \quad i = 1, \dots, K.$$

2. Draw i_t randomly accordingly to $p_1(t), \dots, p_K(t)$

The basic algorithm (EXP3)

For each $t = 1, 2, \dots$

1. Set

$$p_i(t) = (1 - \gamma) \frac{w_i^t}{\sum_{j=1}^K w_j^t} + \frac{\gamma}{K} \quad i = 1, \dots, K.$$

2. Draw i_t randomly accordingly to $p_1(t), \dots, p_K(t)$

3. Receive reward $x_{i_t}(t) \in [0, 1]$

The basic algorithm (EXP3)

For each $t = 1, 2, \dots$

1. Set

$$p_i(t) = (1 - \gamma) \frac{w_i^t}{\sum_{j=1}^K w_j^t} + \frac{\gamma}{K} \quad i = 1, \dots, K.$$

2. Draw i_t randomly accordingly to $p_1(t), \dots, p_K(t)$

3. Receive reward $x_{i_t}(t) \in [0, 1]$

4. For $j = 1, \dots, K$ set

$$\hat{x}_j(t) = \begin{cases} x_j(t)/p_j(t) & \text{if } j = i_t \\ 0 & \text{otherwise,} \end{cases}$$

$$w_j^{t+1} = w_t^j \exp(\gamma \hat{x}_j(t)/K) .$$

Basic bound

- ▶ Let T be the number of iterations and that algorithm **Exp3** is run with

$$\gamma = \min \left\{ 1, \sqrt{\frac{K \ln K}{(e-1)T}} \right\}.$$

Basic bound

- ▶ Let T be the number of iterations and that algorithm **Exp3** is run with

$$\gamma = \min \left\{ 1, \sqrt{\frac{K \ln K}{(e-1)T}} \right\}.$$

- ▶ Then

$$G_{\max} - \mathbf{E}[G_{\text{Exp3}}] \leq 2\sqrt{e-1}\sqrt{TK \ln K} \leq 2.63\sqrt{TK \ln K}$$

Ideas of proof

1. Setting

$$\hat{x}_j(t) = \begin{cases} x_j(t)/p_j(t) & \text{if } j = i_t \\ 0 & \text{otherwise,} \end{cases}$$

guarantees that $\mathbf{E}\left(\sum_{t=1}^t \hat{x}_j(t)\right) = \sum_{t=1}^T x_j(t)$ i.e. estimate of total gain is **Unbiased**.

Ideas of proof

1. Setting

$$\hat{x}_j(t) = \begin{cases} x_j(t)/p_j(t) & \text{if } j = i_t \\ 0 & \text{otherwise,} \end{cases}$$

guarantees that $\mathbf{E}\left(\sum_{t=1}^t \hat{x}_j(t)\right) = \sum_{t=1}^T x_j(t)$ i.e. estimate of total gain is **Unbiased**.

2. Setting $\gamma = O\left(\sqrt{\frac{K \log K}{T}}\right)$ guarantees **variance** of estimator is not too large.

Ideas of proof

1. Setting

$$\hat{x}_j(t) = \begin{cases} x_j(t)/p_j(t) & \text{if } j = i_t \\ 0 & \text{otherwise,} \end{cases}$$

guarantees that $\mathbf{E}\left(\sum_{t=1}^t \hat{x}_j(t)\right) = \sum_{t=1}^T x_j(t)$ i.e. estimate of total gain is **Unbiased**.

2. Setting $\gamma = O\left(\sqrt{\frac{K \log K}{T}}\right)$ guarantees **variance** of estimator is not too large.
3. **Exp3** mimicks **Hedge** sufficiently well.

Lower bound

- ▶ Choose all gains independently at random to be 0 or 1.

Lower bound

- ▶ Choose all gains independently at random to be 0 or 1.
- ▶ $K - 1$ actions use probs $(1/2, 1/2)$.

Lower bound

- ▶ Choose all gains independently at random to be 0 or 1.
- ▶ $K - 1$ actions use probs $(1/2, 1/2)$.
- ▶ One action (chosen at random) uses probs $1/2 + \epsilon, 1/2 - \epsilon$.

Lower bound

- ▶ Choose all gains independently at random to be 0 or 1.
- ▶ $K - 1$ actions use probs $(1/2, 1/2)$.
- ▶ One action (chosen at random) uses probs $1/2 + \epsilon, 1/2 - \epsilon$.
- ▶ The Bayes optimal algorithm has expected regret at least

$$\frac{1}{20} \min \left(\sqrt{KT}, T \right)$$

Tuning γ online

Algorithm Exp3.1

Initialization: Let $t = 1$, and $\hat{G}_i(1) = 0$ for $i = 1, \dots, K$

Repeat for $r = 0, 1, 2, \dots$

1. Let $g_r = (K \ln K) / (e - 1) 4^r$.

2. Restart Exp3 choosing $\gamma_r = \min \left\{ 1, \sqrt{\frac{K \ln K}{(e - 1)g_r}} \right\}$.

3. **While** $\max_i \hat{G}_i(t) \leq g_r - K/\gamma_r$ **do:**

(a) Let i_t be the random action chosen by Exp3 and $x_{i_t}(t)$ the corresponding reward.

(b) $\hat{G}_i(t+1) = \hat{G}_i(t) + \hat{x}_i(t)$ for $i = 1, \dots, K$.

(c) $t := t + 1$

Bound for Exp3.1

$$G_{\max} - \mathbf{E}[G_{\text{Exp3.1}}] \leq 8\sqrt{e-1}\sqrt{G_{\max}K\ln K} + 8(e-1)K + 2K\ln K$$

Bound for Exp3.1

$$\begin{aligned} G_{\max} - \mathbf{E}[G_{\text{Exp3.1}}] &\leq 8\sqrt{e-1}\sqrt{G_{\max}K\ln K} + 8(e-1)K + 2K\ln K \\ &\leq 10.5\sqrt{G_{\max}K\ln K} + 13.8K + 2K\ln K \end{aligned}$$

Allowing switching actions

Algorithm Exp3.S

Parameters: Reals $\gamma \in (0, 1]$ and $\alpha > 0$.

Initialization: $w_i(1) = 1$ for $i = 1, \dots, K$.

For each $t = 1, 2, \dots$

1. Set

$$p_i(t) = (1 - \gamma) \frac{w_i(t)}{\sum_{j=1}^K w_j(t)} + \frac{\gamma}{K} \quad i = 1, \dots, K.$$

2. Draw i_t according to the probabilities $p_1(t), \dots, p_K(t)$.

3. Receive reward $x_{i_t}(t) \in [0, 1]$.

4. For $j = 1, \dots, K$ set

$$\hat{x}_j(t) = \begin{cases} x_j(t)/p_j(t) & \text{if } j = i_t \\ 0 & \text{otherwise,} \end{cases}$$

$$w_j(t+1) = w_j(t) \exp(\gamma \hat{x}_j(t)/K) + \frac{e\alpha}{K} \sum_{i=1}^K w_i(t).$$

Bound for Exp3.S

- **Hardness** of sequence = number of switches offline is allowed:

$$S \geq H(j_1, \dots, j_T) \stackrel{\text{def}}{=} 1 + |\{1 \leq \ell < T : j_\ell \neq j_{\ell+1}\}| .$$

Bound for Exp3.S

- **Hardness** of sequence = number of switches offline is allowed:

$$S \geq H(j_1, \dots, j_T) \stackrel{\text{def}}{=} 1 + |\{1 \leq \ell < T : j_\ell \neq j_{\ell+1}\}| .$$

- Assume $\alpha = 1/T$ and $\gamma = \min \left\{ 1, \sqrt{\frac{K(S \ln(KT) + e)}{(e-1)T}} \right\} .$

Bound for Exp3.S

- ▶ **Hardness** of sequence = number of switches offline is allowed:

$$S \geq H(j_1, \dots, j_T) \stackrel{\text{def}}{=} 1 + |\{1 \leq \ell < T : j_\ell \neq j_{\ell+1}\}| .$$

- ▶ Assume $\alpha = 1/T$ and $\gamma = \min \left\{ 1, \sqrt{\frac{K(S \ln(KT) + e)}{(e-1)T}} \right\} .$
- ▶ Then

$$G_{j_T} - \mathbf{E} [G_{\text{Exp3.S}}] \leq 2\sqrt{e-1} \sqrt{KT (S \ln(KT) + e)}$$

Combining strategies

- ▶ K possible actions and N prediction strategies or experts.

Combining strategies

- ▶ K possible actions and N prediction strategies or experts.
- ▶ $N \gg K$

Combining strategies

- ▶ K possible actions and N prediction strategies or experts.
- ▶ $N \gg K$
- ▶ Expert i predicts with a distribution over actions
 $\xi^i(t) \in [0, 1]^K$

Combining strategies

- ▶ K possible actions and N prediction strategies or experts.
- ▶ $N \gg K$
- ▶ Expert i predicts with a distribution over actions
 $\xi^i(t) \in [0, 1]^K$
- ▶ Reward of expert i is $\xi^i(t) \cdot \mathbf{x}(t)$

Combining strategies

- ▶ K possible actions and N prediction strategies or experts.
- ▶ $N \gg K$
- ▶ Expert i predicts with a distribution over actions
 $\xi^i(t) \in [0, 1]^K$
- ▶ Reward of expert i is $\xi^i(t) \cdot \mathbf{x}(t)$
- ▶ Considering experts as actions, we get a bound
 $O(\sqrt{gN \log N})$ on the regret.

Combining strategies

- ▶ K possible actions and N prediction strategies or experts.
- ▶ $N \gg K$
- ▶ Expert i predicts with a distribution over actions
 $\xi^i(t) \in [0, 1]^K$
- ▶ Reward of expert i is $\xi^i(t) \cdot \mathbf{x}(t)$
- ▶ Considering experts as actions, we get a bound
 $O(\sqrt{gN \log N})$ on the regret.
- ▶ By acting smarter, we can get a bound $O(\sqrt{gK \log N})$

Allowing switching actions

For each $t = 1, 2, \dots$

1. Get advice vectors $\xi^1(t), \dots, \xi^N(t)$.

2. Set $W_t = \sum_{i=1}^N w_i(t)$ and for $j = 1, \dots, K$ set

$$p_j(t) = (1 - \gamma) \sum_{i=1}^N \frac{w_i(t) \xi_j^i(t)}{W_t} + \frac{\gamma}{K}.$$

3. Draw action i_t randomly according to the probabilities $p_1(t), \dots, p_K(t)$.

4. Receive reward $x_{i_t}(t) \in [0, 1]$.

5. For $j = 1, \dots, K$ set

$$\hat{x}_j(t) = \begin{cases} x_j(t)/p_j(t) & \text{if } j = i_t \\ 0 & \text{otherwise,} \end{cases}$$

6. For $i = 1, \dots, N$ set

$$\begin{aligned} \hat{y}_i(t) &= \xi^i(t) \cdot \hat{\mathbf{x}}(t) \\ w_i(t+1) &= w_i(t) \exp(\gamma \hat{y}_i(t)/K). \end{aligned}$$

Summary

- ▶ We can achieve diminishing regret even when only gain of chosen action is observable.

Summary

- ▶ We can achieve diminishing regret even when only gain of chosen action is observable.
- ▶ The increase in the regret is a result of the limited information. $O(\sqrt{TK \log K})$ instead of $O(\sqrt{T \log K})$.

Summary

- ▶ We can achieve diminishing regret even when only gain of chosen action is observable.
- ▶ The increase in the regret is a result of the limited information. $O(\sqrt{TK \log K})$ instead of $O(\sqrt{T \log K})$.
- ▶ We can handle non-stationary setups.

Summary

- ▶ We can achieve diminishing regret even when only gain of chosen action is observable.
- ▶ The increase in the regret is a result of the limited information. $O(\sqrt{TK \log K})$ instead of $O(\sqrt{T \log K})$.
- ▶ We can handle non-stationary setups.
- ▶ If we have many strategies N but only few actions K we can achieve bounds of the form $O(\sqrt{TK \log N})$.

Summary

- ▶ We can achieve diminishing regret even when only gain of chosen action is observable.
- ▶ The increase in the regret is a result of the limited information. $O(\sqrt{TK \log K})$ instead of $O(\sqrt{T \log K})$.
- ▶ We can handle non-stationary setups.
- ▶ If we have many strategies N but only few actions K we can achieve bounds of the form $O(\sqrt{TK \log N})$.
- ▶ Example application: choosing a route for an IP packet.

Summary

- ▶ We can achieve diminishing regret even when only gain of chosen action is observable.
- ▶ The increase in the regret is a result of the limited information. $O(\sqrt{TK \log K})$ instead of $O(\sqrt{T \log K})$.
- ▶ We can handle non-stationary setups.
- ▶ If we have **many** strategies N but only **few** actions K we can achieve bounds of the form $O(\sqrt{TK \log N})$.
- ▶ Example application: choosing a route for an IP packet.
- ▶ **Next class**: what happens when both opponents use **Hedge**?