#### The **Hedge**( $\eta$ )Algorithm

Yoav Freund

January 8, 2014

**Hedge**( $\eta$ )Algorithm Hedging vs. Halving

#### Bound on total loss

Upper bound on  $\sum_{i=1}^{N} w_i^{T+1}$ Lower bound on  $\sum_{i=1}^{N} w_i^{T+1}$ Combining Upper and Lower bounds

```
Hedge(\eta)Algorithm Hedging vs. Halving
```

#### Bound on total loss

```
Upper bound on \sum_{i=1}^{N} w_i^{T+1}
Lower bound on \sum_{i=1}^{N} w_i^{T+1}
Combining Upper and Lower bounds
```

tuning  $\eta$ 

```
Hedge(\eta)Algorithm Hedging vs. Halving
```

#### Bound on total loss

Upper bound on  $\sum_{i=1}^{N} w_i^{T+1}$ Lower bound on  $\sum_{i=1}^{N} w_i^{T+1}$ Combining Upper and Lower bounds

tuning  $\eta$ 

Lower Bounds

N possible actions

- N possible actions
- At each time step t = 1, 2, ..., T:

- N possible actions
- At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.

- N possible actions
- ▶ At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.
  - ▶ Losses  $0 \le \ell_i^t \le 1$  of all actions i = 1, ..., N are revealed.

- N possible actions
- At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.
  - ▶ Losses  $0 \le \ell_i^t \le 1$  of all actions i = 1, ..., N are revealed.
  - Algorithm suffers expected loss p<sup>t</sup> ⋅ ℓ<sup>t</sup>

- N possible actions
- ▶ At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.
  - ▶ Losses  $0 \le \ell_i^t \le 1$  of all actions i = 1, ..., N are revealed.
  - ▶ Algorithm suffers expected loss p<sup>t</sup> · ℓ<sup>t</sup>
- ► Goal: minimize total expected loss

- N possible actions
- At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.
  - ▶ Losses  $0 \le \ell_i^t \le 1$  of all actions i = 1, ..., N are revealed.
  - Algorithm suffers expected loss p<sup>t</sup> · l<sup>t</sup>
- Goal: minimize total expected loss
- ▶ What is p<sup>t</sup>?

- N possible actions
- At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.
  - ▶ Losses  $0 \le \ell_i^t \le 1$  of all actions i = 1, ..., N are revealed.
  - Algorithm suffers expected loss p<sup>t</sup> · l<sup>t</sup>
- Goal: minimize total expected loss
- What is p<sup>t</sup>?
  - Distribution wealth in a portfolio.

- N possible actions
- At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.
  - ▶ Losses  $0 \le \ell_i^t \le 1$  of all actions i = 1, ..., N are revealed.
  - Algorithm suffers expected loss p<sup>t</sup> · l<sup>t</sup>
- Goal: minimize total expected loss
- What is p<sup>t</sup>?
  - Distribution wealth in a portfolio.
  - The algorithm chooses one of the actions at random.

- N possible actions
- At each time step t = 1, 2, ..., T:
  - Algorithm chooses a distribution p<sup>t</sup> over actions.
  - ▶ Losses  $0 \le \ell_i^t \le 1$  of all actions i = 1, ..., N are revealed.
  - Algorithm suffers expected loss p<sup>t</sup> · l<sup>t</sup>
- Goal: minimize total expected loss
- ▶ What is p<sup>t</sup>?
  - Distribution wealth in a portfolio.
  - The algorithm chooses one of the actions at random.
- Prediction is a game played between algorithm and nature, in which the goal of the algorithm is to minimize regret.

Experts interaction (1 round):

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.
  - 2. Algorithm makes it's prediction.

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.
  - 2. Algorithm makes it's prediction.
  - 3. Nature Chooses label/outcome.

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.
  - 2. Algorithm makes it's prediction.
  - 3. Nature Chooses label/outcome.
  - Loss is associated with each action according to a loss function.

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.
  - 2. Algorithm makes it's prediction.
  - 3. Nature Chooses label/outcome.
  - Loss is associated with each action according to a loss function.
- Actions interaction (1 round):

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.
  - 2. Algorithm makes it's prediction.
  - 3. Nature Chooses label/outcome.
  - Loss is associated with each action according to a loss function.
- Actions interaction (1 round):
  - 1. **Algorithm** a distribution over the actions.

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.
  - 2. Algorithm makes it's prediction.
  - 3. Nature Chooses label/outcome.
  - Loss is associated with each action according to a loss function.
- Actions interaction (1 round):
  - 1. **Algorithm** a distribution over the actions.
  - Nature reveals the loss of each action.

- Experts interaction (1 round):
  - 1. **Experts** make their predictions.
  - 2. **Algorithm** makes it's prediction.
  - 3. Nature Chooses label/outcome.
  - Loss is associated with each action according to a loss function.
- Actions interaction (1 round):
  - 1. **Algorithm** a distribution over the actions.
  - 2. Nature reveals the loss of each action.
  - Loss of algorithm is expected loss wrt to chosen distribution.

► Expert framework assumes more structure: algorithm gets expert predictions before choosing it's own prediction. The set of loss vectors is restricted - better for algorithm. Experts framework achieves better bounds.

- Expert framework assumes more structure: algorithm gets expert predictions before choosing it's own prediction. The set of loss vectors is restricted - better for algorithm. Experts framework achieves better bounds.
- Actions framework assumes bounded losses: In exprets framework, we can deal with some unbounded loss functions.

- Expert framework assumes more structure: algorithm gets expert predictions before choosing it's own prediction. The set of loss vectors is restricted - better for algorithm. Experts framework achieves better bounds.
- Actions framework assumes bounded losses: In exprets framework, we can deal with some unbounded loss functions.
- Partial visibility: In experts framework, the outcome defines all of the losses. In actions framework you might not know the loss of all of the actions (the multiple-arm-bandit problem).

- Expert framework assumes more structure: algorithm gets expert predictions before choosing it's own prediction. The set of loss vectors is restricted - better for algorithm. Experts framework achieves better bounds.
- Actions framework assumes bounded losses: In exprets framework, we can deal with some unbounded loss functions.
- Partial visibility: In experts framework, the outcome defines all of the losses. In actions framework you might not know the loss of all of the actions (the multiple-arm-bandit problem).
- Actions framework is simple and general: We can usually get bounds in the experts framework using algorithm designed for the actions framework, but the constants can be worse.

- Expert framework assumes more structure: algorithm gets expert predictions before choosing it's own prediction. The set of loss vectors is restricted - better for algorithm. Experts framework achieves better bounds.
- Actions framework assumes bounded losses: In exprets framework, we can deal with some unbounded loss functions.
- Partial visibility: In experts framework, the outcome defines all of the losses. In actions framework you might not know the loss of all of the actions (the multiple-arm-bandit problem).
- Actions framework is simple and general: We can usually get bounds in the experts framework using algorithm designed for the actions framework, but the constants can be worse.

- Expert framework assumes more structure: algorithm gets expert predictions before choosing it's own prediction. The set of loss vectors is restricted - better for algorithm. Experts framework achieves better bounds.
- Actions framework assumes bounded losses: In exprets framework, we can deal with some unbounded loss functions.
- Partial visibility: In experts framework, the outcome defines all of the losses. In actions framework you might not know the loss of all of the actions (the multiple-arm-bandit problem).
- Actions framework is simple and general: We can usually get bounds in the experts framework using algorithm designed for the actions framework, but the constants can be worse.

▶ Like halving - we want to zoom into best action.

- Like halving we want to zoom into best action.
- Unlike halving no action is perfect.

- Like halving we want to zoom into best action.
- Unlike halving no action is perfect.
- Basic idea reduce probability of lossy actions, but not all the way to zero.

- Like halving we want to zoom into best action.
- Unlike halving no action is perfect.
- Basic idea reduce probability of lossy actions, but not all the way to zero.
- Modified Goal: minimize Regret=difference between expected total loss and minimal total loss of repeating one action.

$$\sum_{t=1}^{T} \mathbf{p}^{t} \cdot \ell^{t} - \min_{i} \left( \sum_{t=1}^{T} \ell_{i}^{t} \right)$$

# Using Hedge to generalize halving alg.

Suppose that there is no perfect action.

## Using Hedge to generalize halving alg.

- Suppose that there is no perfect action.
- ▶ actions: i for  $i \in (1, 2, ..., N)$

- Suppose that there is no perfect action.
- $\blacktriangleright$  actions: i for  $i \in (1, 2, ..., N)$
- Now each iteration t ∈ {1,..., T} of game consists of two steps:

- Suppose that there is no perfect action.
- $\blacktriangleright$  actions: i for  $i \in (1, 2, ..., N)$
- Now each iteration t ∈ {1,..., T} of game consists of two steps:
  - Algorithm chooses a distribution  $\mathbf{p}^t = (\mathbf{p}_1^t, \dots, \mathbf{p}_N^t)$  over the actions.

- Suppose that there is no perfect action.
- $\blacktriangleright$  actions: i for  $i \in (1, 2, ..., N)$
- Now each iteration  $t \in \{1, ..., T\}$  of game consists of two steps:
  - ▶ Algorithm chooses a distribution  $\mathbf{p}^t = (\mathbf{p}_1^t, \dots, \mathbf{p}_N^t)$  over the actions.
  - Nature chooses the loss of each action:  $\ell^t = (\ell_1^t, \dots, \ell_N^t), \ell_i^t \in [0, 1]$

- Suppose that there is no perfect action.
- $\blacktriangleright$  actions: i for  $i \in (1, 2, ..., N)$
- Now each iteration  $t \in \{1, ..., T\}$  of game consists of two steps:
  - Algorithm chooses a distribution  $\mathbf{p}^t = (\mathbf{p}_1^t, \dots, \mathbf{p}_N^t)$  over the actions.
  - Nature chooses the loss of each action:  $\ell^t = (\ell_1^t, \dots, \ell_N^t), \ell_i^t \in [0, 1]$
- ▶ Algorithm's cumulative loss is  $L_A^T = \sum_{t=1}^T \mathbf{p}^t \cdot \ell^t$

- Suppose that there is no perfect action.
- ▶ actions: i for  $i \in (1, 2, ..., N)$
- Now each iteration  $t \in \{1, ..., T\}$  of game consists of two steps:
  - Algorithm chooses a distribution  $\mathbf{p}^t = (\mathbf{p}_1^t, \dots, \mathbf{p}_N^t)$  over the actions.
  - Nature chooses the loss of each action:  $\ell^t = (\ell_1^t, \dots, \ell_N^t), \ell_i^t \in [0, 1]$
- ▶ Algorithm's cumulative loss is  $L_A^T = \sum_{t=1}^T \mathbf{p}^t \cdot \ell^t$
- ► Cumulative loss of action *i* is  $L_i^t = \sum_{t=1}^T \ell_i^t$

- Suppose that there is no perfect action.
- ▶ actions: i for  $i \in (1, 2, ..., N)$
- Now each iteration  $t \in \{1, ..., T\}$  of game consists of two steps:
  - Algorithm chooses a distribution  $\mathbf{p}^t = (\mathbf{p}_1^t, \dots, \mathbf{p}_N^t)$  over the actions.
  - Nature chooses the loss of each action:  $\ell^t = (\ell^t_1, \dots, \ell^t_N), \ell^t_i \in [0, 1]$
- ▶ Algorithm's cumulative loss is  $L_A^T = \sum_{t=1}^T \mathbf{p}^t \cdot \ell^t$
- ▶ Cumulative loss of action *i* is  $L_i^t = \sum_{t=1}^T \ell_i^t$
- ▶ Our goal is to minimize the **regret**:  $L_A^t \min_i L_i^t$  for all t and all possible loss sequences.

Consider action *i* at time *t* 

► Total loss:

$$L_i^t = \sum_{s=1}^{t-1} \ell_i^s$$

Consider action *i* at time *t* 

Total loss:

$$L_i^t = \sum_{s=1}^{t-1} \ell_i^s$$

$$\mathbf{w}_i^t = \mathbf{e}^{-\eta L_i^t}$$

Consider action *i* at time *t* 

► Total loss:

$$L_i^t = \sum_{s=1}^{t-1} \ell_i^s$$

Weight:

$$\mathbf{w}_i^t = \mathbf{e}^{-\eta L_i^t}$$

▶  $\eta > 0$  is the learning rate parameter. Halving:  $\eta \to \infty$ 

Consider action *i* at time *t* 

► Total loss:

$$L_i^t = \sum_{s=1}^{t-1} \ell_i^s$$

$$\mathbf{w}_i^t = \mathbf{e}^{-\eta L_i^t}$$

- ▶  $\eta > 0$  is the learning rate parameter. Halving:  $\eta \to \infty$
- Probability:

$$p_i^t = \frac{w_i^t}{\sum_{i=1}^N w_i^t},$$

Consider action *i* at time *t* 

► Total loss:

$$L_i^t = \sum_{s=1}^{t-1} \ell_i^s$$

$$\mathbf{w}_i^t = \mathbf{e}^{-\eta L_i^t}$$

- ▶  $\eta > 0$  is the learning rate parameter. Halving:  $\eta \to \infty$
- Probability:

$$p_i^t = \frac{w_i^t}{\sum_{i=1}^N w_i^t},$$

Consider action *i* at time *t* 

► Total loss:

$$L_i^t = \sum_{s=1}^{t-1} \ell_i^s$$

$$\mathbf{w}_i^t = \mathbf{e}^{-\eta L_i^t}$$

- ▶  $\eta > 0$  is the learning rate parameter. Halving:  $\eta \to \infty$
- Probability:

$$\rho_i^t = \frac{w_i^t}{\sum_{j=1}^N w_i^t}, \ \mathbf{p}^t = \frac{\mathbf{w}^t}{\sum_{j=1}^N w_i^t}$$

# Bound on the loss of $Hedge(\eta)$ Algorithm

## Bound on the loss of **Hedge**( $\eta$ )Algorithm

Theorem (main theorem)
For any sequence of loss vectors ℓ¹,..., ℓ<sup>T</sup>, and for any
i ∈ {1,..., N}, we have

$$L_{\mathsf{Hedge}(\eta)} \leq \frac{\mathsf{In}(N) + \eta L_i}{1 - e^{-\eta}}.$$

# Bound on the loss of $Hedge(\eta)$ Algorithm

► Theorem (main theorem)
For any sequence of loss vectors  $\ell^1, \dots, \ell^T$ , and for any  $i \in \{1, \dots, N\}$ , we have

$$L_{\mathsf{Hedge}(\eta)} \leq rac{\mathsf{In}(\mathcal{N}) + \eta L_i}{1 - e^{-\eta}}.$$

► Proof: by combining upper and lower bounds on  $\sum_{i=1}^{N} w_i^{T+1}$ 

# Upper bound on $\sum_{i=1}^{N} w_i^{T+1}$

Lemma (upper bound)

For any sequence of loss vectors  $\ell^1, \dots, \ell^T$  we have

$$\ln\left(\sum_{i=1}^N w_i^{T+1}\right) \le -(1-e^{-\eta})L_{\mathsf{Hedge}(\eta)}.$$


▶ If  $a \ge 0$  then  $a^r$  is convex.

Upper bound on  $\sum_{i=1}^{N} w_i^{T+1}$ 

## Proof of upper bound (slide 1)

- ▶ If a > 0 then a' is convex.
- ► For  $r \in [0, 1]$ ,  $a^r \le 1 (1 a)r$

- ▶ If  $a \ge 0$  then  $a^r$  is convex.
- ▶ For  $r \in [0, 1]$ ,  $a^r \le 1 (1 a)r$



Applying 
$$a^r \le 1 - (1 - a)^r$$
 where  $a = e^{-\eta}, r = \ell_i^t$ 

$$\sum_{i=1}^{N} w_i^{t+1} = \sum_{i=1}^{N} w_i^t e^{-\eta \ell_i^t}$$

Applying 
$$a^r \le 1 - (1 - a)^r$$
 where  $a = e^{-\eta}, r = \ell_i^t$ 

$$\sum_{i=1}^{N} w_{i}^{t+1} = \sum_{i=1}^{N} w_{i}^{t} e^{-\eta \ell_{i}^{t}}$$

$$\leq \sum_{i=1}^{N} w_{i}^{t} \left(1 - (1 - e^{-\eta}) \ell_{i}^{t}\right)$$

Applying  $a^r \le 1 - (1 - a)^r$  where  $a = e^{-\eta}, r = \ell_i^t$ 

$$\sum_{i=1}^{N} w_i^{t+1} = \sum_{i=1}^{N} w_i^t e^{-\eta \ell_i^t} 
\leq \sum_{i=1}^{N} w_i^t \left( 1 - (1 - e^{-\eta}) \ell_i^t \right) 
= \left( \sum_{i=1}^{N} w_i^t \right) \left( 1 - (1 - e^{-\eta}) \frac{\mathbf{w}^t}{\sum_{i=1}^{N} w_i^t} \cdot \ell^t \right)$$

Applying  $a^r \le 1 - (1 - a)^r$  where  $a = e^{-\eta}, r = \ell_i^t$ 

$$\begin{split} \sum_{i=1}^{N} w_i^{t+1} &= \sum_{i=1}^{N} w_i^t e^{-\eta \ell_i^t} \\ &\leq \sum_{i=1}^{N} w_i^t \left( 1 - (1 - e^{-\eta}) \ell_i^t \right) \\ &= \left( \sum_{i=1}^{N} w_i^t \right) \left( 1 - (1 - e^{-\eta}) \frac{\mathbf{w}^t}{\sum_{i=1}^{N} w_i^t} \cdot \ell^t \right) \\ &= \left( \sum_{i=1}^{N} w_i^t \right) \left( 1 - (1 - e^{-\eta}) \mathbf{p}^t \cdot \ell^t \right) \end{split}$$

$$\sum_{i=1}^{N} w_i^{t+1} \le \left(\sum_{i=1}^{N} w_i^{t}\right) \left(1 - (1 - e^{-\eta}) \mathbf{p}^{t} \cdot \ell^{t}\right)$$

$$\sum_{i=1}^N w_i^{t+1} \leq \left(\sum_{i=1}^N w_i^t\right) \left(1 - (1 - e^{-\eta}) \mathbf{p}^t \cdot \ell^t\right)$$

$$ightharpoonup$$
 for  $t = 1, \dots, T$ 

$$\sum_{i=1}^{N} w_i^{t+1} \leq \left(\sum_{i=1}^{N} w_i^t\right) \left(1 - (1 - e^{-\eta})\mathbf{p}^t \cdot \ell^t\right)$$

- ightharpoonup for  $t = 1, \dots, T$
- yields

$$\sum_{i=1}^{N} w_i^{T+1} \leq N \prod_{t=1}^{T} (1 - (1 - e^{-\eta}) \mathbf{p}^t \cdot \ell^t)$$

$$\sum_{i=1}^{N} w_i^{t+1} \leq \left(\sum_{i=1}^{N} w_i^t\right) \left(1 - (1 - e^{-\eta})\mathbf{p}^t \cdot \ell^t\right)$$

- ightharpoonup for  $t = 1, \dots, T$
- yields

$$\sum_{i=1}^{N} w_i^{T+1} \leq N \prod_{t=1}^{T} (1 - (1 - e^{-\eta}) \mathbf{p}^t \cdot \ell^t)$$

$$\sum_{i=1}^N w_i^{t+1} \leq \left(\sum_{i=1}^N w_i^t\right) \left(1 - (1 - e^{-\eta})\mathbf{p}^t \cdot \ell^t\right)$$

- ightharpoonup for  $t = 1, \ldots, T$
- yields

$$\sum_{i=1}^{N} w_i^{T+1} \leq N \prod_{t=1}^{T} (1 - (1 - e^{-\eta}) \mathbf{p}^t \cdot \ell^t)$$

$$\leq \exp \left( \ln N - (1 - e^{-\eta}) \sum_{t=1}^{T} \mathbf{p}^t \cdot \ell^t \right)$$

since 
$$1 + x \le e^x$$
 for  $x = -(1 - e^{-\eta})$ .

# Lower bound on $\sum_{i=1}^{N} w_i^{T+1}$

For any 
$$j = 1, \dots, N$$
:

$$\sum_{i=1}^{N} w_i^{T+1} \ge w_j^{T+1} = e^{-\eta L_j}$$

## Combining Upper and Lower bounds

► Combining bounds on  $\ln \left( \sum_{i=1}^{N} w_i^{T+1} \right)$ 

$$-\eta L_{j} \leq \ln \sum_{i=1}^{N} w_{i}^{T+1} \leq \ln N - (1 - e^{-\eta}) \sum_{t=1}^{T} \mathbf{p}^{t} \cdot \ell^{t}$$

## Combining Upper and Lower bounds

► Combining bounds on  $\ln \left( \sum_{i=1}^{N} w_i^{T+1} \right)$ 


$$-\eta L_{j} \leq \ln \sum_{i=1}^{N} w_{i}^{T+1} \leq \ln N - (1 - e^{-\eta}) \sum_{t=1}^{T} \mathbf{p}^{t} \cdot \ell^{t}$$

► Reversing signs, using  $L_{\text{Hedge}(\eta)} = \sum_{t=1}^{T} \mathbf{p}^t \cdot \boldsymbol{\ell}^t$  and reorganizing we get

$$L_{\mathsf{Hedge}(\eta)} \leq \frac{\ln N + \eta L_i}{1 - e^{-\eta}}$$

How to Use Expert Advice

451



▶ Suppose  $\min_i L_i \leq \tilde{L}$ 

- ▶ Suppose  $\min_i L_i \leq \tilde{L}$
- set

$$\eta = \ln\left(1 + \sqrt{rac{2 \ln N}{\tilde{L}}}
ight) pprox \sqrt{rac{2 \ln N}{\tilde{L}}}$$

- ▶ Suppose  $\min_i L_i \leq \tilde{L}$
- set

$$\eta = \ln\left(1 + \sqrt{\frac{2\ln N}{\tilde{L}}}\right) \approx \sqrt{\frac{2\ln N}{\tilde{L}}}$$

Then

$$L_{\mathsf{Hedge}(\eta)} \leq \frac{-\ln(w_i^1) + \eta L_i}{1 - e^{-\eta}} \leq \min_i L_i + \sqrt{2\tilde{L} \ln N} + \ln N$$

#### Tuning $\eta$ as a function of T

▶ trivially  $\min_i L_i \leq T$ , yielding

$$L_{\mathsf{Hedge}(\eta)} \leq \min_i L_i + \sqrt{2T \ln N} + \ln N$$

# Tuning $\eta$ as a function of T

▶ trivially  $\min_i L_i \leq T$ , yielding

$$L_{\mathsf{Hedge}(\eta)} \leq \min_i L_i + \sqrt{2T \ln N} + \ln N$$

per iteration we get:

$$\frac{L_{\mathsf{Hedge}(\eta)}}{T} \leq \min_{i} \frac{L_{i}}{T} + \sqrt{\frac{2 \ln N}{T}} + \frac{\ln N}{T}$$

# How good is this bound?

Very good! There is a closely matching lower bound!

# How good is this bound?

- Very good! There is a closely matching lower bound!
- There exists a stochastic adversarial strategy such that with high probability for any hedging strategy S after T trials

$$L_{S} - \min_{i} L_{i} \geq (1 - o(1))\sqrt{2T \ln N}$$

#### How good is this bound?

- Very good! There is a closely matching lower bound!
- There exists a stochastic adversarial strategy such that with high probability for any hedging strategy S after T trials

$$L_{S} - \min_{i} L_{i} \geq (1 - o(1))\sqrt{2T \ln N}$$

► The adversarial strategy is random, extremely simple, and does not depend on the hedging strategy!

Adversary sets each loss  $\ell_i^t$  indepedently at random to 0 or 1 with equal probabilities (1/2, 1/2).


- Adversary sets each loss  $\ell_i^t$  indepedently at random to 0 or 1 with equal probabilities (1/2, 1/2).
- ► Obviously, nothing to learn !  $L_S \approx T/2$ .

- Adversary sets each loss  $\ell_i^t$  indepedently at random to 0 or 1 with equal probabilities (1/2, 1/2).
- ► Obviously, nothing to learn!  $L_S \approx T/2$ .
- ▶ On the other hand  $\min_i L_i \approx T/2 \sqrt{2T \ln N}$

- Adversary sets each loss  $\ell_i^t$  independently at random to 0 or 1 with equal probabilities (1/2, 1/2).
- ► Obviously, nothing to learn!  $L_S \approx T/2$ .
- ▶ On the other hand  $\min_i L_i \approx T/2 \sqrt{2T \ln N}$
- ► The difference L<sub>S</sub> min<sub>i</sub> L<sub>i</sub> is due to unlearnable random fluctuations!

- Adversary sets each loss  $\ell_i^t$  indepedently at random to 0 or 1 with equal probabilities (1/2, 1/2).
- ► Obviously, nothing to learn !  $L_S \approx T/2$ .
- ▶ On the other hand  $\min_i L_i \approx T/2 \sqrt{2T \ln N}$
- ► The difference L<sub>S</sub> min<sub>i</sub> L<sub>i</sub> is due to unlearnable random fluctuations!
- Detailed proof in "Adaptive Game playing using multiplicative weights" Freund and Schapire.

#### The adversarial construction



#### Summary

▶ Given learning rate  $\eta$  the **Hedge**( $\eta$ )algorithm satisfies

$$L_{\mathsf{Hedge}(\eta)} \leq rac{\ln N + \eta L_i}{1 - e^{-\eta}}$$

#### Summary

▶ Given learning rate  $\eta$  the **Hedge**( $\eta$ )algorithm satisfies

$$L_{\mathsf{Hedge}(\eta)} \leq rac{\ln N + \eta L_i}{1 - e^{-\eta}}$$

▶ Setting  $\eta \approx \sqrt{\frac{2 \ln N}{T}}$  guarantees

$$L_{\mathsf{Hedge}(\eta)} \leq \min_i L_i + \sqrt{2T \ln N} + \ln N$$

# Summary

▶ Given learning rate  $\eta$  the **Hedge**( $\eta$ )algorithm satisfies

$$L_{\mathsf{Hedge}(\eta)} \leq rac{\ln N + \eta L_i}{1 - e^{-\eta}}$$

▶ Setting  $\eta \approx \sqrt{\frac{2 \ln N}{T}}$  guarantees

$$L_{\mathsf{Hedge}(\eta)} \leq \min_i L_i + \sqrt{2T \ln N} + \ln N$$

A trivial random data, for which there is nothing to be learned forces any algorithm to suffer this total regret.