

000  
001  
002  
003  
004  
005  
006  
007  
008  
009  
010  
011  
012  
013  
014  
015  
016  
017  
018  
019  
020  
021  
022  
023  
024  
025  
026  
027  
028  
029  
030  
031  
032  
033  
034  
035  
036  
037  
038  
039  
040  
041  
042  
043  
044  
045  
046  
047  
048  
049  
050  
051  
052  
053

---

# Optimal independence tests for Bayesian Networks

---

Anonymous Author(s)

Affiliation

Address

email

## Abstract

## 1 Introduction

Learning Bayesian networks for general distributions is intractable task Chickering [1996]. However, in practise for distributions appearing in real data, still we are able to recover Bayesian network structure. This implies that real data distribution has some special properties, which simplify process of structure recovery. This process is almost always based on computation local statistics, and then reasoning about global structure Jaakkola et al. [2010]; Tsamardinos et al. [2006]. Local statistics describe complexity (e.g. number of parameters in case of BIC), and level of independence between nodes (e.g. mutual information tests, conditional independence tests). We focus in this work on improvement of independence tests by learning it for CPDs present in data.

We consider parameterized family of independence tests. Before inferring about structure of Bayesian network, we tune classifier predict independence or dependence on CPDs present in data. This way, we obtain highly sensitive independence test, which fires on dependence or independence phenomenas present in our data.

## 2 Related work

Independence tests used in Bayesian networks

- Schäfer and Strimmer [2005] Here they learn a Gaussian Graphical Model (GGM) using estimates of the partial correlation matrix.
- Opgen-Rhein and Strimmer [2007] Here they learn an approximate causal structure on gene expression based on full-order partial correlation (as an approximation to lower-order partial correlation that is called for theoretically for a Bayesian network).
- Tsamardinos et al. [2006] MMHC algorithm. They use a test based on what is called the  $G^2$  statistic (asymptotically distributed as  $\chi^2$ ) and they also talk about a couple other independence tests that we may want to look into.

There has been extensive research in area of scoring functions for Bayesian networks. This step is critical to recover no-complete graph structure. Without any scoring function, log-likelihood term would force optimization to choose fully connected graph. There have been proposed few regularizations (scoring functions) to address this problem. One most widely used is Bayesian Information Criterion (BIC) Schwarz et al. [1978]. Variety of such scoring functions calculate dependency between nodes conditioned on potential parents De Campos [2006]. Usual measures of dependency are based on mutual information, conditional independence test, or are fully Bayesian. Fully Bayesian methods assume probability distribution over CPDs of independent variables, and dependent variables.

We should discuss:

- LL (Log-likelihood) (1912-22)
- MDL/BIC (Minimum description length/Bayesian Information Criterion) (1978)
- AIC (Akaike Information Criterion) (1974)
- NML (Normalized Minimum Likelihood) (2008)
- MIT (Mutual Information Tests) (2006)

Use in Bayesian networks Schäfer and Strimmer [2005]

Existing independence tests:


- Pearson's  $\chi$ -squared. The problem is the null hypothesis is independence, but independence is what we're trying to show.

Margaritis [2003]

### 3 Independence testing

TODO : Wojciech (give a pass to Arthur Gretton) Independence tests have to decide if random variables are independent. Samples of this random variables gives us indirect access to the conditional probability distribution (CPD), which decides on independence. However, samples itself provide only empirical estimate on conditional probability distribution. Moreover, manifold 1 of independent CPDs among all possible CPDs have a measure zero.

Manifold of Independence



**Figure 1:** The manifold of independence for binary distributions. The simplex represents all possible joint distributions over two binary variables.  $a$ ,  $b$ , and  $c$  are three of the four entries in the joint distribution table, and the simplex is formed by the constraint that all entries must be positive and sum to one. The manifold corresponds to the set (of measure zero) of independent distributions.

#### 3.1 Curse of conditioning

#### 3.2 Partial correlation

#### 3.3 Kernelized partial correlation

### 4 Experiments

#### 4.1 Classification of Synthetic CPDs

We generated distributions from toy Bayesian networks.




Figure 2: A




Figure 3: A

## 4.2 Classification of CPDs from Gene Expression

## 4.3 Synthetic Bayesian networks

## 4.4 Gene expression data

## 5 Discussion

## References

- D. M. Chickering. Learning bayesian networks is np-complete. In *Learning from data*, pages 121–130. Springer, 1996.
- L. M. De Campos. A scoring function for learning bayesian networks based on mutual information and conditional independence tests. *The Journal of Machine Learning Research*, 7:2149–2187, 2006.
- T. Jaakkola, D. Sontag, A. Globerson, and M. Meila. Learning bayesian network structure using lp relaxations. In *International Conference on Artificial Intelligence and Statistics*, pages 358–365, 2010.
- D. Margaritis. *Learning Bayesian network model structure from data*. PhD thesis, University of Pittsburgh, 2003.
- R. Opgen-Rhein and K. Strimmer. From correlation to causation networks: a simple approximate learning algorithm and its application to high-dimensional plant gene expression data. *BMC systems biology*, 1(1): 37, 2007.

162 J. Schäfer and K. Strimmer. An empirical bayes approach to inferring large-scale gene association networks.  
163 *Bioinformatics*, 21(6):754–764, 2005.

164 G. Schwarz et al. Estimating the dimension of a model. *The annals of statistics*, 6(2):461–464, 1978.

165 I. Tsamardinos, L. E. Brown, and C. F. Aliferis. The max-min hill-climbing bayesian network structure learning  
166 algorithm. *Machine learning*, 65(1):31–78, 2006.

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215