



FEATURES

- MICROPROCESSOR BASED ELECTRONICALLY DRIVEN VENTILATOR
- PATIENT DATA MONITORING LIKE TIDAL VOLUME, PEAK AIRWAY PRESSURE
- CMV/AV (VC), CMV/AV (PC), SIMV (VC), SIMV (PC), NIV (OPTIONAL)
- OPTION FOR VOLUME AND PRESSURE CONTROL
- FACILITY OF CPAP AND PRESSURE SUPPORT
- APNEA BACKUP
- ELECTRONIC FIO2 CONTROLLER
- GRAPHIC DISPLAY OF CURVE
- STANDBY AND ALL SAFETY ALARM
- USER FRIENDLY
- BATTERY BACKUP



SPECIFICATIONS :

Source Operating Pressure	: 40 to 60 PSI
Functional Characteristics	: Flow Generator
Gas supply	: Oxygen at 3 to 4 bar and air from external air compressor or From air pipe line
Mode of Ventilation	: CMV/AV (VC), CMV/AV (PC), SIMV (VC),
Oxygen Concentration	: 21% to 100%
Frequency	: 80 BPM
Tidal Volume	: 50 – 1500 ml
Inspiratory Time	: 0.3 To 5 sec
Inspiratory Flow	: 120 L/min
Inspiratory Pressure	: 60 cm H2O
PEEP/CPAP	: 0 TO 20 cm H2O
Trigger Sensitivity	: 0 To – 10 cm H2O Bellow CPAP
Pressure Support	: 0 to 40 cm H2O
Apnea Backup	: Programable
PIP	: 10 To 60 cm H2O
Panel Lock	: Automatic
Alarm	: Low / High Pressure
Equipment Alarm	: Gas-Supply Failure, Power Failure etc.
Monitored Parameter	: Peak Inspiratory Pressure, PEEP, Tidal Volume, FIO2, Expiratory Time, IE Ratio
Mount	: Trolley Mount
Display Size	: 7-inch Touch Screen
Battery Backup	: LI-ION, 3 Hours on full charge

List of standard accessories:

- Breathing Circuit
- High Pressure Tube
- Expiratory Valve and Sensors Tube

Address :

panakeia medtech pvt. ltd.

AMTZ Campus, VM Steel Projects, Pragathi Maidan,
Visakhapatnam 530 031 (AP)

Rights reserved to panakeia to change any specifications

