

HVAC equipment and commissioning draft

UNVERIFIED - no measured results, certification or verified quote eligibility.

Project: job-sc09-room-roof | Source: Synthetic fitting topology only | sample

SHA-256: 8b3c7b13313be6a926f0de1f90ec4161cadb92b1f799ef09c2e3bb343e7b54db

Integrity seal identifies content, not engineering approval.

Equipment / terminal schedule: design L/s; allowable test range +/-10%

A | Plant | pump | pipe | unknown | unknown to unknown | NOT TESTED

Z | East | pipe-terminal | pipe | unknown | unknown to unknown | NOT TESTED

B | East | pipe-terminal | pipe | unknown | unknown to unknown | NOT TESTED

Airflow review (project threshold 6 m/s; not a code assessment)

Pipe flow - inside diameter used for velocity; no design limit assessed

AE | OD 0.4 m | ID 0.35 m | 2 L/s | 0.021 m/s | Allowance unknown Pa

ET | OD 0.4 m | ID 0.35 m | 2 L/s | 0.021 m/s | Allowance unknown Pa

TR | OD 0.4 m | ID 0.35 m | 2 L/s | 0.021 m/s | Allowance unknown Pa

RZ | OD 0.2 m | ID 0.15 m | 2 L/s | 0.113 m/s | Allowance unknown Pa

TB | OD 0.4 m | ID 0.35 m | 2 L/s | 0.021 m/s | Allowance unknown Pa

Declared coordination fittings - conservative clearance; no fabrication quantities

E | elbow | pipe | Synthetic fitting sheet | 2 ports | no bounded clash

T | tee | pipe | Synthetic fitting sheet | 3 ports | no bounded clash

R | reducer | pipe | Synthetic fitting sheet | 2 ports | no bounded clash

Pressure allowance uses the entered Pa/m only; no friction or fitting solver.

Network review

No issues detected by these bounded checks. Professional review still required.

Beam checks use conservative envelopes. Full source schedule is attached as JSON.