

Kabul University
Computer Science Faculty
Information System Department

JavaScript Lecture#4th

JavaScript Events

- The change in the state of an object is known as an **Event**.
- In html, there are various events which represents that some activity is performed by the user or by the browser.
- When JavaScript code is included in HTML, js react over these events and allow the execution. This process of reacting over the events is called **Event Handling**.

Mouse events:

• Event Performed	Event Handler	Description
• Click	onclick	When mouse click on an element
• mouseover	onmouseover	When the cursor of the mouse comes over the element
• mouseout	onmouseout	When the cursor of the mouse leaves an element
• Mousedown	onmousedown	When the mouse button is pressed over the element
• mouseup	onmouseup	When the mouse button is released over the element
• mousemove	onmousemove	When the mouse movement takes place.

Keyboard events:

- | Event | Performed | Event Handler | Description |
|-------|-----------------|---------------------|--|
| • | Keydown & Keyup | onkeydown & onkeyup | When the user press and then release the key |

Form events:

• Event Performed		Event Handler	Description
• focus		onfocus	When the user focuses on an element
• submit		onsubmit	When the user submits the form
• blur		onblur	When the focus is away from a form element
• Change		onchange	When the user modifies or changes the value of a form element

Window/Document events

- | Event | Performed | Event Handler | Description |
|----------|-----------|---------------|---|
| • load | | onload | When the browser finishes the loading of the page |
| • Unload | | onunload | When the visitor leaves the current webpage, the browser unloads it |
| • Resize | | onresize | When the visitor resizes the window of the browser |

JavaScript Events

DEMO-1

JavaScript Animation

The idea behind JavaScript-based animation is fairly simple; a number of DOM elements (`<img />`, `<div>` or otherwise) are moved around the page according to some sort of pattern determined by a logical equation or function.

with `setTimeout` and `setInterval`, which when called as `setTimeout(c,t)` and `setInterval(c,t)` allow for execution of JavaScript code `c` at `t` milliseconds from now in the case of `setTimeout`, and every `t` milliseconds in the case of `setInterval`.

`setTimeout(doSomething,500);` // calls `doSomething()` 500 milliseconds from now

`setInterval(doSomething,500);` // calls `doSomething()` every 500 milliseconds until stopped

JavaScript Animation

DEMO-2