



HTML

CSS

Java Script

Web Design and Development I

Mohammad Zafar Shafaq



Agenda

CSS Basics
Selectors



CSS - LINKS




You will learn about different properties of a hyperactive link using CSS. You can set following properties of a hyperactive link –

The **a:link** signifies unvisited hyperlinks.

The: **a:visited** signifies visited hyperlinks.


The: **a:hover** signifies an element that currently has the user's mouse pointer hovering over it.

The: **a:active** signifies an element on which the user is currently clicking.





CSS - LINKS



DEMO-1



CSS – MARGINS



The *margin* property defines the space around an HTML element. It is possible to use negative values to overlap content.

We have the following properties to set an element margin.


The **margin-bottom** specifies the bottom margin of an element.

The **margin-top** specifies the top margin of an element.

The **margin-left** specifies the left margin of an element.


The **margin-right** specifies the right margin of an element.

The **margin** specifies a shorthand property for setting the margin properties in one declaration.






CSS – MARGINS



DEMO-2



CSS - PADDINGS



The *padding* property allows you to specify how much space should appear between the content of an element and its border


The **padding-bottom** specifies the bottom padding of an element.

The **padding-top** specifies the top padding of an element.

The **padding-left** specifies the left padding of an element.


The **padding-right** specifies the right padding of an element.

The **padding** serves as shorthand for the preceding properties.






CSS - PADDINGS



DEMO-3



CSS - LISTS




We have the following five CSS properties, which can be used to control lists –

The **list-style-type** allows you to control the shape or appearance of the marker.

The **list-style-position** specifies whether a long point that wraps to a second line should align with the first line or start underneath the start of the marker.

The **list-style-image** specifies an image for the marker rather than a bullet point or number.


The **marker-offset** specifies the distance between a marker and the text in the list.

- The **list-style** serves as shorthand for the preceding properties.
- 

VALUES OF LIST-STYLE-TYPE PROPERTY FOR UNORDERED LIST



Sr.No.	Value & Description
1	None NA
2	disc (default) A filled-in circle
3	Circle An empty circle
4	Square A filled-in square




VALUES OF LIST-STYLE-TYPE PROPERTY FOR ORDERED LIST

Value	Description	Example
decimal	Number	1,2,3,4,5
decimal-leading-zero	0 before the number	01, 02, 03, 04, 05
lower-alpha	Lowercase alphanumeric characters	a, b, c, d, e
upper-alpha	Uppercase alphanumeric characters	A, B, C, D, E
lower-roman	Lowercase Roman numerals	i, ii, iii, iv, v
upper-roman	Uppercase Roman numerals	I, II, III, IV, V
lower-greek	The marker is lower-greek	alpha, beta, gamma
lower-latin	The marker is lower-latin	a, b, c, d, e
upper-latin	The marker is upper-latin	A, B, C, D, E
hiragana	The marker is hiragana	a, i, u, e, o, ka, ki
katakana	The marker is katakana	A, I, U, E, O, KA, KI
hiragana-iroha	The marker is hiragana-iroha	i, ro, ha, ni, ho, he, to
katakana-iroha	The marker is katakana-iroha	I, RO, HA, NI, HO, HE, TO



CSS - LISTS



DEMO-4

Questions?
