



HTML

CSS

Java Script

Web Design and Development I

Mohammad Zafar Shafaq



Agenda

• HTML Basics

• Tags

• Page Structure

TABLES


There are several types of information that need to be displayed in a grid or table. For example: sports results, stock reports, train timetables.

Family type	Proportion of people from each household type living in poverty
single aged person	6% (54,000)
aged couple	4% (48,000)
single, no children	19% (359,000)
couple, no children	7% (211,000)
sole parent	21% (232,000)
couple with children	12% (933,000)
all households	11% (1,837,000)



BASIC TABLE STRUCTURE




- `<table>`
 - `<tr>`
 - `<th>`
 - `<td>`
- 
- 



TABLE


DEMO-1





ATTRIBUTES OF TABLE TAG




- Border
 - Width
 - Height
 - Cellspacing : increase space between cells
 - Cellpadding: increase space between cell border and cell content
- 
- 



ATTRIBUTES OF TABLE TAG

DEMO-2



ATTRIBUTES OF <TD> AND <TH> TAG

Colspan: is used to merge more than one column into one


Rowspan: is used to merge more than one rows into one

Top Selling Games on Steam		
Rank	Title	Developer
1	ARK: Survival Evolved	Studio Wildcard
2	Fallout 4	Bethesda Game Studios
3	Grand Theft Auto 5	Rockstar
4	LEGO Worlds	TT Games
5	The Witcher 3: Wild Hunt	CD Projekt Red



ATTRIBUTES OF <TD> AND <TH> TAG

DEMO-3



HTML FORM



HTML forms is used to collect data from your users.

Attribute & Description

Action : Backend script ready to process your passed data.

Method: Method to be used to upload data. The most frequently used are GET and POST methods.


Target: Specify the target window or frame where the result of the script will be displayed. It takes values like `_blank`, `_self`, `_parent` etc.

Enctype: You can use the enctype attribute to specify how the browser encodes the data before it sends it to the server. Possible values are – `application/x-www-form-urlencoded` – This is the standard method most forms use in simple scenarios. `multipart/form-data` – This is used when you want to upload binary data in the form of files like image, word file etc.



HTML FORM CONTROLS

There are different types of form controls that you can use to collect data using HTML form –

- Text Input Controls
 - Checkboxes Controls
 - Radio Box Controls
 - Select Box Controls
 - File Select boxes
 - Clickable Buttons
 - Submit and Reset Button
- 
- 




TEXT INPUT CONTROLS

There are three types of text input used on forms –

Single-line text input controls – This control is used for items that require only one line of user input, such as search boxes or names.

Password input controls – This is also a single-line text input but it masks the character as soon as a user enters it.

Multi-line text input controls – This is used when the user is required to give details that may be longer than a single sentence. Multi-line input controls are created using HTML **<textarea>** tag





ATTRIBUTES OF INPUT TAG

Following is the list of attributes for <input> tag for creating text field.

Attribute & Description
Type: Indicates the type of input control and for text input control it will be set to text.
Name: Used to give a name to the control which is sent to the server to be recognized and get the value.
Value : This can be used to provide an initial value inside the control.
Size: Allows to specify the width of the text-input control in terms of characters.
Maxlength: Allows to specify the maximum number of characters a user can enter into the text box.




ATTRIBUTES FOR <TEXTAREA> TAG

Attribute & Description

Name: Used to give a name to the control which is sent to the server to be recognized and get the value.

Rows: Indicates the number of rows of text area box.

Cols: Indicates the number of columns of text area box






• BUTTON CONTROLS

Type & Description

Submit: This creates a button that automatically submits a form.

Reset: This creates a button that automatically resets form controls to their initial values.

Button: This creates a button that is used to trigger a client-side script when the user clicks that button.






FORM TEXT AND BUTTON CONTROL



DEMO-4





SUMMARY




The **<table>** element is used to add tables to a web page.

A table is drawn out row by row. Each row is created with the **<tr>** element.

Inside each row there are a number of cells represented by the **<td>** element (or **<th>** if it is a header).

You can make cells of a table span more than one row or column using the **rowspan** and **colspan** attributes.



Questions?
