

Nama : Afina Putri Dayanti  
NIM : 825200049  
Jurusan : Sistem Informasi  
Mata Kuliah : Database Design and Management (Praktikum)

---

## Vocabulary

Identify the vocabulary word for each definition below:

USER_SOURCE	The dictionary table that contains source code for all of the subprograms that you own.
USER_OBJECTS	The dictionary table that contains the names and types of procedures and functions that you own.
ALL_SOURCE	The dictionary table that contains source code for subprograms that are owned by others who have granted you the EXECUTE privilege.

## Try It / Solve It


1. Complete the steps below to see how exceptions are propagated.
  - a. Execute the following two SQL statements to create a duplicate of the DEPARTMENTS table, with department\_id as the primary key.

```
CREATE TABLE my_depts AS SELECT * FROM departments;
```

```
ALTER TABLE my_depts
```

```
ADD CONSTRAINT my_dept_id_pk PRIMARY KEY (department_id);
```

Answer :




- b. Examine the following code and create the procedure. Save your work (you will need to modify the procedure code later).

```
CREATE OR REPLACE PROCEDURE add_my_dept (  
p_dept_id IN VARCHAR2,  
p_dept_name IN VARCHAR2) IS  
BEGIN
```

```

INSERT INTO my_depts (department_id, department_name)
VALUES (p_dept_id, p_dept_name);
END add_my_dept;
Answer :

```




- c. What do you think would happen if you execute this procedure to insert department\_id 10 (which already exists)? Write and execute an anonymous block to test your theory.

Answer : It will give an error.

```

begin
  add_my_dept(10, 'afina');
end;

```



- d. Modify your procedure to handle the exception in a generic WHEN OTHERS exception handler.

Answer :

```

CREATE OR REPLACE PROCEDURE add_my_dept (

```


```

p_dept_id IN VARCHAR2,
p_dept_name IN VARCHAR2) IS
BEGIN
    INSERT INTO my_depts (department_id, department_name)
    VALUES (p_dept_id, p_dept_name);
    EXCEPTION WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('ERROR');
END add_my_dept;

```

- e. Now what do you think would happen if you execute this procedure for department\_id 10 (which already exists)? Test it again as in step C.

Answer : The exception was executed “ERROR”




- f. Modify the procedure code to leave out the exception section again. Run the code.

```

CREATE OR REPLACE PROCEDURE add_my_dept (
    p_dept_id IN VARCHAR2,
    p_dept_name IN VARCHAR2) IS
BEGIN
    INSERT INTO my_depts (department_id, department_name)
    VALUES (p_dept_id, p_dept_name);
END add_my_dept;

```

Answer :




- g. Execute the following code to create a new procedure called `outer_proc` which calls `add_my_dept`, passing `department_id` 10 to it:

```


CREATE OR REPLACE PROCEDURE outer_proc IS
  v_dept  NUMBER(2)  := 10;
  v_dname VARCHAR2(30) := 'Admin';
BEGIN
  add_my_dept(v_dept, v_dname);
EXCEPTION WHEN OTHERS THEN
  DBMS_OUTPUT.PUT_LINE('Exception was propagated to outer_proc');
END;

```



- h. Execute `outer_proc` from an anonymous block. What happens and why?

Answer : The exception from `add_my_dept` was propagated to `outer_proc` and handled there.




- Write and execute a SELECT statement to list the names of all the procedures you have created so far.

Answer :

```

select object_name
from user_objects
where object_type = 'PROCEDURE';

```




- Delete the last procedure you created: outer\_proc.

Answer :

```

drop procedure outer_proc;

```



4. Write and execute a SELECT statement to list the source code of your add\_my\_dept procedure. Make sure your SELECT statement list the lines of code in the correct order.

Answer :

```
select text from user_source
where name = 'ADD_MY_DEPT'
order by line;
```

