## R2 Reasonable Potential Tool Parameter Report

Compiled on 26 March, 2025

PR0024163 - 001 : Solids, total dissolved

Evaluated from 2020-05-31 to 2025-02-28

FACILITY INFORMATION:

PRASA HATILLO WTP

STATE ROAD 2, KM 88.9

HATILLO, PR

**SUMMARY STATISTICS:** 

Number of Samples: 20

Min: 160 NA

Mean: 188.5 NA

Max: 230 NA

WQS - SB: NA NA

WQS - SD: NA NA

RWC: 245.89 NA

## RECEIVING WATER CONCENTRATION CALCULATIONS

## assuming a 95% confidence level and a 95% probability basis

calculations from 1991 Technical Support Document pgs 51-55

Number of samples = n

Maximum effluent concentration = max

Dilution Ratio = DR

Coefficient of Variation (CV) =  $S_n/\mu$  or 0.6 when n < 10

Z-statistic =  $Z_x$ 

Reasonable Potential Multiplier (RPM) =  $\frac{exp(Z_{95} \ln(1 + CV^2)^{0.5} - 0.5 \ln(1 + CV^2))}{exp(Z_x \ln(1 + CV^2)^{0.5} - 0.5 \ln(1 + CV^2))}$ 

Receiving Water Concentration = max \* RPM/Dilution Ratio

n = 20

max=230

DR = 1

CV=0.12

 $Z_{95} = 1.645$ 

 $Z_x = 1.084$ 

$$RPM = \frac{exp(1.645\ln(1+0.12^2)^{0.5} - 0.5\ln(1+0.12^2))}{exp(1.084\ln(1+0.12^2)^{0.5} - 0.5\ln(1+0.12^2))}$$
  
= 1.07

$$RWC = 230 * 1.07/1$$

= 245.89