Date:

Question 4.

Input	Output
• Number of festival Days • orders • Amount of each order.	• Bar chart • ~~Mar~~ Highest Sales, Total sales, • Avg Order amount

Pseudocode:

```
FUNCTION getValidDays () Rebues INT.
    PRINT ("Enter festival Days") INPUT festivalDays.

    WHILE (festival Days <1 OR festival Days >7) DO.
        print ("Enter Again)
        INPUT Festival Days.
    RETURN Festived Days.
ENDFUNCTION.
```


DECENT PAPER PRODUCT

Teacher's Signature:

Scanned with CamScanner

Date:

```
FUNCTION calculateDays(dayNumber) RETURN INT.
    PRINT("Current Day", dayNumber)

    PRINT("Enter No. of Orders") INPUT order.

    total = 0, highest = 0, amount = 0.

    FOR(i = 0, i < order)
        PRINT("Enter Amount").
        INPUT Amount.

        WHILE (amount <= 0)
            PRINT("Enter Again").
            INPUT Amount.
        total += amount.

        IF (highest < amount) & highest = amount.

    PRINT("Highest Order Amount" highest)
    PRINT("Total Sales", total)
    PRINT("Avg Order Amount", total/order).
    Return total.

ENDFUNCTION
```


DECENT PAPER PRODUCT

Teacher's Signature:

Scanned with CamScanner

Date: _____

```
FUNCTION findHighestSalesDay (arr[][], NumDays)
                                RETURNS INT.
    index = 0 , max = arr[0]
    FOR (i = 0, i < NumDays)
        IF (arr[i] > max) max = arr[i], index = i

    RETURN index.
ENDFUNCTION.

PROCEDURE displayBarChart (arr[], NumDays)
        num = 0
    FOR (i = 0, i < numDays)
        num = arr[i] / 100;.

        PRINT ("Day", i)
        FOR (j = 0, j < num)
            PRINT ("*").

ENDPROCEDURE
```


Scanned with CamScanner

Date: _____

```
days = getValidDays()
DECLARE dailySales[7] : ARRAY OF FLOAT
total = 0.
FOR (i = 0, i < days).
    dailySales[i] = calculateDailySales(i+1).
    total += dailySales[i].

highest = findHighestSalesDay(dailySales, days).

PRINT ("Total Sales", total)
PRINT ("Highest Sales Day", ans).

displayBarChart (dailySales, days)
```

Scanned with CamScanner