REDACTED CLIENT CASE STUDY / 31 OCTOBER 2026

External perimeter security assessment

Nmap discovery and OpenVAS vulnerability enumeration, translated into a concise risk and remediation brief.

ASSESSMENT SNAPSHOT

5	Nmap TCP services open
2	OpenVAS findings retained
0	Critical / High OpenVAS

Target identity and address are intentionally omitted for portfolio use.

Scope, tools and scan approach

Scope

One client-authorized internet-facing host (identity redacted). Evidence comes from the supplied Nmap output and a 3-page OpenVAS report. This document interprets those outputs; it is not a fresh scan.

Nmap command profile

SYN scan, service/version detection, OS fingerprinting, default and vulnerability scripts, all TCP ports, faster timing, and output saved in all formats. The supplied run completed in about 71 minutes.

OpenVAS scan window

31 Oct 2026, 18:14-19:28 UTC (about 74 minutes). Host scan: 18:15-19:28 UTC. The report retained results at QoD >= 70%; 2 of 36 results are shown after filtering.

How to read this brief

Severity reflects the OpenVAS report where available. Nmap observations describe exposure and fingerprints. A detected service or version is not by itself proof of an exploitable weakness.

Internet-facing service exposure

PORT	SERVICE	OBSERVED FINGERPRINT	ASSESSMENT NOTE
21/tcp	FTP	ProFTPD or KnFTPD	Open; TLS is supported but OpenVAS found it is not enforced for login.
80/tcp	HTTP	Version not identified	Open; several scripted checks errored or were inconclusive.
443/tcp	HTTPS	Version not identified	Open; selected checks found no XSS/CSRF, but timeouts/errors limit assurance.
3306/tcp	MySQL	MariaDB 11.8.9-log	Open database listener; restrict to application networks / trusted sources.
65002/tcp	SSH	OpenSSH 9.9	Open on a nonstandard port; restrict source IPs and verify provider patch level.

Also observed: 65,227 filtered TCP ports (no response), 303 closed (reset). The remaining five of 65,535 ports were open. Nmap OS identification was a probabilistic Linux-family guess, not an exact match.

OpenVAS findings and meaning

MEDIUM | FTP cleartext login

CVSS 4.8 | QoD 70% | Port 21 The service accepts login before an AUTH TLS command. Credentials can be exposed to network observers on an unencrypted path. OpenVAS confirmed the behavior by testing FTP negotiation; this is the clearest actionable finding.

LOW | TCP timestamps

CVSS 2.6 | QoD 80% | General TCP RFC 1323/7323 timestamps were observed. In some conditions, timestamp progression can help estimate host uptime. This is information disclosure with limited direct impact, not evidence of host compromise.

Why only two findings appear

OpenVAS reports 36 results before filtering, but this export includes only the 2 selected results meeting its minimum Quality of Detection threshold of 70%. It also states vendor security updates are not trusted. Treat this as a filtered view, not proof that no other issues exist.

Nmap signals: evidence versus leads

Confirmed by the supplied output

FTP, HTTP, HTTPS, MariaDB, and SSH ports responded as open. MariaDB and OpenSSH reported version strings. SSH host keys and a 13-hop traceroute were recorded.

Web checks are not a clean bill

Some scripts reported no DOM-based or stored XSS and no CSRF detected. Other scripts failed or timed out. Script coverage is narrow and errors leave those checks unresolved.

SSH CVE list: treat as leads

The Nmap vulners script associated many CVE records with the OpenSSH 9.9 fingerprint, including future-dated identifiers in the scan output. Version matching can misstate exposure because of backports, platform packaging, or inaccurate mappings. Validate each candidate with vendor advisories and installed package data.

OS guess and filtered ports

The Linux-family OS estimate is explicitly non-exact and affected by network conditions. A filtered port means probes received no response; it does not prove that a service is absent or that a firewall rule is correctly scoped.

Recommended remediation sequence

1	**Enforce encrypted FTP or retire FTP**	Require AUTH TLS before credentials are accepted; prefer SFTP where operationally suitable. Verify both anonymous and named-user behavior, then retest.
2	**Restrict database reachability**	Allow TCP/3306 only from required application or administration networks. Confirm no public clients need direct database access; review authentication and TLS.
3	**Limit SSH exposure**	Restrict TCP/65002 by source IP or private access path, enforce key-based authentication and MFA where supported, and confirm the host package includes current vendor fixes.
4	**Decide on TCP timestamps**	If uptime inference is unnecessary and compatibility permits, disable timestamps per the host OS guidance. Validate performance and protocol impact before rollout.
5	**Close assessment gaps**	Re-run targeted checks for web services and validate all SSH CVE candidates against the hosting provider package/build and security advisories.

Limitations and portfolio handling

Snapshot, not a guarantee

These are point-in-time outputs from 31 Oct 2026. Service banners can be inaccurate or intentionally generic; Nmap script errors and OpenVAS filtering constrain coverage. No manual exploitation or authenticated configuration review is represented here.

Ownership and authorization

The original reports contain client-identifying details. This portfolio copy redacts the domain and address. Share it only where the engagement terms permit portfolio use; obtain client approval if required by contract or policy.

Sources used

User-supplied Nmap output (full TCP scan, service/version and script results); user-supplied OpenVAS PDF (scan dates, result overview, FTP cleartext login, TCP timestamps). No CVE list entry is presented here as a verified vulnerability. No additional network probing was performed for this brief.