

# Energy Aware Programming

Afonso Carreira - 62701

Estudo Orientado

Mestrado em Engenharia Informática

Faculdade de Ciências, Universidade de Lisboa

fc62701@fc.ul.pt

## Abstract

your abstract (about 10 lines).

**Keywords** 5 keywords

## 1 Introduction

In recent years, the use and control of energy has become a global issue. The search is on for renewable energies that reduce the ecological impact on our planet. However, these energies are neither as cheap nor as consistent as other alternatives. There are many ways to help reduce global energy consumption and costs, and the IT sector is one of them.

Saving energy in programs is crucial for the operation of certain devices, such as mobile phones or IoT devices, so certain techniques need to be applied in order to reduce the energy of a program. For mobile devices, techniques are already used to save the battery when necessary, but for systems that don't use batteries, such as servers, energy is rarely taken into account when developing a program. This lack of concern or awareness on the part of developers, although it appears to have a small impact, turns out to be quite significant, as in 2020 around 7% of global electricity use is due to information and communications technology, with an anticipated rise in line with the growing demand for new technologies[1]. This trend has become even more significant with the increased use of artificial intelligence [2], especially large scale models such as ChatGPT, which require significant computing resources to train and run. These energy-intensive processes contribute significantly to global energy consumption and carbon emissions, raising environmental concerns as AI adoption continues to grow. For instance, training the GPT-3 model required 1,287 MWh of energy, equivalent to the annual energy usage of approximately 117 U.S. households, and produced 552 metric tons of CO<sub>2</sub>—comparable to the emissions from driving 120 cars for a year. With the release of GPT-4 and ongoing development of even more advanced models, these numbers are expected to rise, further amplifying their environmental footprint.

There are several reasons why there is a need to save energy in software, be it for mobile systems or data centers applications.

- The dependence of mobile devices on batteries. All mobile devices rely on their batteries, so the software

they run needs to make the best use of resources to conserve battery power.

- Reducing operating costs in data centers. It is crucial to reduce the operating cost of data centers by using energy-efficient programs. This reduction results in economic benefits for companies and contributes positively to environmental sustainability.
- Reducing energy consumption has a positive impact on our environment by saving energy that can be used for other things.

When developing a program, most of the time developers only care for the time the program takes to complete, or the memory it uses, and rarely take into account the energy it uses. In the cases where developers actually want to improve the energy efficiency of the code, they normally have difficulties and seek help, relying on blogs, websites, YouTube videos and nowadays even chatbots like ChatGPT, which in most cases do not give completely right answers, and sometimes even the wrong ones. This is due to a lack of knowledge and guidelines, because understanding the energy usage of a program and how to make more efficient is not trivial, as running the same program multiple times will output different values each time and even if the execution time of the program is reduced, is not guaranteed to also reduce energy consumption. Because of its difficulty, there is still a need for tools that can help with this task[3].

Also, most current tools can measure the energy of programs and applications as they run, but this usually requires extra steps that many developers may not have the time or inclination to take, so there is a need for a tool that can help the developer without the need for extra effort[4].

This thesis proposes the development of a tool capable of identifying the energy consumption of methods in programs and presenting this information quickly to programmers, enabling them to make informed decisions in software design. The goal is to create an IDE extension that integrates these functionalities, provides immediate feedback on the energy impact of applications, and allows developers to adjust their code to meet efficiency requirements. The tool should be easy to use, requiring minimal knowledge of energy consumption, while helping programmers understand the energy footprint of their software. This increased awareness will enable them to understand the overall impact of their coding choices on energy consumption and efficiency.

To create this tool, it is essential to understand the current state of the art, including the techniques previously used and the tools currently in use. The tool will employ static analysis techniques to identify which instructions are utilized, and through inferences from previously collected data, indicate the estimated energy levels of the program's execution. The inference will be made using energy data collected from low-level library functions. More complex functions are built on the basis of function composition, which means that, based on the estimated consumption of low-level functions, we can generalize our estimates to more complex functions and ultimately to the program as a whole.

## Organization

- Background (2) contains information of concepts that should be known to understand the complete report. It explains why it is difficult to predict and measure energy consumption of programs. It explains different energy tools, how they work, and what they do. It explains static and dynamic analysis and why it is important in this work.
- Related work (3) contains the initial solutions proposed to the theme of energy aware programming, how they changed during the years, and what the most recent tools do. And comparing with the proposed tool in this work.
- This section (4) explains in detail the existing problem and what is the solution, and a detailed explanation on how the solution will be built.
- The preliminary results (5) contains the tests made until the moment, and what results were obtained.
- Final conclusions (6) of the work done until the moment, and explanation of what work will be continued to be done.

## 2 Background

To fully understand the processes involved in this work, it is important to first understand what energy profiling is, as it will be frequently referenced and used later.

Energy profiling is the systematic process of measuring, monitoring, and analyzing the power consumption of a system using specialized software or hardware tools to collect detailed power consumption data. This data can be collected from different parts of a system, including applications, processes, and specific snippets of code, to provide insight into how different components and activities contribute to overall energy consumption. Through this type of power consumption profiling, developers are able to identify inefficiencies and optimize software to improve energy efficiency. This makes it very important for extending battery life in mobile devices, reducing operating costs in data centers, and

also minimizing environmental impact through energy consumption. Energy profiling is a step toward making informed decisions to develop more sustainable and cost-effective computing solutions.

When programming, developers usually consider the time it takes to complete a program, or the response time from client to server, or the amount of memory it uses. Most don't have an idea of how much energy their program consumes, or how much it can consume in certain cases, and getting this idea is not as trivial as it seems. To get this awareness, measurements could be made, but they are also difficult to get compared to measuring the time a program takes, which is checking the differences in timestamps, or understanding the memory usage. As for measuring energy, the same program can produce different values due to its non deterministic nature, meaning that results are often expressed as a range of possible values. Also, reducing the execution time of a program does not guarantee that the power consumption will follow. To obtain the measurements it is necessary to use some techniques that may require hardware devices for accurate values or software based tools that can facilitate this process, sometimes at the cost of less accurate readings.

To perform hardware-based measurements, a power monitor or power meter device must be used to obtain the precise values that a system uses when connected to the electrical grid. These devices measure the power drawn from the grid to the machine, but they usually measure the power consumed by the entire system rather than by specific pieces of hardware, which means they have low granularity. To gain this granularity and perform the measurements for only some parts of the machine, such as CPU and RAM, a harder setup is required to avoid reading unnecessary power consumption. This technique is not suitable for developers who only want to analyze the energy performance of their programs, which shows the difficulty of measuring energy consumption.

Another alternative is to use software-based tools. These tools are typically easier to use, but may not provide values as accurate as hardware-based measurements. However, they are more versatile and can be implemented or modified to meet the user's needs.

### 2.1 Energy Tools

There are some tools capable of displaying the energy consumption of programs, in this work, powerjoular will be used for energy profiling.

Intel RAPL (Running Average Power Limit) is a tool for monitoring power consumption. It utilizes Model-Specific Registers (MSRs), which are used for program execution tracing, performance monitoring, and toggling CPU features. These registers can store the total energy usage of the CPU

and memory, allowing it to be read and analyzed. Most software based tools rely on RAPL to measure energy consumption, since it is pretty accurate and is widely available in most CPUs.

To perform this work a tool is needed in order to measure the energy of programs, methods or code snippets. The tool used was powerjoular [5], a open source tool, capable of measuring energy, from the CPU and GPU, using the Intel RAPL power data through the Linux powercap interface it can read the energy from the CPU and for the GPU it uses NVIDIA SMI to directly read the power consumption. To read the power consumption of specific processes, PowerJoular monitors the CPU cycles and utilization of each process. By knowing the total power consumption of the CPU through the RAPL interface, it can calculate the power usage of individual processes based on their CPU utilization. It is build in ADA, that is considered one of most energy efficient programming languages and it can monitor applications by name or PID.

Experiment-Runner[6] is a framework built in python made to facilitate experiments, it is easily customizable and can be used with energy measurement tools, such as powerjoular, to monitor the power consumption of another process.

## 2.2 Code static and dynamic analysis

Also, the tool proposed in this work will mainly use static analysis to achieve its goal, so it is crucial to understand why it is preferred over dynamic analysis in this context.

Static analysis, as the name implies, analyzes the code statically, meaning it examines the code without executing it. By examining the code, static analysis tools can understand how the program will behave at runtime[7], this analysis often aims for soundness, meaning that if the tool catches an error, it means that the error really exists, there are no false negatives. However, this can come at the cost of producing false positives, where issues that are not actually problems are flagged, so its important to keeps a balance between them. This analysis allows to check the entire source code and every path, much like compilers check syntax and types. Still, they can only predict some behaviors, as some can only be found when the program is executed, for example, by using dynamic analysis.

Dynamic analysis, on the other hand, executes the program and observes its exact behavior without having to estimate or predict. This type of analysis leaves no doubt about memory usage, output, the path taken, how much time it took[7]. A good example of dynamic analysis is unit testing, which tries to cover as many code paths as possible with different inputs, to understand as much as possible how the program works, and to find something that might be difficult to find with static analysis. However, dynamic analysis can be time consuming, especially for programs that take a long time to complete.

For fast power estimation, static analysis is preferable. It analyzes code faster and is better suited for large projects with multiple dependencies, where dynamic analysis can be very difficult to achieve due to complex setup and long execution times. Although static analysis may not be as accurate as dynamic analysis, it is still a viable solution. In addition, static analysis is more portable because its setup is much simpler than the more complex setup required for dynamic analysis. Developers typically prefer not to run the program just to get an average measure of energy consumption for a code snippet or program, as it is time consuming and impractical. Therefore, using static analysis to infer energy consumption makes sense in this context.

The use of static analysis implies the use of a parsing technique. This technique involves analyzing the syntactic structure of the provided code, respecting the rules of the language in which it is written. First, it is necessary to perform a lexical analysis to obtain the keywords, identifiers and tokens that the language contains. Then the parser uses these tokens together with the grammar rules of the programming language and outputs a tree. The output is an Abstract Syntax Tree, which contains the logical structure of the code and allows further analysis. In the context of this work, this technique allows to analyze, for example, Java code and obtain its structure to find out which statements have been used.

## 3 Related Work

Energy efficiency is a critical focus across industries, as it directly impacts global sustainability, economic costs, and product quality. The goal is to reduce greenhouse gases to create a sustainable future, reduce infrastructure costs, and improve product quality[8].

In particular, large scale computation and communication consume a lot of global energy, and these values have been increasing in the last decades, so the topic of energy aware programming and energy efficient software has been targeted by many researchers in recent years with the objective of reducing energy costs in large IT infrastructure[9]. This improvement can be considered a optimization problem and can be tackled in several ways for example an heuristic approach by adjusting the hardware performance dynamically, or completing tasks in their deadlines, using the least energy possible. However some of this implementations can only be short term solutions and in long term, the focus will be toward more complex models that can predict and optimize performance relative to hardware configurations[10].

An approach to increasing developers awareness of the energy consumption of their code involves creating extensions to already used programming languages, such as Java. For example, ECO [11], a programming model as an minimal extension of Java. By rewriting some parts of the code to this extension syntax it is possible to defining resource limits on

the battery or temperature implementing adaptive behaviors through modes, and leveraging runtime monitoring.

In addition, new languages can be developed to address these goals, as demonstrated by ENT[12]. ENT is a Java extension that empowers programmers with more direct control over the energy consumption of their applications. ENT’s type system enables applications to adapt dynamically to power constraints by switching operational modes based on resource availability, such as battery level or CPU temperature, allowing for software-level energy optimization. However, the language introduces complexity, making it potentially challenging for developers to learn and adapt to existing codebases.

The use of static analysis can be valuable for understanding how instructions affect the energy consumption of programs. This paper[13] shows that system calls are directly related to energy consumption in Android applications. With this insight, it’s possible to use static analysis to identify system calls within the code. This information can then be used to infer potential energy usage patterns, providing an early indication of where higher energy consumption may occur. This approach highlights the importance static analysis can have to understand program energy behaviors.

To tackle the problem of energy consumption in IT, some solutions have been presented. Some researchers focused on using energy measurement tools, like JRAPL to measure common libraries in Java and understand how much energy they use and what are the best alternatives to improve the energy efficiency of the code[14]. Observing common libraries for the implementation of list, sets and maps, is possible to see which ones have the better energy efficiency and what changes could improve the code. Hasan et al.’s [15] research adds to this by creating detailed energy profiles for various Java collection classes, including lists, maps, and sets, across different implementations (Java Collections Framework, Apache Commons Collections, and Trove). Their work presents concrete quantification of energy consumption in these collections based on common operations such as insertion, iteration, and random access, and highlights the performance impact of collection types on energy efficiency for different input sizes.

However, because these collections are often used with threads, it is important to understand how much energy efficiency can be improved without compromising thread safety. The energy consumption of Java’s thread-safe collections was studied in [16], where researchers demonstrated that switching to more energy-efficient collection implementations can reduce energy usage while maintaining thread safety.

Building on these efforts, [17], Pereira et al. introduced a static analysis tool (Jstanley), as part of a Eclipse plugin, that can detect energy inefficient collections and recommend better alternatives. While Jstanley demonstrated notable improvements in energy efficiency within its specific context,

it has several limitations. For example they only account for 3 collections, (Lists, Sets and Maps), they only account for 3 sizes of the collections (25,000, 250,000 and 1,000,000), it does not account for loops, thread safe and thread unsafe collections. Compared to our approach, Jstanley is limited, as it does not provide the actual information about the energy spent, it just shows recommendations. While the tool shows great improvements in its tested environment, replacing collections may not be enough in many practical cases. A more extensive tool, capable of analyzing a wider range of collections and providing energy metrics, would enable developers to achieve even greater energy efficiency and awareness.

In this work[18], a tool (CT+) has been proposed that is capable of performing static analysis of the code and recommending changes that reduce energy consumption. It improved from previous works by taking into account more collections implementations, more operations, thread safety and support for mobile applications.

In addition, SEEP [19] uses symbolic execution for energy profiling, generating multiple binaries representing different code paths and input scenarios. By analyzing these binaries with hardware-based energy measurement devices, SEEP provides energy consumption data, offering a deeper understanding of code efficiency across various inputs and paths. This approach complements other tool, such as PEEK, which builds on SEEP to help developers optimize energy usage with minimal effort [20]. PEEK is an IDE-integrated framework that guides developers in writing energy-efficient code. It has a front end for IDE interfaces (e.g., Eclipse, Xcode), a middle end to manage data and versioning via Git, and a backend where energy analysis is performed—either through SEEP or hardware devices. Through these layers, PEEK identifies inefficiencies and suggests optimizations, supporting efficient coding practices. However, it has some limitations when compared to the proposed approach in this work, it uses dynamic analysis instead of static analysis, which was already explained in, 2.2, why it was chosen over dynamic analysis.

Other tools worth mentioning are Perf, Powertop, and JoularJx.

Perf is a command line tool already available in linux, and is mainly used for performance monitoring and profiling. Although its not specific for energy measurement, it can do it, with Intel RAPL but not as pratical as other tools, specially when its needed to meausre a single process energy consumption.

Powertop is another tool capable of providing the power consumption, however it only works for laptops, as it requires to check the battery to see how much energy was used and calculate the power consumption.

JoularJX[5] is a Java agent that attaches to the JVM at startup to monitor energy consumption. It runs in a separate thread, collecting CPU usage data for the JVM, its threads, and individual methods using statistical sampling. JoularJX

provides power estimation to platform-specific tools, such as the Intel API, the Linux RAPL interface, or a custom regression model. It periodically analyzes stack traces to isolate energy consumption at the method level, taking into account execution paths and separating application-specific calls from system or agent-induced calls. That's how JoularJX is able to provide detailed insight into the energy consumption of Java applications.

These solutions have some limitations, like the need to execute the code before showing the average energy cost to the developer or having limited collections.

This work has the objective of creating a user friendly tool that quickly estimates energy consumption through static analysis and providing developers recommendations. This energy will then be displayed to the developer making him more aware of the energy consumption of the program and help make better decisions.

## 4 «Section(s) about your Work»

As described in the previous sections, the challenge is to make developers aware of the energy consumption of their programs. By using a simple and practical tool, they can quickly and accurately estimate their program's energy consumption. This allows them to get immediate feedback on energy consumption with every code change, facilitating energy-efficient development. It's important to note that this tool serves as a guide, providing energy consumption estimates to raise awareness rather than dictate action. Ultimately, it is up to developers to decide whether to prioritize performance, energy efficiency or any other factor. For example, if a program only needs to run within a certain timeframe and can afford a slight reduction in performance, developers may choose to trade some performance for improved energy efficiency, making more informed decisions thanks to the insights provided by the tool.

To provide this insight to developers it is necessary to build a tool that can provide all of that. The tool needs to be practical, which means that integrating it in an IDE is a very good option. With this the developer only needs to download an extension for an IDE and will have the insights desired. The tool will be an extension using Language Server Protocol (LSP), so it can be integrated in all the IDEs that support this feature (VScode, Eclipse, Neovim, IntelliJ IDEA). This will make it accessible to most developers wanting feedback on the energy consumption. To make it fast, it will use static analysis to parse the code into an AST, from there its capable of analyzing the code and using an inference function it will output the estimated cost. **It will also be possible to make a more precise estimation, by running the code and also provide recommendations. optional/if i have time.**

Many devices rely on Java and the Java Virtual Machine (JVM), so it is important that the code they run is energy efficient. Several factors can affect the power consumption of

Java applications, including the behavior of the garbage collector and the efficiency of the memory management system [21] making it difficult to predict the power consumption of Java programs. This unpredictability highlights the need for a specialized tool to accurately measure and analyze power consumption so that developers can optimize their applications for energy efficiency. Java is an excellent choice for developing this tool because of its high interoperability with various operating systems and its widespread usage across the globe, making it a reliable and option. It has a wide range of useful libraries (JRAPL, joularjx, Jalen) that help to measure energy accurately, and Java's typing and object-oriented features make the code easier to maintain and extend, so the tool can evolve with new energy metering standards and technologies.

### 4.1 Step 1: Energy Profiling

To give energy consumption estimates, first it is necessary to obtain energy profiles so the inference function can obtain the most accurate results possible. The goal in this step is to first obtain energy profiles of collections and APIs that are widely used, break them down to their smallest functions, and understand their energy behavior. From there, it is possible to build from these granular functions to more complex and interconnected functions, ultimately covering the entire API set in detail. So whenever an API call is detected in the code, pre-built energy profiles are already available for it. For that, a process was created in order to efficiently obtain the energy usage of code snippets. The process uses an orchestrator that is responsible for invoking the target program and the measurement tool (powerjoular) to accurately measure the energy consumption of the program or the specific computation being analyzed within it.

Bellow it is explained how the energy profiles process was done.

- On the start of the orchestrator it launches a command to start the target Java Program and waits a signal.
- The Java program start and setup the necessary things to run (starting threads, reading/writing files, etc.) and then it sends a start signal to the orchestrator to start monitoring the computation wanted, and waits for some milliseconds.
- The orchestrator receives the start signal and reads the PID of the target program from a file and starts PowerJoular using that PID. Then it waits for the stop signal.
- The target Java program when it finishes the computation it sends a stop signal back.
- The orchestrator on receiving the stop signal, first stops PowerJoular and then stops the target program, if needed. Then it displays the energy measurement information stored in the files created by PowerJoular.




Figure 1. orchestrators process




Figure 2. energy inference function

This allows for more precise energy measurements, avoiding reading the JVM startup, and focusing only on the computation between the signals.

This process is more clearly illustrated in Figure 1

This process will be repeated across multiple machines to gather data from as many locations as possible. This global approach ensures that the model developed in the next step will generate accurate outputs applicable to a wide range of machines and scenarios.

## 4.2 Step 2: Energy Inference Function

The inference function will receive as input the energy profiles obtained previously and the code that the developer wants to analyze. On receiving the code, static analyzes will be used in order to inspect the code using a Java parser (Spoon), which will provide the AST. Later this AST will be used to feed a machine learning model with the return types of the function, collections used, loops and so on, alongside

with the energy profiles. After that the model will output the estimated energy values to be displayed to the developer. The model will be trained using a variety of energy profiles and code inputs from different devices to achieve the most accurate energy estimates possible. This approach will improve its accuracy across devices with different hardware and software configurations. The estimation will be the total energy used by the program, the total energy used for each function and the snippets of the function that spend the most energy.

The Figure 2 helps to visualize the function.

## 4.3 Step 3: Implementation and testing

Once the main components of the tool are built, they need to be assembled into the extension. When using it, the developers should be able to see the total energy estimate of their code in the IDE, and it should also show the estimates for each function and its most energy consuming lines. The estimate alone may be enough to understand if the code is high or low in energy consumption, for example, if the developer has 2 implementations of the same function and they both give different values, it may be easy to understand which one consumes the most. However, this may not always be the case, so the tool will also provide some information to help the developer know how good or bad the energy efficiency of the code is. **choose something to show to compare like how much a washing machine uses or something**

Another important step is to test and ensure that the tool performs as expected on most machines, delivers the most accurate estimations possible, and undergoes a final comparison with other tools to evaluate its effectiveness.

## 5 Preliminary Results (optional)

In the start of the project, some tools were tested in order to see how to get the energy profiles for later use. The tools tested were PowerJoular, powertop, perf and joularjx.

Perf is a Linux tool primarily designed for analyzing application performance characteristics rather than precise energy measurement. While it can provide some energy-related metrics, its measurements tend to be imprecise. In this context, perf was used mainly to get a rough idea of energy consumption and to serve as an alternative when more accurate tools were unavailable.

Powertop was also tested, but it could only perform energy measurements on laptops, as it relies on battery drain data to calculate energy consumption. Since this approach doesn't align with our specific requirements, we considered Powertop as a last-resort option.

JoularJx is a energy measurement tool capable of measuring the consumption of Java programs and its methods. However it is not as precise as other tools as it requires to measure the entire start of the JVM and whole functions instead of small code blocks.

As described in the the 2.1, PowerJoular is the best option. As a command line program it can be easily adapted to measure any program or code snippet in most languages. So it was combined with the framework experiment-runner, that facilitates the process.

Initially, JoularJx and the experiment-runner using powerjoular were used to explore their capabilities and familiarize with the tools. A sample Fibonacci program written in Java and C was used as a test case. However, the energy measurements provided by the two tools differed, and the experiment runner occasionally encountered errors. Later, it was determined that these problems were due to incorrect use of the framework. However it was still decided the the best approach was to make a new orchestrator similar to the Experiment-Runner, but simpler and specifically focused on measuring process energy consumption using PowerJoular. A Java-based orchestrator was initially developed because the Fibonacci implementation was also in Java. However, when tested, the energy measurement results differed significantly from those of the experiment runner, even though the main difference was the programming language (Java vs. Python).

To further analyze these inconsistencies, another orchestrator was developed in Python. This allowed for a closer examination of the differences in energy measurements and a deeper understanding of the behavior of the tools.

Using the process explained on 4 it was noticeable that the Java orchestrator was getting significantly more energy consumption than the Python one, which is not very logical, since they both target the same program. So, to try and check which one was having problems, two more orchestrators were implemented, one in C and another in bash.

After running the tests again it was possible to see that the Python orchestrator was getting values way more different than the other three orchestrators as show in Figure 3. The figure contains 100 runs of the Fibonacci recursive program written in Java and order by the less energy to highest energy. And it shows the energy reads for the four different orchestrators used. The labels contain the average energy values and its standard deviation.

Further analysis of the orchestrators revealed a notable difference in behavior. When the Python orchestrator was running, both the parent and child processes consumed CPU resources. In contrast, the other orchestrators (Java, C, and Bash) showed CPU usage only in the child process. This disparity may explain why powerjoular reported lower energy consumption for the Python orchestrator. Since the CPU load was shared between the parent and child processes, powerjoular, which measures energy only for the child process (the target Fibonacci program), captured less total energy usage. Since the experiment runner included an example demonstrating how to use the framework with powerjoular, the authors were made aware of this potential conflict when launching powerjoular from Python.




Figure 3. orchestrators comparison

## 6 Forthcoming Work and Conclusions

During this year, the work will have the following structure: Building on the progress made so far, additional energy profiles must be created to develop a robust energy inference function. This task involves collecting profiles from different machines and gathering enough data to effectively train the machine learning model.

After that the efforts will be on developing the actual energy inference function. This task is expected to be the most time consuming, as it is crucial to the tool functioning. It is possible that this task overlaps the energy profiling task as more profiles might need to be collected. The task will start by building the machine learning model and improving its accuracy for many possible cases, using the energy profiles. After that, the static analysis tool will be implemented and used to provide important code to be analyzed by the model.

When the function is completed, it will be tested against other tools to ensure its quality. The extension will then be built and tested in IDEs. While developing the function and the extension, the writing of the thesis will also be done in parallel documenting every information.

The work plan is illustrated more clearly in Figure 4, which provides a visual representation of the described tasks. While the dates shown in the figure may not precisely align with the actual timeline, the sequence of tasks remains accurate.

## References

- [1] Anders Andrae. New perspectives on internet electricity use in 2030. *Engineering and Applied Science Letters*, 3:19–31, 06 2020.
- [2] David Patterson, Joseph Gonzalez, Quoc Le, Chen Liang, Lluís-Miquel Munguia, Daniel Rothchild, David So, Maud Texier, and Jeff Dean. Carbon emissions and large neural network training. *arXiv preprint arXiv:2104.10350*, 2021.
- [3] Gustavo Pinto, Fernando Castor, and Yu David Liu. Mining questions about software energy consumption. In *Proceedings of the 11th Working Conference on Mining Software Repositories*, MSR 2014, page 22–31, New York, NY, USA, 2014. Association for Computing Machinery.






Figure 4. Work Plan

- [4] Gustavo Pinto and Fernando Castor. Energy efficiency: a new concern for application software developers. *Commun. ACM*, 60(12):68–75, November 2017.
- [5] Adel Nouredine. Powerjoular and joularjx: Multi-platform software power monitoring tools. In *18th International Conference on Intelligent Environments (IE2022)*, Biarritz, France, Jun 2022.
- [6] S2 Group. Experiment Runner.
- [7] Michael D Ernst. Static and dynamic analysis: Synergy and duality. In *WODA 2003: ICSE Workshop on Dynamic Analysis*, pages 24–27, 2003.
- [8] Kenneth Gillingham, Richard G. Newell, and Karen Palmer. Energy efficiency economics and policy. *Annual Review of Resource Economics*, 1(Volume 1, 2009):597–620, 2009.
- [9] Alcides Fonseca, Rick Kazman, and Patricia Lago. A manifesto for energy-aware software. *IEEE Software*, 36(6):79–82, 2019.
- [10] David J. Brown and Charles Reams. Toward energy-efficient computing. *Commun. ACM*, 53(3):50–58, March 2010.
- [11] Haitao Steve Zhu, Chaoren Lin, and Yu David Liu. A programming model for sustainable software. In *2015 IEEE/ACM 37th IEEE International Conference on Software Engineering*, volume 1, pages 767–777, 2015.
- [12] Anthony Canino and Yu David Liu. Proactive and adaptive energy-aware programming with mixed typechecking. In *Proceedings of the 38th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2017*, page 217–232, New York, NY, USA, 2017. Association for Computing Machinery.
- [13] Karan Aggarwal, Z Chenlei, J Campbell, Abram Hindle, and Eleni Stroulia. The power of system call traces: Predicting the software energy consumption impact of changes. 2014.
- [14] Rui Pereira, Marco Couto, João Saraiva, Jácome Cunha, and João Paulo Fernandes. The influence of the java collection framework on overall energy consumption. In *Proceedings of the 5th International Workshop on Green and Sustainable Software, GREENS '16*, page 15–21, New York, NY, USA, 2016. Association for Computing Machinery.
- [15] Samir Hasan, Zachary King, Munawar Hafiz, Mohammed Sayagh, Bram Adams, and Abram Hindle. Energy profiles of java collections classes. In *Proceedings of the 38th International Conference on Software Engineering, ICSE '16*, page 225–236, New York, NY, USA, 2016. Association for Computing Machinery.
- [16] Gustavo Pinto, Kenan Liu, Fernando Castor, and Yu David Liu. A comprehensive study on the energy efficiency of java’s thread-safe collections. In *2016 IEEE International Conference on Software Maintenance and Evolution (ICSME)*, pages 20–31, 2016.
- [17] Rui Pereira, Pedro Simão, Jácome Cunha, and João Saraiva. jstanley: placing a green thumb on java collections. In *Proceedings of the 33rd ACM/IEEE International Conference on Automated Software Engineering, ASE '18*, page 856–859, New York, NY, USA, 2018. Association for Computing Machinery.
- [18] Wellington Oliveira, Renato Oliveira, Fernando Castor, Benito Fernandes, and Gustavo Pinto. Recommending energy-efficient java collections. In *2019 IEEE/ACM 16th International Conference on Mining Software Repositories (MSR)*, pages 160–170, 2019.
- [19] Timo Hönig, Christopher Eibel, Rüdiger Kapitza, and Wolfgang Schröder-Preikschat. Seep: exploiting symbolic execution for energy-aware programming. *SIGOPS Oper. Syst. Rev.*, 45(3):58–62, January 2012.
- [20] Timo Hönig, Heiko Janker, Christopher Eibel, Oliver Mihelic, and Rüdiger Kapitza. Proactive Energy-Aware programming with PEEK. In *2014 Conference on Timely Results in Operating Systems (TRIOS 14)*, Broomfield, CO, October 2014. USENIX Association.
- [21] N. Vijaykrishnan, M. Kandemir, S. Kim, S. Tomar, A. Sivasubramanian, and M. J. Irwin. Energy behavior of java applications from the memory perspective. In *Proceedings of the 2001 Symposium on JavaTM Virtual Machine Research and Technology Symposium - Volume 1, JVM'01*, page 23, USA, 2001. USENIX Association.