# Data Access and Authorization

The Google Health API utilizes a robust and standardized framework for managing user data access and security. A central component of this modernization is the transition from legacy Fitbit Authorization (FOT) to Google OAuth 2.0. This shift allows developers to leverage standard Google authentication libraries, simplifying implementation while providing users with a familiar and centralized interface for managing their permissions.

## App Registration

All Google Health API apps must be registered using the Google Cloud console (https://console.cloud.google.com/), which serves as a central hub for managing all of your Google apps.

For instructions on how to register your app, follow the steps at Getting Started (/health/get-started). Here are the differences you'll notice when registering your apps.

| | **Fitbit Web API** | **Google Health API** |
|---|---|---|
| **Public link(s)** | https://dev.fitbit.com/apps (https://dev.fitbit.com/apps) | https://console.cloud.google.com (https://console.cloud.google.com) |
| Adding a new app | Press **Register a new app** | 1. Create a Google Cloud Project<br>2. Enable **Google Health API** |
| **Basic Info** | Fields to complete:<br>• Application Name<br>• Description<br>• Application Website URL<br>• Organization<br>• Organization Website URL<br>• Terms of Service URL<br>• Privacy Policy URL | Fields to complete:<br>• Application name<br>• Support email<br>• Audience (internal or external)<br>• Contact email<br>• Logo icon<br>• Application website URL<br>• Privacy policy URL<br>• Terms of Service URL |

| | | |
|---|---|---|
| | | • Authorized Domain |
| **Application Types** | A developer is required to select:<br>• Server<br>• Client<br>• Personal | • Web application<br>• Android<br>• Chrome Extension<br>• iOS<br>• TVs<br>• Desktop app<br>• Universal Windows platform |
| Client ID | Registered when the application settings are saved | Registered separately |
| Access Type | Read and Write access is controlled at the app level | Read and Write access is controlled at the scope level |
| Additional URLs | • **Redirect URL**: Site where users are redirected to after the authorize the scopes | • **Authorized JavaScript Origins**: HTTP origin that hosts the web application<br>• **Redirect URL**: Site where users are redirected to after the authorize the scopes |

# OAuth Implementation

Google Health API apps only support the Google OAuth2 Client libraries (https://developers.google.com/identity/protocols/oauth2#libraries). Client libraries are available for popular frameworks, which makes implementing OAuth 2.0 simpler. The differences between the Google OAuth2 libraries and the open source OAuth2 libraries are as follows:

| | **Fitbit Web API** | **Google Health API** |
|---|---|---|
| **OAuth2 library support** | Open Source | Google OAuth2 Client libraries (https://developers.google.com/identity/pro |
| **Functionality** | Inconsistent across platforms | Consistent across platforms |
| **Authorization** | https://www.fitbit.com/oauth2/authorize | https://accounts.google.com/o/oauth2/v2/a |

| URL | | |
|---|---|---|
| **Token URL** | https://api.fitbit.com/oauth2/token | https://oauth2.googleapis.com/token |
| **Access Token Lifetime** | 8 hours | 1 hour |
| **Access Token Size** | 1024 bytes | 2048 bytes |
| **Refresh Token** | Refresh tokens are generated when using the Authorization Code Grant Flow. Only 1 refresh token can be generated for a user. Tokens never expire and can only be used once. | To generate a refresh token, the authorizatio the query parameter "access_type=offline". N can be created for a single user. Refresh tok They will expire if they have not been used ir granted time- based access, or the app is in Refresh token expiration (https://developers.google.com/identity/pro details. |
| **Token Response** | JSON response contains:<br>• access token<br>• access token expiration<br>• scopes<br>• token type<br>• refresh token<br>• user ID | JSON response contains:<br>• access token<br>• access token expiration<br>• scopes<br>• token type<br>• refresh token<br><br>To obtain the user id, use the **users.getIdent** |

# User Re-authentication (Mandatory Re-consent)

Fitbit users must re-consent to your new integration, because your app is using a different OAuth library. It is not possible for access tokens and refresh tokens to be transferred to the Google Health API and work.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 4.0 License (https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the Apache 2.0 License (https://www.apache.org/licenses/LICENSE-2.0). For details, see the Google Developers Site Policies (https://developers.google.com/site-policies). Java is a registered trademark

of Oracle and/or its affiliates.

Last updated 2026-06-06 UTC.