# Chapter 4
Network Layer:
The Data Plane

A note on the use of these Powerpoint slides:
We're making these slides freely available to all (faculty, students, readers).
They're in PowerPoint form so you see the animations; and can add, modify,
and delete slides (including this one) and slide content to suit your needs.
They obviously represent a *lot* of work on our part. In return for use, we only
ask the following:

- If you use these slides (e.g., in a class) that you mention their source
  (after all, we'd like people to use our book!)
- If you post any slides on a www site, that you note that they are adapted
  from (or perhaps identical to) our slides, and note our copyright of this
  material.

Thanks and enjoy! JFK/KWR

Computer Networking: A Top Down Approach

7th Edition, Global Edition
Jim Kurose, Keith Ross
Pearson
April 2016

Chapter 4: outline

Chapter 4: network layer

chapter goals:

- understand principles behind network layer services, focusing on data plane:
  - network layer service models
  - forwarding versus routing
  - how a router works
  - generalized forwarding
- instantiation, implementation in the Internet

Network layer

- transport segment from sending to receiving host
- on sending side encapsulates segments into datagrams
- on receiving side, delivers segments to transport layer
- network layer protocols in *every* host, router
- router examines header fields in all IP datagrams passing through it

Two key network-layer functions

network-layer functions:

forwarding: move packets from router's input to appropriate router output

routing: determine route taken by packets from source to destination

  • *routing algorithms*

analogy: taking a trip

- *forwarding:* process of getting through single interchange

- *routing:* process of planning trip from source to destination

---

Network layer: data plane, control plane

Data plane

- local, per-router function
- determines how datagram arriving on router input port is forwarded to router output port
- forwarding function

values in arriving packet header

Control plane

- network-wide logic
- determines how datagram is routed among routers along end-end path from source host to destination host
- two control-plane approaches:
  • *traditional routing algorithms:* implemented in routers
  • *software-defined networking (SDN):* implemented in (remote) servers

Per-router control plane

Individual routing algorithm components *in each and every router* interact in the control plane

Network Layer: Control Plane 5-7

Logically centralized control plane

A distinct (typically remote) controller interacts with local control agents (CAs)

Network Layer: Control Plane 5-8

4

Network service model

Q: What *service model* for "channel" transporting datagrams from sender to receiver?

example services for individual datagrams:
- guaranteed delivery
- guaranteed delivery with less than 40 msec delay

example services for a flow of datagrams:
- in-order datagram delivery
- guaranteed minimum bandwidth to flow
- restrictions on changes in inter-packet spacing

Network layer service models:

Network Architecture	Service Model	Guarantees ?				Congestion feedback
		Bandwidth	Loss	Order	Timing	
Internet	best effort	none	no	no	no	no (inferred via loss)
ATM	CBR	constant rate	yes	yes	yes	no congestion
ATM	VBR	guaranteed rate	yes	yes	yes	no congestion
ATM	ABR	guaranteed minimum	no	yes	no	yes
ATM	UBR	none	no	yes	no	no

Chapter 4: outline

Router architecture overview

- high-level view of generic router architecture:

routing, management control plane (software) operates in millisecond time frame

forwarding data plane (hardware) operttes in nanosecond timeframe

routing processor

high-seed switching fabric

router input ports

router output ports

6

Input port functions

physical layer:
bit-level reception

data link layer:
e.g., Ethernet
see chapter 5

decentralized switching:

- using header field values, lookup output port using forwarding table in input port memory *("match plus action")*
- goal: complete input port processing at 'line speed'
- queuing: if datagrams arrive faster than forwarding rate into switch fabric

Input port functions

physical layer:
bit-level reception

data link layer:
e.g., Ethernet
see chapter 5

decentralized switching:

- using header field values, lookup output port using forwarding table in input port memory *("match plus action")*
- *destination-based forwarding:* forward based only on destination IP address (traditional)
- *generalized forwarding:* forward based on any set of header field values

Destination-based forwarding

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through 11001000 00010111 00010111 11111111	0
11001000 00010111 00011000 00000000 through 11001000 00010111 00011000 11111111	1
11001000 00010111 00011001 00000000 through 11001000 00010111 00011111 11111111	2
otherwise	3

Q: but what happens if ranges don't divide up so nicely?

Longest prefix matching

longest prefix matching

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

Destination Address Range	Link interface
11001000 00010111 00010*** ********	0
11001000 00010111 00011000 ********	1
11001000 00010111 00011*** ********	2
otherwise	3

examples:

DA: 11001000 00010111 00010110 10100001   which interface?

DA: 11001000 00010111 00011000 10101010   which interface?

Longest prefix matching

- we'll see *why* longest prefix matching is used shortly, when we study addressing
- longest prefix matching: often performed using ternary content addressable memories (TCAMs)
  - *content addressable:* present address to TCAM: retrieve address in one clock cycle, regardless of table size
  - Cisco Catalyst: can up ~1M routing table entries in TCAM

Switching fabrics

- transfer packet from input buffer to appropriate output buffer
- switching rate: rate at which packets can be transfer from inputs to outputs
  - often measured as multiple of input/output line rate
  - N inputs: switching rate N times line rate desirable
- three types of switching fabrics

memory   bus   crossbar

Switching via memory

first generation routers:
- traditional computers with switching under direct control of CPU
- packet copied to system's memory
- speed limited by memory bandwidth (2 bus crossings per datagram)

| input port (e.g., Ethernet) | memory | output port (e.g., Ethernet) |

system bus

Switching via a bus

- datagram from input port memory to output port memory via a shared bus
- *bus contention:* switching speed limited by bus bandwidth
- 32 Gbps bus, Cisco 5600: sufficient speed for access and enterprise routers

bus

Switching via interconnection network

- overcome bus bandwidth limitations
- banyan networks, crossbar, other interconnection nets initially developed to connect processors in multiprocessor
- advanced design: fragmenting datagram into fixed length cells, switch cells through the fabric.
- Cisco 12000: switches 60 Gbps through the interconnection network

crossbar

Input port queuing

- fabric slower than input ports combined -> queueing may occur at input queues
  - *queueing delay and loss due to input buffer overflow!*
- Head-of-the-Line (HOL) blocking: queued datagram at front of queue prevents others in queue from moving forward

switch fabric

switch fabric

output port contention:
only one red datagram can be transferred.
lower red packet is blocked

one packet time later:
green packet
experiences HOL
blocking

Output ports

This slide in HUGELY important!

- *buffering* required from fabric faster rate

  Datagram (packets) can be lost due to congestion, lack of buffers

- *scheduling* datagrams

  Priority scheduling – who gets best performance, network neutrality

---

Output port queueing

at *t,* packets more from input to output

one packet time later

- buffering when arrival rate via switch exceeds output line speed
- *queueing (delay) and loss due to output port buffer overflow!*

How much buffering?

- RFC 3439 rule of thumb: average buffering equal to "typical" RTT (say 250 msec) times link capacity C
  - e.g., C = 10 Gpbs link: 2.5 Gbit buffer
- recent recommendation: with *N* flows, buffering equal to

$$\frac{RTT \cdot C}{\sqrt{N}}$$

Scheduling mechanisms

- *scheduling:* choose next packet to send on link
- *FIFO (first in first out) scheduling:* send in order of arrival to queue
  - real-world example?
  - *discard policy:* if packet arrives to full queue: who to discard?
    - *tail drop:* drop arriving packet
    - *priority:* drop/remove on priority basis
    - *random:* drop/remove randomly

packet arrivals → queue (waiting area) — link (server) → packet departures

Scheduling policies: priority

priority scheduling: send highest priority queued packet

- multiple *classes*, with different priorities
  - class may depend on marking or other header info, e.g. IP source/dest, port numbers, etc.
  - real world example?

high priority queue (waiting area)

arrivals → classify → low priority queue (waiting area) → link (server) → departures

arrivals ② ①③ ④ ⑤

packet in service ❶ ❸ ❷ ❹ ❺

departures ① ③ ② ④ ⑤

Scheduling policies: still more

Round Robin (RR) scheduling:

- multiple classes
- cyclically scan class queues, sending one complete packet from each class (if available)
- real world example?

arrivals ② ①③ ④ ⑤

packet in service ❶ ❸ ❷ ❹ ❺

departures ① ③ ③ ④ ⑤

Scheduling policies: still more

Weighted Fair Queuing (WFQ):
- generalized Round Robin
- each class gets weighted amount of service in each cycle
- real-world example?

Chapter 4: outline

4.1 Overview of Network layer
  - data plane
  - control plane

4.2 What's inside a router

4.3 IP: Internet Protocol
  - datagram format
  - fragmentation
  - IPv4 addressing
  - network address translation
  - IPv6

4.4 Generalized Forward and SDN
  - match
  - action
  - OpenFlow examples of match-plus-action in action

15

The Internet network layer

host, router network layer functions:

transport layer: TCP, UDP

network layer

routing protocols
• path selection
• RIP, OSPF, BGP

forwarding table

IP protocol
• addressing conventions
• datagram format
• packet handling conventions

ICMP protocol
• error reporting
• router "signaling"

link layer

physical layer

IP datagram format

IP protocol version number

header length (bytes)

"type" of data

max number remaining hops (decremented at each router)

upper layer protocol to deliver payload to

32 bits

total datagram length (bytes)

for fragmentation/ reassembly

ver	head. len	type of service	length	
16-bit identifier			flgs	fragment offset
time to live	upper layer		header checksum	
32 bit source IP address				
32 bit destination IP address				
options (if any)				
data (variable length, typically a TCP or UDP segment)				

e.g. timestamp, record route taken, specify list of routers to visit.

how much overhead?
❖ 20 bytes of TCP
❖ 20 bytes of IP
❖ = 40 bytes + app layer overhead

IP fragmentation, reassembly

- network links have MTU (max.transfer size) - largest possible link-level frame
  - different link types, different MTUs
- large IP datagram divided ("fragmented") within net
  - one datagram becomes several datagrams
  - "reassembled" only at final destination
  - IP header bits used to identify, order related fragments

fragmentation:
in: one large datagram
out: 3 smaller datagrams

reassembly

IP fragmentation, reassembly

example:

❖ 4000 byte datagram
❖ MTU = 1500 bytes

	length =4000	ID =x	fragflag =0	offset =0		

one large datagram becomes several smaller datagrams

1480 bytes in data field

offset = 1480/8

	length =1500	ID =x	fragflag =1	offset =0		

	length =1500	ID =x	fragflag =1	offset =185		

	length =1040	ID =x	fragflag =0	offset =370		

17

Chapter 4: outline

IP addressing: introduction

- *IP address:* 32-bit identifier for host, router *interface*

- *interface:* connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)

- *IP addresses associated with each interface*

223.1.1.1
223.1.2.1
223.1.1.2
223.1.1.4   223.1.2.9
223.1.1.3
223.1.3.27
223.1.2.2
223.1.3.1   223.1.3.2

223.1.1.1 = 11011111 00000001 00000001 00000001

　　　　　　　223　　　　1　　　　1　　　　1

18

IP addressing: introduction

Q: how are interfaces actually connected?

A: we'll learn about that in chapter 5, 6.

A: wired Ethernet interfaces connected by Ethernet switches

For now: don't need to worry about how one interface is connected to another (with no intervening router)

223.1.1.1

223.1.1.2

223.1.1.3

223.1.1.4

223.1.2.9

223.1.3.27

223.1.2.1

223.1.2.2

223.1.3.1

223.1.3.2

A: wireless WiFi interfaces connected by WiFi base station

Subnets

- IP address:
  - subnet part - high order bits
  - host part - low order bits
- *what's a subnet ?*
  - device interfaces with same subnet part of IP address
  - can physically reach each other *without intervening router*

223.1.1.1

223.1.1.2

223.1.1.3

223.1.1.4

223.1.2.9

223.1.3.27

223.1.2.1

223.1.2.2

subnet

223.1.3.1

223.1.3.2

network consisting of 3 subnets

Subnets

recipe

- to determine the subnets, detach each interface from its host or router, creating islands of isolated networks
- each isolated network is called a *subnet*

223.1.1.0/24

223.1.1.1

223.1.1.2

223.1.1.4   223.1.2.9

223.1.1.3   223.1.3.27

223.1.2.0/24

223.1.2.1

223.1.2.2

subnet

223.1.3.1   223.1.3.2

223.1.3.0/24

subnet mask: /24

Subnets

how many?

223.1.1.2

223.1.1.1   223.1.1.4

223.1.1.3

223.1.9.2   223.1.7.0

223.1.9.1   223.1.8.1   223.1.8.0   223.1.7.1

223.1.2.6   223.1.3.27

223.1.2.1   223.1.2.2   223.1.3.1   223.1.3.2

IP addressing: CIDR

CIDR: Classless InterDomain Routing
- subnet portion of address of arbitrary length
- address format: a.b.c.d/x, where x is # bits in subnet portion of address

```
         subnet                host
         part                  part
11001000  00010111  00010000  00000000

           200.23.16.0/23
```

IP addresses: how to get one?

Q: How does a *host* get IP address?

- hard-coded by system admin in a file
  - Windows: control-panel->network->configuration->tcp/ip->properties
  - UNIX: /etc/rc.config
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

DHCP: Dynamic Host Configuration Protocol

goal: allow host to *dynamically* obtain its IP address from network server when it joins network

- can renew its lease on address in use
- allows reuse of addresses (only hold address while connected/"on")
- support for mobile users who want to join network (more shortly)

DHCP overview:

- host broadcasts "DHCP discover" msg [optional]
- DHCP server responds with "DHCP offer" msg [optional]
- host requests IP address: "DHCP request" msg
- DHCP server sends address: "DHCP ack" msg

DHCP client-server scenario

223.1.1.0/24

223.1.1.1

223.1.1.2

223.1.1.4   223.1.2.9

223.1.1.3   223.1.3.27

DHCP server

223.1.2.1

223.1.2.2

223.1.2.0/24

arriving DHCP client needs address in this network

223.1.3.1   223.1.3.2

223.1.3.0/24

DHCP client-server scenario

DHCP server: 223.1.2.5

DHCP discover

Broadcast: is there a DHCP server out there?

arriving client

DHCP offer

Broadcast: I'm a DHCP server! Here's an IP address you can use

DHCP request

Broadcast: OK. I'll take that IP address!

DHCP ACK

Broadcast: OK. You've got that IP address!

DHCP: more than IP addresses

DHCP can return more than just allocated IP address on subnet:
- address of first-hop router for client
- name and IP address of DNS sever
- network mask (indicating network versus host portion of address)

DHCP: example

- connecting laptop needs its IP address, addr of first-hop router, addr of DNS server: use DHCP

- DHCP request encapsulated in UDP, encapsulated in IP, encapsulated in 802.1 Ethernet

- Ethernet frame broadcast (dest: FFFFFFFFFFFF) on LAN, received at router running DHCP server

- Ethernet demuxed to IP demuxed, UDP demuxed to DHCP

DHCP: example

- DCP server formulates DHCP ACK containing client's IP address, IP address of first-hop router for client, name & IP address of DNS server

- encapsulation of DHCP server, frame forwarded to client, demuxing up to DHCP at client

- client now knows its IP address, name and IP address of DSN server, IP address of its first-hop router

24

DHCP: Wireshark output (home LAN)

request

Message type: <u>**Boot Request (1)**</u>
Hardware type: Ethernet
Hardware address length: 6
Hops: 0
Transaction ID: 0x6b3a11b7
Seconds elapsed: 0
Bootp flags: 0x0000 (Unicast)
Client IP address: 0.0.0.0 (0.0.0.0)
Your (client) IP address: 0.0.0.0 (0.0.0.0)
Next server IP address: 0.0.0.0 (0.0.0.0)
Relay agent IP address: 0.0.0.0 (0.0.0.0)
Client MAC address: Wistron_23:68:8a (00:16:d3:23:68:8a)
Server host name not given
Boot file name not given
Magic cookie: (OK)
Option: (t=53,l=1) **DHCP Message Type = DHCP Request**
Option: (61) Client identifier
   Length: 7; Value: 010016D323688A;
   Hardware type: Ethernet
   Client MAC address: Wistron_23:68:8a (00:16:d3:23:68:8a)
Option: (t=50,l=4) Requested IP Address = 192.168.1.101
Option: (t=12,l=5) Host Name = "nomad"
Option: (55) Parameter Request List
   Length: 11; Value: 010F03062C2E2F1F21F92B
   1 = Subnet Mask; 15 = Domain Name
   3 = Router; 6 = Domain Name Server
   44 = NetBIOS over TCP/IP Name Server
   ......

reply

Message type: **Boot Reply (2)**
Hardware type: Ethernet
Hardware address length: 6
Hops: 0
Transaction ID: 0x6b3a11b7
Seconds elapsed: 0
Bootp flags: 0x0000 (Unicast)
Client IP address: 192.168.1.101 (192.168.1.101)
Your (client) IP address: 0.0.0.0 (0.0.0.0)
Next server IP address: 192.168.1.1 (192.168.1.1)
Relay agent IP address: 0.0.0.0 (0.0.0.0)
Client MAC address: Wistron_23:68:8a (00:16:d3:23:68:8a)
Server host name not given
Boot file name not given
Magic cookie: (OK)
Option: (t=53,l=1) DHCP Message Type = DHCP ACK
Option: (t=54,l=4) Server Identifier = 192.168.1.1
Option: (t=1,l=4) Subnet Mask = 255.255.255.0
Option: (t=3,l=4) Router = 192.168.1.1
Option: (6) Domain Name Server
   Length: 12; Value: 445747E2445749F244574092;
   IP Address: 68.87.71.226;
   IP Address: 68.87.73.242;
   IP Address: 68.87.64.146
Option: (t=15,l=20) Domain Name = "hsd1.ma.comcast.net."

IP addresses: how to get one?

Q: how does *network* get subnet part of IP addr?

A: gets allocated portion of its provider ISP's address space

ISP's block	11001000 00010111 00010000 00000000	200.23.16.0/20	
Organization 0	11001000 00010111 00010000 00000000	200.23.16.0/23	
Organization 1	11001000 00010111 00010010 00000000	200.23.18.0/23	
Organization 2	11001000 00010111 00010100 00000000	200.23.20.0/23	
...	.....	....	....
Organization 7	11001000 00010111 00011110 00000000	200.23.30.0/23	

Hierarchical addressing: route aggregation

hierarchical addressing allows efficient advertisement of routing information:

Organization 0
200.23.16.0/23

Organization 1
200.23.18.0/23

Organization 2
200.23.20.0/23

Organization 7
200.23.30.0/23

Fly-By-Night-ISP

"Send me anything with addresses beginning 200.23.16.0/20"

Internet

ISPs-R-Us

"Send me anything with addresses beginning 199.31.0.0/16"

Hierarchical addressing: more specific routes

ISPs-R-Us has a more specific route to Organization 1

Organization 0
200.23.16.0/23

Organization 2
200.23.20.0/23

Organization 7
200.23.30.0/23

Fly-By-Night-ISP

"Send me anything with addresses beginning 200.23.16.0/20"

Internet

ISPs-R-Us

Organization 1
200.23.18.0/23

"Send me anything with addresses beginning 199.31.0.0/16 or 200.23.18.0/23"

IP addressing: the last word...

Q: how does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned
Names and Numbers http://www.icann.org/

- allocates addresses
- manages DNS
- assigns domain names, resolves disputes

NAT: network address translation

rest of Internet

local network (e.g., home network) 10.0.0/24

10.0.0.1

10.0.0.2

10.0.0.3

10.0.0.4

138.76.29.7

all datagrams *leaving* local network have *same* single source NAT IP address: 138.76.29.7,different source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: network address translation

motivation: local network uses just one IP address as far as outside world is concerned:

- range of addresses not needed from ISP: just one IP address for all devices
- can change addresses of devices in local network without notifying outside world
- can change ISP without changing addresses of devices in local network
- devices inside local net not explicitly addressable, visible by outside world (a security plus)

NAT: network address translation

implementation: NAT router must:

- *outgoing datagrams: replace* (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)
    . . . remote clients/servers will respond using (NAT IP address, new port #) as destination addr

- *remember (in NAT translation table)* every (source IP address, port #) to (NAT IP address, new port #) translation pair

- *incoming datagrams: replace* (NAT IP address, new port #) in dest fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: network address translation

NAT translation table

WAN side addr	LAN side addr
138.76.29.7, 5001	10.0.0.1, 3345
……	……

2: NAT router changes datagram source addr from 10.0.0.1, 3345 to 138.76.29.7, 5001, updates table

1: host 10.0.0.1 sends datagram to 128.119.40.186, 80

S: 10.0.0.1, 3345
D: 128.119.40.186, 80

①

10.0.0.1

②

S: 138.76.29.7, 5001
D: 128.119.40.186, 80

10.0.0.4

138.76.29.7

10.0.0.2

S: 128.119.40.186, 80
D: 138.76.29.7, 5001

③

S: 128.119.40.186, 80
D: 10.0.0.1, 3345

④

10.0.0.3

3: reply arrives dest. address: 138.76.29.7, 5001

4: NAT router changes datagram dest addr from 138.76.29.7, 5001 to 10.0.0.1, 3345

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Network Layer: Data Plane 4-57

NAT: network address translation

- 16-bit port-number field:
  - 60,000 simultaneous connections with a single LAN-side address!
- NAT is controversial:
  - routers should only process up to layer 3
  - address shortage should be solved by IPv6
  - violates end-to-end argument
    - NAT possibility must be taken into account by app designers, e.g., P2P applications
  - NAT traversal: what if client wants to connect to server behind NAT?

Network Layer: Data Plane 4-58

Chapter 4: outline

IPv6: motivation

- *initial motivation:* 32-bit address space soon to be completely allocated.
- additional motivation:
  - header format helps speed processing/forwarding
  - header changes to facilitate QoS

IPv6 datagram format:
- fixed-length 40 byte header
- no fragmentation allowed

IPv6 datagram format

priority: identify priority among datagrams in flow
flow Label: identify datagrams in same "flow."
  (concept of "flow" not well defined).
next header: identify upper layer protocol for data

ver	pri	flow label		
payload len			next hdr	hop limit
source address (128 bits)				
destination address (128 bits)				
data				

← 32 bits →

Other changes from IPv4

- *checksum:* removed entirely to reduce processing time at each hop
- *options:* allowed, but outside of header, indicated by "Next Header" field
- *ICMPv6:* new version of ICMP
  - additional message types, e.g. "Packet Too Big"
  - multicast group management functions

Transition from IPv4 to IPv6

- not all routers can be upgraded simultaneously
  - no "flag days"
  - how will network operate with mixed IPv4 and IPv6 routers?
- *tunneling*: IPv6 datagram carried as *payload* in IPv4 datagram among IPv4 routers

IPv4 header fields
IPv4 source, dest addr

IPv6 header fields
IPv6 source dest addr
UDP/TCP payload

IPv4 payload

IPv6 datagram

IPv4 datagram

Tunneling

logical view:

A B   *IPv4 tunnel connecting IPv6 routers*   E F
IPv6 IPv6   IPv6 IPv6

physical view:

A B C D E F
IPv6 IPv6 IPv4 IPv4 IPv6 IPv6

Tunneling

logical view:

A — B ═══ *IPv4 tunnel connecting IPv6 routers* ═══ E — F
IPv6   IPv6   IPv6   IPv6

physical view:

A — B — C — D — E — F
IPv6 IPv6 IPv4 IPv4 IPv6 IPv6

flow: X	src:B	src:B	flow: X
src: A	dest: E	dest: E	src: A
dest: F	Flow: X	Flow: X	dest: F
	Src: A	Src: A	
	Dest: F	Dest: F	
data			data
	data	data	

A-to-B: IPv6

B-to-C: IPv6 inside IPv4

B-to-C: IPv6 inside IPv4

E-to-F: IPv6

IPv6: adoption

- Google: 8% of clients access services via IPv6
- NIST: 1/3 of all US government domains are IPv6 capable

- *Long (long!) time for deployment, use*
  - 20 years and counting!
  - think of application-level changes in last 20 years: WWW, Facebook, streaming media, Skype, …
  - *Why?*

Chapter 4: outline

Network Layer: Data Plane 4-67

Generalized Forwarding and SDN

Each router contains a *flow table* that is computed and distributed by a *logically centralized* routing controller

Network Layer: Data Plane 4-68

OpenFlow data plane abstraction

- *flow*: defined by header fields
- generalized forwarding: simple packet-handling rules
  - *Pattern:* match values in packet header fields
  - *Actions: for matched packet:* drop, forward, modify, matched packet or send matched packet to controller
  - *Priority*: disambiguate overlapping patterns
  - *Counters:* #bytes and #packets

Flow table in a router (computed and distributed by controller) define router's match+action rules

OpenFlow data plane abstraction

- *flow*: defined by header fields
- generalized forwarding: simple packet-handling rules
  - *Pattern:* match values in packet header fields
  - *Actions: for matched packet:* drop, forward, modify, matched packet or send matched packet to controller
  - *Priority*: disambiguate overlapping patterns
 - *Counters:* #bytes and #packets

* : wildcard

1. src=1.2.*.*, dest=3.4.5.* → drop
2. src = *.*.*.*, dest=3.4.*.* → forward(2)
3. src=10.1.2.3, dest=*.*.*.* → send to controller

OpenFlow: Flow Table Entries

Rule	Action	Stats

Packet + byte counters

1. Forward packet to port(s)
2. Encapsulate and forward to controller
3. Drop packet
4. Send to normal processing pipeline
5. Modify Fields

Switch Port	VLAN ID	MAC src	MAC dst	Eth type	IP Src	IP Dst	IP Prot	TCP sport	TCP dport

Link layer   Network layer   Transport layer

Examples

Destination-based forwarding:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Action
*	*	*	*	*	*	51.6.0.8	*	*	*	port6

IP datagrams destined to IP address 51.6.0.8 should be forwarded to router output port 6

Firewall:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Forward
*	*	*	*	*	*	*	*	*	22	drop

do not forward (block) all datagrams destined to TCP port 22

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Forward
*	*	*	*	*	128.119.1.1	*	*	*	*	drop

do not forward (block) all datagrams sent by host 128.119.1.1

Examples

Destination-based layer 2 (switch) forwarding:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Action
*	22:A7:23: 11:E1:02	*	*	*	*	*	*	*	*	port3

layer 2 frames from MAC address 22:A7:23:11:E1:02
*should be forwarded to output port* **6**

OpenFlow abstraction

- *match+action:* unifies different kinds of devices

- Router
  - *match:* longest destination IP prefix
  - *action:* forward out a link
- Switch
  - *match:* destination MAC address
  - *action:* forward or flood

- Firewall
  - *match*: IP addresses and TCP/UDP port numbers
  - *action:* permit or deny
- NAT
  - *match:* IP address and port
  - *action:* rewrite address and port

OpenFlow example

Example: datagrams from hosts h5 and h6 should be sent to h3 or h4, via s1 and from there to s2

match	action
IP Src = 10.3.*.* IP Dst = 10.2.*.*	forward(3)

Host h6 10.3.0.6

s3

OpenFlow controller

Host h5 10.3.0.5

s1

Host h1 10.1.0.1

Host h2 10.1.0.2

Host h3 10.2.0.3

s2

Host h4 10.2.0.4

match	action
ingress port = 1 IP Src = 10.3.*.* IP Dst = 10.2.*.*	forward(4)

match	action
ingress port = 2 IP Dst = 10.2.0.3	forward(3)
ingress port = 2 IP Dst = 10.2.0.4	forward(4)

Chapter 4: *done!*

4.1 Overview of Network layer: data plane and control plane

4.2 What's inside a router

4.3 IP: Internet Protocol
- datagram format
- fragmentation
- IPv4 addressing
- NAT
- IPv6

4.4 Generalized Forward and SDN
- match plus action
- OpenFlow example

Question: how do forwarding tables (destination-based forwarding) or flow tables (generalized forwarding) computed?

Answer: by the control plane (next chapter)