

3.3 Incident Table

Phase 3 - System and Configuration Setup | Implement Client Script & UI Policy (Incident)

1. Table Details

All incident records are stored in the **Incident** table. The table extends the base **Task** table, inheriting common fields such as Number, State, Assignment group and Short description, and adds incident-specific fields.

Property	Value
Label	Incident
Name (database)	incident
Extends	Task [task]
Number prefix	INC
Display value	Number

2. Key Fields Used in the Project

Field Label	Column Name	Type	Use in Project
Number	number	String	Unique incident identifier
Caller	caller_id	Reference	Person reporting the issue
Category	category	Choice	Read-only when Closed
Impact	impact	Choice	Determines Priority
Urgency	urgency	Choice	Determines Priority
Priority	priority	Choice	Triggers Client Script; UI Policy condition
State	state	Choice	UI Policy condition
Assignment group	assignment_group	Reference	Mandatory when Priority is Critical
On hold reason	hold_reason	Choice	Visible and mandatory when On Hold
Short description	short_description	String	Read-only when Closed

3. Priority Calculation

Priority is calculated from Impact and Urgency through a standard priority lookup. For example, High impact with High urgency results in Priority 1 - Critical. As Priority changes automatically when Impact or Urgency is changed, the onChange Client Script is triggered for either action.