

Lecture 2: R Markdown, Version Control with Git(Hub), and Other Productivity Tools

James Sears*

AFRE 891/991 FS 26

Michigan State University

*Parts of these slides are adapted from [“Advanced Data Analytics”](#) by Nick Hagerty and [“Data Science for Economists”](#) by Grant McDermott.

Table of Contents

1. [Prologue](#)
2. [Version Control](#)
3. [GitHub Desktop](#)
4. [R Markdown](#)
5. [Other Tips and Productivity Tools](#)
6. [Not Covered: Git\(Hub\) + RStudio](#)
7. [Not Covered: Troubleshooting Git Credential Issues in RStudio](#)

Prologue


Prologue

Before we dive in, let's double check that we all have

- ☑ Installed [R](#).
- ☑ Installed [RStudio](#).
- ☑ Signed up for an account on [Github](#)
- ☑ Applied for a [Github Education](#) license
- ☑ Installed [Git](#) and [Github Desktop](#)
- ☑ Log into your Github account on Github Desktop

Version Control

Why Use Version Control



Goals of Version Control

While building project folders with the above naming conventions is *fun*, a good **version control system** can solve this problem.

- Save each set of changes sequentially
- Keep track of different versions of a file
- Merge changes from multiple versions/sources

Git(Hub) Solves this Problem

Git

- **Git** is a **distributed version control system**
 - Each team member has a **local copy** of files on their computer
- Imagine if Dropbox and the "Track changes" feature in MS Word had a baby. Git would be that baby.
- In fact, it's even better than that because Git is optimised for the things that economists and data scientists spend a lot of time working on (e.g. code).
- There is a learning curve, but I promise you it's worth it.

Git(Hub) Solves this Problem

GitHub

- It's important to realise that **Git** and **GitHub** are distinct things.
- **GitHub** is an **online hosting platform** that provides an array of services built on top of the **Git** system. (Similar platforms include Bitbucket and GitLab.)
- Just like we don't *need* **Rstudio** to run **R** code, we don't *need* **GitHub** to use **Git**... but it will make our lives so much easier.

Git(Hub) for Scientific Research

From software development...

- **Git** and **GitHub**'s role in global software development is not in question.
- There's a high probability that your favorite app, program or package is built using Git-based tools. (RStudio is a case in point.)

... to scientific research

- Benefits of VC and collaboration tools aside, Git(Hub) helps to operationalise the ideals of open science and reproducibility.²
- Journals have increasingly strict requirements regarding reproducibility and data access. GH makes this easy (DOI integration, off-the-shelf licenses, etc.)
- I host [teaching materials](#) on GH. I even use it to host and maintain my [website](#) for free.
2: [Democratic databases: Science on GitHub \(Nature\)](#) (Perkel, 2016).

Using GitHub

There are a couple of different main ways that we could use GitHub:

1. Through github.com Only

- **Pros:** doesn't require any software/local repo copies
- **Cons:** much more time-intensive and not automated (the whole point of this thing!)

2. Through the command line ([GitHub CLI](#))

- **Pros:** fully programmatic, requires no additional software
- **Cons:** fully programmatic!

Using GitHub

There are a couple of different main ways that we could use GitHub:

3. Integrated with RStudio

- **Pros:** fully integrates RStudio projects
- **Cons:** limited to R projects, doesn't play as nicely with GitHub Classroom

4. Through the GitHub Desktop App

- **Pros:** Intuitive GUI, sync any kinds of files/projects
- **Cons:** requires an extra piece of software, [GitHub Desktop](#)

We're going to focus primarily on **4**, but the back of the deck will contain slides working through **3** if you want to experiment with that on your own too.

GitHub Desktop

Version Control with GitHub Desktop

Although GitHub integration with RStudio has lots of functionality, there are times where we want to keep track of files and projects **outside of RStudio**.

- For example, when you want version control of projects that **don't only use R** (or don't use it at all)

This is where **GitHub Desktop** comes in.

Version Control with GitHub Desktop

This next section is about learning the basic Git(Hub) commands and the recipe for successful version control with GitHub Desktop.

I also want to bookmark a general point that we'll revisit many times during this course:


- The tools that we're using all form part of a coherent **data science ecosystem**.
- Greatly reduces the cognitive overhead ("aggregation") associated with traditional workflows, where you have to juggle multiple programs and languages at the same time.

Github Desktop Workflow

With GitHub, if we were working

1. On our own
2. From a single computer

we could just follow the below workflow:



Since we're collaborating with others/potentially across machines, we'll also add in a few more actions.

Main Git operations

The first Git operation in the workflow is **Cloning**



(Git) Cloning

No, not *that* kind of cloning.

Cloning: making a local copy of a **GitHub Repository** (repo for short).

In order to clone a repo, we first need a repo to clone. Let's start by cloning our Course repo!

We can do this

1. From the repo page on github.com (direct link or SSH)
2. From GitHub Desktop directly

Course Repo Cloning (github.com)

Let's start with the first approach. With GitHub Desktop installed/open, navigate to our [class web page repo](#).

The screenshot shows the GitHub interface for the repository 'afre-msu / AFRE-891-991-FS26'. The repository is public and has 0 forks, 0 stars, and 0 watchers. The main branch is 'main'. The repository contains several files and folders:

File/Folder	Commit Message	Commit Date
Course Logistics	Update Syllabus AFRE 991 FS26.pdf	last week
Lecture Slides	Update 02-Productivity.pdf	yesterday
.gitattributes	Initial commit	last week
LICENSE	Initial commit	last week
README.md	Update README.md	last week

The README file is selected, showing the title 'Course Materials for AFRE 891/991'. The right sidebar contains links to the README, License, Activity, Custom properties, 0 stars, 0 watching, 0 forks, Audit log, and Report repository. There are also links to Releases and a link to 'Create a new release'.

Course Repo Cloning

Click the green **Code** button and then "Open with GitHub Desktop"

The screenshot shows the GitHub interface for the repository 'AFRE-891-991-FS26'. The repository is public and has a 'main' branch. The file list includes 'Course Logistics', 'Lecture Slides', '.gitattributes', 'LICENSE', and 'README.md'. The 'Code' button is highlighted with a green arrow. The dropdown menu is open, showing options to 'Clone' (with HTTPS, SSH, and GitHub CLI buttons), 'Open in GitHub Copilot app', 'Open with GitHub Desktop' (highlighted with a green arrow), and 'Download ZIP'.

AFRE-891-991-FS26 Public

main 1 Branch 0 Tags

searsjm Update 02-Productivity.pdf

Course Logistics Update Syllabus AFR

Lecture Slides Update 02-Productiv

.gitattributes Initial commit

LICENSE Initial commit

README.md Update README md

README License

Go to file T Add file <> Code

Local Codespaces

Clone

HTTPS SSH GitHub CLI

https://github.com/afre-msu/AFRE-891-991-FS26.1

Clone using the web URL.

Open in GitHub Copilot app


Open with GitHub Desktop

Download ZIP

Course Repo Cloning

Allow your web browser to open the link. This will redirect you to GitHub Desktop, automatically adding in the repo URL.

Next, choose where you want the local copy of the repo file's saved and hit **Clone**



Course Repo Cloning

Wait a little bit, and navigate to the local path you gave it. Voila!

Github

>

AFRE-891-991-FS26

>

Search AFRE-891-991-FS26

...

Name	Status	Date modified	Type	Size
 .git		9/3/2026 10:11 AM	File folder	
 Course Logistics		8/25/2026 3:51 PM	File folder	
 Lecture Slides		9/2/2026 3:01 PM	File folder	
 .gitattributes		8/25/2026 4:18 PM	GITATTRIBUTES File	1 KB
 LICENSE		1/7/2025 3:29 PM	File	21 KB
 README.md		9/3/2026 10:10 AM	MD File	6 KB

Creating a Repo


While there are *tons* of awesome repositories on GitHub that we might want to clone and use as our starting point, other times we want to **create our own repo!**

Let's see how to do this from github.com.

Start by creating your own repo on GitHub — call it "test" — and clone it, this time using the HTTPS link.³

³ It's easiest to start with HTTPS, but **SSH** is advised for more advanced users.

Create a Repository on GitHub (Repo)



The screenshot shows the GitHub profile page for user 'searsjm'. The profile includes a circular profile picture of a man with a beard and glasses, the name 'James Sears', the username 'searsjm', and a bio: 'I am an assistant professor in the Department of Agricultural, Food, and Resource Economics at Michigan State University.' The page displays a grid of 'Popular repositories' including 'searsjm.github.io' (Personal Website, CSS), 'R-Notebook-Test' (Jupyter Notebook), 'covid_ex' (Example repo for filepaths), 'datahub' (Forked from vini, JupyterHubs for, Python), 'test_repo' (Test repository for AFRE 891 lecture, TeX), and 'Assignment-5-AFRE891-SS25' (Template repository for Assignment 5 AFRE 891 SS25). A dropdown menu is open from the '+' icon in the top right, showing options: 'New issue', 'New repository' (highlighted), 'Import repository', 'New codespace', 'New gist', 'New organization', and 'New project'. The bottom of the page shows '74 contributions in the last year' and a '2026' button.

searsjm

Overview Repositories 9 Projects Packages Stars

Popular repositories

- searsjm.github.io (Public) Personal Website CSS
- R-Notebook-Test (Public) Jupyter Notebook
- covid_ex (Public) Example repo for filepaths
- datahub (Public) Forked from vini JupyterHubs for Python
- test_repo (Public archive) Test repository for AFRE 891 lecture TeX
- Assignment-5-AFRE891-SS25 (Public template) Template repository for Assignment 5 AFRE 891 SS25

James Sears
searsjm

I am an assistant professor in the Department of Agricultural, Food, and Resource Economics at Michigan State University.

74 contributions in the last year

Contribution settings 2026

- New issue
- New repository
- Import repository
- New codespace
- New gist
- New organization
- New project

Create a Repository on GitHub (Repo)


Create a new repository

Repositories contain a project's files and version history. Have a project elsewhere? [Import a repository](#).

Required fields are marked with an asterisk (*).

General

Owner *



Repository name *

Test FS26

✓ Your new repository will be created as Test-FS26. The repository name can only contain ASCII letters, digits, and the characters ., -, and _.

Great repository names are short and memorable. How about [laughing-octo-goggles](#)?

Description

Test Repo for AFRE 891/991 Fall 2026

36 / 350 characters

Configuration

Choose visibility *

Choose who can see and commit to this repository

Public

Start with a template

Templates pre-configure your repository with files.

No template

Add README

READMEs can be used as longer descriptions. [About READMEs](#)

On

Add .gitignore

.gitignore tells git which files not to track. [About ignoring files](#)

No .gitignore

Add license

Licenses explain how others can use your code. [About licenses](#)

MIT License

Create a Repository on GitHub (Repo)

The screenshot shows the GitHub interface for a repository named 'Test-FS26' owned by 'searsjm'. The repository is public and has 0 stars, 0 forks, and 0 watchers. It contains a single commit (474c649) with files 'LICENSE' and 'README.md'. The README file is open, showing the title 'Test-FS26' and the description 'Test Repo for AFRE 891/991 Fall 2026'. The right sidebar shows the 'About' section with links to Readme, License, and Activity, and the 'Releases' section with a link to 'Create a new release'.

searsjm / Test-FS26

Type to search

<> Code Issues Pull requests Actions Projects Wiki Security and quality Insights Settings

Test-FS26 Public

Pin Watch 0 Fork 0 Star 0

main 1 Branch 0 Tags

Go to file

Code

searsjm Initial commit 474c649 · now 1 Commit

LICENSE	Initial commit	now
README.md	Initial commit	now

README MIT license

Test-FS26

Test Repo for AFRE 891/991 Fall 2026

About

Test Repo for AFRE 891/991 Fall 2026

- Readme
- License
- Activity
- 0 stars
- 0 watching
- 0 forks

Releases

No releases published

[Create a new release](#)

Packages

Clone a Repository from GitHub (HTTPS)

The screenshot shows the GitHub interface for a repository named 'Test-FS26' by user 'searsjm'. The repository is public and has 0 stars, 0 forks, and 0 watchers. The 'Code' button is clicked, opening a dropdown menu with the 'Clone' option selected. The 'Clone' menu shows the 'HTTPS' tab active, with the URL 'https://github.com/searsjm/Test-FS26.git' highlighted. The repository page shows the README, license (MIT), and repository statistics (0 stars, 0 forks, 0 watching).

searsjm / Test-FS26

Code Issues Pull requests Actions Projects Wiki Security and quality Insights Settings

Test-FS26 Public

Pin Watch 0 Fork 0 Star 0

main 1 Branch 0 Tags

searsjm Initial commit

LICENSE

README.md

README MIT license

Test-FS26

Test Repo for AFRE 891/991 Fall 2026

About

Test Repo for AFRE 891/991 Fall 2026

Readme

License

Activity

0 stars

0 watching

0 forks

Releases

No releases published

[Create a new release](#)

Packages

Local Codespaces

Clone

HTTPS SSH GitHub CLI

`https://github.com/searsjm/Test-FS26.git`


Clone using the web URL.

Open in GitHub Copilot app


Open with GitHub Desktop

Download ZIP

Clone a Repository from GitHub (HTTPS)



Clone a Repository from GitHub (HTTPS)



Clone a Repository from GitHub (HTTPS)

Github > Test-FS26		Search Test-FS26			
...				 Details	
Name	Status	Date modified	Type	Size	
 .git		9/4/2026 10:35 AM	File folder		
 LICENSE		9/4/2026 10:34 AM	File	2 KB	
 README.md		9/4/2026 10:34 AM	MD File	1 KB	

Clone a Repository from GitHub (HTTPS)

The screenshot shows the RStudio interface with a dark theme. The top menu bar includes File, Edit, View, Repository, Branch, and Help. Below the menu, the 'Current repository' is 'Test-FS26', the 'Current branch' is 'main', and the 'Fetch origin' button shows 'Never fetched'. The left sidebar has two tabs: 'Changes' (selected) and 'History'. Under 'Changes', there is a 'Filter' input field and a status bar indicating '0 changed files'. The main workspace area displays the message 'No local changes' with a subtext: 'There are no uncommitted changes in this repository. Here are some friendly suggestions for what to do next.' To the right of this text is a small illustration of a stack of books. Below the message are three suggestions, each with a button: 1. 'Open the repository in your external editor' with a button 'Open in RStudio' and keyboard shortcuts 'Repository menu or Ctrl + Shift + A'. 2. 'View the files of your repository in Explorer' with a button 'Show in Explorer' and keyboard shortcuts 'Repository menu or Ctrl + Shift + F'. 3. 'Open the repository page on GitHub in your browser' with a button 'View on GitHub' and keyboard shortcuts 'Repository menu or Ctrl + Shift + G'. At the bottom left, there is a 'Summary (required)' field and a 'Description' text area. At the bottom center, there is a blue button labeled 'Commit to main'.

File Edit View Repository Branch Help

Current repository
Test-FS26

Current branch
main

Fetch origin
Never fetched

Changes History

Filter

0 changed files

No local changes

There are no uncommitted changes in this repository. Here are some friendly suggestions for what to do next.

Open the repository in your external editor
Select your editor in [Options](#)
Repository menu or **Ctrl** + **Shift** + **A** Open in RStudio

View the files of your repository in Explorer
Repository menu or **Ctrl** + **Shift** + **F** Show in Explorer

Open the repository page on GitHub in your browser
Repository menu or **Ctrl** + **Shift** + **G** View on GitHub

Summary (required)


Description

Commit to main


Making Local Changes

Let's start by making some changes to our local copies of the test repo files.

Open up the README file. Add some text and save the README.



```
# Test-FS26
Test Repo for AFRE 891/991 Fall 2026
```



```
# Test Repository, AFRE 891/991 Fall 2026
```

```
This is a **test repository** to help us *figure out*
```

1. How to use GitHub
2. How to use GitHub Desktop
3. How to be open source and reproducible!

What this is	What this isn't
A test of what we're learning	Everything GitHub can do

Making Local Changes

Open up Github Desktop. Do you see any changes?

The screenshot shows the GitHub Desktop application interface. At the top, the menu bar includes File, Edit, View, Repository, Branch, and Help. Below the menu bar, the status bar shows the current repository is 'Test-FS26', the current branch is 'main', and the 'Fetch origin' button is available, with a note 'Last fetched 1 minute ago'.

The main workspace is divided into three panes. The left pane shows the 'Changes' tab with a filter input and a list of changes: '1 changed file' and 'README.md'. The middle pane shows the diff view for 'README.md', with a table of changes. The right pane shows the content of the file being edited.

Line	Change	Content
1	-	# Test-FS26
2	-	Test Repo for AFRE 891/991 Fall 2026
3	+	# Test Repository, AFRE 891/991 Fall 2026
4	+	
5	+	This is a **test repository** to help us *figure out*
6	+	
7	+	1. How to use GitHub
8	+	
9	+	2. How to use GitHub Desktop
10	+	
11	+	3. How to be open source and reproducible!
12	+	
13	+	
14	+	
15	+	
16	+	


The bottom pane shows the content of the file being edited, which is a README.md file. It contains a table with two columns: 'what this is' and 'what this isn't'. The table has a header row and a body row. The body row contains the text 'A test of what we're learning' and 'Everything GitHub can do'.

At the bottom of the interface, there is a section for 'Update README.md' with a 'Description' field and a 'Commit' button.

Stage

Github Desktop detects local changes and automatically **stages** those changes


- Tells Git that you edited the `README.md` file and documents *how* it changed from the upstream repo version



Commit and Push

For now, these changes are **local to our own repo copy**.

Local System



A screenshot of a local text editor window titled 'README.md'. The window has a menu bar with 'File', 'Edit', and 'View'. The content of the file is as follows:

```
# Test Repository, AFRE 891/991 Fall 2026

This is a test repository to help us figure out


1. How to use GitHub

2. How to use GitHub Desktop

3. How to be open source and reproducible!

|           What this is           |           What this isn't           |
|-----|-----|
| A test of what we're learning | Everything GitHub can do |
```

GitHub



A screenshot of the GitHub web interface for a repository named 'Test-FS26'. The file 'README.md' is selected. The commit history shows an 'Initial commit' by user 'searsjm' 8 minutes ago. The file content is displayed in a code viewer with tabs for 'Preview', 'Code', and 'Blame'. The content of the file is as follows:

```
1 # Test-FS26
2 Test Repo for AFRE 891/991 Fall 2026
```

In order for them to **update the main repo itself**, we need to do two actions: **Commit** and **Push**.


Commit

Github Desktop automatically stages any changes it detects, so that's part of the trouble taken care of already!

Now we need to **Commit:** tell Git that, yes, you are sure these staged changes should be part of the repo history.

Commit


To **commit** in GitHub Desktop, we need to first give our commit a name and a description (bottom-left):



Push


Next we need to **Push**: send the local file changes/additions to update the repo on GitHub.

In the upper-right corner you should now see the option to **Push origin**:



Push

Click it and wait. That's it!



The screenshot shows the RStudio application window. The top menu bar includes File, Edit, View, Repository, Branch, and Help. Below the menu bar, the 'Current repository' is 'Test-FS26' and the 'Current branch' is 'main'. The 'Fetch origin' button is visible, indicating the last fetch was 'just now'. The left sidebar has two tabs: 'Changes' (selected) and 'History'. Under 'Changes', there is a filter input and a checkbox indicating '0 changed files'. The main pane displays the message 'No local changes' with a friendly suggestion to do next. Below this, there are three options with buttons: 'Open the repository in your external editor' (with 'Open in RStudio' button), 'View the files of your repository in Explorer' (with 'Show in Explorer' button), and 'Open the repository page on GitHub in your browser' (with 'View on GitHub' button). The bottom left shows a 'Summary (required)' field and a 'Description' text area.

File Edit View Repository Branch Help

Current repository
Test-FS26

Current branch
main

Fetch origin
Last fetched just now

Changes History

Filter

0 changed files

No local changes

There are no uncommitted changes in this repository. Here are some friendly suggestions for what to do next.

Open the repository in your external editor
Select your editor in [Options](#)
Repository menu or **Ctrl + Shift + A** Open in RStudio

View the files of your repository in Explorer
Repository menu or **Ctrl + Shift + F** Show in Explorer

Open the repository page on GitHub in your browser
Repository menu or **Ctrl + Shift + G** View on GitHub

Summary (required)

Description

Person icon | Gear icon

Changes Now Visible on GitHub

 **Test-FS26** Public

 Pin  Watch **0**  Fork **0**  Star **0**

 main  1 Branch  0 Tags   Code

 **searsjm** Update Readme File  228b44c · 2 minutes ago  2 Commits

 LICENSE Initial commit 13 minutes ago

 README.md Update Readme File 2 minutes ago

README MIT license 

Test Repository, AFRE 891/991 Fall 2026

This is a **test repository** to help us *figure out*

1. How to use GitHub
2. How to use GitHub Desktop
3. How to be open source and reproducible!

What this is	What this isn't
A test of what we're learning	Everything GitHub can do

About

Test Repo for AFRE 891/991 Fall 2026

-  Readme
-  MIT license
-  Activity
-  0 stars
-  0 watching
-  0 forks

Releases

No releases published
[Create a new release](#)

Packages

No packages published
[Publish your first package](#)

Contributors 1

 **searsjm** James Sears

Recap

Here's a step-by-step summary of what we just did.

- Cloned a repo from GitHub
- Made same changes to a repo file and saved them locally.
- **Staged** these local changes (okay, Github Desktop did that for us).
- **Committed** these local changes to our Git history with a helpful message.
- **Pushed** our changes to the GitHub repo.

This completes the single collaborator/computer workflow.

But what if we're in a multiple author and/or multiple system situation?

A: we need to bring the last Git Action: **Pull**.

Pull

Just like we **Pushed** our downstream changes to the GitHub repo, we can also **Pull** upstream changes *from* the repo


- Overwrites our current version of files with the newer versions from the GitHub repo

When working with others, it's **critical** to **Pull** updates from the GitHub repo just in case anyone else made changes too (not expected here, but good practice).

Aside: Always pull from the upstream repo *before* you push any changes. Seriously, do this even on solo projects; making it a habit will save you headaches down the road.

Pull

To set up a possible pull, let's make some **upstream changes**. On Github, click on the plus symbol to **add a new file**.



The screenshot shows the GitHub interface for a repository named 'Test-FS26' by user 'searsjm'. The repository is public. The top navigation bar includes links for Code, Issues, Pull requests, Actions, Projects, Wiki, Security and quality, Insights, and Settings. Below the repository name, there are buttons for Pin, Watch (0), Fork (0), and Star (0). The main content area shows the 'main' branch with 1 branch and 0 tags. A search bar 'Go to file' is present. A green '+ Code' button is highlighted, and a dropdown menu is open showing options: 'Create new file' and 'Upload files'. The commit history shows a commit 'searsjm Update Readme File' with hash '228b44c' and a message 'Initial commit'.

Pull

[Code](#) [Issues](#) [Pull requests](#) [Actions](#) [Projects](#) [Wiki](#) [Security and quality](#) [More](#)

 **Test-FS26** / Another Readme.md in main Cancel changes Commit changes...

Edit Preview

Spaces 2 No wrap

```
1  # Another Readme
2
3  Oh dang, now there's two of them!
```

Pull

Test-FS26 / Another Readme.md in main

Cancel changes Commit changes...

Edit Preview

1 # Another Readme

2

3 Oh dang, now the

Commit changes

Commit message

Create Another Readme.md

Extended description

Add an optional extended description...

Commit Email

james.sears.m@gmail.com

☒ Commit directly to the main branch

☐ Create a **new branch** for this commit and start a pull request [Learn more about pull requests](#)

Cancel Commit changes

Pull

  main  **Test-FS26 / Another Readme.md** 

 Go to file  

 **searsjm** Create Another Readme.md a804905 · now 

Preview Code Blame

 3 lines (2 loc) · 52 Bytes

Raw    


Another Readme

Oh dang, now there's two of them!


Pull

Flip back over to GitHub Desktop. One of two things may have happened.

1. Your GitHub Desktop already detected the upstream changes




If you just see **fetch origin**, click it to refresh and retrieve the changes.



Pull

Click the **pull origin** button to add the new file to your local clone

- Same thing would have happened if someone had modified existing files



Github > Test-FS26 Search Test-FS26

... Details

Name	Status	Date modified	Type	Size
.git	✓	9/4/2026 10:51 AM	File folder	
Another Readme.md	✓	9/4/2026 10:51 AM	MD File	1 KB
LICENSE	✓	9/4/2026 10:34 AM	File	2 KB
README.md	✓	9/4/2026 10:39 AM	MD File	1 KB

Why this Workflow: GitHub

Creating the repo on GitHub first means that it will **always be "upstream"** of your (and any other) local copies.

- In effect, this allows GitHub to act as the **central node** in the distributed VC network.
- Especially valuable when you are collaborating on a project with others, but also has advantages when you are working alone.
- If you would like to move an existing project to GitHub, my advice is still to **create an empty repo there first**, clone it locally, and then copy all your files across.

R Markdown

R Markdown

Before we dive into version control, let's chat about **R Markdown**.

R Markdown is a document type that allows for integration of R code and output into a Markdown document.

Resources:

- Website: rmarkdown.rstudio.com
- [R Markdown Cheatsheet](#)
- Book: [R Markdown: The Definitive Guide](#) (Yihui Xie, JJ Allaire, and Garrett Grolemund)

R Markdown

Before we dive into version control, let's chat about **R Markdown**.

R Markdown is a document type that allows for integration of R code and output into a Markdown document.

Other points:

- We'll be completing assignments using R Markdown.
- FWIW, my lecture slides and notes are all written in R Markdown too.
(E.g. This slide deck is built using the xaringan package with the metropolis theme.)

R Markdown: Getting Started

☒ Installed [R](#).

☒ Installed [RStudio](#).

☐ Add the `rmarkdown` package


```
install.packages("rmarkdown")
```

☐ Install LaTeX

- If just for this, can use [TinyTex](#)

```
# Install only if you don't have LaTeX already  
install.packages("tinytex")  
tinytex::install_tinytex()
```

R Markdown: Creating a New .Rmd File



R Markdown: Creating a New .Rmd File

New R Markdown

Document

Presentation

Shiny

From Template

Title: Test R Markdown

Author: James

Date: 2024-01-10

☐ Use current date when rendering document


Default Output Format:

☒ HTML
Recommended format for authoring (you can switch to PDF or Word output anytime).

☐ PDF
PDF output requires TeX (MiKTeX on Windows, MacTeX 2013+ on OS X, TeX Live 2013+ on Linux).

☐ Word
Previewing Word documents requires an installation of MS Word (or Libre/Open Office on Linux).

R Markdown: Creating a New .Rmd File



RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function Addins

02-Productivity.Rmd x Untitled1 x R-Markdown-example.Rmd x 02-Git.Rmd x 01-R-Intro.Rmd x

Knit on Save ABC Knit Run

Source Visual Outline

```
1 ---
2 title: "Test R Markdown"
3 author: "James"
4 date: "2024-01-10"
5 output: html_document
6 ---
7
8 ```{r setup, include=FALSE}
9 knitr::opts_chunk$set(echo = TRUE)
10 ```
11
12 ## R Markdown
13
14 This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML,
15 PDF, and MS Word documents. For more details on using R Markdown see
16 <http://rmarkdown.rstudio.com>.
17
18 When you click the Knit button a document will be generated that includes both content
19 as well as the output of any embedded R code chunks within the document. You can embed an R
20 code chunk like this:
21
22 ```{r cars}
23 summary(cars)
24 ```
```

Modify Chu

R Markdown Components

R Markdown combines

1. **Markdown:** lightweight markup language
2. **LaTeX:** typesetting for math
3. **R:** include code and generate output

Let's do some practice: **open a new .Rmd file** and try adding content as we go

Markdown

Markdown allows for formatting text in a lightweight way

I highly recommend the handy [Markdown Guide](#) for more details

Markdown: Heading

Headings emphasize text and add chunks to your script

Largest heading with one leading # (slide title above)

Second Largest (##)

Third Largest (###)

Getting Smaller... (####)

Bold Text for comparison

Normal Text for comparison

Markdown: Text Format

Bold text with `**your text**`

Italicize with `*single asterisks*`

Add `code text` with grave accents (the back tick symbol, ```)

- The other output of the tilde key `~` on keyboard

End a line with two spaces to start a new paragraph

- or leave a line space between sentences

Can also start a new line with backslash (`\`)

Markdown: Text Format

Add superscripts² with ^carets^

Add ~~strikethroughs~~ with ~~double tildes~~

Add a line break (horizontal rule)

with ***

Markdown: Text Format

Draw **tables** using | and -

- | to delineate column breaks
- --- to separate headers from entries

```
| Col A | Col B | Col C |
```

```
| ---   | ---   | ---   |
```

```
| This  | is    | a      |
```

```
| Table |      | wow    |
```

Col A Col B Col C		
This	is	a
Table		wow

Markdown: Text Format

You can adjust the **alignment** of table text by adding `:`'s in the second row:

- `:-----` for left-aligned
- `:---:---` for center-aligned
- `-----:` for right-aligned

Column A	Column B	Column C
Col A	is	left-aligned
Col B	is	center-aligned
Col C	is	right-aligned

Markdown: Lists

Add an **ordered list** with **1.**

1. First Item
2. Second Item
3. No need to change the number - keep using 1. It will automatically update.

Add an **unordered list** with *** or -**

- A thing
- Another related thing
 - Indent to nest
 1. Can mix ordered and unordered

Markdown: Inputs

Add a **link** with `[]()`

- `[text label](URL)`
- Add direct link with `<URL>` **<https://www.markdownguide.org>**

Add an image with `![]()`

- `![alt text](link)`
 - Where *link* is either a local file path or a URL

practice by adding `images/smile.png`:



Markdown: LaTeX

Another advantage of Markdown is that it integrates $\text{\LaTeX}$ functionality for typesetting math.

Add an **inline equation** with $\$TeX\$$

$$\textit{Var}(X) = \sum_{i=1}^n \frac{(x_i - \bar{x})^2}{n} \quad Y_{it} = \beta_0 + \beta_1 X_{it} + \epsilon_{it}$$

Add multiple rows of LaTeX with

$\$$

LaTeX lines here

$\$$


Use the **standard LaTeX commands** for symbols/characters

Rmd: R Code

R code is primarily executed with **code chunks**

Add a chunk with

- Cmd + Option + I (Ctrl + Alt + I on PC)
- The **Insert** button in the UI
- Manually type



Rmd: Code Chunks


307

308 ~~~{r}

309

310 ~~~

311



Code chunks allow us to add as many lines of code as we want

- Output will appear underneath after executing the full chunk
- Can customize whether it runs, how output is displayed
- Can run manually
 - Line by line with `Cmd/Ctrl + Enter`
 - Entire chunk with `Run Entire Chunk` button

Code Chunk Options

You can **add chunk options** in brackets after `r` and separated by commas.

Some commonly-used options include:

Chunk label (i.e. `sum`)

- Must be unique names!
- Doesn't appear in compiled document

RMarkdown File

```
14 ~~~ {r sum}
15 2 + 2
16 ~~~
```

Compiled File

```
2 + 2
```

```
## [1] 4
```

Code Chunk Options

`echo = FALSE` will

- **run the code** and
- **display output** but
- **hide the code chunk** from the final document

RMarkdown File

```
19 {r, echo = FALSE}  
20 2 + 2  
21 }
```

Compiled File

```
## [1] 4
```

Code Chunk Options

`include = FALSE` will

- **run the code** but
- **hide the output** and
- **hide the code chunk** from the final document

RMarkdown File

```
26 {r, include = FALSE}  
27 2 + 2  
28 }
```

Compiled File

Code Chunk Options

You can **add chunk options** in brackets after `r` and separated by commas.

Some commonly-used options include:

`eval = FALSE` will

- **display code** in the chunk but
- **not run it**
- i.e. **no output** to display

RMarkdown File

```
33 {r, eval = F}  
34 2 + 2  
35
```

Compiled File

2 + 2

Code Chunk Options

You can also **change the color** of code chunks and/or output in the rendered document through code chunk options¹

- `class.source` to change the **code chunk**
- `output.source` to change the **output**

```
14 {r sum, class.source = "bg-success", output.source = "bg-danger"}  
15 2 + 2  
16 }
```

Code Chunk Options

You can also **change the color** of code chunks and/or output in the rendered document through code chunk options¹

- `class.source` to change the **code chunk**
- `output.source` to change the **output**

default

```
1 + 2 * 3 ^ 4
```

```
## [1] 163
```

bg-primary

```
1 + 2 * 3 ^ 4
```

```
## [1] 163
```

¹ We'll chat more about this when we get to web scraping, but what's actually happening here is that we're harnessing some built-in CSS classes to change the backgrounds. This also means that, using CSS, you can define custom classes and format things however you'd like.

Code Chunk Options

You can also **change the color** of code chunks and/or output in the rendered document through code chunk options¹

- `class.source` to change the **code chunk**
- `output.source` to change the **output**

bg-success

```
1 + 2 * 3 ^ 4
```

```
## [1] 163
```

bg-info

```
1 + 2 * 3 ^ 4
```

```
## [1] 163
```

¹ We'll chat more about this when we get to web scraping, but what's actually happening here is that we're harnessing some built-in CSS classes to change the backgrounds. This also means that, using CSS, you can define custom classes and format things however you'd like.

Code Chunk Options

You can also **change the color** of code chunks and/or output in the rendered document through code chunk options¹

- `class.source` to change the **code chunk**
- `output.source` to change the **output**

bg-warning

```
1 + 2 * 3 ^ 4
```

```
## [1] 163
```

bg-danger

```
1 + 2 * 3 ^ 4
```

```
## [1] 163
```

¹ We'll chat more about this when we get to web scraping, but what's actually happening here is that we're harnessing some built-in CSS classes to change the backgrounds. This also means that, using CSS, you can define custom classes and format things however you'd like.

Rmd: Inline Code

You can call R objects from earlier chunks **inline** with

```
- r -
```

```
four = 2+2
```


This can output in line with text: $2 + 2 = 4$

R Markdown File Organization

1. Header

RStudio automatically builds the R Markdown file from a template, which begins with a **header**

- Title
- Author
- Date
- Output Format
 - Main options²: HTML
(`html_document`), PDF
(`pdf_document`), LaTeX
(`latex_document`), or Word
(`word_document`)



```
1 ---  
2 title: "Test RMD"  
3 author: "James Sears"  
4 date: "2024-01-11"  
5 output: html_document  
6 ---
```

² See [CH 3 of "R Markdown: The Definitive Guide" for more on how to customize output formats](#)

2. R Setup

By default, RStudio adds a **setup** code chunk next.

```
8  ```{r setup, include=FALSE}
9  knitr::opts_chunk$set(echo = TRUE)
10 ```
11
```

- Can set global options
- Useful as your preamble
- For **R Notebooks**, this will automatically be run and is the only place where you can change your working directory


3. Contents

From here on you can build the report/notebook as needed for the task.

- Add any writing and outside graphics or **bibTeX citations**
- Add code chunks to carry out desired analysis
- Employ sections and formatting to structure the document as desired

Compiling/Knitting

When you are ready to compile your final document, use the **Knit** button or **Ctrl/Cmd + Shift + K**



R Markdown: Knit to Compile Output



The screenshot shows a web browser window with the address bar displaying the file path: `F:/OneDrive - Michigan State University/Teaching/MSU 2023-2024/AFRE 891 SS23/Lecture-Slides/02-Productivity/output/R-Markdown-example.html`. The browser tab is labeled "R-Markdown-example.html". The document content includes a title, author, date, a section header, an introductory paragraph with a link, a paragraph about the Knit button, a code chunk for `summary(cars)`, and a table of summary statistics.

Test R Markdown

James
2024-01-10

R Markdown

This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see <http://rmarkdown.rstudio.com>.

When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:

```
summary(cars)
```

##	speed	dist
## Min.	: 4.0	Min. : 2.00
## 1st Qu.:	12.0	1st Qu.: 26.00
## Median :	15.0	Median : 36.00
## Mean :	15.4	Mean : 42.98
## 3rd Qu.:	19.0	3rd Qu.: 56.00
## Max.	:25.0	Max. :120.00

Markdown Practice!

Markdown Practice

1. Create a new R Markdown file named "R-Markdown-Ex.RMD"
2. In the setup chunk, load the `dslabs` and `tidyverse` packages
 - Use the `data()` function to read in the `divorce_margarine` dataset
3. Add a header labeled "Correlation vs. Causation" and a text explanation below for why we often want to differentiate between the two
4. Add a code chunk with the label `plot`
 - Type the following code:

```
ggplot(divorce_margarine) +  
  geom_point(aes(x = margarine_consumption_per_capita,  
                 y = divorce_rate_maine)) +  
  labs(title = "Relationship between Margarine Consumption and  
             Divorce Rates in Maine",  
        subtitle = "2000-2009",  
        x = "Margarine Consumption per Capita",  
        y = "Divorce Rate")
```

5. Knit and save a PDF/HTML copy of the file to the "output" folder

Other Tips and Productivity Tools

Productivity Miscellanea

What follows are miscellaneous things that I find **improve my productivity**

- **Synced Cloud Storage** (SpartanDrive or Dropbox/Box)
- **Overleaf** for LaTeX collaboration
- **Connected Papers** for literature networks

Synced Cloud Storage and OneDrive

Synced Cloud Storage is hugely beneficial if you work across **multiple computers** or **with many collaborators**.

- Make sure each computer has the most up-to-date version of all your files
- Renders flash drives almost entirely obsolete!

Synced Cloud Storage and OneDrive

One easy way to do this: **SpartanDrive/OneDrive**

All faculty + staff get **5 TB of free storage** on **SpartanDrive (MSU's version of OneDrive)**.

Pros

- Free
- Syncable desktop apps
- Part of the MSU Office365 ecosystem

Cons

- Part of the MSU Office365 ecosystem
- Limited storage (5TB, 250gb max filesize)
- Sometimes finicky

Synced Cloud Storage

Alternatives to SpartanDrive:


- **Dropbox**: 2GB free (\$10/mo for 2TB)
- **Box**: 10GB free (\$10/mo for 100GB)

Ultimate choice of platform may depend on coauthors + your current choice, but it's a good idea to **download the desktop app** to keep your files synced + backed up!

- Also gives basic version control

Overleaf


If you typeset using LaTeX, **Overleaf** streamlines access and collaboration



Free Version: remotely host all files, access for you + 1 collaborator

Paid (\$7.40/mo): track changes + full document history, Git(hub) + Dropbox integration, up to 6 collaborators

Connected Papers



- Graphical representation of paper networks
 - Visualize literature as directed graph
 - 5 free per month (unlimited for \$6/mo)

Your Productivity Tips + Tricks?

Not Covered: Git(Hub) and RStudio

Git(Hub) Integration in RStudio

One of the (many) features of RStudio is how well it integrates version control into your everyday workflow.

- Even though Git is a completely separate program to R, they feel like part of the same "thing" in RStudio.
- This next section is about learning the basic Git(Hub) commands and the recipe for successful project integration with RStudio.

Link a GitHub Repo to an RStudio

The starting point for our workflow is to link a GitHub repository (i.e. "repo") to an RStudio Project. Here are the steps we're going to follow:

1. Create the repo on GitHub and initialize with a README.
2. Copy the HTTPS/SSH link (the green "Clone or Download" button).
3. Open up RStudio.
4. Navigate to **File -> New Project -> Version Control -> Git**.
5. Paste your copied link into the "Repository URL:" box.
6. Choose the project path ("Create project as subdirectory of:") and click **Create Project**.

Let's practice this using our existing test repo. Start by copying the repo link.


Create new R Project

To start, we need to create an **R Project**


- A project (i.e. folder) specific to a given task

Open a new RStudio window and click **"File > New Project"**

Version Control



Choose Git



Add Repo info

New Project Wizard

[Back](#)

Clone Git Repository



Repository URL:


Project directory name:

Create project as subdirectory of:
 [Browse...](#)

☐ Open in new session

[Create Project](#) [Cancel](#)

Add Repo into RStudio



The screenshot shows the RStudio interface with the following components:

- Console:** Displays the R version 4.2.2 (2022-10-31 ucrt) -- "Innocent and Trusting" and the current directory: F:/OneDrive - Michigan State University/Github Test/test/.
- Environment:** Shows the Global Environment, which is currently empty.
- Files:** Displays the file explorer for the current directory, showing files: .gitignore (44 B), LICENSE (1.1 KB), README.md (25 B), and test.Rproj (250 B).

The console output includes the following text:

```
R version 4.2.2 (2022-10-31 ucrt) -- "Innocent and Trusting"
Copyright (C) 2022 The R Foundation for Statistical Computing
Platform: x86_64-w64-mingw32/x64 (64-bit)

R is free software and comes with ABSOLUTELY NO WARRANTY.
You are welcome to redistribute it under certain conditions.
Type 'license()' or 'licence()' for distribution details.

R is a collaborative project with many contributors.
Type 'contributors()' for more information and
'citation()' on how to cite R or R packages in publications.

Type 'demo()' for some demos, 'help()' for on-line help, or
'help.start()' for an HTML browser interface to help.
Type 'q()' to quit R.

>
```

Making Local Changes

Look at the **top-right panel** in your RStudio IDE. Do you see the **Git** tab?


- Click on it.
- There should already be some files in there, which we'll ignore for the moment.⁴

Now open up the README file (see the "Files" tab in the bottom-right panel).

- Add some text and save the README.
- Do you see any changes in the **Git** panel? Good. (Raise your hand if not.)

⁴ They're important, but not for the purposes of this section.

Stage and Commit



The screenshot shows the RStudio interface with a project named "test - main". The main editor displays a README.md file with the following content:

```
1 # Test Repository
2
3 This is a test repository to help us figure out
4 1. How to use GitHub
5 1. How to integrate it with RStudio Projects
6
7 | what this is | what this isn't |
8 | ----- | ----- |
9 | A test of what we're learning | Everything GitHub can do |
```

The right-hand pane shows the Git status. The "Staged" tab is active, displaying a list of files with their status icons:

Staged	Status	File
☐	?	.gitignore
☐	M	README.md
☐	?	test.Rproj

A tooltip for the "Commit" button indicates "Commit pending changes (Ctrl+Alt+M)". Below the Git pane, the "Files" pane shows the project structure:

Name	Size
..	
.gitignore	44 B

Stage and Commit

The screenshot shows the RStudio 'Review Changes' window. At the top, there are tabs for 'Changes' and 'History', and a dropdown for the current branch 'main'. Below these are buttons for 'Stage' (checked), 'Revert', and 'Ignore'. On the right, there are 'Pull' and 'Push' buttons. A status bar indicates 'Your branch is ahead of 'origin/main' by 1 commit.'

The main area is divided into two panes. The left pane shows a list of files with their status and a checkbox to stage them:


Staged	Status	Path
☐	? ?	.gitignore
☒	M	README.md
☐	? ?	test.Rproj

The right pane is for the 'Commit message', which currently contains the text 'Update readme text|'. Below the message box is an 'Amend previous commit' checkbox and a 'Commit' button.

At the bottom, there is a 'Show' section with radio buttons for 'Staged' (selected) and 'Unstaged'. It also includes a 'Context' dropdown set to '5 lines', an 'Ignore Whitespace' checkbox, and an 'Unstage All' button. Below this, a diff view shows the changes to the README.md file:

```
@@ -1,8 +1,8 @@
1 1 # Test Repository
2 2
3 3 This is a **test repository** to help us *figure out*
3 3 This is a **test repository** to help us *figure out*
4 4 1. How to use GitHub
5 5 1. How to integrate it with RStudio Projects
6 6
7 7 | what this is | what this isn't |
8 8 | ----- | ----- |
```


Stage and Commit

A screenshot of a terminal window titled "Git Commit" with a "Close" button in the top right corner. The terminal shows the output of a git commit command. The first line is the command prompt and the command itself: ">>> C:/Program Files/Git/bin/git.exe commit -F C:/Users/James/AppData/Local/Temp/". The second line shows the commit message: "[main 50fe2dd] Update readme text". The third line shows the summary of changes: "1 file changed, 1 insertion(+), 1 deletion(-)". There is a vertical cursor on the line below the summary. A scrollbar is visible at the bottom of the terminal area.

```
>>> C:/Program Files/Git/bin/git.exe commit -F C:/Users/James/AppData/Local/Temp/
[main 50fe2dd] Update readme text
1 file changed, 1 insertion(+), 1 deletion(-)
|
```

Pull

The screenshot shows the RStudio interface. A 'Git Pull' dialog box is open in the center, displaying the command `>>> C:/Program Files/Git/bin/git.exe pull` and the message 'Already up to date.' with a 'Close' button. In the background, the 'Changes' pane on the left shows a file named 'Test Repository' with a status of 'M' (modified). The main editor window shows the content of 'Test Repository', which includes a header, a list of topics, and a table. The table has two columns: 'What this is' and 'What this isn't'. The content is as follows:

```
1 # Test Repository
2
3 This is a **test repository** to help us *figure out*
4 1. How to use GitHub
5 1. How to integrate it with RStudio Projects
6
7 | What this is | What this isn't |
8 | ----- | ----- |
9 | A test of what we're learning | Everything GitHub can do |
No newline at end of file
```

On the right side of the RStudio window, there are panels for 'Commit', 'Unstage chunk', and 'Present'.

Push



Sign RStudio into Github

The screenshot shows the RStudio interface. At the top, a 'Git Push' window is open, displaying a terminal with the command `>>> C:/Program Files/Git/bin/git.exe push origin HEAD:refs/heads/main`. Below this, a green console window shows the text `**test repository** to help us *figure out* to use GitHub`. In the bottom left, a 'Connect to GitHub' dialog box is visible, featuring the GitHub logo and the text 'Sign in'. The bottom right corner of the screen displays the page number '108 / 120'.

Git Push

```
>>> C:/Program Files/Git/bin/git.exe push origin HEAD:refs/heads/main
```

istory
epository

```
**test repository** to help us *figure out*  
to use GitHub
```


Connect to GitHub

GitHub
Sign in

do |

108 / 120

Sign RStudio into Github



Authorize Git Credential Manager



Git Credential Manager by [Git Ecosystem](#)

wants to access your [searsjm](#) account



Gists

Read and write access



Repositories



Changes Now Visible on Github

  searsjm / test

Q Type to search

>

+









<> Code

Issues

Pull requests

Actions

Projects

Wiki

Security

Insights

Settings

 test Public

Pin

Unwatch 1

Fork 0

Star 0

main

1 Branch

0 Tags

Go to file

t

+

<> Code

About

 searsjm Update Readme 52525f2 · now 3 Commits

 LICENSE Initial commit 42 minutes ago

 README.md Update Readme now

README

MIT license



Test Repository

This is a **test repository** to help us *figure out*

- How to use GitHub
- How to integrate it with RStudio Projects

What this is	What this isn't
A test of what we're learning	Everything GitHub can do

Test Repository

 Readme

 MIT license

 Activity

 0 stars

 1 watching

 0 forks

Releases

No releases published

[Create a new release](#)

Packages

No packages published

[Publish your first package](#)

Changes Now Visible Locally Too

OneDrive - Michigan State University > Github > test

Name	Status	Date modified	Type	Size
.git	✓	1/15/2024 4:35 PM	File folder	
.Rproj.user	✓	1/15/2024 3:47 PM	File folder	
.gitignore	✓	1/15/2024 3:47 PM	Text Document	1 KB
.Rhistory	✓	1/15/2024 4:35 PM	RHISTORY File	0 KB
LICENSE	✓	1/15/2024 3:47 PM	File	2 KB
README.md	✓	1/15/2024 4:32 PM	MD File	1 KB
test.Rproj	✓	1/15/2024 4:32 PM	R Project	1 KB

README.md — Github\test — F:\OneDrive - Michigan State University\Github\test — Atom

File Edit View Selection Find Packages Help

Project



Your project is currently empty

Add folders

Reopen a project

Sunsetting Atom

README.md — Course...

README2.md

README.md — Github...

```
1 # Test Repository
2
3 This is a **test repository** to help us *figure out*
4   1. How to use GitHub
5   1. How to integrate it with RStudio Projects
6
7 | What this is | What this isn't |
8 | ----- | ----- |
9 | A test of what we're learning | Everything GitHub can do |
```

Recap

Here's a step-by-step summary of what we just did.

- Made same changes to a file and saved them locally.
- **Staged** these local changes.
- **Committed** these local changes to our Git history with a helpful message.
- **Pulled** from the GitHub repo just in case anyone else made changes too (not expected here, but good practice).
- **Pushed** our changes to the GitHub repo.

PS — You were likely challenged for your GitHub credentials at some point. Learn how to cache these [here](#).

Why this Workflow: RStudio

RStudio Projects are great.

- They interact seamlessly with Git(Hub), as we've just seen.
- They also solve absolute vs. relative path problems, since the .Rproj file acts as an anchor point for all other files in the repo.⁵

Note however that R Markdown files do the same thing re: paths *and* extend functionality to incorporating text, images, latex, and html.


⁵ Calling files from their full `YourComputer/YourName/Documents/Special-Subfolder/etc` paths in your scripts is the enemy of reproducibility!

Troubleshooting Git Credential Issues in RStudio

Troubleshooting Git Credential Issues

One reason I'm not focusing on the GitHub + RStudio integration is **credential errors**.

For instance, do you get a password authentication error when trying to push to GitHub from RStudio?



Troubleshooting Steps

To begin, install the `usethis` package:

```
pacman:p_load(usethis)
```

```
# or:
```

```
# install.packages("usethis")
```

```
# followed by
```

```
# library(usethis)
```

Troubleshooting Steps

Next, run the following:

```
library("usethis")  
git_sitrep()
```

View the output: do you see any Xs or lines saying "lacks recommended scopes", "error", or "can't retrieve"?

Create a Personal Access Token (PAT)

To fix these errors, we'll create a **Personal Access Token (PAT)** on GitHub.

The below code will open a browser window - follow the steps to create a PAT

```
usethis::create_github_token()
```

New personal access token (classic)

Personal access tokens (classic) function like ordinary OAuth access tokens. They can be used instead of a password for Git over HTTPS, or can be used to [authenticate to the API over Basic Authentication](#).

Note

DESCRIBE THE TOKEN'S USE CASE

What's this token for?

Expiration *

No expiration  The token will never expire!

GitHub strongly recommends that you set an expiration date for your token to help keep your information secure.

[Learn more](#)

Select scopes

Scopes define the access for personal tokens. [Read more about OAuth scopes](#).

- | | |
|---|--------------------------------------|
| ☒ repo | Full control of private repositories |
| ☒ repo:status | Access commit status |

Add a PAT to RStudio

Back in RStudio, run

```
gitcreds::gitcreds_set()
```

Follow the prompts to add/replace existing credentials, pasting in the PAT.

Check PAT

Once added, run `git_sitrep` one last time to verify.

If all looks good, try pushing again!

```
> git_sitrep()
Git config (global)
• Name: 'James Sears'
• Email: 'james.sears.m@gmail.com'
• Global (user-level) gitignore file: <unset>
• Vaccinated: FALSE
i See `?git_vaccinate` to learn more
• Default Git protocol: 'https'
• Default initial branch name: 'master'
GitHub
• Default GitHub host: 'https://github.com'
• Personal access token for 'https://github.com': '<discovered>'
• GitHub user: 'searsjm'
• Token scopes: 'gist, repo, user, workflow'
• Email(s): 'james.sears.m@gmail.com (primary)', 'searsja1@msu.edu'
Git repo for current project
i No active usethis project
>
```