

App.jsx

```
import { useState } from 'react'
import Login from './LoginForm';

function App() {
  return(
    <>
      <Login/>
    </>
  )
}

export default App;
```

LoginForm.jsx

```
import { useState } from "react";
import TextInput from "./TextInput";

function Login() {
  const [form, setForm] = useState({
    name: "",
    email: "",
    password: "",
  });

  const [data, setData] = useState(null);
```

```
const [errors, setErrors] = useState({});
```

```
function handleChange(e) {  
  setForm({  
    ...form,  
    [e.target.name]: e.target.value,  
  });  
}
```

```
function validate() {  
  let newErrors = {};
```

```
  if (!form.name) {  
    newErrors.name = "Name required";  
  }
```

```
  if (!form.email) {  
    newErrors.email = "Email required";  
  } else if (!form.email.includes("@")) {  
    newErrors.email = "Invalid email";  
  }
```

```
  if (!form.password) {  
    newErrors.password = "Password required";  
  }
```

```
  setErrors(newErrors);
```

```
    return Object.keys(newErrors).length === 0;
  }
```

```
function handleSubmit(e) {
  e.preventDefault();
```

```
  if (validate()) {
    setData(form);
  }
}
```

```
function handleClear() {
  setForm({
    name: "",
    email: "",
    password: "",
  });
```

```
  setErrors({});
  setData(null);
}
```

```
return (
  <div>
    <h1>Signup Form</h1>

    <form onSubmit={handleSubmit}>
```

```
<TextInput
  type="text"
  name="name"
  placeholder="Enter Name"
  value={form.name}
  onChange={handleChange}
  error={errors.name}
/>
```

```
<TextInput
  type="email"
  name="email"
  placeholder="Enter Email"
  value={form.email}
  onChange={handleChange}
  error={errors.email}
/>
```

```
<TextInput
  type="password"
  name="password"
  placeholder="Enter Password"
  value={form.password}
  onChange={handleChange}
  error={errors.password}
/>
```

```
<button type="submit">
```

Submit

</button>

<button type="button" onClick={handleClear}>

Clear

</button>

</form>

{data && (

<div>

<h2>Preview</h2>

<p>Name: {data.name}</p>

<p>Email: {data.email}</p>

<p>Password: {data.password}</p>

</div>

))

</div>

);

}

export default Login;

Output:

