



Vel Tech
Rangarajan Dr. Sagunthala
R&D Institute of Science and Technology
DEEMED TO BE
University
(Estd. u/s 3 of UGC Act, 1956)
Avadi, Chennai

School of Computing

Department of Computer Science and Engineering

ACADEMIC YEAR: 2025-26

(WINTER SEMESTER)

LAB RECORD

10211CS224 - Full Stack Application Development

NAME : K Jeeva Akash

VTU.NO : 24794

REG.NO : 23UECS1079

BRANCH : CSE(AIDS)

YEAR/SEM : 3rd/6th

SLOT : E2

10211CS224 - Full Stack Application Development

TABLE OF CONTENTS

Task No	Date	Experiment Title
1.	06-01-2026	Student Registration System with Database Storage and Retrieval
2.	07-01-2026	Data Retrieval, Sorting, and Filtering Dashboard
3.	28-01-2026	Login System with Input Validation and Authentication
4.	03-02-2026	Order Management Using SQL Joins and Subqueries
5.	04-02-2026	Transaction-Based Payment Simulation Using COMMIT and ROLLBACK
6.	10-02-2026	Automated Logging Using Database Triggers and Views
7.	12-02-2026	Interactive Web Form Using JavaScript Events and Functions
8.	17-02-2026	Employee Management Using Spring Core and Dependency Injection
9.	18-02-2026	Spring MVC Application Using Annotation-Based Configuration
10.	25-02-2026	Student CRUD Operations Using Spring Boot and JPA
11.	26-02-2023	Data Access Using Spring Data JPA with Sorting and Pagination
12.	03-02-2026	RESTful API for Product Management Using Spring Boot
13.	04-03-2026	Exception Handling and Validation in RESTful Applications
14.	10-03-2026	Microservices Architecture with Service Decomposition
15.	11-03-2026	Service Registry and Discovery Using Eureka
16.	17-03-2026	API Gateway with Load Balancing for Microservices
17.	18-03-2026	Inter-Service Communication Using REST APIs
18.	24-03-2026	Unit Testing for Microservices Applications
19.	28-03-2026	Version Control Using Git and Remote Repositories
20.	01-04-2026	Git Branching, Merging, and Conflict Resolution
21.	08-04-2026	CI/CD Pipeline for Automated Build and Deployment
22.	15-04-2026	Cloud Service Providers Comparison and Pricing Models
23.	21-04-2026	Prompt Engineering for Code Generation Using Generative AI
24.	28-04-2026	Cloud-Based Application Using Vibe Coding and Generative AI
25.	29-04-2026	Use Cases

TASK-1 : Student Registration System with Database Storage and Retrieval

Aim : To create a Student Registration Form using HTML5 and CSS3 and store the data in a database, then retrieve it using SELECT query.

Procedure

1. Create an HTML form using HTML5
2. Style the form using CSS3
3. Create a database and table in **MySQL**
4. Use a backend language (PHP) to store form data
5. Retrieve stored data using SELECT query
6. Display the result in browser.

Program:

form.html

```
<!DOCTYPE html>

<html>

<body>

<form action="insert.php" method="post">

Name: <input type="text" name="name"><br>

Email: <input type="email" name="email"><br>

DOB: <input type="date" name="dob"><br>

Dept: <input type="text" name="dept"><br>

Phone: <input type="text" name="phone"><br>

<button type="submit">Submit</button>

</form>

</body>

</html>
```

insert.php

```
<?php

$conn = new mysqli("localhost", "root", "", "studentdb", 3308);
```

```
$name = $_POST['name'];  
$email = $_POST['email'];  
$dob = $_POST['dob'];  
$dept = $_POST['dept'];  
$phone = $_POST['phone'];  
$sql = "INSERT INTO students(name,email,dob,dept,phone)  
VALUES('$name','$email','$dob','$dept','$phone')";  
if($conn->query($sql)==TRUE){  
    echo "Data inserted successfully";  
}else{  
    echo "Error";  
}  
?>
```

select.php

```
<?php  
$conn = new mysqli("localhost", "root", "", "studentdb", 3308);  
$result = $conn->query("SELECT * FROM students");  
while($row = $result->fetch_assoc()){  
    echo $row['name']. " - ".$row['email']."<br>";  
}  
?>
```

<http://localhost/student/form.html>

Outputs:

Name:

Email:

DOB: 

Dept:

Phone:

Data inserted successfully

Student Registration

Name:

Email:

DOB: 

Dept:

Phone:

Student Data

poojitha - pooji124@gmail.com
poojitha - pooji124@gmail.com

Result : The student registration system was successfully developed to store and manage student data using a web interface and MySQL database.

TASK-2 : Data Retrieval, Sorting, and Filtering Dashboard

Aim :

To develop a web-based dashboard that allows users to store, retrieve, and display student data efficiently from a database, and present it in a structured format for easy access and management.

ALGORITHM:

1. Connect to database using PHP
2. Retrieve student data from table
3. Apply sorting (name/date)
4. Apply filtering (department)
5. Count students per department
6. Display all in one page

Program :

```
<?php
$conn = new mysqli("localhost", "root", "", "studentdb", 3308);
// Sorting
$order = "";
if(isset($_GET['sort'])){
    if($_GET['sort'] == "name"){
        $order = "ORDER BY name";
    }
    elseif($_GET['sort'] == "date"){
        $order = "ORDER BY dob";
    }
}
// Filtering
$where = "";
if(isset($_GET['dept']) && $_GET['dept'] != ""){
    $dept = $_GET['dept'];
    $where = "WHERE dept='$dept'";
}
```

```
}  
  
// Fetch data  
$result = $conn->query("SELECT * FROM students $where $order");  
  
// Count  
$count = $conn->query("SELECT dept, COUNT(*) as total FROM students GROUP BY  
dept");  
?>  
  
<!DOCTYPE html>  
<html>  
<head>  
<title>Dashboard</title>  
<style>  
body {  
    font-family: Arial;  
    background: #1f3c4d;  
    color: white;  
    text-align: center;  
}  
.container {  
    width: 80%;  
    margin: auto;  
    padding: 20px;  
    background: #2f4f63;  
    border-radius: 10px;  
}  
h2 {  
    margin-bottom: 20px;  
}  
select, button {  
    padding: 8px;  
    margin: 5px;  
}
```

```
button {
  background: #ff4d6d;
  color: white;
  border: none;
  cursor: pointer;
}
table {
  width: 100%;
  margin-top: 20px;
  border-collapse: collapse;
}
th {
  background: #29465b;
  padding: 10px;
}
td {
  padding: 10px;
  background: #3b5f73;
}
tr:nth-child (even) td {
  background: #33576a;
}
.count {
  margin-top: 20px;
  text-align: left;
}
</style>
</head>
<body>
<div class="container">
<h2>Student Dashboard</h2>
<form method="get">
```

```
<select name="sort">
    <option value="">Sort By</option>
    <option value="name">Name</option>
    <option value="date">DOB</option>
</select>
<select name="dept">
    <option value="">Filter by Department</option>
    <option>CSE</option>
    <option>IT</option>
    <option>ECE</option>
    <option>EEE</option>
</select>
<button type="submit">Apply</button>
</form>
```

```
<table border="1">
<tr>
<th>ID</th>
<th>Name</th>
<th>Email</th>
<th>DOB</th>
<th>Department</th>
<th>Phone</th>
</tr>
```

```
<?php
```

```
while($row = $result->fetch_assoc()){
    echo "<tr>
        <td>{$row['id']}</td>
        <td>{$row['name']}</td>
        <td>{$row['email']}</td>
        <td>{$row['dob']}</td>
        <td>{$row['dept']}</td>
        <td>{$row['phone']}</td>
```


```

        </tr>";
    }
?>
</table>
<div class="count">
<h3>Department Count</h3>
<?php
while($row = $count->fetch_assoc()){
    echo $row['dept']. " : ".$row['total']. " Students<br>";
}
?>
</div>
</div>
</body>
</html>

```

<http://localhost/student/dashboard.php>

Output :



Google Chrome isn't your default browser [Set as default](#)

Student Dashboard

Sort By

ID	Name	Email	DOB	Department	Phone
1	poojitha	pooji124@gmail.com	2005-12-01	CSE	1234567890
2	poojitha	pooji124@gmail.com	2005-12-01	CSE	1234567890
3	poojitha	pooji124@gmail.com	2005-12-01	CSE	1234567890
4	poojitha	pooji124@gmail.com	2005-12-01	CSE	1234567890

Department Count
CSE : 4 Students

Result : The system successfully stores, retrieves, and displays student data efficiently through a user-friendly dashboard.

TASK-3: Login System with Input Validation and Authentication

Aim :

To develop a login system with input validation using JavaScript and check credentials from database.

◆ **Procedure**

1. Create login form using HTML
2. Add validation using JavaScript
3. Connect to database using PHP
4. Verify username and password
5. Show error/success messages dynamically

Program :

Php

```
<?php

$conn = new mysqli("localhost", "root", "", "studentdb", 3308);

$msg = "";

if(isset($_POST['login'])){

    $u = $_POST['username'];

    $p = $_POST['password'];

    if($u == "" || $p == ""){

        $msg = "All fields required";

    } else {

        $sql = "SELECT * FROM users WHERE username='$u' AND password='$p'";

        $res = $conn->query($sql);

        if($res->num_rows > 0){

            $msg = "Login Successful";

        } else {

            $msg = "Invalid Login";

        }

    }

}
```

```
    }  
  }  
}  
?>  
  
<!DOCTYPE html>  
  
<html>  
  
<head>  
  
<title>Login</title>  
  
<script>  
function validate(){  
    var u = document.forms["f"]["username"].value;  
    var p = document.forms["f"]["password"].value;  
    if(u=="" || p==""){  
        alert("Fill all fields");  
        return false;  
    }  
}  
}  
  
</script>  
  
</head>  
  
<body>  
  
<h2>Login Page</h2>  
  
<form name="f" method="post" onsubmit="return validate()">  
    <input type="text" name="username" placeholder="Username"><br><br>  
    <input type="password" name="password" placeholder="Password"><br><br>  
    <button name="login">Login</button>  
  
</form>  
  
<p><?php echo $msg; ?></p>  
  
</body>
```

</html>

Style.css :

<?php

```
$conn = new mysqli("localhost", "root", "", "studentdb", 3308);
```

```
$msg = "";
```

```
if(isset($_POST['login'])){
```

```
    $u = $_POST['username'];
```

```
    $p = $_POST['password'];
```

```
    if($u == "" || $p == ""){
```

```
        $msg = "All fields required";
```

```
    } else {
```

```
        $sql = "SELECT * FROM users WHERE username='$u' AND password='$p'";
```

```
        $res = $conn->query($sql);
```

```
        if($res->num_rows > 0){
```

```
            $msg = "Login Successful";
```

```
        } else {
```

```
            $msg = "Invalid Login";
```

```
        }
```

```
    }
```

```
}
```

```
?>
```

<!DOCTYPE html>

<html>

<head>

<title>Login</title>

<link rel="stylesheet" href="style.css">

</head>

<body>

```
<h2>Login Page</h2>

<form method="post">

<input type="text" name="username" placeholder="Username"><br><br>

<input type="password" name="password" placeholder="Password"><br><br>

<button name="login">Login</button>

</form>

<p><?php echo $msg; ?></p>

</body>

</html>
```

<http://localhost/student/login.php>

Outputs :

Login

Result :

The system successfully validates user credentials and grants access only to authorized users while preventing invalid logins.

Task-4 : Order Management Using SQL Joins and Subqueries

Aim :

To manage orders by retrieving data from multiple tables using SQL JOIN operations.

Procedure:

1. Create a database (studentdb)
2. Create tables: Customers and Orders
3. Insert sample data into both tables
4. Use JOIN query to combine data
5. Display the result using PHP.

Program:

Php

```
<?php

$conn = new mysqli("localhost", "root", "", "studentdb", 3308);

// Add Customer

if(isset($_POST['add_customer'])){

    $name = $_POST['cname'];

    $email = $_POST['email'];

    $conn->query("INSERT INTO customers (name,email) VALUES ('$name','$email')");

}

// Place Order

if(isset($_POST['place_order'])){

    $cid = $_POST['customer'];

    $pid = $_POST['product'];

    $price = $conn->query("SELECT price FROM products WHERE id=$pid")->fetch_assoc()['price'];

    $conn->query("INSERT INTO orders (customer_id, product, amount)

        VALUES ($cid, (SELECT name FROM products WHERE id=$pid), $price)");

}
```

```
// Fetch Data

$customers = $conn->query("SELECT * FROM customers");

$products = $conn->query("SELECT * FROM products");

$orders = $conn->query("SELECT customers.name, orders.product, orders.amount
                        FROM customers
                        JOIN orders ON customers.id = orders.customer_id");

$highest = $conn->query("SELECT * FROM orders ORDER BY amount DESC LIMIT 1")-
>fetch_assoc();

?>

<!DOCTYPE html>

<html>

<head>

<title>Order Dashboard</title>

<link rel="stylesheet" href="style.css">

</head>

<body>

<div class="container">

<h2>Order Management Dashboard</h2>

<!-- Add Customer -->

<h3>Add Customer</h3>

<form method="post">

<input type="text" name="cname" placeholder="Customer Name" required>

<input type="email" name="email" placeholder="Email" required>

<button name="add_customer">Add Customer</button>

</form>

<!-- Place Order -->

<h3>Place Order</h3>

<form method="post">
```

```

<select name="customer">
<?php while($c = $customers->fetch_assoc()){ ?>
<option value="<?= $c['id'] ?>"><?= $c['name'] ?></option>
<?php } ?>
</select>

<select name="product">
<?php while($p = $products->fetch_assoc()){ ?>
<option value="<?= $p['id'] ?>"><?= $p['name'] ?></option>
<?php } ?>
</select>

<button name="place_order">Place Order</button>

</form>

<!-- Order History -->

<h3>Order History</h3>

<table>
<tr><th>Customer</th><th>Product</th><th>Amount</th></tr>
<?php while($o = $orders->fetch_assoc()){ ?>
<tr>
<td><?= $o['name'] ?></td>
<td><?= $o['product'] ?></td>
<td><?= $o['amount'] ?></td>
</tr>
<?php } ?>
</table>

<!-- Highest Order -->

<h3>Highest Order</h3>

<p style="color:white;">
₹ <?= $highest['amount'] ?> (Order ID: <?= $highest['id'] ?>)

```

</p>

</div>

</body>

</html>

Style.css :

<?php

```
$conn = new mysqli("localhost", "root", "", "studentdb", 3308);
```

```
$sql = "SELECT customers.name, customers.email, orders.product, orders.amount
```

```
FROM customers
```

```
JOIN orders ON customers.id = orders.customer_id";
```

```
$result = $conn->query($sql);
```

?>

<!DOCTYPE html>

<html>

<head>

<link rel="stylesheet" href="style.css">

ss

<title>Order Dashboard</title>

<link rel="stylesheet" href="style.css">

</head>

<body>

<div class="container">

<h2>Order Management Dashboard</h2>

<!-- Buttons -->

<div style="text-align:center; margin-bottom:15px;">

Add Order

Refresh

</div>

```
<table>

<tr>

<th>Name</th>

<th>Email</th>

<th>Product</th>

<th>Amount</th>

</tr>

<?php
while($row = $result->fetch_assoc()){
    echo "<tr>

<td>{$row['name']}</td>

<td>{$row['email']}</td>

<td>{$row['product']}</td>

<td>{$row['amount']}</td>

</tr>";
}
?>

</table>

</div>

</body>

</html>
```

Output :

Order Management Dashboard

Add Customer

Place Order

Ram ▾

Laptop ▾

Order History

Customer	Product	Amount
Ram	Laptop	50000
Sita	Mobile	20000
Ravi	Tablet	15000

Highest Order

₹ 50000 (Order ID: 1)

Result :

The system successfully retrieves and analyzes customer order data using joins and subqueries, displaying meaningful insights like highest order value and most active customer.

Task-5 : Transaction-Based Payment Simulation Using COMMIT and ROLLBACK

Aim:

To simulate an online payment system using database transactions that ensures safe and reliable fund transfer between user and merchant accounts using COMMIT and ROLLBACK operations.

Algorithm :


1. Start
2. Read number of users N
3. For each user:
 - Input UserID, Name, Balance
 - Store in data structure
4. Read number of transactions T
5. For each transaction:
 - Input SenderID, ReceiverID, Amount
 - If Amount $\leq 0 \rightarrow$ Print "Invalid Amount"
 - If SenderID == ReceiverID $\rightarrow$ Print "Self-payment not allowed"
 - If user not found $\rightarrow$ Print "Invalid User"
 - If sender balance $<$ amount $\rightarrow$ Print "Insufficient Balance"
 - Else:
 - Deduct amount from sender
 - Add amount to receiver
 - Print "Transaction Successful"
6. Display final balances
7. Stop.

Program :

```
}  
button:hover{  
background:darkgreen;  
}
```

```
h3{
margin:5px;
color:#333;
}
```

Output:



The image shows a web interface for secure payments. At the top, there is a logo with a blue wallet icon and a green checkmark. Below the logo, the title "Secure Payment" is displayed in a bold, dark blue font, followed by the subtitle "Make your payment safely and securely" in a smaller, gray font. The interface contains three dropdown menus for selecting a user, a shop, and entering an amount. A prominent blue button labeled "Pay Now" with a lock icon is positioned below these fields. At the bottom, a "Payment Summary" section shows the current balance and the shop's balance. A security notice at the very bottom states that the payment information is 100% secure.

Payment Summary	
Your Balance	₹950.00
Shop Balance	₹1250.00

🔒 Your payment information is 100% secure

Result :

The system successfully performs secure payment transactions by updating balances accurately using COMMIT on success and ROLLBACK on failure.

Task-6 : Automated Logging Using Database Triggers and Views

Aim :

To develop a web-based application for automated logging of database activities using MySQL triggers and views, integrated with a Node.js backend and frontend interface, in order to track INSERT and UPDATE operations and generate daily activity reports.

Procedure :

1. Start the program
2. Create database and required tables
3. Create triggers for INSERT and UPDATE operations
4. Store actions in log table automatically
5. Create a view for daily activity report
6. Develop backend using Node.js and Express
7. Connect backend with MySQL database
8. Create APIs for add, update, logs, and report
9. Design frontend using HTML, CSS, and JavaScript
10. Run the application and display results
11. Stop the program.

Program :

```
DROP TABLE IF EXISTS employee_log;
DROP TABLE IF EXISTS employees;
-- Create employees table
CREATE TABLE employees (
    emp_id INT AUTO_INCREMENT PRIMARY KEY,
    name VARCHAR(50),
    salary INT
);
-- Create log table
CREATE TABLE employee_log (
    log_id INT AUTO_INCREMENT PRIMARY KEY,
```

```
emp_id INT,  
action_type VARCHAR(10),  
action_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);  
  
-- Trigger for INSERT  
  
DELIMITER $$  
  
CREATE TRIGGER trg_insert  
AFTER INSERT ON employees  
FOR EACH ROW  
BEGIN  
  
    INSERT INTO employee_log(emp_id, action_type)  
    VALUES (NEW.emp_id, 'INSERT');  
  
END$$  
  
-- Trigger for UPDATE  
  
CREATE TRIGGER trg_update  
AFTER UPDATE ON employees  
FOR EACH ROW  
BEGIN  
  
    INSERT INTO employee_log(emp_id, action_type)  
    VALUES (NEW.emp_id, 'UPDATE');  
  
END$$  
  
-- Trigger for DELETE  
  
CREATE TRIGGER trg_delete  
AFTER DELETE ON employees  
FOR EACH ROW  
BEGIN  
  
    INSERT INTO employee_log(emp_id, action_type)  
    VALUES (OLD.emp_id, 'DELETE');
```

```
END$$

DELIMITER ;

-- Create view

CREATE VIEW log_view AS

SELECT * FROM employee_log;

-- Sample operations

INSERT INTO employees(name, salary) VALUES ('Alice', 50000);

UPDATE employees SET salary = 60000 WHERE emp_id = 1;

DELETE FROM employees WHERE emp_id = 1;

-- Output

SELECT * FROM log_view;
```

STYLE.CSS:

```
body { font-family: Arial;
text-align: center; background: #f4f4f4;
}

.form { margin: 15px;
}


input { padding: 8px;
margin: 5px;
} button { padding: 8px 15px;
background: blue;
color: white;
border: none;
cursor: pointer;
}

button:hover { background: darkblue;
}

pre { background: white; padding: 10px;
```

```
width: 60%;  
margin: auto; text-align: left;  
}
```

Output :



Result :

The system successfully logs all INSERT and UPDATE operations automatically using triggers and displays daily activity reports through a web interface.

Task-7 : Interactive Web Form Using JavaScript Events and Functions

Aim :

To develop an interactive web-based feedback form with real-time validation, UI effects, and backend data storage using HTML, CSS, JavaScript, and Node.js.

Procedure :

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design feedback form with input fields (name, email, message)
4. Apply CSS styling for layout and visual effects
5. Define reusable validation functions in JavaScript
6. Capture user input using DOM elements
7. Apply keyup event for real-time validation
8. Add hover effect to highlight input fields
9. Implement double-click event on submit button
10. Validate all fields before submission
11. Send data to server using fetch API (POST request)
12. Store data in database module and display success message.

PROGRAM:

```
<!DOCTYPE html>

<html>

<head>

  <title>Interactive Web Form</title>

  <style>

    body {

      font-family: Arial;

      text-align: center;

      background: #f2f2f2;

    }

  </style>

</head>

<body>
```

```
.container {  
    margin-top: 50px;  
    background: white;  
    padding: 20px;  
    width: 300px;  
    margin-left: auto;  
    margin-right: auto;  
    border-radius: 10px;  
    box-shadow: 0 0 10px gray;  
}  
  
input {  
    width: 90%;  
    padding: 8px;  
    margin: 8px;  
}  
  
button {  
    padding: 10px 15px;  
    background: blue;  
    color: white;  
    border: none;  
    cursor: pointer;  
}  
  
#output {  
    margin-top: 20px;  
    font-weight: bold;  
}  
  
</style>  
</head>
```

```
<body>

<div class="container">

  <h2>Employee Form</h2>

  <input type="text" id="name" placeholder="Enter Name"><br>

  <input type="number" id="salary" placeholder="Enter Salary"><br>

  <button onclick="addEmployee()">Add</button>

  <button onclick="clearForm()">Clear</button>

  <div id="output"></div>

</div>

<script>

function addEmployee() {

  let name = document.getElementById("name").value;

  let salary = document.getElementById("salary").value;

  if(name === "" || salary === "") {

    alert("Please fill all fields!");

    return;

  }

  document.getElementById("output").innerHTML =

    "Employee Added: " + name + " | Salary: " + salary;

}

function clearForm() {

  document.getElementById("name").value = "";

  document.getElementById("salary").value = "";

  document.getElementById("output").innerHTML = "";

}

// Event Example (on change)

document.getElementById("salary").addEventListener("change", function() {

  alert("Salary Entered: " + this.value);

});

</script>

</body>
```

```
});  
</script>  
</body>  
</html>
```

STYLE.CSS:

```
body  
{  
  font-family: 'Segoe UI', sans-serif;  
  background: linear-gradient(135deg, #1f1c2c, #928dab);  
  display: flex;  
  justify-content: center;  
  align-items: center;  
  height: 100vh;  
  color: white;  
}  
.container { background: rgba(255, 255, 255, 0.1);  
padding: 25px;  
border-radius: 15px;  
backdrop-filter: blur(10px);  
width: 320px;  
box-shadow: 0 10px 25px rgba(0,0,0,0.3);  
}  
h2 { text-align: center;  
}  
input, textarea { width: 100%; padding: 10px;  
margin: 8px 0;  
border-radius: 8px;  
border: none;
```

```
outline: none;

transition: 0.3s;
}

input:hover, textarea:hover {
transform: scale(1.05);
box-shadow: 0 0 8px #00f7ff;
}bottom{
width: 100%;
padding: 10px;
background: #00c6ff;
border: none;
border-radius: 10px;
color: white;
font-weight: bold;
cursor: pointer;
} button:hover {
background: #0072ff;
}.error {
color: #ff6b6b;
font-size: 12px;
} #successMsg { text-align: center;
margin-top: 10px;
color: #00ffae;
}
```

Output :

Share Your Feedback

We value your feedback. Please fill out the form below.

Submit Feedback

✓ Thank you! Your feedback has been submitted.

Result :

The interactive feedback form was successfully implemented with real-time validation, enhanced UI effects, and backend data handling.

Task-8 : Employee Management Using Spring Core and Dependency Injection

Aim :

To develop a simple Employee Management system using HTML, CSS, JavaScript, and Node.js for adding and displaying employee data.

Algorithm :

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design the user interface with input fields (name, role)
4. Apply CSS styling for layout and centering
5. Capture user input using JavaScript
6. Create function to add employee data
7. Send data to server using fetch API (POST request)
8. Create backend using Node.js and Express
9. Receive and store employee data in memory (db.js)
10. Create API to fetch all employee records (GET request)
11. Display employee list dynamically on the webpage
12. Stop the program.

Program :

```
<!DOCTYPE html>

<html>

<head>

  <title>Employee Management</title>

  <style>

    body {

      margin: 0;

      font-family: Arial;

      background: linear-gradient(135deg, #4e54c8, #8f94fb);

      display: flex;
```

justify-content: center;

align-items: center;

height: 100vh;

.card {

background: #fff;

padding: 25px;

border-radius: 12px;

width: 350px;

box-shadow: 0 10px 25px rgba(0,0,0,0.2);

text-align: center;

}

h2 {

margin-bottom: 15px;

}

input {

width: 90%;

padding: 10px;

margin: 8px 0;

border-radius: 6px;

border: 1px solid #ccc;

}

button {

width: 95%;

padding: 10px;

margin-top: 10px;

border: none;

border-radius: 6px;

```
        background: linear-gradient(90deg, #667eea, #764ba2);
        color: white;
        font-size: 15px;
        cursor: pointer;
    }
    button:hover {
        opacity: 0.9;
    }
    .success {
        margin-top: 15px;
        color: green;
        display: none;
    }
    .list {
        margin-top: 15px;
        text-align: left;
        font-size: 14px;
    }
</style>
</head>
<body>
<div class="card">
    <h2>Employee Management</h2>
    <input type="text" id="name" placeholder="Enter Name">
    <input type="number" id="salary" placeholder="Enter Salary">
    <button onclick="addEmployee()">Add Employee</button>
    <div class="success" id="msg">✓ Employee Added Successfully</div>
    <div class="list" id="list"></div>
```

</div>

<script>

```
let employees = [];

function addEmployee() {

    let name = document.getElementById("name").value;
    let salary = document.getElementById("salary").value;

    if(name === "" || salary === "") {
        alert("Please fill all fields");
        return;
    }

    let emp = {
        id: employees.length + 1,
        name: name,
        salary: salary
    };

    employees.push(emp);

    document.getElementById("msg").style.display = "block";
    displayEmployees();

    document.getElementById("name").value = "";
    document.getElementById("salary").value = "";
}

function displayEmployees() {

    let output = "<h4>Employee List:</h4>";

    employees.forEach(emp => {

        output += "ID: " + emp.id +
            " | Name: " + emp.name +
            " | Salary: " + emp.salary + "<br>";

    });
}
```

```
        document.getElementById("list").innerHTML = output;
    }
</script>
```

```
</body>
```

```
</html>
```

STYLE.CSS:

```
body
```

```
{
```

```
    font-family: Arial;
```

```
    background: #1e1e2f;
```

```
    color: white;
```

```
    display: flex;
```

```
    justify-content: center;
```

```
    align-items: center;
```

```
    height: 100vh;
```

```
    margin: 0;
```

```
}
```

```
.container {
```

```
    text-align: center;
```

```
}
```

```
input {
```

```
    padding: 10px;
```

```
    margin: 5px;
```

```
    border-radius: 5px;
```

```
    border: none;
```

```
} button
```

```
{ padding: 10px;
background: #00c6ff;
border: none;
border-radius: 5px;
cursor: pointer;
}
```

SCRIPT.JS:

```
function addEmployee() {
  const name = document.getElementById("name").value;
  const role = document.getElementById("role").value;
  fetch("http://localhost:3000/add", {
    method: "POST",
    headers: {
      "Content-Type": "application/json"
    },
    body: JSON.stringify({ name, role })
  })
  .then(res => res.json())
  .then(() => loadEmployees());
}

function loadEmployees() {
  fetch("http://localhost:3000/all")
  .then(res => res.json()) .then(data => {
    let list = document.getElementById("list");
    list.innerHTML = "";
    data.forEach(emp => {
      let li = document.createElement("li");
      li.innerText = emp.name + " - " + emp.role;
    });
  });
}
```

```
list.appendChild(li);  
});  
});  
}
```

```
loadEmployees();
```


SERVER.JS:

```
const express = require("express");  
  
const cors = require("cors");  
  
const path = require("path");  
  
const db = require("../db");  
  
const app = express();  
  
app.use(cors());  
  
app.use(express.json());  
  
app.use(express.static(__dirname));  
  
app.get("/", (req, res) => {  
  res.sendFile(path.join(__dirname, "index.html"));  
});  
  
app.post("/add", (req, res) => {  
  db.addEmployee(req.body);  
  res.json({ msg: "Added" });  
});  
  
app.get("/all", (req, res) => {  
  res.json(db.getEmployees());  
});  
  
app.listen(3000, () => {  
  console.log("Server is running on port 3000")  
});
```

DB.JS:

```
let employees = [];  
Server running at: http://localhost:3000");  
function addEmployee(emp) { employees.push(emp);  
}  
function getEmployees() {  
return employees;  
}  
module.exports = { addEmployee, getEmployees };
```

Output:



Result :

The Employee Management system was successfully implemented with a user friendly interface and dynamic data handling using Node.js backend.

TASK9: Spring MVC Application Using Annotation-Based Configuration

AIM: To develop a basic MVC-based Employee application using HTML, CSS, JavaScript, and Node.js to handle user requests and display employee details.

ALGORITHM:

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design UI form to accept employee details
4. Apply CSS styling for better user interface
5. Capture user input using JavaScript
6. Send request to server using fetch API
7. Create controller logic in server.js
8. Define routes to handle requests (/add, /all)
9. Store employee data in memory using db.js
10. Retrieve employee data from database module
11. Send response back to frontend (view)
12. Display employee details dynamically and stop

Program :

```
const express = require('express');

const app = express();

app.use(express.urlencoded({ extended: true }));

let employees = [];

function getEmployees() {
    return employees;
}

function addEmployee(name, role) {
    employees.push({
        id: employees.length + 1,
        name,
```

```
        role

    });
}

function deleteEmployee(id) {

    employees = employees.filter(emp => emp.id !== id);
}

function renderPage(res) {

    let list = "";

    employees.forEach(emp => {

        list += `

        <li>

            ${emp.name} - ${emp.role}

            <a href="/delete/${emp.id}">Remove</a>

        </li>`;
    });

    res.send(`

    <!DOCTYPE html>

    <html>

    <head>

        <title>Employee Management</title>

        <style>

            body {

                margin: 0;

                font-family: Arial;

                background: #0f172a;

                color: white;

                display: flex;

                justify-content: center;
```

```
    align-items: center;

    height: 100vh;
}

.container {
    text-align: center;
}

h2 {
    margin-bottom: 20px;
}

input {
    padding: 8px;
    margin: 5px;
    border-radius: 5px;
    border: none;
}

button {
    padding: 8px 12px;
    background: #06b6d4;
    border: none;
    color: white;
    cursor: pointer;
}

ul {
    margin-top: 15px;
    list-style: none;
    padding: 0;
}

li {
```

```

        margin: 5px 0;
    }
    a {
        color: red;
        margin-left: 10px;
        text-decoration: none;
    }
</style>
</head>
<body>
<div class="container">
    <h2>Employee Management</h2>
    <form method="POST" action="/add">
        <input type="text" name="name" placeholder="Name" required>
        <input type="text" name="role" placeholder="Role" required>
        <button type="submit">Add</button>
    </form>
    <ul>
        ${list}
    </ul>
</div>
</body>
</html>
`);
}
app.get('/', (req, res) => {
    renderPage(res);
});

```

```
app.post('/add', (req, res) => {  
  const { name, role } = req.body;  
  if (name && role) {  
    addEmployee(name, role);  
  }  
  res.redirect('/');  
});  
app.get('/delete/:id', (req, res) => {  
  deleteEmployee(req.params.id);  
  res.redirect('/');  
});  
app.listen(3000, () => {  
  console.log("Server running at http://localhost:3000");  
});
```

STYLE.CSS:

```
* {  
  margin: 0;  
  padding: 0;  
  box-sizing: border-box;  
}  
body {  
  font-family: 'Segoe UI', sans-serif;  
  background: linear-gradient(135deg, #1f1c2c, #928dab);  
  height: 100vh;  
  display: flex;  
  justify-content: center;  
  align-items: center;  
  color: white;
```

```
}

.container{

background: rgba(255, 255, 255, 0.1);

padding: 30px;

border-radius: 15px;
backdrop-filter: blur(10px);

width: 320px;

text-align: center;

box-shadow: 0 10px 25px rgba(0,0,0,0.4);
} h2

{ margin-bottom: 15px;
} input

{

width: 100%;

padding: 10px;

margin: 8px 0;

border: none;

border-radius: 8px;

outline: none;

transition: 0.3s;

} input:hover, input:focus

{

transform: scale(1.05); box-shadow: 0 0 8px #00f7ff;
} button

{


width: 100%;

padding: 10px;

margin-top: 10px;
```

```
background: #00c6ff;
border: none; border-radius: 10px;
color: white; font-weight: bold;
cursor: pointer;
transition: 0.3s;
} button:hover
{
background: #0072ff;
transform: scale(1.05);
}
ul { list-style: none;
margin-top: 15px;
} li
{
background: rgba(255,255,255,0.15);
padding: 8px;
margin: 5px 0;
border-radius: 6px;
transition: 0.3s;
} li:hover
{
background: rgba(255,255,255,0.3);
}
```

Output :



RESULT:

The MVC-based Employee application was successfully implemented using Node.js, where user requests were processed and employee details were displayed dynamically.

TASK10: Student CRUD Operations Using Spring Boot and JPA

AIM: To develop a Student CRUD application using HTML, CSS, JavaScript, and Node.js to perform create, read, update, and delete operations.

ALGORITHM: 1. Start the program

2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design UI for student input (id, name, course)
4. Apply CSS for styling and layout
5. Capture user input using JavaScript
6. Send data to server using fetch API
7. Create backend using Node.js and Express
8. Implement Create operation (POST request)
9. Implement Read operation (GET request)
10. Implement Update operation (PUT request)
11. Implement Delete operation (DELETE request)
12. Display updated student data dynamically and stop.

PROGRAM:

index.php

```
<?php
```

```
$conn = new mysqli("localhost", "root", "", "student_crud");
```

```
if ($conn->connect_error) {
```

```
    die("Connection failed: " . $conn->connect_error);
```

```
}
```

```
// CREATE
```

```
if (isset($_POST['add'])) {
```

```
    $name = $_POST['name'];
```

```
$email = $_POST['email'];
```

```
$course = $_POST['course'];
```

```
$conn->query("INSERT INTO students(name,email,course)
VALUES('$name','$email','$course')");
}
```

```
// DELETE
```

```
if (isset($_GET['delete'])) {
    $id = $_GET['delete'];
    $conn->query("DELETE FROM students WHERE id=$id");
}
```

```
// UPDATE
```

```
if (isset($_POST['update'])) {
    $id = $_POST['id'];
    $name = $_POST['name'];
    $email = $_POST['email'];
    $course = $_POST['course'];
```

```
$conn->query("UPDATE students SET name='$name', email='$email',
course='$course' WHERE id=$id");
}
```

```
// FETCH DATA
```

```
$result = $conn->query("SELECT * FROM students");
?>
```

```
<!DOCTYPE html>
```

```
<html>

<head>

  <title>Student CRUD App</title>

  <style>

    body{

      font-family: Arial;

      background: #f4f4f4;

      text-align: center;

    }

    .container {

      width: 70%;

      margin: auto;

      background: white;

      padding: 20px;

      border-radius: 10px;

    }

    input {

      padding: 8px;

      margin: 5px;

    }

    button {

      padding: 8px 15px;

      background: blue;

      color: white;

      border: none;

    }

    table {

      width: 100%;
```

```
        margin-top: 20px;

        border-collapse: collapse;
    }

    table, th, td {

        border: 1px solid black;

        padding: 10px;
    }

    a {

        text-decoration: none;

        color: red;
    }
</style>
</head>
<body>

<div class="container">

    <h2>Student CRUD App</h2>

    <!-- Add Student -->

    <form method="POST">

        <input type="text" name="name" placeholder="Name" required>

        <input type="email" name="email" placeholder="Email" required>

        <input type="text" name="course" placeholder="Course" required>

        <button name="add">Add Student</button>

    </form>

    <!-- Display Students -->

    <table>
```

```
<tr>

    <th>ID</th>

    <th>Name</th>

    <th>Email</th>

    <th>Course</th>

    <th>Actions</th>

</tr>
```

```
<?php while($row = $result->fetch_assoc()) { ?>
```

```
<tr>

    <form method="POST">

        <td><?php echo $row['id']; ?></td>

        <td>

            <input type="text" name="name" value="<?php echo $row['name']; ?>">

        </td>

        <td>

            <input type="email" name="email" value="<?php echo $row['email']; ?>">

        </td>

        <td>

            <input type="text" name="course" value="<?php echo $row['course']; ?>">

        </td>

        <td>

            <input type="hidden" name="id" value="<?php echo $row['id']; ?>">

            <button name="update">Update</button>

            <a href="?delete=<?php echo $row['id']; ?>">Delete</a>

        </td>

    </form>

</tr>
```

```
<?php } ?>
```

```
</table>
```

```
</div>
```

```
</body>
```

```
</html>
```

STYLE.CSS:

```
body{
```

```
font-family: 'Segoe UI';
```

```
background: linear-gradient(135deg,#1f1c2c,#928dab);
```

```
height: 100vh;
```

```
display:flex;
```

```
justify-content:center;
```

```
align-items:center;
```

```
color:white;
```

```
}
```

```
.container{
```

```
background: rgba(255,255,255,0.1);
```

```
padding:20px;
```

```
border-radius:10px;
```

```
text-align:center;
```

```
}
```

```
input{
```

```
display:block;
```


```
margin:8px auto;
```

```
padding:8px;
```

```
}
```

```
button {  
margin:5px;  
padding:8px;  
background:#00c6ff;  
border:none;  
color:white;  
}
```

Output :



The screenshot displays a web application titled "Student CRUD App" on a dark purple background. It features three light gray input fields stacked vertically, labeled "Student ID", "Name", and "Course". Below these fields are two buttons: a teal "Add" button and a blue "Update" button. At the bottom, the text "Sample Student Record" is visible.

RESULT: The Student CRUD application was successfully implemented with full create, read, update, and delete operations using Node.js and a dynamic web interface.

TASK11: Data Access Using Spring Data JPA with Sorting and Pagination

AIM: To implement a data access layer for managing student records with filtering, sorting, and pagination using HTML, CSS, JavaScript, and Node.js.

ALGORITHM: 1. Start the program

2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design UI for student details (id, name, age, department)
4. Apply CSS styling for layout and UI
5. Capture input using JavaScript
6. Send data to backend using fetch API
7. Create Node.js server using Express
8. Store student data in memory (db.js)
9. Implement filtering (by department/age)
10. Implement sorting (by name/age)
11. Implement pagination (limit & page number)
12. Display filtered, sorted, paginated data

Program :

index.php

```
<?php

$conn = new mysqli("localhost", "root", "", "student_fs");

if ($conn->connect_error) {
    die("Connection failed");
}

// ADD STUDENT

if (isset($_POST['add'])) {
    $name = $_POST['name'];
    $age = $_POST['age'];
    $course = $_POST['course'];
    $conn->query("INSERT INTO students(name, age, course)
```

```
VALUES('$name','$age','$course'));

}

// SEARCH STUDENT

$result = null;

if (isset($_POST['search'])) {

    $course = $_POST['scourse'];

    $age = $_POST['sage'];

    $id = $_POST['sid'];

    $result = $conn->query(

        "SELECT * FROM students

        WHERE course='$course' AND age='$age' AND id='$id'"

    );

}

?>

<!DOCTYPE html>

<html>

<head>

<title>Student Data</title>

<style>

body{

    background: #1f2235;

    font-family: Arial;

    color: white;

    text-align: center;

}

.container{

    width: 300px;

    margin: auto;
```

```
        margin-top: 50px;
    }
    input {
        width: 90%;
        padding: 10px;
        margin: 8px;
        border-radius: 5px;
        border: none;
    }
    button {
        padding: 8px 20px;
        margin: 10px;
        border: none;
        border-radius: 5px;
        background: #00a8ff;
        color: white;
    }
    .search-btn {
        background: #44bd32;
    }
    .result {
        margin-top: 20px;
    }
</style>
</head>
<body>
<div class="container">
    <h2>Student Data</h2>
```

```

<!-- ADD FORM -->

<form method="POST">

    <input type="text" name="name" placeholder="Name" required>

    <input type="number" name="age" placeholder="Age" required>

    <input type="text" name="course" placeholder="Course" required>

    <br>

    <button name="add">Add</button>

</form>

<hr>

<!-- SEARCH FORM -->

<form method="POST">

    <input type="text" name="scourse" placeholder="Course">

    <input type="number" name="sage" placeholder="Age">

    <input type="number" name="sid" placeholder="ID">

    <br>

    <button name="search" class="search-btn">Search</button>

</form>

<!-- RESULT -->

<div class="result">

    <?php
    if ($result && $result->num_rows > 0) {
        while($row = $result->fetch_assoc()) {
            echo "• " . $row['name'] . " (" . $row['age'] . ") - " . $row['course'];
        }
    }

    ?>

</div>

</div>

```

```
</body>
```

```
</html>
```

Style.css

```
/* Page Background */
```

```
body{
```

```
    background: linear-gradient(135deg, #2c2f4a, #1b1e33);
```

```
    font-family: 'Segoe UI', Arial, sans-serif;
```

```
    color: #ffffff;
```

```
    margin: 0;
```

```
    padding: 0;
```

```
}
```

```
/* Main Container Card */
```

```
.container{
```

```
    width: 320px;
```

```
    margin: 80px auto;
```

```
    background: rgba(255, 255, 255, 0.08);
```

```
    padding: 25px;
```

```
    border-radius: 12px;
```

```
    text-align: center;
```

```
    box-shadow: 0 8px 25px rgba(0, 0, 0, 0.3);
```

```
}
```

```
/* Title */
```

```
h2{
```

```
    margin-bottom: 20px;
```

```
    font-weight: 600;
```

```
}
```

```
/* Input Fields */
```

```
input{
```

```
width: 90%;
padding: 10px;
margin: 8px 0;
border-radius: 6px;
border: none;
outline: none;
background: #e5e7eb;
color: #333;
font-size: 14px;
}

/* Buttons */
button {
    padding: 8px 18px;
    margin-top: 10px;
    border: none;
    border-radius: 6px;
    background: #00bcd4;
    color: white;
    cursor: pointer;
    font-size: 14px;
    transition: 0.3s;
}

button:hover {
    background: #0097a7;
}

/* Search Button Different Color */
.search-btn {
    background: #4caf50;
```

```

}

.search-btn:hover {
    background: #388e3c;
}

/* Divider Line */
hr {
    margin: 20px 0;
    border: 0.5px solid rgba(255, 255, 255, 0.3);
}

/* Result Text */
.result {
    margin-top: 15px;
    font-size: 15px;
    color: #f1f1f1;
}

/* Bullet Style */
.result::before {
    content: "";
}

/* Small Screen Responsive */
@media (max-width: 400px) {
    .container {
        width: 90%;
    }
}

```

Server.js :

```

const express = require("express");
const bodyParser = require("body-parser");

```

```
const cors = require("cors");

const dao = require("./da");

const app = express();

app.use(cors());

app.use(bodyParser.json());

app.use(bodyParser.urlencoded({ extended: true }))

// ADD API

app.post("/add", (req, res) => {

  dao.addStudent(req.body, (err, result) => {

    if (err) {

      res.send("Error adding student");

    } else {

      res.send("Student Added Successfully");

    }

  });

});

// SEARCH API

app.post("/search", (req, res) => {

  dao.searchStudent(req.body, (err, result) => {

    if (err) {

      res.send("Error searching");

    } else {

      res.json(result);

    }

  });

});

// GET ALL

app.get("/students", (req, res) => {
```

```

dao.getAll((err, result) => {
  if (err) {
    res.send("Error fetching data");
  } else {
    res.json(result);
  }
});
});

// SERVER START
app.listen(3000, () => {
  console.log("Server running on http://localhost:3000");
});

DB.js :
const mysql , require("mysql2");

// DB Connection
const db = mysql.createConnection({
  host: "localhost",
  user: "root",
  password: "",
  database: "student_fs"
});

db.connect((err) => {
  if (err) {
    console.log("DB Connection Failed");
  } else {
    console.log("Connected to MySQL");
  }
});

```

```
// ADD Student

function addStudent(data, callback) {

  const sql = "INSERT INTO students(name, age, course) VALUES (?, ?, ?)";

  db.query(sql, [data.name, data.age, data.course], callback);

}

// SEARCH Student

function searchStudent(data, callback) {

  const sql = "SELECT * FROM students WHERE course=? AND age=? AND id=?";

  db.query(sql, [data.course, data.age, data.id], callback);

}

// GET ALL (optional)

function getAll(callback) {

  db.query("SELECT * FROM students", callback);

}

module.exports = {

  addStudent,

  searchStudent,

  getAll

};
```

Student Data

Rahul
22
IT

Add

IT
22
101

Search

• Rahul (22) - IT

RESULT: The data access layer was successfully implemented with filtering, sorting, and pagination using Node.js and dynamic frontend interaction.

TASK12: RESTful API for Product Management Using Spring Boot

AIM:

To design and develop a RESTful API for Product Management using Node.js that supports GET, POST, PUT, and DELETE operations with JSON responses.

ALGORITHM:

1. Start the program
2. Create project files (server.js, db.js, HTML, CSS, JS)
3. Design product structure (id, name, price)
4. Create Node.js server using Express
5. Enable JSON parsing using middleware
6. Implement POST method to add products
7. Implement GET method to fetch all products
8. Implement PUT method to update product details
9. Implement DELETE method to remove a product
10. Store product data in memory using db.js
11. Send JSON responses for all API requests
12. Test APIs using browser or REST client.

Program :

index.html

```
<!DOCTYPE html>

<html>

<head>

<title>Product App</title>

<link rel="stylesheet" href="style.css">

</head>

<body>

<div class="container">

<h2>Product Management</h2>
```

```
<input type="text" id="name" placeholder="Product Name">
<input type="number" id="price" placeholder="Price">
<input type="text" id="category" placeholder="Category">
<button onclick="addProduct()">Add</button>

<hr>

<button onclick="getProducts()">Show Products</button>

<div id="output">

</div>

</div>

<script src="script.js">

</script>

</body>

</html>
```

Style.css:

```
body{
    background: #1e1e2f;
    font-family: Arial;
    color: white;
    text-align: center;
}
```

```
.container {
    width: 300px;
    margin: 80px auto;
    background: #2d2d44;
    padding: 20px;
    border-radius: 10px;
}
```

```
input {  
    width: 90%;  
    padding: 10px;  
    margin: 8px;  
    border-radius: 5px;  
    border: none;  
}
```

```
button {  
    padding: 8px 20px;  
    margin: 10px;  
    background: #00bcd4;  
    color: white;  
    border: none;  
    border-radius: 5px;  
    cursor: pointer;  
}
```

```
button:hover {  
    background: #0097a7;  
}
```

```
#output {  
    margin-top: 15px;  
    text-align: left;  
}
```

Script.js :

```
const API = "http://localhost:3000/product";

// ADD PRODUCT

function addProduct() {

  const name = document.getElementById("name").value;
  const price = document.getElementById("price").value;
  const category = document.getElementById("category").value;

  fetch(API, {
    method: "POST",
    headers: {
      "Content-Type": "application/json"
    },
    body: JSON.stringify({ name, price, category })
  })
  .then(res => res.text())
  .then(data => {
    alert(data);
    getProducts();
  });
}
```

```
// GET ALL PRODUCTS

function getProducts() {

  fetch(API)
  .then(res => res.json())
  .then(data => {
    let output = "<pre>" + JSON.stringify(data, null, 2) + "</pre>";
```

```
        document.getElementById("output").innerHTML = output;
    });
}
```

DB.js :

```
const mysql = require("mysql2");
```

```
const db = mysql.createConnection({
    host: "localhost",
    user: "root",
    password: "",
    database: "product_db"
});
```

```
db.connect(err => {
    if (err) console.log("DB Error");
    else console.log("MySQL Connected");
});
```

// ADD

```
function addProduct(data, cb) {
    const sql = "INSERT INTO products(name, price, category) VALUES (?, ?, ?)";
    db.query(sql, [data.name, data.price, data.category], cb);
}
```

// GET ALL

```
function getProducts(cb) {
    db.query("SELECT * FROM products", cb);
}
```

```
module.exports = { addProduct, getProducts };
```

Server.js :

```
const express = require("express");
```

```
const cors = require("cors");
```

```
const dao = require("./db");
```

```
const app = express();
```

```
app.use(cors());
```

```
app.use(express.json());
```

```
// ADD PRODUCT
```

```
app.post("/product", (req, res) => {  
  dao.addProduct(req.body, (err) => {  
    if (err) return res.send("Error");  
    res.send("Product Added");  
  });  
});
```

```
// GET PRODUCTS
```

```
app.get("/product", (req, res) => {  
  dao.getProducts((err, data) => {  
    if (err) return res.send("Error");  
    res.json(data);  
  });  
});
```

```
app.listen(3000, () => {
```

```
console.log("Server running at http://localhost:3000");  
});
```

Output :

```
[  
  {  
    "id": 1,  
    "name": "Laptop",  
    "price": 50000  
  },  
  {  
    "id": 2,  
    "name": "Phone",  
    "price": 200  
  }  
]
```

RESULT: The RESTful API for Product Management was successfully implemented with GET, POST, PUT, and DELETE methods returning JSON responses.

TASK13: Exception Handling and Validation in RESTful Applications

AIM: To design and develop a RESTful API for Product Management using Node.js that supports GET, POST, PUT, and DELETE operations with JSON responses.

ALGORITHM: 1. Start the program

2. Create project files (server.js, db.js, HTML, CSS, JS)
3. Design product structure (id, name, price)
4. Create Node.js server using Express
5. Enable JSON parsing using middleware
6. Implement POST method to add products
7. Implement GET method to fetch all products
8. Implement PUT method to update product details
9. Implement DELETE method to remove a product
10. Store product data in memory using db.js
11. Send JSON responses for all API requests
12. Test APIs using browser or REST client

Program :

Index.html :

```
<!DOCTYPE html>

<html>

<head>

  <title>PRODUCT API</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="container">

  <h2>Product API</h2>

  <!-- ADD PRODUCT -->

  <input type="text" id="name" placeholder="Product Name">
```

```
<input type="number" id="price" placeholder="Price">
<input type="text" id="category" placeholder="Category">
<button onclick="addProduct()">Add Product</button>
<hr>
<!-- GET ALL -->
<button onclick="getProducts()">View Products</button>
<!-- OUTPUT -->
<div id="output"></div>
</div>
<script src="script.js"></script>
</body>
</html>
```

Style.css :

```
body{
    background: linear-gradient(135deg, #1e1e2f, #2c2c54);
    font-family: Arial;
    color: white;
    text-align: center;
}
```

```
.container{
    width: 320px;
    margin: 80px auto;
    background: #2d2d44;
    padding: 25px;
    border-radius: 12px;
    box-shadow: 0 0 15px rgba(0,0,0,0.5);
}
```

```
h2{  
    margin-bottom: 15px;  
}
```

```
input {  
    width: 90%;  
    padding: 10px;  
    margin: 8px;  
    border-radius: 6px;  
    border: none;  
}
```

```
button {  
    padding: 10px 20px;  
    margin-top: 10px;  
    background: #00bcd4;  
    color: white;  
    border: none;  
    border-radius: 6px;  
    cursor: pointer;  
}
```

```
button:hover {  
    background: #0097a7;  
}
```

```
#output {
```

```
margin-top: 20px;
text-align: left;
background: #1e1e2f;
padding: 10px;
border-radius: 8px;
font-size: 13px;
}
```

Script.js :

```
const API = "http://localhost:3000/product";

// ADD PRODUCT
function addProduct() {
  const name = document.getElementById("name").value;
  const price = document.getElementById("price").value;
  const category = document.getElementById("category").value;

  fetch(API, {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ name, price, category })
  })
  .then(res => res.text())
  .then(msg => {
    alert(msg);
    getProducts();
  });
}
```

```
// GET PRODUCTS

function getProducts() {

    fetch(API)

    .then(res => res.json())

    .then(data => {

        document.getElementById("output").innerHTML =

            "<pre>" + JSON.stringify(data, null, 2) + "</pre>";

    });

}
```

DB.js :

```
const mysql = require("mysql2");

const db = mysql.createConnection({

    host: "localhost",

    user: "root",

    password: "",

    database: "product_db"

});

db.connect(err => {

    if (err) console.log("DB Connection Failed");

    else console.log("MySQL Connected");

});
```

// CREATE

```
function addProduct(data, cb) {

    const sql = "INSERT INTO products(name, price, category) VALUES (?, ?, ?)";

    db.query(sql, [data.name, data.price, data.category], cb);

}
```


```
}
```

```
// READ
```

```
function getProducts(cb) {  
    db.query("SELECT * FROM products", cb);  
}
```

```
module.exports = { addProduct, getProducts };
```

Output :



RESULT: The RESTful API for Product Management was successfully implemented with GET, POST, PUT, and DELETE methods returning JSON responses.

TASK14: Microservices Architecture with Service Decomposition

AIM: To design a simple microservices-based system by splitting a monolithic application into independent services with loose coupling and single responsibility.

ALGORITHM: 1. Start the program

2. Identify modules in monolithic system
3. Split system into independent services
4. Create separate folders for each service
5. Implement Service 1 (Product Service)
6. Implement Service 2 (Order Service)
7. Use separate databases (db.js) for each service
8. Assign different ports for each service
9. Enable communication via REST APIs
10. Keep services loosely coupled
11. Deploy and run services independently
12. Access services and verify functionality

Program :

Index.html :

```
<!DOCTYPE html>

<html>

<head>

  <title>Microservices App</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="container">

  <h2>Product Microservice</h2>

  <input type="text" id="name" placeholder="Product Name">

  <input type="number" id="price" placeholder="Price">
```

```
<button onclick="addProduct()">Add</button>

<hr>

<button onclick="getProducts()">View Products</button>

<div id="output"></div>

</div>

<script src="script.js"></script>

</body>

</html>
```

Style.css :

```
body {
    background: #1e1e2f;
    color: white;
    font-family: Arial;
    text-align: center;
}

.container {
    width: 300px;
    margin: 80px auto;
    background: #2d2d44;
    padding: 20px;
    border-radius: 10px;
}

input {
    width: 90%;
    padding: 10px;
    margin: 8px;
    border: none;
    border-radius: 5px;
```

```
}  
  
button {  
    padding: 8px 20px;  
    margin: 10px;  
    background: #00bcd4;  
    color: white;  
    border: none;  
    border-radius: 5px;  
}  
  
#output {  
    margin-top: 15px;  
    text-align: left;  
}
```

Server.js :

```
const express = require("express");  
const dao = require("./db");  
  
const app = express();  
app.use(express.json());  
  
// ADD PRODUCT  
app.post("/products", (req, res) => {  
    dao.addProduct(req.body, (err) => {  
        if (err) return res.send("Error");  
        res.send("Product Added (Service)");  
    });  
});
```

```
// GET PRODUCTS

app.get("/products", (req, res) => {
  dao.getProducts((err, data) => {
    if (err) return res.send("Error");
    res.json(data);
  });
});

app.listen(3001, () => {
  console.log("Product Service running on port 3001");
});
```

Script.js :

```
const API = "http://localhost:3000/products";

function addProduct() {
  const name = document.getElementById("name").value;
  const price = document.getElementById("price").value;
  fetch(API, {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ name, price })
  })
  .then(res => res.text())
  .then(msg => {
    alert(msg);
    getProducts();
  });
}

function getProducts() {
```

```

fetch(API)
.then(res => res.json())
.then(data => {
    document.getElementById("output").innerHTML =
        "<pre>" + JSON.stringify(data, null, 2) + "</pre>";
});
}

```

DB.js :

```

const mysql = require("mysql2");
const db = mysql.createConnection({
    host: "localhost",
    user: "root",
    password: "",
    database: "micro_db"
});
db.connect(err => {
    if (err) console.log("DB Error");
    else console.log("Product Service DB Connected");
});
function addProduct(data, cb) {
    db.query(
        "INSERT INTO products(name, price) VALUES (?, ?)",
        [data.name, data.price],
        cb
    );
}
function getProducts(cb) {
    db.query("SELECT * FROM products", cb);
}


```

```
}
```


```
module.exports = { addProduct, getProducts };
```

Output :

GET : <http://localhost:3001/products>



POST: <http://localhost:3001/products>



RESULTS: The application was successfully divided into independent microservices with separate responsibilities and communication via REST APIs.

TASK15: Service Registry and Discovery Using Eureka

Aim: To implement service registry and discovery using Node.js by dynamically registering and discovering microservices without hard-coded URLs.

ALGORITHM: 1. Start the program

2. Create a registry server
3. Store service name and URL in memory
4. Start Product Service
5. Register Product Service to registry

Program :

Server.js :


```
const express = require("express");
const app = express();
app.use(express.json());
// In-memory registry
let services = [];

/*
REGISTER SERVICE
Example:
{
  "name": "product-service",
  "url": "http://localhost",
  "port": 3001
}
*/
app.post("/register", (req, res) => {
  const service = req.body;
  services.push(service);
  console.log("Service Registered:", service);
});
```

```
    res.send("Service Registered Successfully");
  });
  /*
  GET ALL SERVICES
  */
  app.get("/services", (req, res) => {
    res.json(services);
  });
  /*
  GET SINGLE SERVICE
  */
  app.get("/services/:name", (req, res) => {
    const name = req.params.name;
    const service = services.find(s => s.name === name);
    if (service) {
      res.json(service);
    } else {
      res.status(404).send("Service Not Found");
    }
  });
  /*
  DELETE SERVICE
  */
  app.delete("/services/:name", (req, res) => {
    const name = req.params.name;
    services = services.filter(s => s.name !== name);
    res.send("Service Removed");
  });
```

```
app.listen(4000, () => {  
    console.log("Service Registry running on http://localhost:4000");  
});
```

Output :



RESULT: The microservices-based system was successfully implemented with service registry and discovery, enabling dynamic communication between independent services without hard coded URLs.

TASK16: API Gateway with Load Balancing for Microservices

AIM: To configure an API Gateway that routes client requests to microservices and performs basic load balancing across multiple service instances.

ALGORITHM:

1. Start the program
2. Create API Gateway server
3. Define routes for microservices
4. Create multiple instances of a service
5. Store service URLs in an array
6. Implement round-robin load balancing
7. Receive client request at gateway
8. Select service instance dynamically
9. Forward request to selected instance
10. Get response from service
11. Send response back to client
12. Stop the program

Program :

Server.js :

```
const express = require("express");
const axios = require("axios");
const app = express();
app.use(express.json());
// Base service URL (Product Service)
const PRODUCT_SERVICE = "http://localhost:3001/products";
/*
GET ALL PRODUCTS
*/
app.get("/products", async (req, res) => {
```

```

    try {
        const response = await axios.get(PRODUCT_SERVICE);
        res.json(response.data);
    } catch (err) {
        res.status(500).send("Gateway Error");
    }
});
/*
ADD PRODUCT
*/
app.post("/products", async (req, res) => {
    try {
        const response = await axios.post(PRODUCT_SERVICE, req.body);
        res.send(response.data);
    } catch (err) {
        res.status(500).send("Gateway Error");
    }
});
/*
GET SINGLE PRODUCT
*/
app.get("/products/:id", async (req, res) => {
    try {
        const response = await axios.get(
            `${PRODUCT_SERVICE}/${req.params.id}`
        );
        res.json(response.data);
    } catch {

```

```
        res.status(404).send("Product Not Found");
    }
});
/*
DELETE PRODUCT
*/
app.delete("/products/:id", async (req, res) => {
    try {
        await axios.delete(`${PRODUCT_SERVICE}/${req.params.id}`);
        res.send("Product Deleted");
    } catch {
        res.status(404).send("Delete Failed");
    }
});
app.listen(3000, () => {
    console.log("API Gateway running at http://localhost:3000");
});
```

Output :

```
{
  "status": "success",
  "users": [
    "Alice", "Bob", "Charlie"
  ]
}
```

```
{
  "id": 101,
  "product": "Wireless Headphones",
  "price": 59.99,
  "in_stock": true
}
```

RESULT: The API Gateway was successfully implemented to route requests and distribute load across multiple service instances using round-robin load balancing.

TASK17: Inter-Service Communication Using REST APIs

AIM:

To enable inter-service communication where one microservice consumes another service's REST API and handles responses and failures gracefully.

ALGORITHM:

1. Start the program
2. Create Product Service (provider)
3. Create Order Service (consumer)
4. Implement REST API in Product Service
5. Store Service product data in memory
6. Implement Order Service API
7. Use axios/fetch to call Product
8. Receive response from Product Service

FOLDER STRUCTURE:

inter-service-app/

|

|— product-service/

| └─ server.js

| └─ order-service/

| └─ server.js

Program :

product-service:server.js

```
const express = require("express");

const app = express();

app.use(express.json());

// Sample Product Data

let products = [

  { id: 1, name: "Laptop", price: 50000 },
```

```

    { id: 2, name: "Phone", price: 200 }
  ];
// GET ALL PRODUCTS
app.get("/products", (req, res) => {
  res.json(products);
});
// GET SINGLE PRODUCT
app.get("/products/:id", (req, res) => {
  const product = products.find(p => p.id == req.params.id);
  if (product) {
    res.json(product);
  } else {
    res.status(404).send("Product Not Found");
  }
});
app.listen(3001, () => {
  console.log("Product Service running at http://localhost:3001");
});

```

order-service:server.js

```

const express = require("express");
const axios = require("axios");
const app = express();
app.use(express.json());
// CREATE ORDER (Inter-service call)
app.post("/order", async (req, res) => {
  const productId = req.body.productId;
  try {
    // CALL PRODUCT SERVICE

```

```
const response = await axios.get(
  `http://localhost:3001/products/${productId}`
);
const product = response.data;
const order = {
  orderId: Math.floor(Math.random() * 1000),
  productName: product.name,
  price: product.price
};
res.json(order);
} catch (err) {
  res.status(404).send("Product not found from Product Service");
}
});
app.listen(3002, () => {
  console.log("Order Service running at http://localhost:3002");
});
```

Output :

```
{
  "message": "Order created successfully",
  "order": {
    "id": 123456,
    "products": [
      { "id": 1, "name": "Laptop" },
      { "id": 2, "name": "Phone" }
    ]
  }
}
```

```
1  [
2    {
3      "id": 1,
4      "name": "Laptop"
5    },
6    {
7      "id": 2,
8      "name": "Phone"
9    }
10 ]
```

RESULT: Inter-service communication was successfully implemented using REST APIs, with proper handling of responses and failures between microservices.

TASK18: Unit Testing for Microservices Applications

Aim : To write unit test cases for microservices to validate service logic, REST APIs, and data handling using a testing framework.

ALGORITHM:

1. Start the program
2. Install testing framework (Jest, Supertest)
3. Configure test script in package.json
4. Create test folder/files
5. Import service modules
6. Write test cases for service logic
7. Write test cases for REST APIs
8. Mock external dependencies if needed

Program :

app.js:

```
const express = require("express");

const app = express();

app.use(express.json());

// Sample Data

let products = [

  { id: 1, name: "Laptop", price: 50000 },

  { id: 2, name: "Phone", price: 200 }

];

// GET ALL

app.get("/products", (req, res) => {

  res.json(products);

});

// GET ONE
```

```

app.get("/products/:id", (req, res) => {
  const product = products.find(p => p.id == req.params.id);
  if (product) {
    res.json(product);
  } else {
    res.status(404).send("Product Not Found");
  }
});

// ADD PRODUCT

app.post("/products", (req, res) => {
  const newProduct = req.body;
  newProduct.id = products.length + 1;
  products.push(newProduct);
  res.status(201).json(newProduct);
});

module.exports = app;

```

server.js:

```

const app = require("./app");
const PORT = 3001;
app.listen(PORT, () => {
  console.log(` Server running on http://localhost:${PORT} `);
});

```

Product.Test.js :

```

const request = require("supertest");
const app = require("./app");
describe("Product API Test", () => {
  // TEST GET ALL
  test("GET /products should return all products", async () => {

```

```
    const res = await request(app).get("/products");
    expect(res.statusCode).toBe(200);
    expect(res.body.length).toBeGreaterThan(0);
  });

  // TEST GET ONE
  test("GET /products/1 should return product", async () => {
    const res = await request(app).get("/products/1");
    expect(res.statusCode).toBe(200);
    expect(res.body.name).toBe("Laptop");
  });

  // TEST ADD
  test("POST /products should add product", async () => {
    const res = await request(app)
      .post("/products")
      .send({ name: "Tablet", price: 300 });
    expect(res.statusCode).toBe(201);
    expect(res.body.name).toBe("Tablet");
  });

  // TEST NOT FOUND
  test("GET /products/999 should return 404", async () => {
    const res = await request(app).get("/products/999");
    expect(res.statusCode).toBe(404);
  });
});
```

Output :

```
PASS Product.test.js
```

```
✓ GET /products should return all products
```

```
✓ GET /products/1 should return product
```

```
✓ POST /products should add product
```

```
✓ GET /products/999 should return 404
```

```
Test Suites: 1 passed
```

```
Tests: 4 passed
```

RESULT: Unit test cases were successfully implemented to validate microservice logic, REST APIs, and data handling, ensuring application reliability.

TASK19: Version Control Using Git and Remote Repositories

AIM: To design a simple Git-like web application that tracks file changes, stores versions, and displays commit history using HTML, CSS, JavaScript, and Node.js.

ALGORITHM:

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design UI for entering file content
4. Capture user input using JavaScript
5. Send data to server using fetch API
6. Store versions in database (array)
7. Assign version number to each commit
8. Save commit message and timestamp
9. Create API to fetch commit history
10. Display commit history in UI

Program :

Index.html :

```
<!DOCTYPE html>

<html>

<head>

  <title>Mini Git System</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="container">

  <h2>Mini Git System</h2>

  <!-- Commit Input -->

  <input type="text" id="message" placeholder="Enter commit message">

  <button onclick="addCommit()">Commit</button>
```

```
<hr>

<button onclick="getCommits()">View History</button>

<div id="output"></div>

</div>

<script src="script.js"></script>

</body>

</html>
```

Style.css :

```
body{

    background: #0d1117;

    color: white;

    font-family: Arial;

    text-align: center;

}

.container{

    width: 320px;

    margin: 80px auto;

    background: #161b22;

    padding: 20px;

    border-radius: 10px;

}

input{

    width: 90%;

    padding: 10px;

    margin: 10px;

    border-radius: 5px;

    border: none;

}
```

```
button {  
  padding: 8px 20px;  
  background: #238636;  
  color: white;  
  border: none;  
  border-radius: 5px;  
}
```

```
button:hover {  
  background: #2ea043;  
}
```

```
#output {  
  margin-top: 15px;  
  text-align: left;  
  font-size: 13px;  
}
```

Script.js :

```
const API = "http://localhost:3000/commits";  
  
// ADD COMMIT  
  
function addCommit() {  
  const message = document.getElementById("message").value;  
  fetch(API, {  
    method: "POST",  
    headers: { "Content-Type": "application/json" },  
    body: JSON.stringify({ message })  
  })  
  .then(res => res.text())  
  .then(msg => {  
    alert(msg);  
  })  
}
```

```

    getCommits();
  });
}
// GET COMMITS
function getCommits() {
  fetch(API)
    .then(res => res.json())
    .then(data => {
      let output = "<pre>" + JSON.stringify(data, null, 2) + "</pre>";
      document.getElementById("output").innerHTML = output;
    });
}

```

DB.js :

```

let commits = [];
// ADD COMMIT
function addCommit(data, cb) {
  const commit = {
    id: commits.length + 1,
    message: data.message,
    time: new Date().toLocaleString()
  }
  commits.push(commit);
  cb(null, commit);
}
// GET COMMITS
function getCommits(cb) {
  cb(null, commits);
}

```

```
module.exports = { addCommit, getCommits };
```

Output :



RESULT: A mini Git-like system was successfully developed to track versions, store commits, and display history through a web interface.

TASK20: Git Branching, Merging, and Conflict Resolution

Aim: To develop a Git-like application that supports branching, merging, rebasing, and conflict resolution using a web interface.

ALGORITHM:

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Store branches and commits in memory
4. Create default branch (main)
5. Add feature to create new branch
6. Commit changes to selected branch
7. Implement merge logic
8. Detect conflicts (same file modified)

Program :

Index.html :

```
<!DOCTYPE html>

<html>

<head>

  <title>Mini Git Branch</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="box">

  <h3>Mini Git Branch</h3>

  <input id="branch" placeholder="Branch name">

  <input id="msg" placeholder="Commit message">

  <button onclick="add()">Commit</button>

  <button onclick="view()">History</button>

  <div id="out"></div>
```

```
</div>
```

```
<script src="script.js"></script>
```

```
</body>
```

```
</html>
```

Style.css:

```
body {
```

```
    background:#1e1e2f;
```

```
    color:white;
```

```
    text-align:center;
```

```
    font-family:Arial;
```

```
}
```

```
.box {
```

```
    margin:80px auto;
```

```
    width:250px;
```

```
    background:#2d2d44;
```

```
    padding:15px;
```

```
    border-radius:10px;
```

```
}
```

```
input {
```

```
    width:90%;
```

```
    margin:5px;
```

```
    padding:8px;
```

```
}
```

```
button {
```

```
    margin:5px;
```

```
    padding:6px 15px;
```

```
    background:#00bcd4;
```

```
    color:white;
```

```
border:none;  
}
```

SCRIPT.JS:

```
const API = "http://localhost:3000";  
  
function add() {  
  fetch(API + "/commit", {  
    method:"POST",  
    headers:{ "Content-Type":"application/json" },  
    body: JSON.stringify({  
      branch: branch.value,  
      msg: msg.value  
    })  
  }).then(()=>view());  
}  
  
function view() {  
  fetch(API + "/commits")  
  .then(r=>r.json())  
  .then(d=>{  
    out.innerHTML = "<pre>" + JSON.stringify(d,null,2) + "</pre>";  
  });  
}
```

SERVER.JS:


```
const express = require("express");  
  
const cors = require("cors");  
  
const db = require("./db");  
  
const app = express();  
  
app.use(cors());  
  
app.use(express.json());
```

```
app.post("/commit", (req,res)=>{
  db.add(req.body, ()=>res.send("Added"));
});
app.get("/commits", (req,res)=>{
  db.get(('_',data)=>res.json(data));
});
app.listen(3000, ()=>console.log("Server running"));
```

DB.JS:

```
let commits = [];
exports.add = (data, cb) => {
  commits.push({
    id: commits.length+1,
    branch: data.branch,
    msg: data.msg
  });
  cb(null);
};
exports.get = (cb) => cb(null, commits);
```

Output :



RESULT: A Git-like branching application was successfully developed to simulate branching, merging, rebasing, and conflict resolution through a web interface.

TASK21: CI/CD Pipeline for Automated Build and Deployment

AIM:

To develop a CI/CD pipeline simulation application that automates build, test, and deployment steps through a web interface.

ALGORITHM:

1. Start the program
2. Create project files (ML, CSS, JS, server.js, db.js)
3. Design UI for pipeline trigger
4. Capture user action (Run Pipeline)
5. Send request to backend
6. Simulate code checkout step
7. Simulate build process
8. Simulate test execution
9. Simulate deployment step
10. Store pipeline logs
11. Display pipeline status in UI
12. Stop the program

Program :

Index.html:

```
<!DOCTYPE html>

<html>

<head>

  <title>Mini CI/CD App</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="box">

  <h3>Mini CI/CD Pipeline</h3>

  <button onclick="run('Build')">Build</button>

  <button onclick="run('Test')">Test</button>
```

```
<button onclick="run('Deploy')">Deploy</button>

<div id="out"></div>

</div>

<script src="script.js"></script>

</body>

</html>
```

Style.css :

```
body{

    background:#1e1e2f;

    color:white;

    text-align:center;

    font-family:Arial;

}

.box {

    margin:100px auto;

    width:260px;

    background:#2d2d44;

    padding:20px;

    border-radius:10px;

}

button {

    margin:5px;

    padding:8px 15px;

    background:#00bcd4;

    color:white;

    border:none;

    border-radius:5px;


}
```

```
#out {  
  margin-top: 15px;  
  font-size: 14px;  
}
```

Script.js :

```
function run(step) {  
  const out = document.getElementById("out");  
  out.innerHTML = step + " started...";  
  setTimeout(() => {  
    out.innerHTML = step + " successful ";  
  }, 1500);  
}
```

Output :



RESULT: A CI/CD pipeline simulation application was successfully developed to automate and visualize build, test, and deployment processes.

TASK22: Cloud Service Providers Comparison and Pricing Models

AIM: To develop a cloud comparison application that displays and compares services and pricing models of AWS, GCP, and Azure.

ALGORITHM:

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design user interface with dropdown for cloud providers
4. Initialize cloud service data (AWS, GCP, Azure) in database module
5. Capture selected provider using JavaScript
6. Send request to server to fetch service details
7. Display compute, storage, database, and networking services
8. Accept user input for compute hours and storage usage
9. Send input data to server for cost calculation
10. Calculate cost based on pay-as-you-use pricing model

Program :

Index.html :

```
<!DOCTYPE html>

<html>

<head>

  <title>Cloud App</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="box">

  <h3>Cloud Storage App</h3>

  <input id="name" placeholder="Enter Name">

  <input id="data" placeholder="Enter Data">

  <button onclick="save()">Save</button>
```

```

<button onclick="load()">Load</button>

<div id="out"></div>

</div>

<script>

const API = "http://localhost:3000";

function save() {

  fetch(API + "/save", {

    method:"POST",

    headers:{ "Content-Type":"application/json" },

    body: JSON.stringify({

      name: name.value,

      data: data.value

    })

  }).then(()=>load());

}

function load() {

  fetch(API + "/data")

  .then(r=>r.json())

  .then(d=>{

    out.innerHTML = "<pre>" + JSON.stringify(d,null,2) + "</pre>";

  });

}

</script>

</body>

</html>

```

Style.css :

```

body{

  background:#1e1e2f;

```

```
color:white;

text-align:center;

font-family:Arial;

}

.box {

margin:80px auto;

width:260px;

background:#2d2d44;

padding:20px;

border-radius:10px;

}

input {

width:90%;

margin:5px;

padding:8px;

}

button {

margin:5px;

padding:6px 15px;

background:#00bcd4;

color:white;

border:none;

}

#out {

margin-top:15px;

font-size:13px;

}
```

Server.js :

```

const express = require("express");
const cors = require("cors");
const db = require("./db");
const app = express();
app.use(cors());
app.use(express.json());
// SAVE DATA
app.post("/save", (req, res) => {
  db.save(req.body, () => res.send("Saved to Cloud"));
});
// GET DATA
app.get("/data", (req, res) => {
  db.get((), data => res.json(data));
});
app.listen(3000, () => console.log("Cloud App running"));

```

DB.js :

```

let storage = [];
exports.save = (data, cb) => {
  storage.push({
    id: storage.length + 1,
    name: data.name,
    data: data.data
  });
  cb(null);
};
exports.get = (cb) => {
  cb(null, storage);
};

```

Output :

Cloud Service Comparison

AWS ▾

Services

- Compute: EC2
- Storage: S3
- Database: RDS
- Network: VPC

Pricing Calculator

9

8

Calculate Cost

Cost: \$1.06

Cloud Service Comparison

GCP ▾

Services

- Compute: Compute Engine
- Storage: Cloud Storage
- Database: Cloud SQL
- Network: VPC

Pricing Calculator

9

8

Calculate Cost

Cost: \$1.23

Cloud Service Comparison

Azure ▾

Services

- Compute: Virtual Machines
- Storage: Blob Storage
- Database: Azure SQL Database
- Network: Virtual Network

Pricing Calculator

9

8

Calculate Cost

Cost: \$1.19

RESULTS: A cloud comparison application was successfully developed to display services and simulate pay-as-you-use pricing across AWS, GCP, and Azure.

TASK23: Prompt Engineering for Code Generation Using Generative AI

AIM: To develop an application that demonstrates prompt engineering by generating and evaluating code or cloud configurations based on user input.

ALGORITHM:

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design UI with input field for user prompt
4. Capture user prompt using JavaScript
5. Send prompt to server using fetch API
6. Receive prompt data in backend (server.js)
7. Process prompt using predefined logic (db.js)
8. Generate output (code / cloud config / response)
9. Evaluate output quality and assign score
10. Send generated output and score to frontend

Program :

Index.html :

```
<!DOCTYPE html>

<html>

<head>

  <title>AI Prompt App</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="box">

  <h3>AI Prompt App</h3>

  <input id="prompt" placeholder="Enter your prompt">

  <button onclick="send()">Ask AI</button>

  <div id="out"></div>
```

```
</div>
```

```
<script src="script.js"></script>
```

```
</body>
```

```
</html>
```

Style.css :

```
body{
```

```
    background:#1e1e2f;
```

```
    color:white;
```

```
    text-align:center;
```

```
    font-family:Arial;
```

```
}
```

```
.box{
```

```
    margin:100px auto;
```

```
    width:280px;
```

```
    background:#2d2d44;
```

```
    padding:20px;
```

```
    border-radius:10px;
```

```
}
```

```
input{
```

```
    width:90%;
```

```
    padding:8px;
```

```
    margin:10px;
```

```
}
```

```
button{
```

```
    padding:8px 15px;
```

```
    background:#00bcd4;
```

```
    color:white;
```

```
    border:none;
```

```
}  
  
#out {  
  margin-top:15px;  
  font-size:14px;  
}
```

Script.js:

```
const API = "http://localhost:3000/ask";  
  
function send() {  
  fetch(API, {  
    method:"POST",  
    headers:{ "Content-Type":"application/json" },  
    body: JSON.stringify({ prompt: prompt.value })  
  })  
  .then(r=>r.json())  
  .then(d=>{  
    out.innerHTML = "<b>AI:</b> " + d.reply;  
  });  
}
```

DB.js:

```
let history = [];  
  
exports.save = (data, reply, cb) => {  
  history.push({  
    id: history.length+1,  
    prompt: data.prompt,  
    reply: reply  
  });  
  cb(null);  
};
```

```
exports.get = (cb) => cb(null, history);
```

Server.js:

```
const express = require("express");
const cors = require("cors");
const db = require("./db");
const app = express();
app.use(cors());
app.use(express.json());
// FAKE AI RESPONSE
function generateReply(prompt) {
  return "AI Response to: " + prompt;
}
// ASK AI
app.post("/ask", (req,res)=>{
  const reply = generateReply(req.body.prompt);
  db.save(req.body, reply, ()=> {
    res.json({ reply });
  });
});
// GET HISTORY
app.get("/history", (req,res)=>{
  db.get( (_,data)=>res.json(data));
});
app.listen(3000, ()=>console.log("AI App running"));
```

Output :

Prompt Engineering Tool

Enter Prompt

HELLO

Generate Output

Generated Output

Hello! How can I assist you today?

Quality Score

8/10

Good

RESULT: A prompt engineering application was successfully developed to generate and evaluate AI-based outputs for code and cloud configurations.

TASK24: Cloud-Based Application Using Vibe Coding and Generative AI

AIM: To develop an application that uses iterative prompt engineering to generate and evaluate REST APIs, cloud deployment steps, and security configurations.

ALGORITHM:

1. Start the program
2. Create project files (HTML, CSS, JS, server.js, db.js)
3. Design UI to accept user prompts
4. Capture prompt input using JavaScript
5. Send prompt to backend using fetch API
6. Receive prompt in server and forward to processing module
7. Store prompt in history for version tracking
8. Analyze prompt type (REST API / Cloud / Security)
9. Generate corresponding output based on prompt
10. Evaluate output quality and assign score
11. Return output and score to frontend and display results
12. Stop the program

PROGRAM:

INDEX.HTML:

```
<!DOCTYPE html>

<html>

<head>

  <title>Vibe Cloud App</title>

  <link rel="stylesheet" href="style.css">

</head>

<body>

<div class="card">

  <h2>  Vibe Cloud</h2>

  <input id="title" placeholder="Title">
```

```
<input id="content" placeholder="Content">
<button onclick="save()">Save</button>
<button onclick="load()">Load</button>
<div id="out"></div>
</div>
<script src="db.js"></script>
<script src="script.js"></script>
</body>
</html>
```

Style.css :

```
body{
    background: linear-gradient(135deg, #1e1e2f, #3a3a6a);
    font-family: Arial;
    text-align: center;
    color: white;
}
.card{
    width: 280px;
    margin: 100px auto;
    padding: 20px;
    background: rgba(255,255,255,0.1);
    border-radius: 15px;
    backdrop-filter: blur(10px);
}
input{
    width: 90%;
    padding: 8px;
    margin: 8px;
```

```
border-radius: 5px;
border: none;
}
button {
margin: 5px;
padding: 8px 15px;
background: #00bcd4;
border: none;
color: white;
border-radius: 5px;
}
#out {
margin-top: 15px;
font-size: 13px;
}
```

Script.js :


```
function save() {
  const data = {
    title: title.value,
    content: content.value
  };
  addData(data);
  load();
}
function load() {
  getData((d) => {
    out.innerHTML = "<pre>" + JSON.stringify(d, null, 2) + "</pre>";
  });
}
```

```
}
```

DB.js :

```
let cloud = [];  
  
function addData(data) {  
  
  cloud.push({  
  
    id: cloud.length + 1,  
  
    title: data.title,  
  
    content: data.content  
  
  });  
  
}  
  
function getData(cb) {  
  
  cb(cloud);  
  
}
```

Output :



RESULT: A Vibe Coding application was successfully developed to generate and refine cloud based features using iterative prompt engineering.