```
mysql> USE college;
Database changed
mysql> CREATE TABLE Student_Details (
    ->     ID INT AUTO_INCREMENT PRIMARY KEY,
    ->     Name VARCHAR(50),
    ->     Department VARCHAR(30)
    -> );
Query OK, 0 rows affected (0.03 sec)

mysql> INSERT INTO Student_Details (Name, Department)
    -> VALUES
    -> ('Arun', 'CSE'),
    -> ('Priya', 'IT'),
    -> ('Rahul', 'ECE'),
    -> ('Divya', 'CSE'),
    -> ('Kumar', 'IT');
Query OK, 5 rows affected (0.02 sec)
Records: 5  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM Student_Details;
+----+-------+------------+
| ID | Name  | Department |
+----+-------+------------+
|  1 | Arun  | CSE        |
|  2 | Priya | IT         |
|  3 | Rahul | ECE        |
|  4 | Divya | CSE        |
|  5 | Kumar | IT         |
+----+-------+------------+
5 rows in set (0.00 sec)

mysql> INSERT INTO Student_Details (Name, Department)
    -> VALUES ('Anitha', 'AIML');
Query OK, 1 row affected (0.01 sec)
```

```
mysql> SELECT * FROM Student_Details;
+----+--------+------------+
| ID | Name   | Department |
+----+--------+------------+
|  1 | Arun   | CSE        |
|  2 | Priya  | IT         |
|  3 | Rahul  | ECE        |
|  4 | Divya  | CSE        |
|  5 | Kumar  | IT         |
|  6 | Anitha | AIML       |
+----+--------+------------+
6 rows in set (0.00 sec)

mysql> DESC Student_Details;
+------------+-------------+------+-----+---------+----------------+
| Field      | Type        | Null | Key | Default | Extra          |
+------------+-------------+------+-----+---------+----------------+
| ID         | int         | NO   | PRI | NULL    | auto_increment |
| Name       | varchar(50) | YES  |     | NULL    |                |
| Department | varchar(30) | YES  |     | NULL    |                |
+------------+-------------+------+-----+---------+----------------+
3 rows in set (0.02 sec)
```