```
mysql> USE CaseLoopDB;
Database changed
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE Grade(IN marks INT)
    -> BEGIN
    ->     CASE
    ->         WHEN marks >= 90 THEN SELECT 'A Grade' AS Result;
    ->         WHEN marks >= 75 THEN SELECT 'B Grade' AS Result;
    ->         WHEN marks >= 50 THEN SELECT 'C Grade' AS Result;
    ->         ELSE SELECT 'Fail' AS Result;
    ->     END CASE;
    -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL Grade(95);
+---------+
| Result  |
+---------+
| A Grade |
+---------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

mysql> CALL Grade(80);
+---------+
| Result  |
+---------+
| B Grade |
+---------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)
```

```
mysql> CALL Grade(60);
+---------+
| Result  |
+---------+
| C Grade |
+---------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

mysql> CALL Grade(30);
+--------+
| Result |
+--------+
| Fail   |
+--------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE NumberLoop()
    -> BEGIN
    ->     DECLARE i INT DEFAULT 1;
    ->
    ->     myloop: LOOP
    ->         SELECT i AS Number;
    ->
    ->         SET i = i + 1;
    ->
    ->         IF i > 10 THEN
    ->             LEAVE myloop;
    ->         END IF;
    ->
    ->     END LOOP myloop;
    -> END //
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> CALL Grade(95);
+---------+
| Result  |
+---------+
| A Grade |
+---------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

mysql> CALL Grade(80);
+---------+
| Result  |
+---------+
| B Grade |
+---------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

mysql> CALL Grade(60);
+---------+
| Result  |
+---------+
| C Grade |
+---------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

mysql> CALL Grade(30);
+--------+
| Result |
+--------+
| Fail   |
+--------+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)
```

```
mysql> CREATE PROCEDURE NumberLoop()
    -> BEGIN
    ->     DECLARE i INT DEFAULT 1;
    ->
    ->     myloop: LOOP
    ->         SELECT i AS Number;
    ->
    ->         SET i = i + 1;
    ->
    ->         IF i > 10 THEN
    ->             LEAVE myloop;
    ->         END IF;
    ->
    ->     END LOOP myloop;
    -> END //
ERROR 1304 (42000): PROCEDURE NumberLoop already exists
mysql>
mysql> DELIMITER ;
mysql> CALL NumberLoop();
+--------+
| Number |
+--------+
|      1 |
+--------+
1 row in set (0.00 sec)

+--------+
| Number |
+--------+
|      2 |
+--------+
1 row in set (0.00 sec)

+--------+
| Number |
+--------+
|      3 |
+--------+
1 row in set (0.01 sec)
```

```
+--------+
| Number |
+--------+
|      4 |
+--------+
1 row in set (0.01 sec)

+--------+
| Number |
+--------+
|      5 |
+--------+
1 row in set (0.01 sec)

+--------+
| Number |
+--------+
|      6 |
+--------+
1 row in set (0.01 sec)

+--------+
| Number |
+--------+
|      7 |
+--------+
1 row in set (0.01 sec)

+--------+
| Number |
+--------+
|      8 |
+--------+
1 row in set (0.01 sec)

+--------+
| Number |
+--------+
|      9 |
+--------+
1 row in set (0.01 sec)
```

```
+--------+
| Number |
+--------+
|     10 |
+--------+
1 row in set (0.02 sec)

Query OK, 0 rows affected (0.02 sec)
```