```
mysql> USE college;
Database changed
mysql> CREATE TABLE student (
    ->     id INT PRIMARY KEY,
    ->     name VARCHAR(30),
    ->     department VARCHAR(20),
    ->     marks INT
    -> );
Query OK, 0 rows affected (0.01 sec)

mysql> INSERT INTO student VALUES
    -> (1, 'Arun', 'CSE', 85),
    -> (2, 'Priya', 'ECE', 90),
    -> (3, 'Kumar', 'CSE', 75),
    -> (4, 'Anu', 'IT', 88),
    -> (5, 'Rahul', 'ECE', 65);
Query OK, 5 rows affected (0.00 sec)
Records: 5  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM student;
+----+-------+------------+-------+
| id | name  | department | marks |
+----+-------+------------+-------+
|  1 | Arun  | CSE        |    85 |
|  2 | Priya | ECE        |    90 |
|  3 | Kumar | CSE        |    75 |
|  4 | Anu   | IT         |    88 |
|  5 | Rahul | ECE        |    65 |
+----+-------+------------+-------+
5 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM student
    -> WHERE marks > 80;
+----+-------+------------+-------+
| id | name  | department | marks |
+----+-------+------------+-------+
|  1 | Arun  | CSE        |    85 |
|  2 | Priya | ECE        |    90 |
|  4 | Anu   | IT         |    88 |
+----+-------+------------+-------+
3 rows in set (0.00 sec)

mysql> SELECT * FROM student
    -> WHERE department = 'CSE';
+----+-------+------------+-------+
| id | name  | department | marks |
+----+-------+------------+-------+
|  1 | Arun  | CSE        |    85 |
|  3 | Kumar | CSE        |    75 |
+----+-------+------------+-------+
2 rows in set (0.00 sec)

mysql> SELECT * FROM student
    -> WHERE marks < 80;
+----+-------+------------+-------+
| id | name  | department | marks |
+----+-------+------------+-------+
|  3 | Kumar | CSE        |    75 |
|  5 | Rahul | ECE        |    65 |
+----+-------+------------+-------+
2 rows in set (0.00 sec)

mysql> SELECT * FROM student
    -> WHERE name LIKE 'A%';
+----+------+------------+-------+
| id | name | department | marks |
+----+------+------------+-------+
|  1 | Arun | CSE        |    85 |
|  4 | Anu  | IT         |    88 |
+----+------+------------+-------+
2 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM student
    -> WHERE name LIKE '%a';
+----+-------+------------+-------+
| id | name  | department | marks |
+----+-------+------------+-------+
|  2 | Priya | ECE        |    90 |
+----+-------+------------+-------+
1 row in set (0.00 sec)

mysql> SELECT * FROM student
    -> WHERE name LIKE '%u%';
+----+-------+------------+-------+
| id | name  | department | marks |
+----+-------+------------+-------+
|  1 | Arun  | CSE        |    85 |
|  3 | Kumar | CSE        |    75 |
|  4 | Anu   | IT         |    88 |
|  5 | Rahul | ECE        |    65 |
+----+-------+------------+-------+
4 rows in set (0.00 sec)

mysql> SELECT * FROM student
    -> WHERE name LIKE '____';
+----+------+------------+-------+
| id | name | department | marks |
+----+------+------------+-------+
|  1 | Arun | CSE        |    85 |
+----+------+------------+-------+
1 row in set (0.00 sec)

mysql> SELECT * FROM student;
+----+-------+------------+-------+
| id | name  | department | marks |
+----+-------+------------+-------+
|  1 | Arun  | CSE        |    85 |
|  2 | Priya | ECE        |    90 |
|  3 | Kumar | CSE        |    75 |
|  4 | Anu   | IT         |    88 |
|  5 | Rahul | ECE        |    65 |
+----+-------+------------+-------+
5 rows in set (0.00 sec)
```