FLEXA Digital Pirani Vacuum Gauge FGE-2GH

The UVS ***Model FLEXA series*** Vacuum Pirani Gauge Controller displays vacuum pressure as measured from a **FG-04 sensor tube**. The ***Model FGE-2GH*** unit covers the range from 0.001 m.Bar to 20 m.bar, and measures two channels.

Exponential order display from $2.0X10^{1}$ to $1.0X10^{-3}$ mbar

The Advantage Of This Vacuum Gauge FLEXA Series Is The Sensor Tube Has The Built In Zero And Atm Adjustments, So That The Sensor Tube Can Be Used As A Transducer, And Each Sensor Is Factory Calibrated At Sensor Level.
With This 1:1 Replacement Of Sensor With The Display Unit Is Established, And There Is No Dependency On Vacuum Gauge Level Adjustment In Case Of Sensor Replacement.

TECHNICAL SPECIFICATIONS

Number of sensor channels	*TWO*
Display Range	1000 mBar to 0.001mBar.
Measuring Range	20 mBar to 0.001mBar.
Units of Display	m.Bar
Vacuum Gauge Head	**FG-04 sensor tube**
Temp. Range	+2 to +50 deg. Celsius
VAC. Display	4-digit bright red LED, 14 mm high
VAC and ATM Adjust	adjusted by trim pot at the signal conditioner PCB of the sensor.
Process control set points	**NIL**
Process Control Relays	NIL
Nonvolatile Memory	NIL
Operating Voltage	universal power supply, input voltages from 90 ~ 264VAC 50/60 Hz
Mounting	¼ DIN 92 x 92 mm (3.62" x 3.62")
Environmental Considerations	not for use with explosive or corrosive gases
Overall dimensions	92mm X 92mm X 110mm Depth
Optional outputs on request	RS485, 0 -10V Dc analog output (OPTIONAL)
Sensor cable	Standard RJ45 male plugs both ends- 2 mtrs long. Optional additional lengths available on request.

Features at a Glance : ■ ***Measurement range 0.001 to 20 mbar*** ■ ***Two channel measurement*** ■ ***Space saving rugged design- 1/8 DIN console*** ■ ***Mounts in any orientation*** ■ ***brass body measuring cell with metal-sealed feed through*** ■ ***interchangeability of the sensor possible without disturbing the display unit.***

Applications: ■ Controlling high vacuum systems ■ Fore vacuum pressure monitoring ■ Safety circuits in vacuum systems ■ General vacuum measurement & control in the fine and rough vacuum range.

Calibration:

Unique Vacuum Solutions ***offers a convenient recalibration service to help users of vacuum measurement pirani/ thermocouple/ full range gauges to maintain all of their vacuum gauges in Certified and peak condition, regardless of the original manufacturer. All makes of vacuum gauges can also be calibrated / repaired if required.***
The calibration certificates are available only on request at additional cost. Pl contact before ordering.

UNIQUE VACUUM SOLUTIONS
#57, 8th cross, 1st B cross, Doddanna industrial area main road, vishwaneedam post, Near Peenya 2nd stage, Bangalore -560091
Ph: 080-28367059, 9886726920. +91-support@uniquevacuum.co.in, *www.uniquevacuum.co.in*