

Alaska Fisheries Science Center

Trawl: PNE
Footgear: GOA



January 30, 2026

Tow #	84/D	83	85	86	87	88	89/A	90/E	91/F
Tow speed (kts)	3.0	2.0	4.0	2.0	3.0	4.0	3.0	3.0	3.0
Door Spread (m)	70.6	70.6	70.8	82.0	81.9	82.0	66.2	66.7	68.6
Upper wingend spread (m)	16.1	16.1	16.0	17.4	17.4	17.4	16.0	15.9	16.0
Middle wingend spread (m)	20.9	20.8	21.0	22.7	23.2	23.1	20.4	20.5	20.7
Lower wingend spread (m)	16.8	16.7	16.6	18.0	18.1	18.0	16.0	16.1	16.5
Headline height (m)	5.6	7.1	4.5	6.5	4.9	4.1	5.1	5.5	5.2
Upper wingend height (m)	4.4	5.3	3.6	4.9	4.0	3.3	3.7	3.8	3.8
Middle wingend height (m)	1.9	2.1	1.5	1.8	1.6	1.3	1.6	1.6	1.3
Fishingline height (m)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Bridle length (m)	26.1	26.1	26.1	26.1	26.1	26.1	27.9	27.9	27.9
Sweep length (m)	0.0	0.0	0.0	0.0	0.0	0.0	27.4	27.4	27.4
Port tension (tonnes)	0.0	0.0	0.0	0.0	0.0	0.0	2.6	2.7	2.6
Stbd. tension (tonnes)	0.0	0.0	0.0	0.0	0.0	0.0	2.9	3.0	2.9
Total tension (tonnes)	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.7	5.5
Mouth area (sq.m)	100.0	126.2	80.5	126.6	96.7	79.6	89.2	95.6	92.2
Mouth drag (kgf per sq.m)	0.0	0.0	0.0	0.0	0.0	0.0	61.4	59.3	59.7
# of floats (9.7 kg buoyancy)	35	35	35	35	35	35	47	47	47
Total buoyancy (kgf)	337.7	337.7	337.7	337.7	337.7	337.7	458.3	458.3	458.3
Bridle Angle (degrees)	23.9	24.0	24.1	28.8	28.7	28.9	21.6	21.8	22.5

Notes:

Rig A: Option 1.2 bridal; middle line to clip 1.63m plus 4 links; Top plus 8 links; bottom plus 8 links
Rig D: Turncated 3.2m plus (13 links top, 0 links middle, 8 bottom)
Rig E: Option 1.2 bridal; middle line to clip 1.63m plus 6 links; Top plus 13 links; bottom plus 8 links
Rig F: Option 2 bridal; middle line to clip 1.63m plus 6 links; Top plus 13 links; bottom plus 8 links