

12.7 — Introduction to pointers

👤 ALEX¹ ⌚ FEBRUARY 7, 2025

Pointers are one of C++'s historical boogeymen, and a place where many aspiring C++ learners have gotten stuck. However, as you'll see shortly, pointers are nothing to be scared of.

In fact, pointers behave a lot like lvalue references. But before we explain that further, let's do some setup.

Related content

If you're rusty or not familiar with lvalue references, now would be a good time to review them. We cover lvalue references in lessons [12.3 -- Lvalue references](https://www.learncpp.com/cpp-tutorial/lvalue-references/)², [12.4 -- Lvalue references to const](https://www.learncpp.com/cpp-tutorial/lvalue-references-to-const/)³, and [12.5 -- Pass by lvalue reference](https://www.learncpp.com/cpp-tutorial/pass-by-lvalue-reference/)⁴.

Consider a normal variable, like this one:

```
1 | char x {}; // chars use 1 byte of memory
```

Simplifying a bit, when the code generated for this definition is executed, a piece of memory from RAM will be assigned to this object. For the sake of example, let's say that the variable `x` is assigned memory address `140`. Whenever we use variable `x` in an expression or statement, the program will go to memory address `140` to access the value stored there.

The nice thing about variables is that we don't need to worry about what specific memory addresses are assigned, or how many bytes are required to store the object's value. We just refer to the variable by its given identifier, and the compiler translates this name into the appropriately assigned memory address. The compiler takes care of all the addressing.

This is also true with references:

```
1 | int main()
2 | {
3 |     char x {}; // assume this is assigned memory address 140
4 |     char& ref { x }; // ref is an lvalue reference to x (when used with a type, &
                        // means lvalue reference)
5 |
6 |     return 0;
7 | }
```

Because `ref` acts as an alias for `x`, whenever we use `ref`, the program will go to memory address `140` to access the value. Again the compiler takes care of the addressing, so that we don't have to think about it.

The address-of operator (&)

Although the memory addresses used by variables aren't exposed to us by default, we do have access to this information. **The address-of operator (&)** returns the memory address of its operand. This is pretty straightforward:

```
1 | #include <iostream>
2 |
3 | int main()
4 | {
5 |     int x{ 5 };
6 |     std::cout << x << '\n'; // print the value of variable x
7 |     std::cout << &x << '\n'; // print the memory address of variable x
8 |
9 |     return 0;
10| }
```

On the author's machine, the above program printed:

```
5
0027FEA0
```

In the above example, we use the address-of operator (&) to retrieve the address assigned to variable `x` and print that address to the console. Memory addresses are typically printed as hexadecimal values (we covered hex in lesson [5.3 -- Numeral systems \(decimal, binary, hexadecimal, and octal\)](https://www.learncpp.com/cpp-tutorial/numeral-systems-decimal-binary-hexadecimal-and-octal/) (<https://www.learncpp.com/cpp-tutorial/numeral-systems-decimal-binary-hexadecimal-and-octal/>⁵), often without the 0x prefix.

For objects that use more than one byte of memory, address-of will return the memory address of the first byte used by the object.

Tip

The & symbol tends to cause confusion because it has different meanings depending on context:

- When following a type name, & denotes an lvalue reference: `int& ref`.
- When used in a unary context in an expression, & is the address-of operator: `std::cout << &x`.
- When used in a binary context in an expression, & is the Bitwise AND operator: `std::cout << x & y`.

The dereference operator (*)

Getting the address of a variable isn't very useful by itself.

The most useful thing we can do with an address is access the value stored at that address. The **dereference operator (*)** (also occasionally called the **indirection operator**) returns the value at a given memory address as an lvalue:

```

1  #include <iostream>
2
3  int main()
4  {
5      int x{ 5 };
6      std::cout << x << '\n'; // print the value of variable x
7      std::cout << &x << '\n'; // print the memory address of variable x
8
9      std::cout << *(&x) << '\n'; // print the value at the memory address of variable x
    (parentheses not required, but make it easier to read)
10
11     return 0;
12 }

```

On the author's machine, the above program printed:

```

5
0027FEA0
5

```

This program is pretty simple. First we declare a variable `x` and print its value. Then we print the address of variable `x`. Finally, we use the dereference operator to get the value at the memory address of variable `x` (which is just the value of `x`), which we print to the console.

Key insight

Given a memory address, we can use the dereference operator (`*`) to get the value at that address (as an lvalue).

The address-of operator (`&`) and dereference operator (`*`) work as opposites: address-of gets the address of an object, and dereference gets the object at an address.

Tip

Although the dereference operator looks just like the multiplication operator, you can distinguish them because the dereference operator is unary, whereas the multiplication operator is binary.

Getting the memory address of a variable and then immediately dereferencing that address to get a value isn't that useful either (after all, we can just use the variable to access the value).

But now that we have the address-of operator (`&`) and dereference operator (`*`) added to our toolkits, we're ready to talk about pointers.

Pointers

A **pointer** is an object that holds a *memory address* (typically of another variable) as its value. This allows us to store the address of some other object to use later.

As an aside...

In modern C++, the pointers we are talking about here are sometimes called "raw pointers" or "dumb pointers", to help differentiate them from "smart pointers" that were introduced into the language

more recently. We cover smart pointers in [chapter 22](https://www.learncpp.com/Chapter22) (<https://www.learncpp.com/Chapter22>)⁶.

A type that specifies a pointer (e.g. `int*`) is called a **pointer type**. Much like reference types are declared using an ampersand (&) character, pointer types are declared using an asterisk (*):

```
1 | int; // a normal int
2 | int&; // an lvalue reference to an int value
3 |
4 | int*; // a pointer to an int value (holds the address of an integer value)
```

To create a pointer variable, we simply define a variable with a pointer type:

```
1 | int main()
2 | {
3 |     int x { 5 }; // normal variable
4 |     int& ref { x }; // a reference to an integer (bound to x)
5 |
6 |     int* ptr; // a pointer to an integer
7 |
8 |     return 0;
9 | }
```

Note that this asterisk is part of the declaration syntax for pointers, not a use of the dereference operator.

Best practice

When declaring a pointer type, place the asterisk next to the type name.

Warning

Although you generally should not declare multiple variables on a single line, if you do, the asterisk has to be included with each variable.

```
1 | int* ptr1, ptr2; // incorrect: ptr1 is a pointer to an int, but ptr2 is just a
   | plain int!
2 | int* ptr3, * ptr4; // correct: ptr3 and ptr4 are both pointers to an int
```

Although this is sometimes used as an argument to not place the asterisk with the type name (instead placing it next to the variable name), it's a better argument for avoiding defining multiple variables in the same statement.

Pointer initialization

Like normal variables, pointers are *not* initialized by default. A pointer that has not been initialized is sometimes called a **wild pointer**. Wild pointers contain a garbage address, and dereferencing a wild pointer will result in undefined behavior. Because of this, you should always initialize your pointers to a known value.

Best practice

Always initialize your pointers.

```

1  int main()
2  {
3      int x{ 5 };
4
5      int* ptr;           // an uninitialized pointer (holds a garbage address)
6      int* ptr2{};        // a null pointer (we'll discuss these in the next lesson)
7      int* ptr3{ &x };    // a pointer initialized with the address of variable x
8
9      return 0;
10 }

```

Since pointers hold addresses, when we initialize or assign a value to a pointer, that value has to be an address. Typically, pointers are used to hold the address of another variable (which we can get using the address-of operator (&)).

Once we have a pointer holding the address of another object, we can then use the dereference operator (*) to access the value at that address. For example:

```

1  #include <iostream>
2
3  int main()
4  {
5      int x{ 5 };
6      std::cout << x << '\n'; // print the value of variable x
7
8      int* ptr{ &x }; // ptr holds the address of x
9      std::cout << *ptr << '\n'; // use dereference operator to print the value at the
10     address that ptr is holding (which is x's address)
11
12     return 0;
13 }

```

This prints:

```

5
5

```

Conceptually, you can think of the above snippet like this:



This is where pointers get their name from -- `ptr` is holding the address of `x`, so we say that `ptr` is “pointing to” `x`.

Author’s note

A note on pointer nomenclature: “X pointer” (where X is some type) is a commonly used shorthand for “pointer to an X”. So when we say, “an integer pointer”, we really mean “a pointer to an integer”. This understanding will be valuable when we talk about const pointers.

Much like the type of a reference has to match the type of object being referred to, the type of the pointer has to match the type of the object being pointed to:

```
1 | int main()
2 | {
3 |     int i{ 5 };
4 |     double d{ 7.0 };
5 |
6 |     int* iPtr{ &i };    // ok: a pointer to an int can point to an int object
7 |     int* iPtr2 { &d };  // not okay: a pointer to an int can't point to a double
8 |     object
9 |     double* dPtr{ &d }; // ok: a pointer to a double can point to a double object
10 |    double* dPtr2{ &i }; // not okay: a pointer to a double can't point to an int
11 |    object
12 |
    return 0;
}
```

With one exception that we'll discuss next lesson, initializing a pointer with a literal value is disallowed:

```
1 | int* ptr{ 5 }; // not okay
2 | int* ptr{ 0x0012FF7C }; // not okay, 0x0012FF7C is treated as an integer literal
```

Pointers and assignment

We can use assignment with pointers in two different ways:

1. To change what the pointer is pointing at (by assigning the pointer a new address)
2. To change the value being pointed at (by assigning the dereferenced pointer a new value)

First, let's look at a case where a pointer is changed to point at a different object:

```
1 | #include <iostream>
2 |
3 | int main()
4 | {
5 |     int x{ 5 };
6 |     int* ptr{ &x }; // ptr initialized to point at x
7 |
8 |     std::cout << *ptr << '\n'; // print the value at the address being pointed to (x's
9 |     address)
10 |
11 |     int y{ 6 };
12 |     ptr = &y; // // change ptr to point at y
13 |
14 |     std::cout << *ptr << '\n'; // print the value at the address being pointed to (y's
15 |     address)
16 |
    return 0;
}
```

The above prints:

```
5
6
```

In the above example, we define pointer `ptr`, initialize it with the address of `x`, and dereference the pointer to print the value being pointed to (`5`). We then use the assignment operator to change the address that `ptr` is holding to the address of `y`. We then dereference the pointer again to print the value being pointed to (which is now `6`).

Now let's look at how we can also use a pointer to change the value being pointed at:

```
1  #include <iostream>
2
3  int main()
4  {
5      int x{ 5 };
6      int* ptr{ &x }; // initialize ptr with address of variable x
7
8      std::cout << x << '\n';    // print x's value
9      std::cout << *ptr << '\n'; // print the value at the address that ptr is holding
10     (x's address)
11
12     *ptr = 6; // The object at the address held by ptr (x) assigned value 6 (note that
13     ptr is dereferenced here)
14
15     std::cout << x << '\n';
16     std::cout << *ptr << '\n'; // print the value at the address that ptr is holding
17     (x's address)
18
19     return 0;
20 }
```

This program prints:

```
5
5
6
6
```

In this example, we define pointer `ptr`, initialize it with the address of `x`, and then print the value of both `x` and `*ptr` (`5`). Because `*ptr` returns an lvalue, we can use this on the left hand side of an assignment statement, which we do to change the value being pointed at by `ptr` to `6`. We then print the value of both `x` and `*ptr` again to show that the value has been updated as expected.

Key insight

When we use a pointer without a dereference (`ptr`), we are accessing the address held by the pointer. Modifying this (`ptr = &y`) changes what the pointer is pointing at.

When we dereference a pointer (`*ptr`), we are accessing the object being pointed at. Modifying this (`*ptr = 6;`) changes the value of the object being pointed at.

Pointers behave much like lvalue references

Pointers and lvalue references behave similarly. Consider the following program:

```

1  #include <iostream>
2
3  int main()
4  {
5      int x{ 5 };
6      int& ref { x }; // get a reference to x
7      int* ptr { &x }; // get a pointer to x
8
9      std::cout << x;
10     std::cout << ref; // use the reference to print x's value (5)
11     std::cout << *ptr << '\n'; // use the pointer to print x's value (5)
12
13     ref = 6; // use the reference to change the value of x
14     std::cout << x;
15     std::cout << ref; // use the reference to print x's value (6)
16     std::cout << *ptr << '\n'; // use the pointer to print x's value (6)
17
18     *ptr = 7; // use the pointer to change the value of x
19     std::cout << x;
20     std::cout << ref; // use the reference to print x's value (7)
21     std::cout << *ptr << '\n'; // use the pointer to print x's value (7)
22
23     return 0;
24 }

```

This program prints:

```

555
666
777

```

In the above program, we create a normal variable `x` with value `5`, and then create an lvalue reference and a pointer to `x`. Next, we use the lvalue reference to change the value from `5` to `6`, and show that we can access that updated value via all three methods. Finally, we use the dereferenced pointer to change the value from `6` to `7`, and again show that we can access the updated value via all three methods.

Thus, pointers and references both provide a way to indirectly access another object. The primary difference is that with pointers, we need to explicitly get the address to point at, and we have to explicitly dereference the pointer to get the value. With references, the address-of and dereference happens implicitly.

There are some other differences between pointers and references worth mentioning:

- References must be initialized, pointers are not required to be initialized (but should be).
- References are not objects, pointers are.
- References can not be reseated (changed to reference something else), pointers can change what they are pointing at.
- References must always be bound to an object, pointers can point to nothing (we'll see an example of this in the next lesson).
- References are "safe" (outside of dangling references), pointers are inherently dangerous (we'll also discuss this in the next lesson).

The address-of operator returns a pointer

It's worth noting that the address-of operator (`&`) doesn't return the address of its operand as a literal (as C++ doesn't support address literals). Instead, it returns a pointer to the operand (whose value is the

address of the operand). In other words, given variable `int x`, `&x` returns an `int*` holding the address of `x`.

We can see this in the following example:

```
1 #include <iostream>
2 #include <typeinfo>
3
4 int main()
5 {
6     int x{ 4 };
7     std::cout << typeid(x).name() << '\n'; // print the type of x
8     std::cout << typeid(&x).name() << '\n'; // print the type of &x
9
10    return 0;
11 }
```

On Visual Studio, this printed:

```
int
int *
```

With gcc, this printed `i` (int) and `pi` (pointer to int) instead. Because the result of `typeid().name()` is compiler-dependent, your compiler may print something different, but it will have the same meaning.

The size of pointers

The size of a pointer is dependent upon the architecture the executable is compiled for -- a 32-bit executable uses 32-bit memory addresses -- consequently, a pointer on a 32-bit machine is 32 bits (4 bytes). With a 64-bit executable, a pointer would be 64 bits (8 bytes). Note that this is true regardless of the size of the object being pointed to:

```
1 #include <iostream>
2
3 int main() // assume a 32-bit application
4 {
5     char* chPtr{}; // chars are 1 byte
6     int* iPtr{}; // ints are usually 4 bytes
7     long double* ldPtr{}; // long doubles are usually 8 or 12 bytes
8
9     std::cout << sizeof(chPtr) << '\n'; // prints 4
10    std::cout << sizeof(iPtr) << '\n'; // prints 4
11    std::cout << sizeof(ldPtr) << '\n'; // prints 4
12
13    return 0;
14 }
```

The size of the pointer is always the same. This is because a pointer is just a memory address, and the number of bits needed to access a memory address is constant.

Dangling pointers

Much like a dangling reference, a **dangling pointer** is a pointer that is holding the address of an object that is no longer valid (e.g. because it has been destroyed).

Dereferencing a dangling pointer (e.g. in order to print the value being pointed at) will lead to undefined behavior, as you are trying to access an object that is no longer valid.

Perhaps surprisingly, the standard says “Any other use of an invalid pointer *value* has implementation-defined behavior”. This means that you can assign an invalid pointer a new value, such as `nullptr` (because this doesn’t use the invalid pointer’s value). However, any other operations that use the invalid pointer’s value (such as copying or incrementing an invalid pointer) will yield implementation-defined behavior.

Key insight

Dereferencing an invalid pointer will lead to undefined behavior. Any other use of an invalid pointer value is implementation-defined.

Here’s an example of creating a dangling pointer:

```
1  #include <iostream>
2
3  int main()
4  {
5      int x{ 5 };
6      int* ptr{ &x };
7
8      std::cout << *ptr << '\n'; // valid
9
10     {
11         int y{ 6 };
12         ptr = &y;
13
14         std::cout << *ptr << '\n'; // valid
15     } // y goes out of scope, and ptr is now dangling
16
17     std::cout << *ptr << '\n'; // undefined behavior from dereferencing a dangling
18     pointer
19
20     return 0;
21 }
```

The above program will probably print:

```
5
6
6
```

But it may not, as the object that `ptr` was pointing at went out of scope and was destroyed at the end of the inner block, leaving `ptr` dangling.

Conclusion

Pointers are variables that hold a memory address. They can be dereferenced using the dereference operator (`*`) to retrieve the value at the address they are holding. Dereferencing a wild or dangling (or null) pointer will result in undefined behavior and will probably crash your application.

Pointers are both more flexible than references and more dangerous. We’ll continue to explore this in the upcoming lessons.

Quiz time

Question #1

What values does this program print? Assume a short is 2 bytes, and a 32-bit machine.

```
1  #include <iostream>
2
3  int main()
4  {
5      short value{ 7 }; // &value = 0012FF60
6      short otherValue{ 3 }; // &otherValue = 0012FF54
7
8      short* ptr{ &value };          0012FF60
9                                     7
10     std::cout << &value << '\n';    0012FF60
11     std::cout << value << '\n';      7
12     std::cout << ptr << '\n';
13     std::cout << *ptr << '\n';
14     std::cout << '\n';              0012FF60
15                                     9
16     *ptr = 9;                      0012FF60
17                                     9
18     std::cout << &value << '\n';
19     std::cout << value << '\n';
20     std::cout << ptr << '\n';        0012FF54
21     std::cout << *ptr << '\n';      3
22     std::cout << '\n';              0012FF54
23                                     3
24     ptr = &otherValue;
25
26     std::cout << &otherValue << '\n'; 4
27     std::cout << otherValue << '\n';  2
28     std::cout << ptr << '\n';
29     std::cout << *ptr << '\n';
30     std::cout << '\n';
31
32     std::cout << sizeof(ptr) << '\n';
33     std::cout << sizeof(*ptr) << '\n';
34
35     return 0;
36 }
```

A brief explanation about the 4 and the 2. A 32-bit machine means that pointers will be 32 bits in length, but sizeof() always prints the size in bytes. 32 bits is 4 bytes. Thus the sizeof(ptr) is 4. Because ptr is a pointer to a short, *ptr is a short. The size of a short in this example is 2 bytes. Thus the sizeof(*ptr) is 2.

[Show Solution](#)(javascript:void(0))⁷

Question #2

What's wrong with this snippet of code?

```
1  int v1{ 45 };
2  int* ptr{ &v1 }; // initialize ptr with address of v1
3
4  int v2 { 78 };
5  *ptr = &v2;      // assign ptr to address of v2
```

[Show Solution](#)(javascript:void(0))⁷



[Next lesson](#)

12.8 [Null pointers](#)

8



[Back to table of contents](#)

9



[Previous lesson](#)

12.6 [Pass by const lvalue reference](#)

10

11



B

U

URL

INLINE CODE

C++ CODE BLOCK

HELP!

Leave a comment...



Name*



Email*



Notify me about replies:



POST COMMENT

🚩 Find a mistake? Leave a comment above!?

👤 Avatars from <https://gravatar.com/>¹⁴ are connected to your provided email address.

531 COMMENTS

Newest ▼



Binary
Rambo

Binary Rambo

🕒 June 2, 2025 5:39 pm PDT

Much like the type of a reference has to match the type of object being referred to, the type of the pointer has to match the type of the object being pointed **to:**

```
int main()
{
```

```
int i{ 5 };  
double d{ 7.0 };  
  
int* iPtr{ &i }; // ok: a pointer to an int can point to an int object  
int* iPtr2 { &d }; // not okay: a pointer to an int can't point to a double object  
double* dPtr{ &d }; // ok: a pointer to a double can point to a double object  
double* dPtr2{ &i }; // not okay: a pointer to a double can't point to an int object  
  
return 0;  
}
```

Hi Alex

Help to explain please.

Irrespective of data type an address is an address, how the address is tied to the type and how C++ distinguish this and disallow a mismatch ?

 0  Reply



kalypto


 May 25, 2025 5:02 am PDT

The address-of operator should be named pointer-to operator. It would make things more clear... And if you print a pointer it will print the address it points to.

 0  Reply



Copernicus

 May 19, 2025 4:55 am PDT

Question #2

Doesn't compile, *ptr returns the value it is pointing to, which is an int. Ints cannot store memory addresses.

 0  Reply



Copernicus

 May 19, 2025 4:48 am PDT

Question #1

1	0012FF60
2	7
3	0012FF60
4	7
5	
6	0012FF60
7	9
8	0012FF60
9	9
10	
11	0012FF54
12	3
13	0012FF54
14	3
15	
16	4
17	2

 0  Reply




RSH

 May 12, 2025 3:16 am PDT

This is really what people were struggling over??

 1  Reply



redshift

 May 2, 2025 3:23 pm PDT

"Pointers are one of C++'s historical boogeymen, and a place where many aspiring C++ learners have gotten stuck. However, as you'll see shortly, pointers are nothing to be scared of."

When I learned C in school, I understood pointers much better than references. With pointers I was taught what the computer is doing, like you do here, but references were a bit of a black box and would make me confused because they sort of looked like pointers but not exactly - I avoided using references as much as possible.

 0  Reply



Hari

 April 17, 2025 2:39 am PDT

This is surprisingly intuitive so far.

I like to use the analogy of 'Thomas', a brunette man living in Flat 42 to simplify objects/references/pointers:

Thomas is the (identifier) of the brunette man (object) living at 42

Tom is a (reference) to Thomas

home is the (pointer) to Thomas' address/location

For references:

Tom is an alias, which evaluates into Thomas (lvalue), which further evaluates to brunette man (rvalue)
Changing the rvalue for this lvalue, is equal to erasing the man from existence and replacing with say, a blonde man.

Thomas = blonde man (not brunette man, as original rvalue was replaced)

Tom = blonde man

For pointers:

home = &Thomas (== 42)

*home returns Thomas (the object living at address)

Let's reset the word 'Home' so 'Peter' can use it to point to Flat 69.

Now,

home = &Peter (== 69)

*home = Peter

Hope this helps. Do correct this if it's wrong. And thanks for the lessons :D

 Last edited 2 months ago by Hari

 1  Reply



Choco

 Reply to [Hari](#)¹⁵  April 18, 2025 2:02 pm PDT

damn bitch, u really know how to teach this type of shit thank u so much.

 2  Reply



smart

 April 4, 2025 5:17 pm PDT

(~_~) ZZZ...

 Last edited 2 months ago by smart

 1  Reply



Leni

 March 2, 2025 8:40 pm PST

Pointers are a fundamental but often intimidating topic in C++. How does understanding their similarities to references helps in grasping their concepts?

 Last edited 3 months ago by Leni

 0  Reply



Nidhi Gupta

🕒 February 28, 2025 3:02 pm PST

cool



0



Reply

Links

1. <https://www.learncpp.com/author/Alex/>
2. <https://www.learncpp.com/cpp-tutorial/lvalue-references/>
3. <https://www.learncpp.com/cpp-tutorial/lvalue-references-to-const/>
4. <https://www.learncpp.com/cpp-tutorial/pass-by-lvalue-reference/>
5. <https://www.learncpp.com/cpp-tutorial/numeral-systems-decimal-binary-hexadecimal-and-octal/>
6. <https://www.learncpp.com/#Chapter22>
7. [javascript:void\(0\)](javascript:void(0))
8. <https://www.learncpp.com/cpp-tutorial/null-pointers/>
9. <https://www.learncpp.com/>
10. <https://www.learncpp.com/cpp-tutorial/pass-by-const-lvalue-reference/>
11. <https://www.learncpp.com/introduction-to-pointers/>
12. <https://www.learncpp.com/general-programming/a-php-script-to-unzip-files-with-file-overwriting/>
13. <https://www.learncpp.com/cpp-tutorial/c-style-array-decay/>
14. <https://gravatar.com/>
15. <https://www.learncpp.com/cpp-tutorial/introduction-to-pointers/#comment-609330>
16. <https://g.ezoic.net/privacy/learncpp.com>