

14.1 — Introduction to object-oriented programming

👤 **ALEX¹** ⌚ **SEPTEMBER 15, 2023**

Procedural programming

Back in lesson [1.3 -- Introduction to objects and variables](https://www.learncpp.com/cpp-tutorial/introduction-to-objects-and-variables/) (<https://www.learncpp.com/cpp-tutorial/introduction-to-objects-and-variables/>)², we defined an object in C++ as, “a piece of memory that can be used to store values”. An object with a name is called a variable. Our C++ programs have consisted of sequential lists of instructions to the computer that define data (via objects) and operations performed on that data (via functions containing statements and expressions).

Up to now, we’ve been doing a type of programming called procedural programming. **In procedural programming, the focus is on creating “procedures” (which in C++ are called functions) that implement our program logic.** We pass data objects to these functions, those functions perform operations on the data, and then potentially return a result to be used by the caller.

In procedural programming, the functions and the data those functions operate on are separate entities. The programmer is responsible for combining the functions and the data together to produce the desired result. This leads to code that looks like this:

```
1 | eat(you, apple);
```

Now, take a look around you -- everywhere you look are objects: books and buildings and food and even you. Such objects have two major components to them: 1) Some number of associated properties (e.g. weight, color, size, solidity, shape, etc...), and 2) Some number of behaviors that they can exhibit (e.g. being opened, making something else hot, etc...). These properties and behaviors are inseparable.

In programming, properties are represented by objects, and behaviors are represented by functions. And thus, **procedural programming represents reality fairly poorly, as it separates properties (objects) and behaviors (functions).**

What is object-oriented programming?

In object-oriented programming (often abbreviated as OOP), **the focus is on creating program-defined data types that contain both properties and a set of well-defined behaviors.** The term “object” in OOP refers to the objects that we can instantiate from such types.

This leads to code that looks more like this:

```
1 | you.eat(apple);
```

This makes it clearer who the subject is (`you`), what behavior is being invoked (`eat()`), and what objects are accessories to that behavior (`apple`).

Because the properties and behaviors are no longer separate, **objects are easier to modularize**, which makes our programs easier to write and understand, and also provides a higher degree of code reusability. These objects also provide a more intuitive way to work with our data by allowing us to define how we interact with the objects, and how they interact with other objects.

We'll discuss how to create such objects in the next lesson.

A procedural vs OOP-like example

Here's a short program written in a procedural programming style that prints the name and number of legs of an animal:

```
1  #include <iostream>
2  #include <string_view>
3
4  enum AnimalType
5  {
6      cat,
7      dog,
8      chicken,
9  };
10
11 constexpr std::string_view animalName(AnimalType type)
12 {
13     switch (type)
14     {
15     case cat: return "cat";
16     case dog: return "dog";
17     case chicken: return "chicken";
18     default: return "";
19     }
20 }
21
22 constexpr int numLegs(AnimalType type)
23 {
24     switch (type)
25     {
26     case cat: return 4;
27     case dog: return 4;
28     case chicken: return 2;
29     default: return 0;
30     }
31 }
32
33
34 int main()
35 {
36     constexpr AnimalType animal{ cat };
37     std::cout << "A " << animalName(animal) << " has " << numLegs(animal) << "
38     legs\n";
39
40     return 0;
41 }
```

In this program, we have written functions that do allow us to do things like get the number of legs an animal has, and get the name of an animal.

While this works just fine, consider what happens when we want to update this program so that our animal is now a **snake**. To add a snake to our code, we'd need to modify **AnimalType**, **numLegs()**, **animalName()**. If this were a larger codebase, we'd also need to update any other function that uses **AnimalType** -- if **AnimalType** was used in a lot of places, that could be a lot of code that needs to get touched (and potentially broken).

Now let's write that same program (producing the same output) using more of an OOP mindset:

```
1  #include <iostream>
2  #include <string_view>
3
4  struct Cat
5  {
6      std::string_view name{ "cat" };
7      int numLegs{ 4 };
8  };
9
10 struct Dog
11 {
12     std::string_view name{ "dog" };
13     int numLegs{ 4 };
14 };
15
16 struct Chicken
17 {
18     std::string_view name{ "chicken" };
19     int numLegs{ 2 };
20 };
21
22 int main()
23 {
24     constexpr Cat animal;
25     std::cout << "a " << animal.name << " has " << animal.numLegs << " legs\n";
26
27     return 0;
28 }
```

In this example, each animal is its own program-defined type, and that type manages everything related to that animal (which in this case, is just keeping track of the name and number of legs).

Now consider the case where we want to update our animal to a snake. All we have to do is create a `Snake` type and use it instead of `Cat`. Very little existing code needs to be changed, which means much less risk of breaking something that already works.

As presented, our `Cat`, `Dog`, and `Chicken` example above has a lot of repetition (as each defines the exact same set of members). In such a case, creating a common `Animal` struct and creating an instance for each animal might be preferable. But what if we want to add a new member to `Chicken` that's not applicable to the other animals (e.g. `wormsPerDay`)? With a common `Animal` struct, all animals will get that member. With our OOP model, we can restrict that member to `Chicken` objects.

OOP brings other benefits to the table

In school, when you submit your programming assignments, your work is essentially done. Your professor or teacher's assistant will run your code to see if it produces the correct result. It either does or doesn't, and you are graded accordingly. Your code is likely discarded at that point.

On the other hand, when you submit your code into a repository that is used by other developers, or into an application that's used by real users, it's an entirely different ballgame. Some new OS or software release will break your code. Users will find some logic error you made. A business partner will demand some new capability. Other developers will need to extend your code without breaking it. Your code needs to be able to evolve, perhaps significantly, and it needs to be able to do so with minimal time investment, minimal headaches, and minimal breakage.

The best way to address these is by keeping your code as modular (and non-redundant) as possible. To assist with this, OOP also brings a number of other useful concepts to the table: inheritance, encapsulation,

abstraction, and polymorphism.

Author's note

Language designers have a philosophy: never use a small word where a big one will do.

Also why is the word abbreviation so long?

We'll cover what all of these are in due time, and how they can assist in making your code less redundant, and easier to modify and extend. Once you've been properly familiarized with OOP and it clicks, you will likely never want to go back to pure procedural programming again.

That said, OOP doesn't replace procedural programming -- rather, it gives you additional tools in your programming tool belt to manage complexity when needed.

The term "object"

Note that the term "object" is overloaded a bit, and this causes some amount of confusion. In traditional programming, an object is a piece of memory to store values. And that's it. In object-oriented programming, an "object" implies that it is both an object in the traditional programming sense, and that it combines both properties and behaviors. We will favor the traditional meaning of the term object in these tutorials, and prefer the term "class object" when specifically referring to OOP objects.

Quiz time

Question #1

Update the animal procedural example above and instantiate a snake instead of a cat.

[Show Solution](#) (javascript:void(0))³

Question #2

Update the animal OOP-like example above and instantiate a snake instead of a cat.

[Show Solution](#) (javascript:void(0))³



Next lesson

14.2 [Introduction to classes](#)

4



[Back to table of contents](#)

5



Previous lesson

13.y [Using a language reference](#)

6

7

**B****U****URL****INLINE CODE****C++ CODE BLOCK****HELP!**

Leave a comment...



Name*



Email*



Notify me about replies:



POST COMMENT

🔍 Find a mistake? Leave a comment above!?

👤 Avatars from <https://gravatar.com/>¹⁰ are connected to your provided email address.

143 COMMENTS

Newest ▼



Copernicus

🕒 May 27, 2025 3:00 am PDT

Question #1

```

1  #include <iostream>
2  #include <string_view>
3
4  enum AnimalType
5  {
6      cat,
7      dog,
8      chicken,
9      snake,
10 };
11
12 constexpr std::string_view animalName(AnimalType type)
13 {
14     switch (type)
15     {
16     case cat: return "cat";
17     case dog: return "dog";
18     case chicken: return "chicken";
19     case snake: return "snake";
20     default: return "";
21     }
22 }
23
24 constexpr int numLegs(AnimalType type)
25 {
26     switch (type)
27     {
28     case cat: return 4;
29     case dog: return 4;
30     case chicken: return 2;
31     case snake: return 0;
32     default: return 0;
33     }
34 }
35
36
37 int main()
38 {
39     constexpr AnimalType animal{ snake };
40     std::cout << "A " << animalName(animal) << " has " << numLegs(animal) << "
41 legs\n";
42
43     return 0;
44 }

```

Question #2

```

1  #include <iostream>
2  #include <string_view>
3
4  struct Cat
5  {
6      std::string_view name{ "cat" };
7      int numLegs{ 4 };
8  };
9
10 struct Dog
11 {
12     std::string_view name{ "dog" };
13     int numLegs{ 4 };
14 };
15
16 struct Chicken
17 {
18     std::string_view name{ "chicken" };
19     int numLegs{ 2 };
20 };
21
22 struct Snake
23 {
24     std::string_view name{ "snake" };
25     int numLegs{ 0 };
26 };
27
28 int main()
29 {
30     constexpr Snake animal;
31     std::cout << "a " << animal.name << " has " << animal.numLegs << " legs\n";
32
33     return 0;
34 }

```



0



Reply



Brayan

🕒 April 5, 2025 10:02 am PDT

For some reason, the code example here wont compile. I literally copied and pasted it.

```
#include <iostream>
```

```
#include <string_view>
```

```
struct Cat
```

```
{
```

```
std::string_view name{ "cat" };
```

```
int numLegs{ 4 };
```

```
};
```

```
struct Dog
```

```
{
```

```
std::string_view name{ "dog" };
```

```
int numLegs{ 4 };
```

```
};
```

```

struct Chicken
{
    std::string_view name{ "chicken" };
    int numLegs{ 2 };
};

int main()
{
    constexpr Cat animal;
    std::cout << "a " << animal.name << " has " << animal.numLegs << " legs\n";

    return 0;
}

```

it has errors such as:

- string_view in namespace std does not name a type.
- const struct cat has no member named name.

But for some reason, this simpler example I made works just fine

```

#include <iostream>
#include <string_view>

int main()
{

    struct Feline
    {
        int legs{4};
        int ears{2};
    };

    Feline Cat;
    Feline Lynx;

    std::cout << Lynx.legs << "\n";

    return 0;

}

```

👍 0 ➡ Reply



AJAY.CHALLA

🗨 Reply to [Brayan](#)¹¹ ⌚ May 21, 2025 8:34 pm PDT

It works fine in codeblocks, online gdb compiler, Visual studio code i checked in al of them and it works fine !!

👍 0 ➡ Reply



Aayush

🗨 Reply to [Brayan](#)¹¹ ⌚ April 18, 2025 4:30 am PDT

i tried the code which you said doesn't compile, and it works just fine in my case? i don't know the reason why it won't compile in yours tho, it is compiling and working fine in my IDE, i am using vs code btw.

👍 0 ➡ Reply



Aleksa

🕒 April 2, 2025 4:51 am PDT

Is it wrong to use `std::string_view` as class member because then our class wont be an owner?

👍 0 ➡ Reply



johnoooooooo

🗨 Reply to [Aleksa](#) ¹² 🕒 May 20, 2025 1:27 pm PDT

No, because it is initialised with a string literal, which has static scope by default and therefore will not generate a dangling reference as the string literal will only die when the program ends

👍 0 ➡ Reply



Troopy

🗨 Reply to [johnoooooooo](#) ¹³ 🕒 June 25, 2025 7:07 am PDT

that's exactly what I was thinking, Troopy (I thought) its because its initialised with a string literal, (with a static scope by default) something something dangling reference....

👍 0 ➡ Reply



Kania

🕒 March 10, 2025 6:02 am PDT

<https://tenor.com/view/gunna-fire-writing-heat-gif-25524005>

📝 Last edited 3 months ago by Kania

👍 6 ➡ Reply



Dinny

🕒 March 6, 2025 4:44 am PST

first

👍 0 ➡ Reply



Kania

🗨 Reply to [Dinny](#) ¹⁴ 🕒 March 10, 2025 6:04 am PDT

Wake up to reality

 Last edited 3 months ago by Kania

 0  Reply



Dinny

 Reply to [Kania](#)¹⁵  March 15, 2025 8:01 pm PDT

first

 1  Reply



PooperShooter

 March 2, 2025 10:19 pm PST

I dont really understand why you are using default initialization for this type of thing. imo should be written like this:

```
1  #include <iostream>
2
3  struct Animal
4  {
5      std::string_view name{};
6      int numLegs{};
7  };
8
9  void animalInfo(const Animal& a)
10 {
11     std::cout << "Animal: " << a.name << "\nNumber of Legs: " << a.numLegs << "\n\n";
12 }
13
14 int main()
15 {
16     // create objects
17     Animal cat{ "Cat", 4 };
18     Animal dog{ "Dog", 4 };
19     Animal chicken{ "chicken", 2 };
20     Animal snake{ "snake", 0 };
21
22     // print the output
23     animalInfo(cat);
24     animalInfo(dog);
25     animalInfo(chicken);
26     animalInfo(snake);
27
28     return 0;
29 }
```

I feel like this would encapsulate object oriented approach better since it gets showcases what oop is best at and thats removing redundant code.

 4  Reply



Nidhi Gupta

 February 2, 2025 9:53 pm PST

This lecture offers a thorough and organized examination of C++ floating point types, stressing both their advantages and disadvantages. Because it clarifies how various systems execute floating point

arithmetic, the topic of IEEE 754 compliance is especially helpful in guaranteeing a greater understanding of potential cross-platform discrepancies. The necessity of cautious numerical programming is reinforced by the clear explanations of precision loss and rounding mistakes, which show why floating point computations can occasionally provide unexpected results. The focus on best practices also provides helpful advice for building dependable code, such as avoiding direct equality comparisons of floating point numbers and using double over float for increased precision. This lecture improves understanding and offers developers working with numerical computations practical insights by segmenting difficult ideas into manageable chunks.

👍 2 ➡ Reply



chaojie

🗨 Reply to [Nidhi Gupta](#)¹⁶ 🕒 February 24, 2025 5:09 am PST

but how to learn comprehensively and make study serve the practical purpose.

👍 0 ➡ Reply



Nidhi Gupta

🕒 February 1, 2025 5:54 pm PST

I find this code below pretty cool: `constexpr std::string_view animalName(AnimalType type)`

```
{
switch (type)
{
case cat: return "cat";
case dog: return "dog";
case chicken: return "chicken";
default: return "";
}
}
```

```
constexpr int numLegs(AnimalType type)
{
switch (type)
{
case cat: return 4;
case dog: return 4;
case chicken: return 2;
default: return 0;
}
}
```

👍 1 ➡ Reply




jack

🕒 January 3, 2025 9:43 pm PST

under no circumstances make utilization of a diminutive expression whither a colossus shall suffice.

👍 1 ➡ Reply



NordicCat

🕒 December 20, 2024 10:31 am PST

Your tutorials are great and simplifies a lot of stuffs especially in c++ while c++ stuff on yt looks like *this

<https://youtu.be/MAISjtxy5ak?si=sfw2ldUoVRG0SGo2>

👍 3 ➡ Reply



NordicCat

↩ Reply to [NordicCat](#) ¹⁷ 🕒 December 20, 2024 10:34 am PST

"Don't worry about this part, we'll come back to it later"

The best phrase for yt tutorials, They never do!

My C++ journey is great, My university is great.

Week 1 - variables

Week 2 to 3 - conditionals

Week 4 to 6 - loops

Assignment - Minecraft

Me: Wtf is that!

✎ *Last edited 6 months ago by NordicCat*

👍 1 ➡ Reply



SPLITZY

↩ Reply to [NordicCat](#) ¹⁸ 🕒 January 28, 2025 4:38 am PST

real, telling you to construct a game engine with just the basics and having no idea of so as to what math is required

👍 1 ➡ Reply

Links

1. <https://www.learncpp.com/author/Alex/>
2. <https://www.learncpp.com/cpp-tutorial/introduction-to-objects-and-variables/>
3. `javascript:void(0)`

4. <https://www.learncpp.com/cpp-tutorial/introduction-to-classes/>
5. <https://www.learncpp.com/>
6. <https://www.learncpp.com/cpp-tutorial/using-a-language-reference/>
7. <https://www.learncpp.com/introduction-to-object-oriented-programming/>
8. <https://www.learncpp.com/cpp-tutorial/user-defined-namespaces-and-the-scope-resolution-operator/>
9. <https://www.learncpp.com/cpp-tutorial/member-functions/>
10. <https://gravatar.com/>
11. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-609072>
12. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-608982>
13. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-610243>
14. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-608292>
15. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-608428>
16. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-607318>
17. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-605497>
18. <https://www.learncpp.com/cpp-tutorial/introduction-to-object-oriented-programming/#comment-605498>
19. <https://g.ezoic.net/privacy/learncpp.com>