

# CS5800 – ALGORITHMS

## MODULE 1. REVIEW OF ASYMPTOTIC NOTATION

### Lesson 3: PCR

Ravi Sundaram

# Topics

- What is PCR?
- Why PCR?
- Basics of biochemistry
- An algorithmic puzzle
- Summary

# What is PCR?

- Polymerase Chain Reaction
  - technique to generate millions of copies of a particular DNA sequence from a single piece of DNA
  - Chain Reaction – nuclear 1 to 2 to 4 to 8 to explosion
  - Polymerase enzyme that enables chain reaction
- Kary Mullis won the 1993 Biology Nobel for discovering PCR
- Revolutionary – Before PCR and After PCR
  - Before: DNA cloning – back-breaking, countless lab hours, low yield
  - After: CSI, 23andMe

# Why PCR?

- Timely
  - In the news thanks to Covid
- At its heart it is an algorithm
  - Should have been discovered by a computer scientist
- Polynomial vs Exponential
  - Exemplary demonstration of exponential growth rate

# Basics of biochemistry

- Deoxyribonucleic acid (DNA)
  - a nucleic acid containing genetic instructions used in development/ functioning of most known living organisms.
  - Segments carrying genetic information are called genes.
  - Consists of two long polymers of simple units called nucleotides. These two strands run in opposite directions to each other.
  - Each nucleotide contains one of four types of molecules called bases (or nucleobases or nucleic acids). These four bases are denoted: A (adenine), T (thymine), C (cytosine) and G (guanine).

A→T→T→C→A→G→T

# Basics of biochemistry (continued)

- Within cells DNA is organized into long structures called chromosomes
- Characterized by the now-legendary Watson-Crick double-helix structure comprised of two anti-parallel strands with the weak bonds: A – T and C – G.

A → T → T → C → A → G → T

|   |   |   |   |   |   |

T ← A ← A ← G ← T ← C ← A

# Puzzle: 4 well-known facts

- **Heating**

- when a test tube of double stranded DNA is **heated** (in a controlled fashion) then it breaks up into two constituent and complementary single strands

- **Cooling**

- when single strands of DNA are **cooled** then complementary copies will rejoin

- **Polymerase**

- when a strand of DNA is cooled in a test tube with an abundant supply of bases along with **polymerase** then polymerase will create a complementary strand by moving along the given strand and adding bases one by one.

A→T→T→C→A→G→T  
| |  
C←A

# Puzzle: 4 well-known facts

- Polymerase will only add in the complementary direction to the given strand:

A→T→T→C→A→G→T

|   |   |

T←A←A

- Complementary strands started by polymerase are not stable until they are many bases long. Addition of polymerase will only rarely result in a complementary strand that starts at the beginning and goes all the way to the end.
- **Primers** - short DNA strands (tens of bases) obtainable in quantities through conventional (pre-PCR) techniques.




# Algorithmic Puzzle

- given a small quantity of DNA containing a DNA subsequence of interest, create many copies of the DNA subsequence.

# PCR - Kary Mullis' algorithm

Let the given double strand be



and let the sequence of interest be bracketed between  $o$  and  $\omega$ , i.e.  
 $o \rightarrow \text{.....} \rightarrow \omega$ .

add enough primers  $o$  and  $\omega'$  and then to heat and cool repeatedly

# 2-sided and 1-sided strands

- after the first heating:

.....→o→.....→ω→.....

and

.....←ó←.....←ów←.....

- Now comes the magic of polymerase with the primers, and we get:

.....→o→.....→ω→.....

      |              |

.....←ó←.....←ów

And

      o→.....→ω→.....

      |              |

.....←ó←.....←ów←.....

# Terminal strands appear

After the second heating:

..... $\rightarrow$ o $\rightarrow$ ..... $\rightarrow$  $\omega$  $\rightarrow$ .....

and

..... $\leftarrow$ ó $\leftarrow$ ..... $\leftarrow$ ó

and

o $\rightarrow$ ..... $\rightarrow$  $\omega$  $\rightarrow$ .....

and


..... $\leftarrow$ ó $\leftarrow$ ..... $\leftarrow$ ó $\leftarrow$ .....

# Distribution of strands – 2-sided, 1-sided and terminal

- Let  $D$  denote desired seq or complement, and  $\_$  denote extension

Heating cycle	$\_D\_\_$	$D\_\_$	$D$
1	2	0	0
2	2	2	0
3	2	4	2
4	2	6	8
5	2	8	22
$n$	2	$2(n-1)$	$2^{n-2}n$

# Distribution of strands – exponential vs polynomial(linear) vs constant



# Summary

- Algorithms are central to the functioning of modern-day society
- The time complexity of an algorithm is a worst-case measure, parameterized in terms of input size and expressed in order notation which is asymptotic and ignores constants
- Main Takeaway: Exponential growth dramatically outpaces polynomial growth, hence the emphasis on discovering and using polynomial-time algorithms