
COMS20001 lecture: week #18

Continued from last lecture ...

COMS20001 lecture: week #18

- ... so far so good, but we need to explore
 - 1. how the file system supports our assumed access model, and
 - 2. how the underling **storage device** supports the file system.

Example: optical disks (inc. CDs and DVDs).



noting that

- one might attempt
 - 1. random access, and/or
 - 2. sequential access

and


efficiency of said access is limited by

transfer rate positioning latency

 \propto read/write head performance

seek latency + rotational latency

Example: magnetic disks.



noting that

- one might attempt
 - 1. random access, and/or
 - 2. sequential access

and


efficiency of said access is limited by

transfer rate positioning latency \propto read/write head performance


seek latency + rotational latency

We add structure to the medium via several steps

We add structure to the medium via several steps




We add structure to the medium via several steps




Master Boot Record (MBR)

We add structure to the medium via several steps




then ...


... assume an interface as previously described, e.g.



... assume an interface as previously described, e.g.




... assume an interface as previously described, e.g.



but, since efficiency is crucial we (typically) also

- 1. amortise overhead by fixing transferring *b*-byte blocks,
- 2. use Logical Block Addressing (LBA), forcing translation by the device controller.

... assume an interface as previously described, e.g.



but, since efficiency is crucial we (typically) also


- 1. amortise overhead by fixing transferring *b*-byte blocks,
- 2. use Logical Block Addressing (LBA), forcing translation by the device controller, and
- 3. buffer and/or cache accesses (in various layers).

- Challenge: given a device with
 - fixed number of logical blocks and
 - fixed sized logical blocks,

realise (hierarchical) file system supporting

- representation and
- manipulation

- variable number of files, and
- variable sized files.
- Solution: we need
 - 1. an allocation algorithm, and
 - 2. a data structure to capture the current allocation state.




- Challenge: given a device with
 - fixed number of logical blocks and
 - fixed sized logical blocks,

realise (hierarchical) file system supporting

- representation and
- manipulation

- variable number of files, and
- variable sized files.
- ► Idea: contiguous allocation.
 - allocation is more challenging,
 - + sequential and random access is efficient,
 - internal and external fragmentation,
 - + no storage overhead.




- Challenge: given a device with
 - fixed number of logical blocks and
 - fixed sized logical blocks,

realise (hierarchical) file system supporting

- representation and
- manipulation

- variable number of files, and
- variable sized files.
- ► Idea: linked allocation.
 - + allocation is less challenging,
 - + sequential access is efficient,
 - random access is inefficient,
 - + internal fragmentation only,
 - some storage overhead due to pointers.




- Challenge: given a device with
 - fixed number of logical blocks and
 - fixed sized logical blocks,

realise (hierarchical) file system supporting

- representation and
- manipulation

- variable number of files, and
- variable sized files.
- ► Idea: linked allocation.
 - + allocation is less challenging,
 - + sequential access is efficient,
 - random access is inefficient,
 - + internal fragmentation only,
 - some storage overhead due to pointers.




- Challenge: given a device with
 - fixed number of logical blocks and
 - fixed sized logical blocks,

realise (hierarchical) file system supporting

- representation and
- manipulation

- variable number of files, and
- variable sized files.
- Idea: indexed allocation.
 - + allocation is less challenging,
 - + sequential and random access is efficient,
 - + internal fragmentation only,
 - some storage overhead due to pointers.



- Challenge: given a device with
 - fixed number of logical blocks and
 - fixed sized logical blocks,

realise (hierarchical) file system supporting


- representation and
- manipulation

of


- variable number of files, and
- variable sized files.
- Problem: what if the index block is full?
- Solution(s): use multiple index blocks, e.g., via
 - 1. linked list,

Daniel Page (

- 2. linked tree, or
- 3. various hybrid(s) ...



- ▶ Problem: larger storage capacity means more logical blocks, so
 - 1. larger logical block addresses,
 - 2. decreased access locality, and
 - 3. greater overhead (in time and space) wrt. allocation.
- ► Solution: use a hybrid part contiguous, part non-contiguous approach, e.g.,
 - 1. **cluster** \simeq fixed size, contiguous group of logical blocks:
 - e.g., divide *w*-bit logical block address into two



- each offset now addresses a contiguous group of 2^t logical blocks.
- 2. **extent** \simeq variable size, contiguous group of logical blocks:
 - e.g., divide w-bit logical block address into two

w-	-1 t	t-1 0
logical block group address =	offset	length

- each offset now addresses a contiguous group of logical blocks whose length is given by the t LSBs,
- this is more flexible, but yields complications wrt. seeking and allocation.

although from here on we ignore this option.

- Problem: each write requires one or more of
 - 1. update the allocation state,
 - 2. update the file meta-data, and
 - 3. update the file data

which *must* be **atomic**: if not, the file system can become inconsistent.

- ► Solution:
 - describe update in write-ahead log (or journal),
 - commit update to file system iff. write to log is complete

- Question: what is a directory?
- Answer: a mapping, e.g.,

 $identifier \mapsto (meta-data, data)$

or

 $(identifier, meta\text{-}data) \; \mapsto \; data$

which also hint at

- 1. options for where meta-data should reside, and
- 2. the fact a file might not itself have an identifier!

- Question: what is a directory?
- Answer: a mapping, e.g.,

 $identifier \mapsto (meta-data, data)$

or

 $(identifier, meta-data) \mapsto data$

which also hint at

- 1. options for where meta-data should reside, and
- 2. the fact a file might not itself have an identifier!
- ▶ Problem: *how* should a directory be represented?
- ► Solution:
 - 1. list,
 - 2. tree,
 - 3. hash table,
 - 4. ...

- Question: what is a directory?
- Answer: a mapping, e.g.,

 $identifier \mapsto (meta-data, data)$

or

 $(identifier, meta-data) \mapsto data$

which also hint at

- 1. options for where meta-data should reside, and
- 2. the fact a file might not *itself* have an identifier!
- ▶ Problem: *where* should a directory representation be stored?
- ► Solution:
 - 1. as a file, plus special-purpose rules for access,
 - 2. as a special-purpose structure,
 - 3. ...

i.e., unified or segregated wrt. the rest of the file system.


Implementation: devices → file systems (1) Windows-centric: FAT

► Idea: File Allocation Table (FAT) ≃ fancy linked allocation.

partition =			
volume =	boot block	File Allocation Table (FAT)	block data


- + resolves issue of random access wrt. linked allocation,
- need to retain FAT in memory ... which, for n logical blocks, can be large!

► Idea: File Allocation Table (FAT) ~ fancy linked allocation.



- + resolves issue of random access wrt. linked allocation,
- need to retain FAT in memory ... which, for *n* logical blocks, can be large!

▶ Idea: Unix File System (UFS) [15, Section 4] \simeq fancy indexed allocation.




me system meta-data

- + inodes are of (small) fixed size, so indexing into the inode table is efficient,
- linked representation of free space (for inodes and blocks).

Implementation: devices \rightarrow file systems (2) UNIX-centric: UFS

► Idea: Unix File System (UFS) [15, Section 4] ~ fancy indexed allocation.



- + inodes are of (small) fixed size, so indexing into the inode table is efficient,
- linked representation of free space (for inodes and blocks).

Implementation: devices \rightarrow file systems (3) UNIX-centric: FFS

Idea: Fast File System (FFS) [8] ≃ UFS + larger block size (≥ 4KiB).



- + bit-map representation of free space (for inodes and blocks),
- redundant copy of super-block improves fault tolerance (for overhead of space),
- cylinder groups increase access locality, includes additional features such as soft links.

Implementation: devices → file systems (4)

► Idea: Second Extended File System (ext2) [9] ~ FFS + caching.



me system meta-dai

- + improved directory representation via hash tables [9, Section 4.2],
- + caching and asynchronous writes improve performance ...
- ... but with disadvantages wrt. coherence (viz. robustness).

Conclusions

Take away points:

- This is a broad and complex topic: it involves (at least)
 - 1. a hardware aspect:
 - · an interrupt controller,
 - a block device
 - 2. a low(er)-level software aspect:
 - · an interrupt handler,
 - · a device driver,
 - · a file system driver
 - 3. a high(er)-level software aspect:
 - · some data structures (e.g., mount and file descriptor tables),
 - any relevant POSIX system calls (e.g., write)
- Keep in mind that, even then,
 - we've excluded and/or simplified various (sub-)topics,
 - there are numerous trade-offs involved, meaning it is often hard to identify one ideal solution.



References

- Wikipedia: Disk formatting. https://en.wikipedia.org/wiki/Disk_formatting.
- [2] Wikipedia: Disk partitioning. https://en.wikipedia.org/wiki/Disk_partitioning.
- [3] Wikipedia: File system. https://en.wikipedia.org/wiki/File_system.
- [4] Wikipedia: HTree. https://en.wikipedia.org/wiki/HTree.
- [5] Wikipedia: Magnetic storage. http://en.wikipedia.org/wiki/Magnetic_storage.
- [6] Wikipedia: Master Boot Record (MRB). https://en.wikipedia.org/wiki/Master_boot_record.
- [7] Wikipedia: Optical disk. http://en.wikipedia.org/wiki/Optical_disc.
- [8] M.K. McKusick, W.N. Joy, S.J. Leffler, and R.S. Fabry. A fast file system for UNIX. ACM Transactions on Computer Systems, 2(3):181–197, 1984.

References

- [9] D. Poirier.Second extended file system.http://www.nongnu.org/ext2-doc/.
- [10] V. Prabhakaran, A.C. Arpaci-Dusseau, and R.H. Arpaci-Dusseau. Analysis and evolution of journaling file systems. In USENIX Annual Technical Conference (ATEC), pages 105–120, 2005.
- [11] A. Silberschatz, P.B. Galvin, and G. Gagne. Chapter 11: Implementing file systems. In Operating System Concepts [13].
- [12] A. Silberschatz, P.B. Galvin, and G. Gagne. Chapter 12: Mass storage structure. In Operating System Concepts [13].
- [13] A. Silberschatz, P.B. Galvin, and G. Gagne. Operating System Concepts. Wiley, 9th edition, 2014.
- [14] A.S. Tanenbaum and H. Bos.Chapter 4: File systems.In Modern Operating Systems. Pearson, 4th edition, 2015.



References

[15] K. Thompson.

UNIX implementation.

Bell System Technical Journal, 57(6):1931-1946, 1978.

[16] S.C. Tweedie.

Journaling the Linux ext2fs filesystem.

In LinuxExpo, 1998.