




University of
BRISTOL

Department of
Computer Science

PROGRAMMING and ALGORITHMS II



Brief Recap on

COMPLEXITY BASICS

Dr Tilo Burghardt

Unit Code COMS10001


Eulerian Cycles

(use each edge once to cycle the graph)



University of
BRISTOL

Department of
Computer Science



source: Wolfram Mathworld










Hamiltonian Cycles

(use each node once to cycle the graph)



University of
BRISTOL

Department of
Computer Science



source: Wolfram Mathworld

Computability Classes...


describe sets of problems (or languages) that can be solved (decided/recognised) **at all** by a given machine (e.g. a Turing Machine)...

Complexity Classes...

describe sets of problems (or languages) that can be solved by a given machine (e.g. a Turing Machine) in a **bounded amount** of time, space or other resource...

- Computability Theory aims at working out what can be computed at all
- Not everything can be computed! – some problems/languages cannot be decided by a Turing Machine ... e.g. halting problem (board)

ALL DECISION PROBLEMS



Recap: Chomsky Hierarchy



University of
BRISTOL

Department of
Computer Science

Undecidable

TM

- Type 0: recursively enumerable

$$X \rightarrow Y$$

Decidable

PDA

- Type 1: context-sensitive

$$XAY \rightarrow XZY$$

- Type 2: context-free

$$A \rightarrow X$$


DFA

- Type 3: regular

$$A \rightarrow a ; A \rightarrow aB$$



trivial



A Noam Chomsky

$X, Y, Z \dots$ strings of terminals
and non-terminals

$a, b, c \dots$ terminals

$A, B, C \dots$ non-terminals

problem complexity



Complexity Boundaries (1960s – today)

1960s: Hartmanis and Stearns: Complexity classes
1971: Cook/Levin, Karp: $P=NP?$
1976: Knuth's O , Ω , Θ

Computability Boundaries (1800s – 1960s)

1900: Hilbert's Problems
1936: Turing's *Computable Numbers*
1957: Chomsky's *Syntactic Structures*

$f(n) = O(g(n))$ defines an **upper bound** and means:

There are *positive* constants c and n_0 such that


$$f(n) \leq cg(n) \quad \text{for all } n \geq n_0$$

$f(n) = \Omega(g(n))$ defines a **lower bound** and means:

There are *positive* constants c and n_0 such that

$$f(n) \geq cg(n) \quad \text{for all } n \geq n_0$$

Recap: Big-O and Big- Ω



Intuitively: $f(n) = \Theta(g(n))$ stipulates a set of functions that grow as fast as f that is:


Formally: $f(n) = \Theta(g(n))$ if and only if:

$$f(n) = O(g(n))$$


and

$$f(n) = \Omega(g(n))$$

We then say ' f is of order g '



Given a path through a game, can you check if it is a valid winning path in polynomial time?



Oracles



Example Problem:

Is $x=96$ part of the list $A = (9, 4, 55, 67, \dots, 96, 8)$?

Deterministic Algorithm

```
• for i=1 to n {  
    if (A(i) = x) return true;  
}  
return false;
```

Non-deterministic Algorithm

```
•  $j \leftarrow \text{oracle\_choice}(1:n)$   
  if {A(j) = x} return true  
  else return false;
```

Deterministic Machines...

running on a particular input will always produce the same output ... and the underlying machine model (e.g. a Turing Machine) will always pass through the same pre-determined sequence of states based on the input data and program.

Non-deterministic Machines (with an oracle) ...

can 'guess correctly' at decision points and their output can be verified quickly by checking the produced certificate in polynomial time.

A decision problem is in P ...

if and only if it can be decided by a deterministic polynomial time Turing Machine.

A decision problem is in NP ...

if and only if it can be decided by a non-deterministic polynomial time Turing Machine

A language is in NP ...

if and only if it has a polynomial time verifier. That is, there is a certificate which can check that a string is part of the language in polynomial time.

Problem Complexity Overview



University of
BRISTOL

Department of
Computer Science

