Session 3

Q. 1) Create a SQL table called Restaurants with columns: id (INT, auto-increment), name (VARCHAR), cuisine (VARCHAR), rating (DECIMAL), and city (VARCHAR). Insert 5 sample restaurants into the table, each with a different cuisine and rating.

Ans. create table restaurants

(id int(11) primary key auto_increment, name varchar(100), cuisine varchar(100), rating decimal(2,1), city varchar(100));

insert into restaurants (name, cuisine, rating, city)

values

('Sankalp', 'South indian Cuisine ', 4.5, 'Chennai'),

('Agashiye ', 'Gujarati Cuisine ', 4.7, 'Ahmedabad'),

('Little Italy ', 'Mexican Cuisine ', 4.3, 'Delhi'),

('ITC Narmada', 'Indian Cuisine ', 4.8, 'Mumbai'),

('Hyatt Regency', 'Chinese Cuisine ', 4.6, 'Banglore');

Q. 2) Write a SQL UPDATE statement to change the rating of the restaurant named 'Spice Villa' to 4.7 in the Restaurants table.

Ans. insert into restaurants (name, cuisine, rating, city)

values

('Spice villa', 'North Indian Cuisine', 4.1, 'Surat');

update restaurants set rating = 4.7 where id =6;

Q. 3) Delete all restaurants from the Restaurants table where the rating is less than 3.5 using a SQL DELETE statement.

Ans. update restaurants set rating = 3.1 where id =4;

update restaurants set rating = 3.4 where id =5;

delete from restaurants where rating < 3.5;

Q. 4) Use a SELECT query with WHERE and LIMIT to fetch the top 2 restaurants in the city 'Ahmedabad' with a rating above 4.0 from the Restaurants table. Combine WHERE for city and rating, and LIMIT to restrict the number of results.

Ans. select * from restaurants where city = 'Ahmedabad' and rating > 4.0 limit 2;



