



# ECE 5984

# Dynamic Programming

Jason J. Xuan, Ph.D.

Department of Electrical & Computer Engineering  
Virginia Tech

# Outline

- 1 Introduction
- 2 Policy Evaluation
- 3 Policy Iteration
- 4 Value Iteration



# Dynamic Programming?

**Dynamic** sequential or temporal component to the problem  
**Programming** optimising a “program”, i.e. a policy

- c.f. linear programming
- A method for solving complex problems
- By breaking them down into subproblems
  - Solve the subproblems
  - Combine solutions to subproblems



# Planning by Dynamic Programming


- Dynamic programming assumes full knowledge of the MDP
- It is used for *planning* in an MDP
- For prediction:
  - Input: MDP  $\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma \rangle$  and policy  $\pi$
  - or: MRP  $\langle \mathcal{S}, \mathcal{P}^\pi, \mathcal{R}^\pi, \gamma \rangle$
  - Output: value function  $v_\pi$
- Or for control:
  - Input: MDP  $\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma \rangle$
  - Output: optimal value function  $v_*$
  - and: optimal policy  $\pi_*$



# Iterative Policy Evaluation

- Problem: evaluate a given policy  $\pi$
- Solution: iterative application of Bellman expectation backup
- $v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_\pi$
- Using *synchronous* backups,
  - At each iteration  $k + 1$
  - For all states  $s \in \mathcal{S}$
  - Update  $v_{k+1}(s)$  from  $v_k(s')$
  - where  $s'$  is a successor state of  $s$

# Iterative Policy Evaluation (cont'd)




$$v_{k+1}(s) = \sum_{a \in \mathcal{A}} \pi(a|s) \left( \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_k(s') \right)$$
$$\mathbf{v}^{k+1} = \mathcal{R}^\pi + \gamma \mathcal{P}^\pi \mathbf{v}^k$$



# Example: Small Grid

## Evaluating a Random Policy in the Small Gridworld



	1	2	3
4	5	6	7
8	9	10	11
12	13	14	

$r = -1$   
on all transitions

- Undiscounted episodic MDP ( $\gamma = 1$ )
- Nonterminal states 1, ..., 14
- One terminal state (shown twice as shaded squares)
- Actions leading out of the grid leave state unchanged
- Reward is  $-1$  until the terminal state is reached
- Agent follows uniform random policy

$$\pi(n|\cdot) = \pi(e|\cdot) = \pi(s|\cdot) = \pi(w|\cdot) = 0.25$$

# Example: Iterative Value Evaluation

$v_k$  for the  
Random Policy

Greedy Policy  
w.r.t.  $v_k$

$k = 0$

0.0	0.0	0.0	0.0
0.0	0.0	0.0	0.0
0.0	0.0	0.0	0.0
0.0	0.0	0.0	0.0

	↕	↕	↕
↕	↕	↕	↕
↕	↕	↕	↕
↕	↕	↕	

← random  
policy

$k = 1$

0.0	-1.0	-1.0	-1.0
-1.0	-1.0	-1.0	-1.0
-1.0	-1.0	-1.0	-1.0
-1.0	-1.0	-1.0	0.0

	←	↕	↕
↑	↕	↕	↕
↕	↕	↕	↓
↕	↕	→	

$k = 2$

0.0	-1.7	-2.0	-2.0
-1.7	-2.0	-2.0	-2.0
-2.0	-2.0	-2.0	-1.7
-2.0	-2.0	-1.7	0.0

	←	←	↕
↑	↖	↕	↓
↑	↕	↘	↓
↕	→	→	



# Example: Iterative Value Evaluation (cont'd)

$k = 3$

0.0	-2.4	-2.9	-3.0
-2.4	-2.9	-3.0	-2.9
-2.9	-3.0	-2.9	-2.4
-3.0	-2.9	-2.4	0.0

	←	←	↖
↑	↖	↖	↓
↑	↗	↘	↓
↖	→	→	

$k = 10$

0.0	-6.1	-8.4	-9.0
-6.1	-7.7	-8.4	-8.4
-8.4	-8.4	-7.7	-6.1
-9.0	-8.4	-6.1	0.0

	←	←	↖
↑	↖	↖	↓
↑	↗	↘	↓
↖	→	→	

$k = \infty$

0.0	-14.	-20.	-22.
-14.	-18.	-20.	-20.
-20.	-20.	-18.	-14.
-22.	-20.	-14.	0.0

	←	←	↖
↑	↖	↖	↓
↑	↗	↘	↓
↖	→	→	

optimal  
policy



# How to Improve a Policy

- Given a policy  $\pi$ 
  - **Evaluate** the policy  $\pi$


$$v_{\pi}(s) = \mathbb{E} [R_{t+1} + \gamma R_{t+2} + \dots | S_t = s]$$

- **Improve** the policy by acting greedily with respect to  $v_{\pi}$

$$\pi' = \text{greedy}(v_{\pi})$$

- In Small Gridworld improved policy was optimal,  $\pi' = \pi^*$
- In general, need more iterations of improvement / evaluation
- But this process of **policy iteration** always converges to  $\pi^*$

# Policy Improvement



# Policy Improvement (cont'd)


0.0	-14.	-20.	-22.
-14.	-18.	-20.	-20.
-20.	-20.	-18.	-14.
-22.	-20.	-14.	0.0

policy improvement



	←	←	↖
↑	↖	↙	↓
↑	↖	↘	↓
↙	→	→	

# Policy Iteration

$$\pi_0 \xrightarrow{E} v_{\pi_0} \xrightarrow{I} \pi_1 \xrightarrow{E} v_{\pi_1} \xrightarrow{I} \pi_2 \rightarrow \dots \rightarrow \pi_* \xrightarrow{E} v_*$$



# Policy Iteration



**Policy evaluation** Estimate  $v_\pi$   
Iterative policy evaluation

**Policy improvement** Generate  $\pi' \geq \pi$   
Greedy policy improvement




# Example: Car Rental



- States: Two locations, maximum of 20 cars at each
- Actions: Move up to 5 cars between locations overnight
- Reward: \$10 for each car rented (must be available)
- Transitions: Cars returned and requested randomly
  - Poisson distribution,  $n$  returns/requests with prob  $\frac{\lambda^n}{n!} e^{-\lambda}$
  - 1st location: average requests = 3, average returns = 3
  - 2nd location: average requests = 4, average returns = 2

# Example: Car Rental

Policy Iteration ( $\gamma=0.9$ )





# Policy Improvement

- Consider a deterministic policy,  $a = \pi(s)$
- We can *improve* the policy by acting greedily

$$\pi'(s) = \operatorname{argmax}_{a \in \mathcal{A}} q_{\pi}(s, a)$$

- This improves the value from any state  $s$  over one step,

$$q_{\pi}(s, \pi'(s)) = \max_{a \in \mathcal{A}} q_{\pi}(s, a) \geq q_{\pi}(s, \pi(s)) = v_{\pi}(s)$$

- It therefore improves the value function,  $v_{\pi'}(s) \geq v_{\pi}(s)$

$$\begin{aligned} v_{\pi}(s) &\leq q_{\pi}(s, \pi'(s)) = \mathbb{E}_{\pi'} [R_{t+1} + \gamma v_{\pi}(S_{t+1}) \mid S_t = s] \\ &\leq \mathbb{E}_{\pi'} [R_{t+1} + \gamma q_{\pi}(S_{t+1}, \pi'(S_{t+1})) \mid S_t = s] \\ &\leq \mathbb{E}_{\pi'} [R_{t+1} + \gamma R_{t+2} + \gamma^2 q_{\pi}(S_{t+2}, \pi'(S_{t+2})) \mid S_t = s] \\ &\leq \mathbb{E}_{\pi'} [R_{t+1} + \gamma R_{t+2} + \dots \mid S_t = s] = v_{\pi'}(s) \end{aligned}$$

# Policy Improvement (cont'd)

- If improvements stop,

$$q_{\pi}(s, \pi'(s)) = \max_{a \in \mathcal{A}} q_{\pi}(s, a) = q_{\pi}(s, \pi(s)) = v_{\pi}(s)$$

- Then the Bellman optimality equation has been satisfied

$$v_{\pi}(s) = \max_{a \in \mathcal{A}} q_{\pi}(s, a)$$

- Therefore  $v_{\pi}(s) = v_{*}(s)$  for all  $s \in \mathcal{S}$
- so  $\pi$  is an optimal policy









# Modified Policy Iteration

- Does policy evaluation need to converge to  $v_\pi$ ?
- Or should we introduce a stopping condition
  - e.g.  $\epsilon$ -convergence of value function
- Or simply stop after  $k$  iterations of iterative policy evaluation?
- For example, in the small gridworld  $k = 3$  was sufficient to achieve optimal policy
- Why not update policy every iteration?
  - This is equivalent to *value iteration* (next section)

# Generalized Policy Iteration



Policy evaluation Estimate  $v_\pi$

Any policy evaluation algorithm

Policy improvement Generate  $\pi' \geq \pi$

Any policy improvement algorithm






# Value Iteration

- Problem: find optimal policy  $\pi$
- Solution: iterative application of Bellman optimality backup
- $v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_*$
- Using synchronous backups
  - At each iteration  $k + 1$
  - For all states  $s \in \mathcal{S}$
  - Update  $v_{k+1}(s)$  from  $v_k(s')$
- Convergence to  $v_*$
- Unlike policy iteration, there is no explicit policy
- Intermediate value functions may not correspond to any policy

# Value Iteration (cont'd)



$$v_{k+1}(s) = \max_{a \in \mathcal{A}} \left( \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_k(s') \right)$$

$$\mathbf{v}_{k+1} = \max_{a \in \mathcal{A}} \mathbf{R}^a + \gamma \mathbf{P}^a \mathbf{v}_k$$

# Complexity of Dynamic Programming Algorithms

Problem	Bellman Equation	Algorithm
Prediction	Bellman Expectation Equation	Iterative Policy Evaluation
Control	Bellman Expectation Equation + Greedy Policy Improvement	Policy Iteration
Control	Bellman Optimality Equation	Value Iteration

- Algorithms are based on state-value function  $v_{\pi}(s)$  or  $v_{*}(s)$
- Complexity  $O(mn^2)$  per iteration, for  $m$  actions and  $n$  states
- Could also apply to action-value function  $q_{\pi}(s, a)$  or  $q_{*}(s, a)$
- Complexity  $O(m^2n^2)$  per iteration

# Question

- Comments are more than welcome!

