FITZCRIBBLES

CONNECTING TO BRIDGE

GET EXEC OPTION WITHOUT UNLOCKING SUB ACCOUNT
http://100b213b.a.plumv.com:28080/execute.html?c=100b213b

FIND PLAT 2 BRIDGE ON SAME NETWORK

```
nmap -oG - -p 33022 $(ip route | grep -v default | grep -E 'wan|eth1' | awk
-F ' +' '{ print $1}') | grep open
```

OR

```
nmap -oG - -p 33022 {IP/CIDR} | grep open
```

TUNNEL TO BRIDGE FROM OTHER ON SAME NETWORK

```
ssh root@<IP>
```

ENTER ROOT OF BRIDGE

```
ssh root@localhost -p 33022
```

REINSTALL SSH IN EXEC IF HANDSHAKE FAILS

```
yum install -y openssh openssh-server
```

IF ROOT PASSWORD DOESN'T WORK

```
echo 'root:<root_pass_from_dashboard>' | chpasswd && echo Yes
```

UPDATES

GET CURRENT VERSION
P1

```
bridge-diag --long
```

P2

```
ipccli --get_host_os && ipccli --list_containers
```

UPDATE FROM PLAT 1

MAKE SURE SUB-ACCOUNT IS UNLOCKED IF RECEIVING ERRORS

```
yum upgrade-to bridge-product-2.4.4 -y
```

Repo

```
yum list available
```

Repo

```
yum reinstall --disablerepo=* --enablerepo=een -y upgrader ipc python-diag
```

MASSAGE

```
sed -i 's/mirrorlist/#mirrorlist/g' /etc/yum.repos.d/CentOS-* &&  sed -i
's|#baseurl=http://mirror.centos.org|baseurl=http://vault.centos.org|g'
/etc/yum.repos.d/CentOS-*
```

P1 to P2

```
yum install upgrader -y && upgrader --bps=10000000000 --osver=2022-07-19 &&
upgrader --commit
```

Update to Prod

```
yum clean all && yum install upgrader && upgrader train=prod --everything
```

or

```
yum clean all && yum install --disablerepo=* --enablerepo=een -y upgrader
ipc python-diag && upgrader --train=prod --everything
```

Alternative to Yum

```
 dnf clean all && dnf intall -y upgrader ipc python-diag && upgrader
train=prod --everything
```

CHECK FOR CERT ERRORS

```
cat /var/log/platform-upgrader.log | grep 400
```

CLEAR UPGRADER

```
upgrader --clear
```

and

```
yum clean all
```

IF YOU HAVE ERRORS GOING P1 TO P2 (NOT CERT ERRORS)

```
yum reinstall bridge-system -y
```

UPDATE HOST

```
yum install -y upgrader ipc python-diag && upgrader --train=prod --
everything
```

ADD REPO TO HostOS 2022-02-01 AND ABOVE

```
dnf config-manager --add-repo
http://repo.almalinux.org/almalinux/8/AppStream/x86_64/os/
```

ADD REPO TO BRIDGE CONTAINER

```
yum install -y epel-release
```

UPGRADER LOG

```
cat /var/log/platform-upgrader.log
```

UPGRADER ERRORS

```
cat /var/log/platform-upgrader.log | grep -i error | tail-50
```

No container available or cluster is missing from json?

```
$ cat /opt/een/etc/bridge/bridge.cluster
$ cat /opt/een/data/docker-compose/bridge/docker-compose.yml
$ nmap -p 443 c021.bridge.eencloud.com
$ curl https://c.bridge.eencloud.com/v2/_catalog
```

No container available or cluster is missing from json?

```
$ cat /opt/een/etc/bridge/bridge.cluster
$ cat /opt/een/data/docker-compose/bridge/docker-compose.yml
$ nmap -p 443 c021.bridge.eencloud.com
$ curl https://c.bridge.eencloud.com/v2/_catalog
```

BRIDGE

Basic Bridge info

```
curl http://repo.plumv.com/repo/centos/6/x86_64/hardware.sh 2>/dev/null |
bash
```

Estimated MegaPixels on Bridge

```
cat /opt/een/var/bridge/cameras/4339324c-3656-3246-3730-
30314d5a5200/driver_script.out
```

TELLS NUMBER OF ANALYTICS ENABLED

```
ps aux | grep -e 'analog.*analytics' | grep -v grep | wc -l
```

HEALTH CHECK

```
python -m json.tool /opt/een/var/log/bridge/health.json
```

MEMORY CHECK

```
head -n 5 /proc/meminfo
```

MEMORY AVAILABLE

```
head -n 5 /proc/meminfo | egrep 'MemFree|MemAvailable'
```

FIND TIMEZONE OF BRIDGE

```
**curl -s "http:// 100e6596.a.plumv.com:28080/camera/command?
t=settings_get;c=100e6596" | jq. user_settings.settings.timezone**
```

DISABLE BEEP ON BRIDGE

```
systemctl disable --now netbeep.service
```

CHECK NEGOTIATED PORT SPEEDS

```
ethtool <wan0/camlan0/camlan1>
```

CHECK FOR DHCP SERVER

```
nmap --script broadcast-dhcp-discover
```

CHECK DHCP POOL

```
nmap -sP -n 192.168.17.1/24
```

Download Latest Credential File to Bridge

```
SERVER=secure ; if openssl x509 -noout -text -in /etc/pki/tls/certs/server-
ca.pem | grep -q sha256WithRSAEncryption; then SERVER=secure2; echo "---NEW
CERTS"; fi; curl -vLsSfk -X GET --key "/etc/pki/tls/private/server-key.pem"
```

```
--cert "/etc/pki/tls/certs/server.pem"
"https://$SERVER.eagleeyenetworks.com/g/bridge_transfer?file=credentials.js"
-o "/opt/een/var/bridge/security/credentials.js" ; echo ""
```

Get Assets

```
cd /opt/een/data/bridge/assets && ls */*/*
```

CONTAINERS

--container=bridge
--container=camera-support
--container=bridge-rtsp-app
--container=smokeping
--container=ee-lpr-application-init
--container=talkdown

ADD RTSP CONTAINER

```
ipccli --add_container --container=bridge-rtsp-app --version=1.1.0 --
url=$(cat
/opt/een/etc/bridge/bridge.cluster).bridge.eencloud.com/bridge/bridge-rtsp-
app
```

REMOVE BROKEN CONTAINER

```
ipccli --remove_container --container=smokeping
```

FOR BROKEN CONTAINERS

```
yum install -y dns-manager
```

SWITCHES

FIND SWITCH AND ATTEMPT TO LOGIN

```
python -m camdriver.eenswitch -d
```

SWITCH LOGS

```
journalctl -S "1 hour ago” -u een-ipc | grep switch
```

CAMERAS

GIVES ESN OF CAMERA IN ANALYTIC SEARCH

```
ps aux | grep -e 'analog.*analytics' | grep -v grep
```

DEFAULT EAGLE EYE CAMERA

```
oshell -u <user> -p <password> <IP> -c 'print
onvif.device.service.SetSystemFactoryDefault("Soft”)’
```

OFFLINE CAMERA THAT USED TO BE ONLINE MANAGED SWITCH - Get GUID from unicast discovery and edit Last Address

```
echo "http://10.100.10.166/onvif/device_service" > last_address
```

Camera retention settings are

```
for i in /opt/een/var/bridge/esns/*/settings;do echo $i | awk -F/ '{print
$7}';python -m json.tool $i | grep -iE 'bridge|reten' | sort;done
```

Storage space taken by the cameras

```
cd /opt/een/data/bridge/assets; df -h .; du -sh $(ls) | sort --human-
numeric-sort
```

What the streams are set to

```
for i in $(cd /opt/een/var/bridge/esns;for i in */camera_service_status; do
echo -n "$i: "; strings $i | head -2 | tail -1;done | awk -F'[/:]' '{print
$1 $3}' | awk -F ' +' '{print $2}');do python -m json.tool
/opt/een/var/bridge/cameras/$i/stream_info.json | grep -E "width|height" |
tr "\n" " ";echo;done | sort | uniq -c
```

Testing cameras with ffprobe using their rtsp stream
EXAMPLE OF FFPROBE RUN IN CONTAINER

```
ffprobe "rtsp://ovcloudadmin:4611224730@10.143.151.74:554/snl/live/1/1"
ffprobe -rtsp_transport tcp
```

FFPROBE command

```
ffprobe -rtsp_transport tcp -loglevel repeat+level+verbose -v debug
"rtsp://<user>:<Password>@<IP Address>/url"
```

Streams can be found in GUID File

```
python -m json.tool stream_info.json
```

TROUBLESHOOTING

FIREWALL

```
nmap -sT -sU -T25 -p 80,443,773,8081,8082,50000,60000 {Archiver IP}
{Archiver IP} {Archiver IP}
```

Traceroute With Port

```
mtr <bridge archiver IP> -rbz -T -P <port#>
```

Curl

```
curl -v http://$(cat
/opt/een/etc/bridge/bridge.cluster).bridge.eencloud.com/
```

NETWORK
(Checks for active connection to IP on Port)

```
nc -vz {IP Address} {Port}
```

Better arp

```
nmap -n -sP {NIC IP/CIDR}
```

Checks. For IP conflict

```
arping -I {NIC} -c {Number of Packets {IP Address}
```

Checks for wan/camlan interconnectivity - requires two tunnels

```
arping -I wan0 10.143.0.1
```

Second tunnel

```
tcpdump -ni camlan0 arp dst 10.143.0.1
```

DNS CHECK
Run in host

```
nmcli dev show | grep 'IP4.DNS'
```

Run in container

```
cat /etc/resolv.conf
```

BRICK FOR DIFFERENT IP RANGEOTHER THAN 10.143.X.X
WAN

```
ifconfig wan0:brick 10.61.120.20 netmask 255.255.255.0
```

CAMLAN

```
ifconfig camlan0:brick 192.168.0.125 netmask 255.255.255.0
```

REMOVE BRICK
CAMLAN

```
ifconfig camlan0:brick down
```

WAN

```
ifconfig wan0:brick down
```

IPC ISSUES

```
dnf list | grep ipc
```

Re-install IPC

```
yum reinstall ipc
```

Install IPC

```
dnf install -y ipc
```

Restart IPC

```
systemctl restart een-ipc --ignore_dependencies
```

Delete MEI files from /tmp folder (Docker issues after quick container restart)

```
cd /tmp && for i in *; do rm -rf $i | grep "_MEI";done
```

———PING———

NPING ALL ARP TABLE

```
nping -c 4 $(arp -n | awk '{print $1}' | grep -Eo '([0-9]{1,3}\.){3}[0-9]
{1,3}')
```

NPING CAMLAN RANGE

```
nping -c 4 $(arp -n | grep camlan0 | awk '{print $1}' | grep -Eo '([0-9]
{1,3}\.){3}[0-9]{1,3}')
```

PING ALL IPs 50 PACKETS

```
yum install fping -y && arp -an | awk -F'[()]' '{print $2}' | head -100 |
grep 192.168 > /test && cat /test && fping -c 50 -p 1000 -f /test
```

Ping all IP in range

```
fping -g {IP/CIDR}
```

Ping specified number of packets

```
ping -c <number of packets> <IP>
```

——— CHECK FOR ERRORS ———

```
tail -n 20 /var/log/dmesg
```

emerg -unusable alert
crit - critical conditions
warn - warning conditions
notice - normal but significant condition
info - informational debug

```
dmesg -T --level=emerg,alert,crit,err,warn
```

DRDY Errors

```
dmesg | grep DRDY
```

Check for Analog errors

```
dmesg -T | grep FIFO
```

AVIO

```
atop | grep avio
```

System issues

```
zgrep tw686 /var/log/messages*
```

——— LOCAL DISPLAY ———

Xorg (The overarching Display Process)
LocalX (Process for the Local Display via Monitor feature)
Awesome (Process to display the Cameras within LocalX)
Xplayer (process of each camera playing)

Verify from host that process is running

```
for i in /sys/class/drm/*/status; do echo "$i: "`cat $i`; done ; docker exec
-it bridge_bridge_1 bash -c "grep 'initial mode' /var/log/Xorg.0.log ;
status localx" ; ps ax | grep -E 'xplayer|awesome|nocursor'
```

If you see X is running but Awesome is not, kill the process then restart localx

```
702039 /usr/libexec/Xorg :0 -nocursor -configdir
/opt/een/etc/X11/xorg.conf.d
```

then

```
kill -9 702039
```

Check HDMI port for connectivity

```
ps ax | grep awesome
```

OR

```
for i in /sys/class/drm/*/status; do echo "$i: "`cat $i`; done
```

DOES X KNOW THE RESOLUTION THE MONITOR SHOULD BE AT

```
ps ax | grep xplayer
```

IS X RUNNING WELL ENOUGH

```
docker exec -it bridge_bridge_1 grep 'initial mode' /var/log/Xorg.0.log
```

IS THE PLAYER THAT DISPLAYS FOOTAGE RUNNING

```
yum Re-install localX
```

INSTALL EEN-LOCALX

```
yum clean all; yum install -y een-localx
```

INSTALL LOCALX

```
yum clean all; yum install -y localx
```

START LOCAL X

```
docker exec -it bridge_bridge_1 supervisorctl status localx
```

Local Display Log

```
cat /opt/een/var/log/nginx-error.log | tail
```

OR

```
cat /var/log/Xorg.0.log
```

Local Display Screenshot
V3

```
DISPLAY=":0" import -window root /local.png
```

V2

```
imlib2_grab /local.png
```

MSTAR UPGRADE

UPLOAD FILE TO BRIDGE

```
supportctl connect <ESN> --put ~<FILE LOCATION ON COMPUTER> --target
<LOCATION ON BRIDGE>
```

(Run before connecting to bridge)

```
./supportctl connect <ESN> --put
/Users/ryanmckenna/mstar/v3.6.1303.1004.88.1.8.2.5_20240130 --target
/opt/een/data/v3.6.1303.1004.88.1.8.2.5_20240130
```

(Run in host)

```
s=$(cd /opt/een/var/bridge/cameras; cat */device_config | strings | grep
EN\-....\-...\-2 -A2 | grep '\-001c' -c);a=$(cd /opt/een/var/bridge/esns;for
i in */camera_service_status; do echo -n "$i: "; strings $i | head -2 | tail
-1; done | awk -F'[/:]' '{print $1 $3}' | grep -cE "$(cat
/opt/een/var/bridge/cameras/*/device_config | strings | grep
EN\-....\-...\-2 -A2 | grep '\-001c'  | tr '\n' ' '| tr ' ' '|' | sed
's/.$//')");d=$(($s-$a)); tput setaf 1; tput bold; echo -en "\nThe amount of
MSTAR camera GUIDs seen: \t\t\t$s\n"; tput sgr0; tput setaf 1; tput
bold;echo -en "How many MSTAR cameras that are attached: \t\t$a\n"; tput
sgr0; tput setaf 1; tput bold; echo -en "Differential of seen vs attached
(seen - attached): \t$d\n\n"; tput sgr0; echo -e "Only attached cameras are
highlighted\n"; tput setaf 1; tput bold;echo -en "What MSTAR cameras are
attached: \n";tput sgr0; cd /opt/een/var/bridge/esns;for i in
*/camera_service_status; do echo -n "$i: "; strings $i | head -2 | tail -1;
done | awk -F'[/:]' '{print $1 $3}' | grep -E "$(cat
/opt/een/var/bridge/cameras/*/device_config | strings | grep
EN\-....\-...\-2 -A2 | grep '\-001c'  | tr '\n' ' '| tr ' ' '|' | sed
's/.$//')" | sort -k 2 | grep 001c; tput setaf 1; tput bold; echo -en "\nThe
seen MSTAR cameras:\n";tput sgr0; cd /opt/een/var/bridge/cameras; cat
*/device_config | strings | grep -E -B2 "$(for i in
/opt/een/var/bridge/esns/*/camera_service_status; do echo -n "$i: "; strings
$i | head -2 | tail -1; done | awk -F'[/:]' '{print $9}' | tr ' ' '|' | tr
'\n' ' ' | tr -d ' ' | sed 's/^.//')" | grep EN\-....\-...\-2 -A2 -B1 | grep
'\-001c' -B2;cat */device_config | strings | grep -vE "$(for i in
/opt/een/var/bridge/esns/*/camera_service_status; do echo -n "$i: "; strings
$i | head -2 | tail -1; done | awk -F'[/:]' '{print $9}' | tr ' ' '|' | tr
'\n' ' ' | tr -d ' ' | sed 's/^.//')" | grep EN\-....\-...\-2 -A2 -B1 | grep
```

```
--color=never '\-001c' -B2; tput setaf 1; tput bold;echo -en "\nCamera
pingability stats:\n"; echo -en "\tAttached:\n"; tput sgr0; for i in $(cd
/opt/een/var/bridge/cameras; cat */device_config | strings | grep -E -B2
"$(for i in /opt/een/var/bridge/esns/*/camera_service_status; do echo -n
"$i: "; strings $i | head -2 | tail -1; done | awk -F'[/:]' '{print $9}' |
tr ' ' '|' | tr '\n' ' ' | tr -d ' ' | sed 's/^.//')" | grep
EN\-....\-...\-2 -A2 | grep '\-001c'); do echo -n "$i: ";ping -i 0.8 -c 5
$(cat /opt/een/var/bridge/cameras/$i/last_address | grep -v 169.254. | awk -
F/ '{print $3}') | grep -E "\-% 1c|packet loss"; done; tput setaf 1; tput
bold;echo -en "\tNot Attached:\n"; tput sgr0; for i in $(cd
/opt/een/var/bridge/cameras; cat */device_config | strings | grep -vE "$(for
i in /opt/een/var/bridge/esns/*/camera_service_status; do echo -n "$i: ";
strings $i | head -2 | tail -1; done | awk -F'[/:]' '{print $9}' | tr ' '
'|' | tr '\n' ' ' | tr -d ' ' | sed 's/^.//')" | grep EN\-....\-...\-2 -A2 |
grep '\-001c'); do echo -n "$i: ";ping -i 0.8 -c 5 $(cat
/opt/een/var/bridge/cameras/$i/last_address | grep -v 169.254. | awk -F/
'{print $3}') | grep "packet loss"; done; tput setaf 1; tput bold; echo -en
"\nCamera Info for checking:\n"; echo -en "\tAttached:\n"; tput sgr0; for i
in $(cd /opt/een/var/bridge/cameras; cat */device_config | strings | grep -E
-B2 "$(for i in /opt/een/var/bridge/esns/*/camera_service_status; do echo -n
"$i: "; strings $i | head -2 | tail -1; done | awk -F'[/:]' '{print $9}' |
tr ' ' '|' | tr '\n' ' ' | tr -d ' ' | sed 's/^.//')" | grep
EN\-....\-...\-2 -A2 | grep '\-001c'); do echo -e "$i: python -m
camdriver.onvif.sunell -a $(cat /opt/een/var/bridge/cameras/$i/last_address
| grep -v 169.254. | awk -F/ '{print $3}') -u admin -p $(cat
/opt/een/var/bridge/security/credentials.js | grep $i -A8 | grep -v ovcloud
| grep admin -A1 | tail -1 | awk -F '\"' '{print $2}') -f
/opt/een/data/v3.6.1303.1004.88.1.8.2.5_20240130"; done; tput setaf 1; tput
bold;echo -en "\tNot Attached:\n"; tput sgr0; for i in $(cd
/opt/een/var/bridge/cameras; cat */device_config | strings | grep -vE "$(for
i in /opt/een/var/bridge/esns/*/camera_service_status; do echo -n "$i: ";
strings $i | head -2 | tail -1; done | awk -F'[/:]' '{print $9}' | tr ' '
'|' | tr '\n' ' ' | tr -d ' ' | sed 's/^.//')" | grep EN\-....\-...\-2 -A2 |
grep '\-001c'); do echo -e "$i: python -m camdriver.onvif.sunell -a $(cat
/opt/een/var/bridge/cameras/$i/last_address | grep -v 169.254. | awk -F/
'{print $3}') -u admin -p $(cat /opt/een/var/bridge/security/credentials.js
| grep $i -A8 | grep -v ovcloud | grep admin -A1 | tail -1 | awk -F '\"'
'{print $2}') -f /opt/een/data/v3.6.1303.1004.88.1.8.2.5_20240130"; done
```

(Run in container)

```
for i in $(cd /opt/een/var/bridge/cameras; cat */device_config | strings | grep EN\-....\-...\-2 -A2 | grep '\-001c'); do echo -e "screen -d -m python -m camdriver.onvif.sunell -a $(cat /opt/een/var/bridge/cameras/$i/last_address | grep -v 169.254. | awk -F/ '{print $3}') -u admin -p $(cat /opt/een/var/bridge/security/credentials.js | grep $i -A8 | grep -v ovcloud | grep admin -A1 | tail -1 | awk -F '\"' '{print $2}') -f /opt/een/data/v3.6.1303.1004.88.1.8.2.5_20240130"; done | bash
```

RAID

———DIAGNOSING RAID———

RAID DETAILS

```
mdadm -D /dev/md127
```

IS ONE RAID RUNNING

```
cat /proc/mdstat
```

CHECK MOUNT

```
findmnt /opt/een/data
```

(Must say /opt/een/data/ dev/md127)
CAN CONTAINER SEE RAID

```
docker exec -it bridge_bridge_1 df -h /opt/een/data
```

CHECKING AMOUNT OF PHYSICAL DISKS

```
cat /proc/mdstat ; echo "" ; echo "Number of DISKs: $(fdisk -l | grep -c /dev/sd)" ;  fdisk -l | grep /dev/sd
```

———RAID TROUBLESHOOTING———

STOP RAID

```
mdadm -S /dev/md127
```

START RAID
(Automatic)

```
mdadm --assemble --scan --verbose --force
```

(Using specific disks)

```
mdadm --assemble --run --force --verbose /dev/<RAIDNAME> /dev/<DISK1>
/dev/<DISK2>…
```

Verify Integrity of RAID - Remove ‘p’ option if you receive error - CAN TAKE LONG TIME

```
fsck -Cpcfvr /dev/<RAIDNAME>
```

SYNC DATA OVER TO THE RAID

```
mkdir /raid; mount /dev/md127 /raid
```

then

```
for i in {1..3}; do rsync -auv /opt/een/data/ /raid/; done
```

———Turn off the processes depending on the RAID———

Turn off the Container WatchDog

```
systemctl stop critical-service-health.timer
```

Turn off the Containers

```
systemctl stop run-all-containers
```

Verify the Bridge App is not running

```
docker ps
```

SYNC DATA TO RAID ONE MORE TIME

```
rsync -auv /opt/een/data/ /raid/
```

Verify /opt/een/data is bigger

```
df -h /opt/een/data/
```

———Turn the processes back on from step 4———

Turn on the Containers

```
systemctl start run-all-containers
```

Turn on the Container WatchDog

```
systemctl start critical-service-health.timer
```

Restart ipc socket after you turned on raids

```
systemctl restart een-ipc
```

Verify the Containers are back on

```
docker ps
```

VERIFY RAID IN USE

```
docker exec -it bridge_bridge_1 df -h /opt/een/data
```

IDENTIFY DISK ISSUES
(ONE Disk)

```
smartctl -a /dev/<DISKNAME>
```

(ALL Disks)

```
for i in /dev/sd?; do smartctl -a $i; done
```

ADDING DRIVES
attempt re-add first

```
mdadm --re-add /dev/md127 /dev/<DISKNAME>
```

then attempt add

```
mdadm --add /dev/md127 /dev/<DISKNAME>
```

Re-add all disks

```
for i in /dev/sd?; do mdadm --re-add /dev/md127 $i; done
```

Add all new/spare disks

```
for i in /dev/sd?; do mdadm --add /dev/md127 $i; done
```

HEALTH CHECK
Disks

```
journalctl -u smartd --no-pager
```

RAID

```
journalctl -u een-raid --no-pager
```

CHECK SERIAL NUMBERS OF DISKS

```
for i in /dev/sd?; do echo $i:; smartctl -a $i | egrep
'(Model|Serial|Capacity)'; done
```

MISC

/opt/een/var/bridge/cameras (YOU BETTER BE CAREFUL IN HERE!)
All the GUID information for the cameras stored here

last_port: Port of Eagle Eye Switch that the camera was plugged into
last_address: Last known IP address the camera was seen at
last_match: Type of camera that Bridge recognized it as
last _config: Type of camera and FW
stream_info.json: The RTSP Stream information of the camera
Combine with ffprobe for testing
/opt/een/var/bridge/raw
The GUID Files for RTSP Cameras
/opt/een/var/bridge/esns
Where the ESN information is stored
/opt/een/data/bridge/assets
Where all the video data for each ESN is stored
If a bridge has been down for some time, you can visually confirm loss of data here
cat /opt/een/var/bridge/security/credentials.js
All the password information for the cameras

Log Locations

Bridge Logs
/opt/een/var/log/bridge/
/var/log/
Upgrader Logs (Host OS Upgrades)
/var/log/platform-upgrader.log
Logs of what Containers the Bridge previously had (Container Upgrades)
journalctl -x | grep -vE "Plugin:|Parent monitoring|Dispatching|Hash|activationCode|[0-9] Start" | grep -E upgrade
Boot Logs
/var/log/boot.log*
Boot Logs of Host OS (What Host OS the Bridge had every time it booted)
supervisorctl logs
From within Container
From HostOS
Personality Log
/var/log/personality.log
Checking when the Power Button was pressed on the Unit:
journalctl -x | grep 'Power key pressed.' -A10
Personality directory (serials.py)
ipc python / ipccli directories

ONVIF LISTENER LOG

```
cat /opt/een/var/log/bridge/listener/listener.log
```

Cam Tool values are

• STRM == Streaming
• PEND == Pending and driver is built, waiting for user to add camera
• HOLD == did not match a driver, need to build driver
• NONE == need password or could not find driver
• PASS == password required
• CONF == in ONVIF configuration state machine
• CERR == Configuration Error
• ERR == camera is in an error state, need to look at username/password, firmware, connection
• FOND == ask jeff camera ip
• COFF == Camera Off
• NSIG == Analog camera

ADT Tech Support (866)494-9120

MFG PASS: eagle23soaring OR een

Notifications Link:

https://api.[cluster].eagleeyenetworks.com/api/v3.0/accounts/[end user account number]/notifications

Ex:

https://api.c014.eagleeyenetworks.com/api/v3.0/accounts/00058171/notifications

Connect to cameras the back way:

open tunnel to bridge, take IP shown and port, enter into below command enter in the IP of the camera, port using http
run below command
use root pw of bridge to confirm

load https://localhost:8088/ in browser

ssh root@208.81.97.25 -o UserKnownHostsFile=/dev/null -p58861 -L8088:192.168.1.27:443 (bridge IP) (bridge port) (camera IP)

Summary Field: Category | Short description of issue

Description Field:

Master account: ${Cases.Master Account ID}

Sub-account: ${Cases.Sub Account ID}

Support PIN and email: ${Cases.Email} / ${Cases.Support PIN}

Bridge information - (One Bridge per Jira. SWAT will link tickets if investigation supports it)

SSN: ${Cases.Bridge Serial Number}

ESN: *${Cases.Bridge ESN}*

Camera(s) - (include all affected cameras, can only be ESN if more than 2+)

Manufacturer:

Model:

Firmware:

MAC Address:

IP Address:

ESN:

Bridge:

Camera Credentials: admin / password

Description of issue:

Here you provide a description of the actual issue and all relevant information, as well as provide timestamps in UTC of when it happen and other useful information

Reproduction steps/Troubleshooting done: *Please provide reproduction and troubleshooting steps done*

Expected result: *Here you provide the expected result.*

Attachments: Add CLI and/or screenshots to comments with a sentence or two of context.

---

docker exec -it $(docker ps --format '{{.Names}}' | grep -E 'bridge.bridge') /bin/bash

---

Brivo Contacts:
anthony.mcphail@brivo.com,
baudel.reyes@brivo.com

Kenny wanted ssh opened for 304-117905

[root@een-br304-117905 ~]# touch /opt/een/data/etc/iptables.d/filter/50-platform2.conf;echo -e "# EEPD-21581 Customer requested override of SSH Port\n# Additional rule for remote access for platform2\n-A INPUT -m state --state NEW -m tcp -p tcp --dport 33022 -j ACCEPT\n-A INPUT -m state --state NEW -m tcp -p tcp --dport 22 -j ACCEPT" >> /opt/een/data/etc/iptables.d/filter/50-platform2.conf; sleep 5; iptablesctl --sync

Got:

Configured Rules:

table 'filter':

chain 'INPUT':

-m state --state ESTABLISHED,RELATED -j ACCEPT (from 01-established.conf)

-p icmp -j ACCEPT (from 01-established.conf)

-i lo -j ACCEPT (from 01-established.conf)

-i docker0 -j ACCEPT (from 10-docker.conf)

-s 127.0.0.0/8 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (from 20-ssh.conf)

-s 10.43.3.0/24 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (from 20-ssh.conf)

-s 10.143.0.0/16 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (from 20-ssh.conf)

-s 172.17.0.0/16 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (from 20-ssh.conf)

-s 127.0.0.0/8 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (from 20-ssh.conf)

-s 10.43.3.0/24 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (from 20-ssh.conf)

-s 10.143.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (from 20-ssh.conf)

-s 172.17.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (from 20-ssh.conf)

-i camlan0 -p udp -m udp --dport 123 -j ACCEPT (from 25-chrony.conf)

-i camlan1 -p udp -m udp --dport 123 -j ACCEPT (from 25-chrony.conf)

-m state --state NEW -m udp -p udp --dport 32768:61000 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m tcp -p tcp --dport 554 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m udp -p udp --dport 554 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m udp -p udp --dport 3702 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m udp -p udp --dport 8919 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m udp -p udp --dport 15947 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m tcp -p tcp --dport 8000:9000 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m udp -p udp --dport 67 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m udp -p udp --dport 53 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m tcp -p tcp --dport 80 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m tcp -p tcp --dport 443 -j ACCEPT (from 50-default.conf)

-m state --state NEW -m tcp -p tcp --dport 33022 -j ACCEPT (from 50-platform2.conf)

-m state --state NEW -m tcp -p tcp --dport 22 -j ACCEPT (from 50-platform2.conf)

-s 127.0.0.0/8 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (from 50-smokeping.conf)

-s 10.43.3.0/24 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (from 50-smokeping.conf)

-s 10.143.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (from 50-smokeping.conf)

-s 172.17.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (from 50-smokeping.conf)

-m state --state NEW -m tcp -p tcp --dport 51500:51599 -j ACCEPT (from 51-mci.conf)

-m state --state NEW -m tcp -p tcp --dport 1935 -j ACCEPT (from 60-rtmp.conf)

-j REJECT --reject-with icmp-host-prohibited (from 99-reject.conf)

chain 'FORWARD':

-i wan0 -m state --state RELATED,ESTABLISHED -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set eec_vms dst --dport 80 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set eec_vms dst --dport 443 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set eec_vms dst --dport 8081 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set ee_cm dst --dport 80 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set ee_cm dst --dport 443 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set ee_cm dst --dport 8081 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set een dst --dport 80 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set een dst --dport 443 -j ACCEPT (from 70-nat-forward.conf)

-p tcp -m set --match-set een dst --dport 8081 -j ACCEPT (from 70-nat-forward.conf)

-m hashlimit --hashlimit-htable-expire 3600000 --hashlimit-name forward_dropped --hashlimit-mode dstip --hashlimit-burst 1 --hashlimit-upto 6/hour -j LOG --log-prefix "iptables-forward-dropped: " --log-level 4 (from 70-nat-forward.conf)

-j REJECT --reject-with icmp-host-prohibited (from 99-reject.conf)

table 'nat':

chain 'PREROUTING':

-i wan0 -p tcp --dport 22 -j REDIRECT --to-port 33022 (from 10-ssh.conf)

chain 'POSTROUTING':

-o wan0 -j MASQUERADE (from 70-nat.conf)

Active Rules:

table 'filter':

chain 'INPUT':

-m state --state RELATED,ESTABLISHED -j ACCEPT (via INPUT_20240816142348)

-p icmp -j ACCEPT (via INPUT_20240816142348)

-i lo -j ACCEPT (via INPUT_20240816142348)

-i docker0 -j ACCEPT (via INPUT_20240816142348)

-s 127.0.0.0/8 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (via INPUT_20240816142348)

-s 10.43.3.0/24 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (via INPUT_20240816142348)

-s 10.143.0.0/16 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (via INPUT_20240816142348)

-s 172.17.0.0/16 -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT (via INPUT_20240816142348)

-s 127.0.0.0/8 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (via INPUT_20240816142348)

-s 10.43.3.0/24 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (via INPUT_20240816142348)

-s 10.143.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (via INPUT_20240816142348)

-s 172.17.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33022 -j ACCEPT (via INPUT_20240816142348)

-i camlan0 -p udp -m udp --dport 123 -j ACCEPT (via INPUT_20240816142348)

-i camlan1 -p udp -m udp --dport 123 -j ACCEPT (via INPUT_20240816142348)

-p udp -m state --state NEW -m udp --dport 32768:61000 -j ACCEPT (via INPUT_20240816142348)

-p tcp -m state --state NEW -m tcp --dport 554 -j ACCEPT (via INPUT_20240816142348)

-p udp -m state --state NEW -m udp --dport 554 -j ACCEPT (via INPUT_20240816142348)

-p udp -m state --state NEW -m udp --dport 3702 -j ACCEPT (via INPUT_20240816142348)

-p udp -m state --state NEW -m udp --dport 8919 -j ACCEPT (via INPUT_20240816142348)

-p udp -m state --state NEW -m udp --dport 15947 -j ACCEPT (via INPUT_20240816142348)

-p tcp -m state --state NEW -m tcp --dport 8000:9000 -j ACCEPT (via INPUT_20240816142348)

-p udp -m state --state NEW -m udp --dport 67 -j ACCEPT (via INPUT_20240816142348)

-p udp -m state --state NEW -m udp --dport 53 -j ACCEPT (via INPUT_20240816142348)

-p tcp -m state --state NEW -m tcp --dport 80 -j ACCEPT (via INPUT_20240816142348)

-p tcp -m state --state NEW -m tcp --dport 443 -j ACCEPT (via INPUT_20240816142348)

-s 127.0.0.0/8 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (via INPUT_20240816142348)

-s 10.43.3.0/24 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (via INPUT_20240816142348)

-s 10.143.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (via INPUT_20240816142348)

-s 172.17.0.0/16 -p tcp -m state --state NEW -m tcp --dport 33080 -j ACCEPT (via INPUT_20240816142348)

-p tcp -m state --state NEW -m tcp --dport 51500:51599 -j ACCEPT (via INPUT_20240816142348)

-p tcp -m state --state NEW -m tcp --dport 1935 -j ACCEPT (via INPUT_20240816142348)

-j REJECT --reject-with icmp-host-prohibited (via INPUT_20240816142348)

chain 'FORWARD':

-i wan0 -m state --state RELATED,ESTABLISHED -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set eec_vms dst -m tcp --dport 80 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set eec_vms dst -m tcp --dport 443 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set eec_vms dst -m tcp --dport 8081 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set ee_cm dst -m tcp --dport 80 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set ee_cm dst -m tcp --dport 443 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set ee_cm dst -m tcp --dport 8081 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set een dst -m tcp --dport 80 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set een dst -m tcp --dport 443 -j ACCEPT (via FORWARD_20240816142348)

-p tcp -m set --match-set een dst -m tcp --dport 8081 -j ACCEPT (via FORWARD_20240816142348)

-m hashlimit --hashlimit-upto 6/hour --hashlimit-burst 1 --hashlimit-mode dstip --hashlimit-name forward_dropped -j LOG --log-prefix "iptables-forward-dropped: " (via FORWARD_20240816142348)

-j REJECT --reject-with icmp-host-prohibited (via FORWARD_20240816142348)

```
    table 'nat':

        chain 'PREROUTING':

            -i wan0 -p tcp -m tcp --dport 22 -j REDIRECT --to-ports 33022 (via
PREROUTING_20240816142349)

        chain 'POSTROUTING':

            -o wan0 -j MASQUERADE (via POSTROUTING_20240816142349)

Calculating list of tables to (re)sync...

Table filter:

    Sync needed.

    Cleaning up chains...

Table nat:

    Sync needed.

    Cleaning up chains...

2 tables were synced.

Zap Martian (extraneous) iptable rules...

[root@een-br304-117905 ~]#
```