



- NOTES**
1. Bathymetric contours are shown at 5.0 m intervals.
 2. Bathymetric survey provided by Claude Resources Inc. October 1, 2015.
 3. Total capacity of Laonil Lake Inlet (extent shown by contours) is approximately 660,000m³ at a lake elevation of 448.2m.
 4. Total tailings volume in East lake TMF is approximately 2.9Mm³ at the end of 2020.
 5. Based on the tailings volume in East Lake TMF, if the East side of the TMF were to fail, the calculated maximum tailings released of 210,000m³ would be accommodated by the Laonil Lake Inlet. Laonil Lake Inlet would however be impacted by tailings and supernatant and remediation efforts would be required.
 6. If there is a global dike / dam failure along the south of the TMF, it is expected that most of the tailings would be accommodated by the Back Pond and topography downstream.
 7. Topographic contours shown at 2.0 m intervals.

REFERENCE

Imagery provided by SSR, received August 26, 2017.

Triangle Lake TMF Drone Imagery provided by SSR. September 15, 2019.

P:\Projects\01_SITES\Seabee Mine\042_AutoCAD\OHS\2020\1CC042.033 - Laonil Lake Bathymetry.dwg



SRK JOB NO.: 1CC042.029
FILE NAME: 1CC042.033 - Laonil Lake Bathymetry.dwg

Seabee Mine

OMS Manual (Version 1)

Laonil Lake Inlet
General Arrangement and Bathymetry

DATE: August 2020	APPROVED: TPCP	FIGURE: 10
----------------------	-------------------	---------------