

Practice of Information Processing

(IMACU)

Fifth lecture(Part 2)

Function definition, call and, recursive call

Makoto Hirota

Contents of this lecture

2

- Example answer of previous exercise
- Definition of function
 - What is function
 - Definition of self-made function
 - Prototype declaration
 - Role of function
- Function with no return value “procedure”
- Recursive call of function
- Data type
- What is structure?

What is function?

3

■ function

- A program that extracts **specific processes** and puts them together as a separate program.
- By **calling a function** in the middle of a program, a specific process is executed and the result is returned (**return value**).
- When calling a function, you can specify the value (**argument**) to be input.

<Technical terms>

Value to enter

= **Argument**, actual arguments

Output value

= **Return value** value,
function value

Main function

```
int main(){
```

```
    int a,b;  
    double result;
```

```
    result = func1(a,b) ;
```

```
    return 0;
```

```
}
```

argument

Return value

function func1

```
double func1 (int x, int y){
```

```
    double z;
```

process

```
    return z ;
```


```
}
```

main (), printf (), scan (), etc. are also functions
(standard functions, library functions)
Functions created by the user are called user functions.

How to define a function

4

■ General form of function definition



(For a function that adds two variables)

- 1) Determine the function name (add_func)
- 2) Determine arguments
(2 variables of int type x, y)
- 3) Determine the return value
(int type a as a solution)
- 4) Write the process
- 5) Return the return value

Example


```
/* User defined add_func */  
  
int add_func(int x, int y)  
  /***** variable declaration****/  
  int a;  
  /***** processing contents****/  
  a = x + y;  
  /***** return value ****/  
  return a;  
}
```

Function: Number of arguments and return values₅

■ Number of arguments and return values

- Multiple arguments are possible (no argument is also OK)
- Only one return value (no return value is also OK)

If it is zero, do not write anything
Or write "void"



- ◆ In C language
 - ◆ Multiple arguments are possible
 - ◆ Only one return value

What if we want to return multiple results?

Method 1: Specify the data storage destination with a **pointer and have the result entered (next lectures)**

Method 2: Rewrite **global variables (next lectures)**

Ex) Function add_func.c

6

- Compile and execute the sample program add_func.c, and check the contents of the program.

```
#include <stdio.h>


/* User defined add_func */
int add_func(int x, int y)
    /*** variable declaration***/
    int a;
    /*** processing contents***/
    a = x + y;
    /*** return value ***/
    return a;
}

int main() {
    /*** variable declaration***/
    int p,q;
    /*** processing contents***/
    q = 2;
    p = add_func(q,3);
    printf("%d\n", p);

    return 0;
}
```

Supplement: Matching the types of arguments and return values⁷

- When calling a function, it is necessary to match the "type" of the argument / return value of the defined function.



In this example, the argument defined by the function is int type and the return value is float type, so in the main function, the types of the argument x (int type) when calling the function func1 and the return value assignment destination y (float type) are matched between at main and at func1.

How to add a user function

```
#include <stdio.h>
```

```
int func1 (int x){  
    process  
    return y;  
}
```

User-function func1

```
int func2 (int x, int y){  
    process  
    return z;  
}
```

User-function func2

```
int main(){  
    process  
    y = func1 (x);  
    z = func2 (p, q);  
    return 0;  
}
```

Main function

Call func1
Call func2

Write outside the main function in order

- In fact, the function definition can be written at any position as long as it is the main function. You can write it in a separate file.
- However, it is necessary to share conventions such as function arguments and return value form (= header file that #includes the file that describes the convention at the beginning).

How to share a defined function type
= **Prototype declaration**

* The main function is also a type of function, but in a program, there is a rule that the main function is executed first, so we will create a processing flow in the main function.

Example: If you need a prototype declaration

9

- Move the code of the user function `add_func.c` of the sample program after the main function and check the operation.
- Add the following sentence to `add_func.c` and compile again.

```
#include <stdio.h>

int add_func(int, int);

int main() {
...
}
```

```
#include <stdio.h>

/* User defined add_func */
int add_func(int x, int y)
    /***** variable declaration*****/
    int a;
    /***** processing contents*****/
    a = x + y;
    /***** return value *****/
    return a;
}


int main() {
    /***** variable declaration*****/
    int p,q;
    /***** processing contents*****/
    q = 2;
    p = add_func(q,3);
    printf("%d\n", p);

    return 0;
}
```

Move here

In the case the compiler does not know the definition of the function

10




The definition of the function can be anywhere in the program. However, if you write your own function after the main function, a compile error will occur.



Because the compiler doesn't know the definition of the user function.

Workaround: Function prototype declaration (prototype declaration)₁₁



If you define a function after the main function, you need to teach the compiler how to use the function with a prototype declaration.

◆ Function prototype declaration

Return type Function name (type of argument 1, type of argument 2, ...);

Only the function name and the "type" of the argument and return value are shown.
No variable name for argument required
";" is required at the end

In many programs, the prototype declaration is written in the header file (.h). This is the reason for including the header file when using the function.

Example: Sample code add_func2.c

Function with no return value (= "procedure") 12


- In C language, you can define a function with no return value..

```
void func(type of argument1 argument1,  
          type of argument 2 argument2, ...)  
{  
    process  
  
    (no return statement)  
}
```

Such a function is sometimes called a "procedure"

* The term "Procedure" seems to be a remnant of the programming language Pascal. In C language, a function with no return value can be considered to be the same kind of the function.

Similarly, you can define a return value or a function that takes no arguments.



```
void  
func(void)  
{  
    process  
}
```

■ Why the return type of main is omitted

- If you do not declare the type of the function, there is a rule that the int type is used by default, so you often see a program in which nothing is written before the main function (also in textbooks). However, in order to clarify the intention of the creator's function definition, it is recommended to write it in full.
- In other words, it is not void main (), so be careful. This is why return 0 is needed at the end of the main function.

■ How to use a function with no arguments

- Parentheses () are required even when calling without arguments
 - `value = func ();`

■ Function prototype declaration with no return value or arguments

- Use "void"
 - When there is no argument: `int func (void);`
 - When there is no return value: `void func (int x);`
 - When neither is available: `void func (void);`

■ Functions have four main roles:

- Structure: The structure of a program is made easy to understand by dividing complicated and intertwined procedures into elemental functions (= functions).
 - It makes it easier to create long programs.
- Repeated use: Use the function many times in the same program.
 - Program gets shorter
- Reuse: Reuse a function in another program
 - The effort of creating a program is reduced.
- Black boxing: Makes the function available even if you do not know the processing inside the function.
 - Facilitates program collaboration.

■ Math library

- A collection of math-related functions prepared in C language
- The following two are required to use
 - Write `#include <math.h>` at the beginning of the program
 - Add `-lm` option at compile time
 - `gcc -Wall -o test test.c -lm`
- Argument and return value are double type

Exercise 5-1 Practice your own function: calc_func.c

16

- Modify the sample program add_func2.c (with prototype declaration) and create a program calc_func.c that adds the three functions of
 - Subtraction function: sub_func
 - Multiplication function: multi_func
 - Division function: div_func
- Also, in the main function, execute the following calculation without using arithmetic operators.
 - $Y = (2.0 + 1.0) \times 6.0 / 1.5 - 3.0$
- However, the variable of each function is double type.
- The function should be defined after the main function and a prototype declaration should be used.

$$y = (2.0 + 1.0) \times 6.0 / 1.5 - 3.0$$

[Hint]

For example, if $y = 2.0 \times 3.0 + 4.0$, it is calculated as follows.

$y = \text{add_func}(\text{multi_func}(2.0, 3.0), 4.0)$

Exercise 5-1 : Tips

17

■ Function calls and assigned variables

Ex): $y = 2.0 \times 3.0 + 4.0$

(solution 1)

```
double p, q ;  
① q = multi_func(2.0, 3.0) ;  
② p = add_func(q, 4.0) ;
```

Better

(solution 2)

```
double p ;  
① p = multi_func(2.0, 3.0) ;  
② p = add_func(p, 4.0) ;  
Next value      Original value
```

The way writing in a sample program style
(Prepare different variables each time you assign)

One variable to assign is enough
(There is a context for assignment operators)

Best

(solution3)

```
double p ;  
p = add_func( multi_func(2.0, 3.0), 4.0 )
```

Functions can be called in a nested structure (put the function inside the function argument)

Exercise 5-2 Finding the least common multiple lcm.c

18

- Create a program lcm.c that displays the least common multiple of two integers input from the keyboard.

- However,

- The least common multiple m of the two integers a and b is expressed by $m = ab / d$ using the greatest common divisor d of a and b .
- Create and use the function $d = \text{gcd}()$ to find the greatest common divisor
- The greatest common divisor can be calculated using the following algorithm called the Euclidean algorithm.

- ① Let two integers a and b ($a > b$), and let r be the remainder of dividing a by b .
- ② If r is 0, then b is the greatest common divisor
- ③ If r is not 0, return to ① with $a = b$ and $b = r$

- If 0 or a negative value is entered in either of the two integers, it should terminate abnormally ($\text{exit}(1)$) in main function.
- Implement $\text{gcd}()$ without using recursive calls

Exercise 5-2: Tips

19

■ Example of main function

```
int main() {  
  
    /**** variable declaration****/  
    int a,b,d;  
  
    /**** processing contents****/  
    printf("input a ->");  
    scanf("%d", &a);  
    printf("input b ->");  
    scanf("%d", &b);  
  
    d = gcd(a,b);  
  
    printf("Least common multiple of %d and %d is %d\n", a, b, a*b/d);  
    return 0;  
}
```

■ Use of exit function

- Note that it is necessary to add
#Include <stdlib.h>
At the beginning to use the exit function

■ Regular functions

```
f () {  
    g () ; Other functions  
    ...  
    h () ; Other functions  
    ...  
}
```

It's not strange to call another function in a function definition

■ Recursive calling of function

```
f () {  
    ...  
    f () ; Call the same  
           function in the  
           function definition  
    ...  
}
```

When the same function f is called again in the definition of function f , it is called a recursive call.

* In the Euclidean algorithm used in the previous exercise 5-2, the inductive algorithm that repeatedly calls the same process can be executed by recursive call of the function.→ Exercise 5-3

Recursive use of function

21

$${}_nC_r = \frac{n!}{r!(n-r)!}$$

```
1: /* combination.c : nCr */
2:
3: #include <stdio.h>
4: #include <stdlib.h>
5: long factorial(int x)
6: {
7:     int    i;
8:     long   f;
9:
10:    i = 0; f = 1;
11:    while (i < x) {
12:        ++i; f = f * i;
13:    }
14:    printf("factorial called, %3d!=%12ld\n", x, f);
15:    return(f);
16: }
17:
18: main()
19: {
20:     int    n, r;
21:     long   ncr;
22:
23:     if (scanf("%d %d", &n, &r) != 2) {
24:         printf("Input 2 integers\n"); exit(1);
25:     }
26:     if (n > 12) {
27:         printf("Too large n=%d > 12\n", n); exit(1);
28:     }
29:     if (n < r) {
30:         printf("Invalid inputs: n=%d < r=%d\n", n, r); exit(1);
31:     }
32:     ncr = factorial(n) / (factorial(r) * factorial(n - r));
33:     printf("n=%d, r=%d, nCr=%ld\n", n, r, ncr);
34: }
```

Functionize the calculation of
factorial() that appears repeatedly (= factorial)

Error handling: Meaning of exit (1)

You can use the exit () statement to exit at any point in the program

- exit (1) ends abnormally
- exit (0) ends normally (same as exiting with return 0 at the end of the main statement).

※Note

Note that you need to add

#Include <stdlib.h>

in the head part of program to use the exit function

Ex: Factorial calculation (recursive call version) r_factorial.c₂₂

Sample code: r_factorial.c

```
#include <stdio.h>

int rfact(int n)
{
    int m;

    if (n == 0){ /* when n=0(0!=1)*/
        m = 1;
    }
    else{ /* when not n=0*/
        m = n * rfact(n - 1);
    }
    return m;
}

int main()
{
    int num, ans;


    printf("Input natural number= ");
    scanf("%d", &num);

    /* factorial by func. rfact()*/

    ans = rfact(num);

    /* output results*/
    printf("%d! = %d\n", num, ans);
    return 0;
}
```

ex: case of num = 4



Recursive call
= Same structure
Repeat

- Create a program lcm2.c that finds the least common multiple by rewriting the function gcd that finds the greatest common divisor in the previous exercise 5-2 using the recursive call of the function.
- Name the function rgcd()

Greatest_commen_divisor = rgcd(a,b)

- ① Let two integers a and b ($a > b$), and let r be the remainder of dividing a by b.
- ② If r is 0, then b is the greatest common divisor
- ③ If r is not 0, return to ① with $a = b$ and $b = r$
 - ➡ Call rgcd () again with $a \leftarrow b$ and $b \leftarrow r$
 - Greatest_commen_divisor = rgcd(b,r)

Effective range (scope) of variables

24

```
#include <stdio.h>
```

```
int total_number; ← location of declaration
```

Function add_total

```
int add_total (int x){
```

```
    int answer; ← location of declaration
```

```
    answer = total_number + x;
```

```
    return answer;
```

```
}
```

Main function

```
int main(){
```

```
    int answer; ← location of declaration
```

```
    total_number = 0;
```

```
    for (i=0; i<10; i++){
```

```
        answer = add_total(i);
```

```
    }
```

```
    printf("Total is %d\n", answer);
```

```
    return 0;
```

```
}
```

Two variables in the program on the left

total_number

answer

What is the effective range (= range treated as the same variable)?

total_number is defined outside functions



Variables that can be referenced by any function
= **Global variable**

answer Is defined in each function



Variables that can only be referenced within that function
= **Local variable**

answer in the add_total function and **answer** in the main function are treated as different things (= different memory areas) even if they use the same name..


```
#include <stdio.h>
```

```
int g_count;
```

```
int func1 (void) {    User defined func1
```

```
    /* process */
```

```
    g_count ++;
```

```
    return 0;
```

```
}
```

```
int main() {    Main function
```

```
    /* process */
```

```
    g_count =0;
```

```
    for(i=0;i<10;i++){
```

```
        func1();
```

```
    }
```

```
    printf("%d\\n", g_count);
```

```
    return 0;
```

```
}
```

- Variables declared outside the function are called global variables and can be called from all functions.

Example

- Since the variable `g_count` is declared outside the function, it can be called and operated from both the main function and the `func1` function.
- In this example, `g_count` is incremented by 1 each time `func1 ()` is called, and finally the value of `g_count` is displayed and the process ends.

Will be explained in detail in 11th lecture

Variable name used in the function = local variable

26

```
#include <stdio.h>

int rfact(int n)
{
    int m;

    if (n == 0){ /* n=0(0!=1)*/
        m = 1;
    }
    else{ /* NOT n=0 */

        m = n * rfact(n - 1);
    }
    return m;
}

int main()
{
    int num, ans;

    printf("Input natural number= ");
    scanf("%d", &num);

    /* factorial is computed by
       function rfact()*/
    ans = rfact(num);

    /* display results */
    printf("%d! = %d\n", num, ans);
    return 0;
}
```

What if we
rename the
variable m in
rfact () to
ans?



Duplicate
with the
variable ans
of the main
function?

```
#include <stdio.h>

int rfact(int n)
{
    int ans;

    if (n == 0){ /* n=0(0!=1)*/
        ans = 1;
    }
    else{ /* NOT n=0 */

        ans = n * rfact(n - 1);
    }
    return ans;
}

int main()
{
    int num, ans;

    printf("Input natural number= ");
    scanf("%d", &num);

    /* factorial is computed by
       function rfact()*/
    ans = rfact(num);

    /* display results */
    printf("%d! = %d\n", num, ans);
    return 0;
}
```

- Example answer of previous exercise
- Definition of function
 - What is function
 - Definition of self-made function
 - Prototype declaration
 - Role of function
- Function with no return value “procedure”
- Recursive call of function
- Data type
- What is structure?