

Traveler - Disruptor 12" Tube		Serial #:
SKU#: 4002P0001 Rev N		CF Internal Control #
		CF Internal Control #

Mandrel Preparation			Mandrel #:	Date: __/__/__
Step #	Part #	Quantity	Description	Technician
1	440	1	Zyvax Flex-Z 6.0 Release Agent	
2			Ensure working temp of mandrel is b/t 70-80°	Temp °F:
3			Ensure working temp of table is b/t 70-80°	Temp °F:

Lay Up Schedule				Temp °F:	Date: __/__/__
Ply #	Part #	Quantity	Description	Technician	
1	301j	1	shell 0/90 twill inner mold line		
ENSURE poly is removed from ply 1					
2	542f	1	shell 0° uni		
3	542j	1	shell 0° uni		
4	542j	1	shell 0° uni		
5	542j	1	shell 0° uni		
6	542k	2	31" x 37.29" piece 90° uni		
6	542m	1	36" x 36 7/8" piece 90° uni		
7	542k	2	31" x 37.29" piece 90° uni		
7	542m	1	36" x 36 7/8" piece 90° uni		
8	301k	1	shell 0/90 twill outer mold line		
In-Process Verification Signature:					

Cello Wrap Schedule				Date: __/__/__
Step #	Part #	Quantity	Description	Technician
Ensure outer layer of poly has been removed.				
1	486	1	Tape, Roll Wrapping Stage 1 Poly .75"W	
2	485	1	Tape, Roll Wrapping Compaction Stage 2 Cello .75"W	

Oven Processes			Date: __/__/__
Clock Time		Oven Temp (335°)	Technician
	Roll mandrel on trolley into preheated oven. Tolerance +/- 15°F. Record oven temp:		
	Remove trolley from oven (105 mins). Tolerance +/- 15°F. Record oven temp:		
	Place trolley into designated cooling area.		
	Aim cooling fan onto the mandrel.		
	Remove compression tape from the tube.		
	Remove tube from mandrel.		

In-Process Inspection			Date: __/__/__
Tolerance	Description	Requirement	Result
	Sand off sharp edges on both ends		
Level I, none	Delamination, edges	ASTM D2563-08(2015)	
Level III, 1/32" & <50	Pit (pinhole) & porosity	ASTM D2563-08(2015)	
Level I, none	Wrinkles	ASTM D2563-08(2015)	
Level II, 1/4" max	Lack of fillout	ASTM D2563-08(2015)	
Level III, 1" max	Scratch	ASTM D2563-08(2015)	
In-Process Verification Signature:			

Final QC			Date: __/__/__
Tolerance	Description	Requirement	Result
Go/No Go	Go/No Go on Inner Dimension	11.780	
+/- .005	End #1 outer dimension measurement	11.891-11.901	
+/- .005	End #2 outer dimension measurement	11.891-11.901	
+/- .005	Middle outer dimension measurement	11.891-11.901	
Y/N	Serial numbers clearly marked on blue tape	Y/N	
Y/N	Center of seams marked with orange marker	Y/N	
Minimum 96"	Tip to tip length	>= 96"	
N/A	Weight (g)	for record only	
		Approved to Ship Signature:	

Technician Notes (if applicable):

Mgmt Notes, Signature, Date (if applicable):