Questions

Гags

Users

Badges

Unanswered

Ask Question

Ten. Million. Questions. Let's celebrate all we've done together.

Stack Overflow is a question and answer site for professional and enthusiast programmers. It's 100% free.

Take the 2-minute tour

R Time series - having trouble making bollinger lines - need simple example please

asked 4 years ago viewed 888 times

active 4 years ago



Learning R language - I know how to do a moving average but I need to do more - but I am not a statistician - unfortunately all the docs seem to be written for statisticians.

I do this in excel a lot, it's really handy for analysis of operational activities.

Here are the fields on each row to make bollinger bands:

Value could be # of calls, complaint ratio, anything

TimeStamp | Value | Moving Average | Moving STDEVP | Lower Control | Upper Control

Briefly, the moving avg and the stdevP point to the prior 8 or so values in the series. Lower control at a given point in time is = moving average - 2*moving stdevP and upper control = moving average + 2*moving stdevP

This can easily be done in excel for a single file, but if I can find a way to make R work R will be better for my needs. Hopefully faster and more reliable when automated, too.

links or tips would be appreciated.

r statistics time-series

share improve this question

edited Mar 31 '11 at 17:23

Joris Meys

46.5k • 14 • 111 • 168



active

oldest

This could be done easily for sure. Please provide a sample datafile to see the struscute of your data, and I could help you with the source code. Retagging your question to R should get faster answeres also. — daroczig Jan 8 '11 at 14:01


add a comment

2 Answers

You could use the function rollapply() from the zoo package, providing you work with a zoo series









BollLines <- rollapply(ZooSeries,9,function(x){
 M <- mean(x)
 SD <- sd(x)
 c(M,M+SD*2,M-SD*2)
})</pre>

Now you have to remember that rollapply uses a centered frame, meaning that it takes the values to the left and the right of the current day. This is also more convenient and more true to the definition of the Bollinger Band than your suggestion of taking x prior values.

If you don't want to convert to zoo, you can use the vectors as well and write your own function. I added an S3 based plotting function that allows you to easily plot the calculations as well. With these functions, you could do something like:



Anil Dash and the Firehose of Nerd-dom

Related

- 8 Simple algorithm for online outlier detection of a generic time series
- On-line/Streaming algorithm for the selection of the top X percent of a time series
- 2 How to produce simple sliding window features over irregular time series in R?
- Plot a Lowess Smoothed Line in a Zoo Time Series
- O Create a simple time series
- R: Very basic example for averaging a Time Series
- Trouble creating multiple time series object in R
- Having trouble with R's time series objects
- O Not able to make daily time series analysis in R
- Make time series data discrete in R, when there are irregular times records per bin and additional location data


Hot Network Questions



```
TimeSeries <- cumsum(rnorm(1000))
X <- BollingerBands(TimeSeries,80)
plot(X,TimeSeries,type="1",main="An Example")</pre>
```

to get:

An Example



The function codes :

```
BollingerBands <- function(x,width){</pre>
  Start <- width +1
  Stop <- length(x)
  Trail <- rep(NA,ceiling(width/2))</pre>
  Tail <- rep(NA,floor(width/2))</pre>
  Lines <- sapplv(Start:Stop.function(i){</pre>
    M <- mean(x[(i-width):i])</pre>
    SD \leftarrow sd(x[(i-width):i])
    c(M,M+2*SD,M-2*SD)
  })
  Lines <- apply(Lines,1,function(i)c(Trail,i,Tail))</pre>
  Out <- data.frame(Lines)
  names(Out) <- c("Mean","Upper","Lower")</pre>
  class(Out) <- c("BollingerBands",class(Out))</pre>
}
plot.BollingerBands <- function(x,data,lcol=c("red","blue","blue"),...){</pre>
    plot(data,...)
    for(i in 1:3){
      lines(x[,i],col=lcol[i])
```

share improve this answer

edited Mar 30 '11 at 14:47

answered Mar 30 '11 at 14:29

Joris Meys
46.5k • 14 • 111 • 168

Joris that is a fantastic answer to my question! I am still making very slow progress toward learning R. I know enough now that I can read and understand your code. I will use your example. thanks. – freewary Apr 1 '11 at 4:58

add a comment

- Injecting UUIDs into ROMduring production
- What is the best US bank account to use for extended world travel
- III Is it ethical to offer a student a job during the final weeks of his thesis if you are partly grading it?
- Partition a list into sublists of different lengths
- Stealth in Space: How realistic is it?
- Loop ignores change of variable from a subshell in the background
- Motivation for the Definition of Compact Space
- Where did the insults generated by the Marauder's map come from?
- Will Karma 'balance out' in most cases by the end of a lifetime?
- ls your vault saved locally or in the cloud?
- Is it a good idea to leave my guitar tuned over night?
- SX Could liquid airlocks work?
- How to display recent upgrade messages?
- Wrapping link in TD tag in Visualforce render as PDF page
- How does Charlie's wand work for Ron?
- Blind spot in the Solar System
- Considerations for older campers?
- Why are isotopes of hydrogen the only ones with special names?
- Why did Walter White refuse to help in S02E12?
- Stop! Stand right where you are!
- The Programming Language Quiz
- What version is this Live CD / Live USB?
- Is Magento 2 Stable enough to start developing new eshop?
- Which character from Star Trek (TNG era) "died" the most times?




There is an illustration in the R Graph Gallery (65) giving code both for calculating the bands and for plotting share prices.

1

The 2005 code still seems to work six years later and will give IBM's current share price and going back several months

IBM: Bollinger Bars, Bands, Indicators and normalized and absolute Volume



The most obvious bug is the width of the bandwidth and volume lower charts which have been narrowed; there may be another over the number of days covered.

share improve this answer

answered Apr 3 '11 at 23:51

Henry

3,513 • 1 • 7 • 22

add a comment

Your Answer

В	I	Ø 66 {} A]=	5 0



Sign up or log in

8	Sign up using Google
f	Sign up using Facebook
=	Sign up using Stack Exchange

Post as a guest

Name	
Email	
required, but never shown	

Post Your Answer

By posting your answer, you agree to the privacy policy and terms of service.

Not the answer you're looking for? Browse other questions tagged r statistics time-series or ask your own question.

question feed

ECHNOLOGY			LIFE/ARTS	CULTURE/ RECREATION	SCIENCE	OTHER
stack Overflow	Programmers	Database	Photography	English Language &	Mathematics	Stack Apps
Server Fault	Unix & Linux	Administrators	Science Fiction & Fantasy Graphic Design	Usage	Cross Validated (stats)	Meta Stack Exchange
Super User	Ask Different (Apple)	Drupal Answers SharePoint		Skeptics	Theoretical Computer	Area 51
Neb Applications	WordPress Development			Mi Yodeya (Judaism)	Science	Stack Overflow Careers
Ask Ubuntu		User Experience	Movies & TV	Travel	Physics	
Vebmasters	Geographic Information Systems Electrical Engineering	Mathematica	Seasoned Advice (cooking) Home Improvement	Christianity	MathOverflow	
Came Development		Salesforce		Arqade (gaming)	Chemistry	
TeX-LaTeX	Android Enthusiasts	ExpressionEngine® Answers	Personal Finance &	Bicycles	Biology	
	Information Security	more (13)	Money	Role-playing Games	more (5)	
			Academia more (21)			
			more (9)			

