



R news and tutorials contributed by (573) R bloggers

- [Home](#)
- [About](#)
- [RSS](#)
- [add your blog!](#)
- [Learn R](#)
- [R jobs](#)
- [Contact us](#)

## Welcome!

Follow @rbloggers { 27.8K }

Here you will find daily **news and tutorials about R**, contributed by over 573 bloggers.

There are many ways to **follow us -**

[By e-mail:](#)

Your e-mail here
   
 Subscribe
   
 24349 readers
   
BY FEEDBURNER

[On Facebook:](#)

R blogg...
   
 30k likes

Like Page

Be the first of your friends to like this

**If you are an R blogger yourself** you are invited to [add your own R content feed to this site](#) (Non-English R bloggers should add themselves- [here](#))

## [Jobs for R-users](#)

- [Junior Data Scientist @ Farnham, England](#)
- [Vehicle Valuations Manager @ Farnham, England](#)
- [Manager – Quantitative Analytics @ London, United Kingdom](#)
- [Pharmacometrics Bootcamp @ Wellesley, Massachusetts, US](#)
- [Data Scientist for](#)

[TIBCO](#)  
(>\$100K/year)

Search & Hit Enter

## Popular Searches

- [web scraping](#)
- [heatmap](#)
- [maps](#)
- [shiny](#)
- [twitter](#)
- [alt=](#)
- [boxplot](#)
- [hadoop](#)
- [time series](#)
- [animation](#)
- [ggplot2](#)
- [trading](#)
- [ggplot](#)
- [latex](#)
- [PCA](#)
- [finance](#)
- [excel](#)
- [quantmod](#)
- [googlevis](#)
- [RSTUDIO](#)
- [how to import image file to R](#)
- [rattle](#)
- [eclipse](#)
- [market research](#)
- [knitr](#)
- [rcmdr](#)
- [tutorial](#)
- [coplot](#)
- [Map](#)
- [SQL](#)

## Recent Posts

- [functions exercises](#)
- [Build your own neural network classifier in R](#)
- [There's a party at Alexa's place](#)
- [Hadley Wickham's Advanced R in Amsterdam](#)
- [Mastering R plot – Part 2: Axis](#)
- [What has Kaggle learned from 2 million machine learning models?](#)
- [Pitfall of XML package: to know the cause](#)
- [Speaking at DataPhilly February 2016](#)
- [Introducing Microsoft R Open: Replay and slides](#)
- [Shiny Developer Conference 2016 Recap](#)
- [Cricket analytics](#)

[with cricketr in paperback and Kindle versions](#)

- [New Version of “Wrangling F1 Data With R” Just Released...](#)
- [Data from the World Health Organization API](#)
- [Alternate R Markdown Templates](#)
- [Death Comes to Us All](#)

## Other sites

- [Statistics of Israel](#)
- [SAS blogs](#)
- [Jobs for R-users](#)

# Computing and visualizing PCA in R

November 28, 2013

By [thiagogm](#)

Like Share {26} Tweet Share 10

(This article was first published on [Thiago G. Martins » R](#), and kindly contributed to [R-bloggers](#).)

Following [my introduction to PCA](#), I will demonstrate how to apply and visualize PCA in R. There are many packages and functions that can apply PCA in R. In this post I will use the function `prcomp` from the `stats` package. I will also show how to visualize PCA in R using Base R graphics. However, my favorite visualization function for PCA is `ggbiplot`, which is implemented by [Vince O. Vu](#) and available on [github](#). Please, let me know if you have better ways to visualize PCA in R.

## Computing the Principal Components (PC)

I will use the classical `iris` dataset for the demonstration. The data contain four continuous variables which corresponds to physical measures of flowers and a categorical variable describing the flowers' species.

```
1 # Load data
2 data(iris)
3 head(iris, 3)
4
5 Sepal.Length Sepal.Width Petal.Length Petal.
6 1          5.1         3.5         1.4
7 2          4.9         3.0         1.4
8 3          4.7         3.2         1.3
```

We will apply PCA to the four continuous variables and use the categorical variable to visualize the PCs later. Notice that in the following code we apply a log transformation to the continuous variables as suggested by [\[1\]](#) and set `center` and `scale.` equal to `TRUE` in the call to `prcomp` to standardize the variables prior to the application of PCA:

```
1 # log transform
2 log.ir <- log(iris[, 1:4])
3 ir.species <- iris[, 5]
4
5 # apply PCA - scale. = TRUE is highly
6 # advisable, but default is FALSE.
7 ir.pca <- prcomp(log.ir,
8                 center = TRUE,
9                 scale. = TRUE)
```

Since skewness and the magnitude of the variables influence the resulting PCs, it is good practice to apply skewness transformation, center and scale the variables prior to the application of PCA. In the example above, we applied a log transformation to the variables but we could have been more general and applied a Box and Cox transformation [2]. See at the end of this post how to perform all those transformations and then apply PCA with only one call to the `preProcess` function of the `caret` package.


### Analyzing the results

The `prcomp` function returns an object of class `prcomp`, which have some methods available. The `print` method returns the standard deviation of each of the four PCs, and their rotation (or loadings), which are the coefficients of the linear combinations of the continuous variables.

```
1 # print method
2 print(ir.pca)
3
4 Standard deviations:
5 [1] 1.7124583 0.9523797 0.3647029 0.1656840
6
7 Rotation:
8
9      Sepal.Length  Sepal.Width  Petal.Length  Petal.Width
10 PC1      0.5038236 -0.45499872  0.708854    -0.331162
11 PC2     -0.3023682 -0.88914419 -0.219279    -0.582900
12 PC3      0.5767881 -0.03378802  0.03545628  0.000000
```

The `plot` method returns a plot of the variances (y-axis) associated with the PCs (x-axis). The Figure below is useful to decide how many PCs to retain for further analysis. In this simple case with only 4 PCs this is not a hard task and we can see that the first two PCs explain most of the variability in the data.

```
1 # plot method
2 plot(ir.pca, type = "l")
```



The `summary` method describe the importance of the PCs. The first row describe again the standard deviation associated with each PC. The second row shows the proportion of the variance in the data explained by each component while the third row describe the cumulative proportion of explained variance. We can see there that the first two PCs accounts for more than 95% of the variance of the data.


```
1 # summary method
2 summary(ir.pca)
3
4 Importance of components:
5
6      PC1      PC2      PC3
7 Standard deviation 1.7125 0.9524 0.36470 0
8 Proportion of Variance 0.7331 0.2268 0.03325 0
9 Cumulative Proportion 0.7331 0.9599 0.99314 1
```

We can use the `predict` function if we observe new data and want to

predict their PCs values. Just for illustration pretend the last two rows of the iris data has just arrived and we want to see what is their PCs values:

```
1 # Predict PCs
2 predict(ir.pca,
3         newdata=tail(log.ir, 2))
4
5      PC1      PC2      PC3      P
6 149 1.0809930 -1.0115751 -0.7082289 -0.068110
7 150 0.9712116 -0.06158655 -0.5008674 -0.124115
```


The Figure below is a biplot generated by the function `ggbiplot` of the `ggbiplot` package available on [github](https://github.com/vqv/ggbiplot).




The code to generate this Figure is given by

```
1 library(devtools)
2 install_github("ggbiplot", "vqv")
3
4 library(ggbiplot)
5 g <- ggbiplot(ir.pca, obs.scale = 1, var.scal
6               groups = ir.species, ellipse =
7               circle = TRUE)
8 g <- g + scale_color_discrete(name = '')
9 g <- g + theme(legend.direction = 'horizontal'
10              legend.position = 'top')
11 print(g)
```

It projects the data on the first two PCs. Other PCs can be chosen through the argument `choices` of the function. It colors each point according to the flowers' species and draws a Normal contour line with `ellipse.prob` probability (default to 68%) for each group. More info about `ggbiplot` can be obtained by the usual `?ggbiplot`. I think you will agree that the plot produced by `ggbiplot` is much better than the one produced by `biplot(ir.pca)` (Figure below).



I also like to plot each variables coefficients inside a unit circle to get insight on a possible interpretation for PCs. Figure 4 was generated by [this code available on gist](#).



### PCA on caret package

As I mentioned before, it is possible to first apply a Box-Cox transformation to correct for skewness, center and scale each variable and then apply PCA in one call to the `preProcess` function of the `caret` package.

```
1 require(caret)
2 trans = preProcess(iris[,1:4],
3                     method=c("BoxCox", "center"
4                               "scale", "pca"))
5 PC = predict(trans, iris[,1:4])
```

By default, the function keeps only the PCs that are necessary to explain at least 95% of the variability in the data, but this can be changed through the argument `thresh`.

```
1 # Retained PCs
2 head(PC, 3)
3
4      PC1      PC2
5 1 -2.303540 -0.4748260
6 2 -2.151310  0.6482903
7 3 -2.461341  0.3463921
8
9 # Loadings
10 trans$rotation
11
12      PC1      PC2
13 Sepal.Length  0.5202351 -0.38632246
14 Sepal.Width  -0.2720448 -0.92031253
15 Petal.Length  0.5775402 -0.04885509
```

16 | Petal.Width 0.5672693 -0.03732262

See [Unsupervised data pre-processing for predictive modeling](#) for an introduction of the `preProcess` function.

#### References:

- [1] Venables, W. N., Ripley, B. D. R. Modern applied statistics with S-PLUS. Springer-verlag. (Section 11.1)  
 [2] Box, G. and Cox, D. (1964). An analysis of transformations. Journal of the Royal Statistical Society. Series B (Methodological) 211-252

Like Share 26 Tweet Share 10

#### Related

##### Comments: 9

A brief introduction to "apply" in R  
 In "R bloggers"



Computing and visualizing LDA in R  
 In "R bloggers"



The reshape function  
 In "R bloggers"

26 Tweet 10  
 Like Share

To leave a comment for the author, please follow the link and comment on their blog: [Thiago G. Martins » R](#)

R-bloggers.com offers [daily e-mail updates](#) about R news and [tutorials](#) on topics such as: [Data science](#), [Big Data](#), [R jobs](#), visualization ([ggplot2](#), [Boxplots](#), [maps](#), [animation](#)), programming ([RStudio](#), [Sweave](#), [LaTeX](#), [SQL](#), [Eclipse](#), [git](#), [hadoop](#), [Web Scraping](#)) statistics ([regression](#), [PCA](#), [time series](#), [trading](#)) and more...

If you got this far, why not [subscribe for updates](#) from the site?  
 Choose your flavor: [e-mail](#), [twitter](#), [RSS](#), or [facebook](#)...

Like Share 26 Tweet Share 10

Comments are closed.

Search & Hit Enter

## Recent popular posts

- [Build your own neural network classifier in R](#)
- [What has Kaggle learned from 2 million machine learning models?](#)
- [Mastering R plot – Part 2: Axis](#)
- [Hadley Wickham's Advanced R in Amsterdam](#)

## Most visited articles of the week


1. [Installing R packages](#)
2. [Scatterplots](#)
3. [Using apply, sapply, lapply in R](#)
4. [How to Learn R](#)
5. [In-depth introduction to machine learning in 15 hours of expert videos](#)

6. [How to Make a Histogram with Basic R](#)
7. [7 Ways to Perplex a Data Scientist](#)
8. [Computing and visualizing PCA in R](#)
9. [Basics of Histograms](#)

## Sponsors



Leading the way in  
R Consulting, Training,  
Data Analytics &  
Application  
Development



[Plotly: collaborative, publication-quality graphing.](#)






Intro and advanced  
R courses for just \$19!

Redeem Promocode

udemy

**Highland Statistics Ltd**

Zero Inflated Models & GLMM  
Beginner's Guide to GAM  
Beginner's Guide to GLM & GLMM  
Beginner's Guide to GAMM



Werden Sie zum Expe[R]ten mit der  
R-Akademie von

**eoda**  
daten • wissen • nutzen

Beratung | Software  
Training | Lösungen

**STATISTICS**  
VIEWS

Bringing Statistics Together

**BECOME A DATA  
SCIENTIST**

NYC DATA SCIENCE  
ACADEMY

12 Weeks to A New Career

**#ODSC**  
BOSTON MAY 20-22

TICKETS ON SALE NOW

Download a **FREE Chapter Today!**

Parallel Computing for Data Science  
With Examples in R, C++ and CUDA

**SAVE 25%**  
on All R Books

Promo Code **CZP40**

**CRC Press**  
Taylor & Francis Group  
www.crcpress.com

**STATWORX**

Consulting  
Schulung  
Data Mining

Mehr erfahren



**Try the FASTEST ML  
for R**

Click for a Free Trial

**YOTTAMINE**  
ANALYTICS





[Contact us](#) if you wish to help support R-bloggers, and place your banner here.

## [Jobs for R users](#)

- [Junior Data Scientist @ Farnham, England](#)
- [Vehicle Valuations Manager @ Farnham, England](#)
- [Manager – Quantitative Analytics @ London, United Kingdom](#)
- [Pharmacometrics Bootcamp @ Wellesley, Massachusetts, US](#)
- [Data Scientist for TIBCO \(>\\$100K/year\)](#)
- [Senior Financial Analyst – Consumer Marketing Analytics @ Seattle, US](#)
- [Post-Doctoral Researcher @ Shanghai, China](#)

### [Full list of contributing R-bloggers](#)

[R-bloggers](#) was founded by [Tal Galili](#), with gratitude to the [R](#) community.

Is powered by [WordPress](#) using a [bavotasan.com](#) design.

Copyright © 2016 **R-bloggers**. All Rights Reserved. [Terms and Conditions](#) for this website