

R news and tutorials contributed by (573) R bloggers

- Home
- About
- <u>RSS</u>
- add your blog!
- R jobs
- Contact us

### Welcome!







If you are an R blogger yourself you are invited to add your own R content feed to this site (Non-English R bloggers should add themselves- here)

## **■** Jobs for R-

### users

- <u>Data Scientist</u> <u>Machine Learning</u> (in booking.com @ Amsterdam)
- <u>Data Scientist</u> <u>Analytics (in</u> <u>booking.com @</u> <u>Amsterdam)</u>
- Data Scientists (@. New York )
- Principal Analysts
   x2, Senior
   Analyst, Analyst

(@ Wellington)

Search & Hit Enter

## **Popular Searches**

- <u>heatmap</u>
- Web Scraping
- maps
- hadoop
- shiny
- **boxplot**
- twitteR
- alt=
- Time series
- animation
- trading
- ggplot2
- latex
- ggplot
- **finance**
- Excel
- **RStudio**
- pca
- how to import image file to R
- quantmod
- googlevis
- market research
- tutorial
- eclipse
- rattle
- undefined
- <u>knitr</u>
- coplot
- GIS
- remdr

### **Recent Posts**

- Replicating
  - NatGeo's
  - "Proper"
  - Earthquake Map
  - in R
- SparkR quick start
- that works
- RcppArmadillo 0.6.100.0.0
- **Imputing missing**
- data with R;
- MICE package
- Predicting Titanic deaths on Kaggle VII: More Stan
- RuleFit: When
- disassembled trees meet Lasso
- Recruiting
  - Analysts for
- dynamic cutting
- edge public sector
- <u>team</u>
- Delta Method
  - Confidence Bands
  - for Gaussian
  - **Density**
- A Simpler
  - Explanation of
- **Differential Privacy**
- Hadley

- Wickham's "Ask Me Anything" on Reddit
- R, Open Source and GSoC
- London Vs Boston
- Jug: Easily Create R APIs
- R User Groups Highlight R Creativity
- ChIPseq data mining with ChIPseeker

### Other sites

- SAS blogs
- Statistics of Israel
- Jobs for R-users

# caretEnsemble Classification example

March 16, 2013 By Zachary Mayer



Here's a quick demo of how to fit a binary classification model with caretEnsemble. Please note that I haven't spent as much time debugging caretEnsemble for classification models, so there's probably more bugs than my last post. Also note that multi class models are not yet supported.

```
#Setup
     rm(list = ls(all = TRUE))
     gc(reset=TRUE)
     set.seed(1234) #From random.org
     #Libraries
6
     library(caret)
     library(devtools)
8
9
     install github('caretEnsemble', 'zachmayer') #Install zach's c
10
     library(caretEnsemble)
     #Data
     library(mlbench)
     dat <- mlbench.xor(500, 2)</pre>
14
     X <- data.frame(dat$x)</pre>
16
     Y <- factor(ifelse(dat$classes=='1', 'Yes', 'No'))
     #Split train/test
     train <- runif(nrow(X)) <= .66
19
20
     #Setup CV Folds
     #returnData=FALSE saves some space
     folds=5
     repeats=1
24
     myControl <- trainControl(method='cv', number=folds, repeats=r</pre>
                                returnResamp='none', classProbs=TRUE
26
                                returnData=FALSE, savePredictions=TR
                                verboseIter=TRUE, allowParallel=TRUE
29
                                summaryFunction=twoClassSummary,
                                index=createMultiFolds(Y[train], k=f
30
     PP <- c('center', 'scale')
```

```
#Train some models
34
      model1 <- train(X[train,], Y[train], method='gbm', trControl=m</pre>
                       tuneGrid=expand.grid(.n.trees=500, .interactio
      model2 <- train(X[train,], Y[train], method='blackboost', trCo</pre>
      model3 <- train(X[train,], Y[train], method='parRF', trControl</pre>
      model4 <- train(X[train,], Y[train], method='mlpWeightDecay',</pre>
      model5 <- train(X[train,], Y[train], method='knn', trControl=m</pre>
      model6 <- train(X[train,], Y[train], method='earth', trControl</pre>
40
      model7 <- train(X[train,], Y[train], method='glm', trControl=m</pre>
41
      model8 <- train(X[train,], Y[train], method='svmRadial', trCon</pre>
42
43
      model9 <- train(X[train,], Y[train], method='gam', trControl=m</pre>
44
      model10 <- train(X[train,], Y[train], method='glmnet', trContr</pre>
45
46
      #Make a list of all the models
      all.models <- list(model1, model2, model3, model4, model5, mod
47
      names(all.models) <- sapply(all.models, function(x) x$method)</pre>
48
49
      sort(sapply(all.models, function(x) min(x$results$ROC)))
      #Make a greedy ensemble - currently can only use RMSE
      greedy <- caretEnsemble(all.models, iter=1000L)</pre>
      sort(greedy$weights, decreasing=TRUE)
      greedy$error
56
      #Make a linear regression ensemble
      linear <- caretStack(all.models, method='glm', trControl=train</pre>
      linear$error
58
60
      #Predict for test set:
61
      library(caTools)
      preds <- data.frame(sapply(all.models, function(x){predict(x,</pre>
      preds$ENS greedy <- predict(greedy, newdata=X[!train,])</pre>
      preds$ENS linear <- predict(linear, newdata=X[!train,], type='</pre>
      sort(data.frame(colAUC(preds, Y[!train])))
4 Ⅲ
Demo2.R hosted with ♥ by GitHub
                                                               view raw
```

Right now, this code fails for me if I try a model like a nnet or an SVM for stacking, so there's clearly bugs to fix.

The greedy model relies 100% on the gbm, which makes sense as the gbm has an AUC of 1 on the training set. The linear model uses all of the models, and achieves an AUC of .5. This is a little weird, as the gbm, rf, SVN, and knn all achieve an AUC of close to 1.0 on the training set, and I would have expected the linear model to focus on these predictions. I'm not sure if this is a bug, or a failure of my stacking model.

#### Related




R-bloggers.com offers daily e-mail updates about R news and tutorials on topics such as: visualization (ggplot2, Boxplots, maps, animation), programming (RStudio, Sweave, LaTeX, SOL, Eclipse, git, hadoop, Web Scraping) statistics (regression, PCA, time series, trading) and more...

If you got this far, why not **subscribe for updates** from the site? Choose your flavor: <u>e-mail</u>, <u>twitter</u>, <u>RSS</u>, or <u>facebook</u>...









Comments are closed.

## Top 3 Posts from the past 2 days

- Imputing missing data with R; MICE package
- In-depth introduction to machine learning in 15 hours of expert videos
- RuleFit: When disassembled trees meet

Search & Hit Enter

## Top 9 articles of the week

- 1. In-depth introduction to machine learning in 15 hours of expert videos
- Installing R packages
- 3. Scatterplots
- 4. Using apply, sapply, lapply in R
- 5. Basics of Histograms
- 6. Learn R interactively with our new Introduction to R tutorial
- How to Make a Histogram with Basic R Why Big Data? Learning Curves
- Adding a legend to a plot

### **Sponsors**













Werden Sie zum Expe[R]ten mit der










Plotly: collaborative, publication-quality graphing.





















Contact us if you wish to help support Rbloggers, and place your banner here. Search & Hit Enter

Full list of contributing R-bloggers

R-bloggers was founded by Tal Galili, with gratitude to the R community.

Is powered by WordPress using a bavotasan.com design.

Copyright © 2015 R-bloggers. All Rights Reserved. Terms and Conditions for this website