


USER MANUAL



CLASSIC DELAY



CubeSuite for Android/iOS: scan the QR code

Preface

Thank you for purchasing the CLASSIC DELAY. This pedal is a pure-circuit analog product. We do our best to develop this pedal, I hope you like it.

Attentions

■ The power supply:

Please use 9V(+/-10%) adapter (negative inside and positive outside), otherwise it may cause equipment damage. Please unplug the power when not in use or during thunderstorm weather.

■ The connection:

Be sure to turn off the power of related equipment before connecting or disconnecting the device.

■ The electrical interference:

The electromagnetic wave of radio, television and other equipment may cause interference to the equipment, so please try to stay away from radio, television and other equipment.

■ The location:


To avoid deformation, discoloration, or other serious damage, do not expose this unit to the following conditions:

- a. Heat sources
- b. Magnetic fields
- c. Sunlight
- d. High temperature or moist district
- e. Excessively dusty or dirty locations
- f. Strong vibrations or shocks

Features

- This product is a compact metal appearance design.
- This pedal can provide a 530ms maximum delay time.
- Real bypass.
- This pedal is a pure-circuit analog product, it can let you get a more sweet, warm and natural timble.

Control panel instruction



①Power jack

Please use 9V DC adapter (negative inside and positive outside).

②USB jack

Support power supply,suggest to use 5V 1A adapter.

③F.BACK knob

Adjust the number of echo repeats by turning the F.BACK knob.

④ECHO knob

Adjust the ratio of wet and dry by turning the ECHO knob.

⑤TIME knob

Adjust the feedback speed of echo repeats by turning the TIME knob.

⑥Output jack

1/4" MONO audio output jack to connect mixer or speaker.

⑦LED

The LED lights up when the effect pedal is enabled ,or goes out in bypass mode.

⑧Input jack

1/4" MONO audio input jack to connect instrument.

⑨Footswitch

Enable/bypass the CLASSIC DELAY by tap the footswitch.

Technical parameter

Input	Standard 1/4"jack-MONO/TS
Output	Standard 1/4"jack-MONO/TS
Power supply 1	DC9V≥300mA ⏻⏻⏻
Power supply 2	USB 5V≥300mA
Size	90mm(L) x 40mm(W) x 34.5mm(H)
Weight	221g

Disclaimer:Specifications are subject to change without notice.