


M-VAVE

USER MANUAL



DIGITAL DELAY

- **Website:** www.m-vave.com
- **CubeSuite for Windows/Mac OS:** <http://www.m-vave.com/appdownload>
- **CubeSuite for Android/iOS:** scan the QR code



Preface

Thank you for purchasing the DIGITAL DELAY. This pedal is a pure-digital product, it provides 9 types of delay. We do our best to develop this pedal, I hope you like it.

Attentions

■ The power supply:

Please use 9V(+/-10%) adapter (negative inside and positive outside), otherwise it may cause equipment damage. Please unplug the power when not in use or during thunderstorm weather.

■ The connection:

Be sure to turn off the power of related equipment before connecting or disconnecting the device.

■ The electrical interference:


The electromagnetic wave of radio, television and other equipment may cause interference to the equipment, so please try to stay away from radio, television and other equipment.

■ The location:

To avoid deformation, discoloration, or other serious damage, do not expose this unit to the following conditions:

- Heat sources
- Magnetic fields
- Sunlight
- High temperature or moist district
- Excessively dusty or dirty locations
- Strong vibrations or shocks

Control panel instruction



①Power jack

Please use 9V DC adapter (negative inside and positive outside).

②USB jack

Support power supply, suggest to use 5V 1A adapter.

③TIME knob

Adjust the feedback speed of echo repeats by turning the TIME knob.

④FEEDBACK knob

Adjust the number of echo repeats by turning the FEEDBACK knob.

⑤DELAY type knob

Select 9 types of delay by dialling the knob, please see the Table below.

⑥Output jack

1/4" MONO audio output jack to connect mixer or speaker.

⑦LED

The LED lights up when the effect pedal is enabled ,or goes out in bypass mode.

⑧Input jack

1/4" MONO audio input jack to connect instrument.

⑨Footswitch

Enable/bypass the DIGITAL DELAY by tap the footswitch.

No.	Delay Type	Description
1.	CLEAN	The original sound with delay effect.
2.	BUBBLE	You can imagine the effect of a sound with a"wow" and delay coming out of the water.
3.	MOD	A clear delay but with tremolo modulation effect.
4.	REVERSE	Reverse Delay organically interact where space and ambience build as the signal is reversed, re-reversed, reverberated, and reversed again within the feedback network.
5.	SWEEP ECHO	An echo delay sound with slight sweep effect.
6.	TAPE	You will hear a smooth sound from old tape echo machine.
7.	MIC	This delay sounds like in a microphone.
8.	ANALOG	It is a delay module with a lowpass filter.
9.	LOFI	Lo-fi means "low fidelity",it is a mystical,profound,especial sound.

Technical parameter

Input	Standard 1/4"jack-MONO/TS
Output	Standard 1/4"jack-MONO/TS
Power supply 1	DC9V≥300mA   
Power supply 2	USB 5V≥300mA
Size	90mm(L) x 40mm(W) x 34.5mm(H)
Weight	221g

Disclaimer:Specifications are subject to change without notice.